



Sparkle Power Inc.
 A Leading Power Supply Manufacturer
 Web site: www.sparklepower.com

FSP500-702UP
(80PLUS Gold, RoHS Compliant)
500 Watts ATX 12V, 2U , PM Bus
Switching Power Supply



Features

- Complied with ATX12V standard
- Active Power Factor Correction (PFC) meet EN61000-3-2
- High efficiency and reliability
- Compatible with European Union Directive 2002/95/EC (Restriction on Hazardous Substances).
- Remote ON/OFF function
- Internal 12V DC fan included
- Low noise and ripple
- Output over voltage, short circuit, and over current protection
- 100% Hi-pot, ATE, and burn-in tested
- Re-settable power shut down
- Complies with FCC part 15 subpart J class B 115Vac operation, and CISPR 22 class B at 230Vac operation
- Approved by : UL/CUL60950-1 2nd TUV EN60950-1 2nd , CB 60950-1 2nd , FCC, EMC

Input Characteristics

Input Range: 90 ~ 264Vac, Full Range Input
Frequency: 47 ~ 63Hz
Input Current: Max 8A @ 115Vac, 4.0A @ 230Vac
Inrush Current: No Damage

Output Characteristics

| Output Voltage | Minimum Load | Normal Load | Maximum Load | Load Reg. | Ripple & Noise |
|----------------|--------------|-------------|--------------|-----------|----------------|
| +3.3V | 0.1A | 10A | 20A | ± 5% | 50mV P-P |
| +5V | 0.1A | 10A | 20A | ± 5% | 50mV P-P |
| +12V1 | 0.5A | 8A | 16A | ± 5% | 120mV P-P |
| +12V2 | 0.5A | 8A | 16A | ± 5% | 120mV P-P |
| +12V3 | 0.5A | 8A | 16A | ± 5% | 120mV P-P |
| -12V | 0A | 0.25A | 0.5A | ± 10% | 120mV P-P |
| +5Vsb | 0A | 1.75A | 3.5A | ± 5% | 50mV P-P |

*+3.3V and +5V total output not exceed 130W
 * Total output for this subject power supply is 500W

Specification

- **Temperature Range:** Operating: 0°C ~ +50°C on full load; storage & shipping: -20°C ~ +80°C
- **Humidity:** 85% on operating, 95% on storage
- **Dielectric Withstand:** Primary frame ground 1800V AC for 2 second
- **Efficiency: Typical > 90%**
- **Rise time:** Less than 20ms
- **Hold-up Time:** 16 ms minimum at nominal input voltage
- **Power Good Signal:** Power on delay time 100 ~ 500ms, off delay 1ms minimum (TTL and CMOS compatible)
- **Leakage Current:** Less than 3.5mA at 264Vac, 50Hz
- **MTBF:** 100,000 hours on maximum load at +25°C
- **Dimensions (LxWxH):** 260x100x70mm / 10.24x3.9x 2.7 inch

Sparkle Power Inc.
Main Office
 1000 Rock Avenue
 San Jose, CA 95131
 TEL: 408-519-8888
 FAX: 408-519-9999
 E-MAIL: info@sparklepower.com

Sparkle Power Inc.
Los Angeles Office
 17071 Green Drive
 City of Industry, CA 91745
 TEL: 626-839-7180
 FAX: 626-839-3395