



75 Ohm Mini SMB Jack Connector Solder Attachment 0.062 inch End Launch PCB

TECHNICAL DATA SHEET

PE44131

75 Ohm Mini SMB Jack Connector Solder Attachment 0.062 inch End Launch PCB

Configuration

Connector	Mini SMB Jack
Connector Specification	MIL-C-39012
Connector Interface Type	0.062 inch End Launch
Cable Attachment Method (Shield/Contact)	Solder
Body Style	Straight

Electrical Specifications

Frequency Range, GHz	DC to 2
Impedance, Ohms	75
Maximum Operating Voltage, Volts	335
Dielectric Withstanding Voltage, Vrms	1,000

Mechanical Specifications

Temperature	
Operating Range, deg C	-65 to +165

Size

Length, in [mm]	0.562 [14.27]
Width/Dia., in [mm]	0.25 [6.35]
Height, in [mm]	0.25 [6.35]
Weight, lbs [g]	0.004 [1.81]

Connector

Type	Mini SMB Jack
Mating Cycles	500
Contact Material and Plating	Beryllium Copper, Gold
Contact Plating Specification	30μ in minimum
Body Material and Plating	Brass, Gold
Body Plating Specification	10μ in minimum
Dielectric Type	Teflon

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant	Yes
----------------	-----

Plotted and Other Data

Notes:	Values at 25 °C, sea level
--------	----------------------------

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [75 Ohm Mini SMB Jack Connector Solder Attachment 0.062 inch End Launch PCB PE44131](#)

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



75 Ohm Mini SMB Jack Connector Solder
Attachment 0.062 inch End Launch PCB

TECHNICAL DATA SHEET

PE44131



75 Ohm Mini SMB Jack Connector Solder Attachment 0.062 inch End Launch PCB from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [75 Ohm Mini SMB Jack Connector Solder Attachment 0.062 inch End Launch PCB PE44131](http://www.pasternack.com/mini-smb-jack-standard-0.062-end-launch-connector-pe44131-p.aspx)

URL: <http://www.pasternack.com/mini-smb-jack-standard-0.062-end-launch-connector-pe44131-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

MATERIALS	
BODY	BRASS GOLD PLATED
CONTACT	GOLD PLATED
INSULATOR	PTFE



DWG TITLE		DES.	
PE44131		MINI "75 OHM SMB" JACK END LAUNCH FOR .062" THICK BOARD, ROUND CONTACT	
SIZE A	FSCM NO. 53919	CAD FILE	070302
		SCALE	N/A
			127

NOTES:

1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.