

Rail Mounted Terminal Blocks

1039900000

When good enough just isn't good enough

Weidmüller

WTR 2.5/ZZ

[Email to a Friend](#)


[View Catalog Page](#)

[View Line Drawing](#)

[Sales Information](#)

[Back to StepSearch](#)

[Catalog Home](#)




Representative Photo

Technical Information

Clamping Type	Screw Clamp
Series	W Series
Rail Type	TS 35
Function	Disconnect
Configuration	Lever
Wire Size	2.5 mm ²
Current	14 A
Voltage	400 V
Color/Material	Beige Wemid

Special Requirements



Technical Data

	UL	CSA	VDE
Rated Voltage			400 V
Rated Current			14 A
Wire Size			2.5 mm ²

Additional Data

Width/Length/Height mm (in.)	5/60/49 (.2"/2.36"/1.93")
Insulation Stripping Length mm (in.)	10 (.39")
Torque Nm (lb. in)	0.6 (5.2)
Clamping Screw	M 3
Flammability Class	UL 94 (V0)

Suggested Accessories

[DIN-rail](#)

[Diode plug](#)

[End plate/partition \(WAP/WTW\)](#)

[Ferrules](#)

[Markers \(SchT\)](#)

Marking pens

Marking system (WS/ZS)

Marking tags (DEK)

Mounting brackets

Test plugs/socket

Tools

ZQV jumpers

Product Liability The above information describes our products. It does not constitute guaranteed properties and is not intended to a the suitability of a product for a particular application. Regrettably, omissions and exceptions cannot be completely ruled out. Techni data are always specified by their average values. Exact data and the tolerances which apply to our processes can be requested from

Weidmüller - North America
United States 001 (800) 849-9343
Canada 001 (800) 268-4080

or

Weidmüller - Germany
Telephone operator 0049 (-5252) 960-0