

**CW INDUSTRIES**130 James Way  
Southampton, PA 18966

Phone: 215-355-7080 • Fax: 215-355-1088

Email: [info@cwind.com](mailto:info@cwind.com) • Website: <http://www.cwind.com>


Item # GRL-4021-0012, 4000 Series Illuminated Miniature Rocker Switches

[Check Distributor Stock](#) · [Specifications](#) · [Materials](#) · [Operating Standards](#)

**Check Distributor Stock**

Check Distributor Stock	<a href="#">DIGI-KEY</a>
-------------------------	--------------------------

**Specifications**

<b>Circuitry</b>	DPST
<b>Switch Function</b>	ON-OFF
<b>Electrical Ratings<sup>1</sup></b>	10 A @ 14 V (T) 16 A @ 125-250 VAC 3 A @ 125 V (L) 3/4 HP @ 125-250 VAC NEON
<b>Acceptable Panel Thickness</b>	0.050 - 0.150 in 1.27 - 3.81 mm
<b>Mounting</b>	Self locks without hardware when inserted into a 0.756" (19.20 mm) x 0.508" (12.90 mm) panel cutout. Acceptable panel thickness range is from 0.050" (1.27 mm) to 0.150" (3.81 mm).  <b>CAUTION:</b> Burr direction must be away from the direction of insertion.
<b>Mounting Polarization</b>	None
<b>Actuator Color</b>	Red
<b>Actuator Legend</b>	None
<b>Illumination</b>	Illuminated
<b>Housing Color</b>	Black
<b>Insulating Barriers</b>	<input checked="" type="checkbox"/> Between Poles <input type="checkbox"/> Between Terminals <input type="checkbox"/> No Barriers
<b>Terminal</b>	<input checked="" type="checkbox"/> 0.187 x 0.032in.    4.75 x 0.81mm.    Quick Connect <input type="checkbox"/> 0.187 x 0.020in.    4.75 x 0.51mm.    Quick Connect <input type="checkbox"/> 0.110 x 0.032in.    2.79 x 0.81mm.    Quick Connect <input type="checkbox"/> 0.110 x 0.032in.    2.79 x 0.81mm.    Solder Terminal
<b>Contact Action</b>	Sliding with Self Cleaning Contacts
<b>Listing Agency (Consult drawing or factory for specific rating)<sup>2</sup></b>	 Listed Agencies

**Compliance**

<sup>1</sup> All ratings are on a load per pole, opposite polarity basis. Additional ratings may be available, contact us for more information.

<sup>2</sup> Due to ongoing advancements, additional agency certifications may be available, contact us for more information.

**Materials**

<b>Rocker Knob</b>	Translucent Nylon 6/6 (Optional) Transparent Polycarbonate (Standard)
<b>Rocker Lamp</b>	High intensity neon lamp type NE-38 with 1/8 watt 47 kΩ resistor, 10,000 hour life for 125 volt applications (standard)
<b>Housing</b>	Nylon 94V-2
<b>Terminal &amp; Moving Contact</b>	Copper Alloy or Copper Alloy Silver Plated

**Operating Standards****Endurance:**

100,000 cycles, no load, minimum

25,000 cycles at rated load minimum up to 16 A @ 125 VAC

10,000 cycles at rated load minimum 16 A @ 250 VAC

**Contact Resistance:**

Less than 0.01 Ω at 10 mA (Initial)

**Operating Temperature:**

From -20°C to 105°C maximum.

Consult factory for higher or lower temperature ranges.

**High Voltage Dielectric Withstanding Voltage:**

2,500 V, 60 Hz for 1 minute between mounting surface and circuit connections

**Humidity:**

Insulation resistance > 10<sup>3</sup> MΩ after 100 hours at 95% R.H. and 50°C followed by 1 hour dry at ambient room conditions

**Operating Standards** described herein are general specifications that vary depending on the switch construction specified and end application. Contact us for specifications for specific models. Specifications subject to change without notice.