

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [0082247705](#)
Status: **Active**
Description: 2.54mm (.100") Pitch Round Conductor Flat Cable - 24 AWG (7 x 32) Stranded, Tinned, 5 Circuits, Reel 30.48m (100.0') Length

Documents:

[Drawing \(PDF\)](#) [RoHS Certificate of Compliance \(PDF\)](#)

General

Product Family	Cable
Series	24226
Crimp Quality Equipment	Yes
Geographic Area	Asia
Product Name	Ribbon

Physical

Cable Length	30.48m (100.0')
Circuits (Loaded)	5
Insulation	PVC
Packaging Type	Reel
Pitch - Term. Interface (in)	0.100 In
Pitch - Term. Interface (mm)	2.54 mm
Temperature Range - Operating	-20°C to +105°C
Wire Size AWG	24
Wire/Cable Type	(7x32) Stranded, Tinned

Electrical


Current - Maximum per Contact	N/A
Voltage - Maximum	300V

Material Info

Old Part Number	24226-05-100B
-----------------	---------------

Reference - Drawing Numbers

Sales Drawing	SD-24226-001
---------------	--------------



EU RoHS

**ELV and RoHS
Compliant**
**REACH SVHC
Not Reviewed**
**Halogen-Free
Status
Not Reviewed**

China RoHS



Need more information on product environmental compliance?

Email productcompliance@molex.com
 For a multiple part number RoHS Certificate of Compliance, [click here](#)


Please visit the [Contact Us](#) section for any non-product compliance questions.

Search Parts in this Series

[24226Series](#)

Use With

[70400](#) C-Grid SL™ IDT Connector Assembly.
[70475](#) SL™ IDT Connector Assembly.
[7720](#) KK® IDT Double Cantilever Contact



- NOTE :
1. THE CABLE SHALL HAVE A MINIMUM OF 0.178mm. (.007") THICKNESS INSULATION AT ANY POINT
 2. RIP TEST:
 - THE 0.13mm. (.005") ZIPPING GROOVE SHALL BE CAPABLE OF BEING RIPPED BY HAND WITHIN THE RECESS, WITHOUT EXPOSING THE ADJACENT CONDUCTORS
 3. RoHS AND LEAD FREE COMPLIANT
 4. SPECIAL REQUIREMENT: N/A

B	E-07-0748	B ₂ : ADD NON-OPERATING TEMP. B ₁ : CHANGE WEB THICKNESS	07/09/26
A	N/A	NEW RELEASE	06/07/12
REV. HISTORY	EC NO.	DETAIL	DATE

SEE CHANGE DETAIL
 EC NO: THL2008-0015
 DRWN: CPANSAKHOM 2007/11/28
 CHKD: DNARINTARA 2007/11/29
 APPR: SVIRATJAPOL 2007/12/04

QUALITY SYMBOLS
▽=3
▽=0
DESCRIPTION
REV

GENERAL TOLERANCES (UNLESS SPECIFIED)	
	mm INCH
4 PLACES	± --- ± ---
3 PLACES	± --- ± ---
2 PLACES	± --- ± ---
1 PLACE	± --- ± ---
ANGULAR ± --- °	
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	

DIMENSION STYLE MM/IN	
DRAWN BY	DATE
CPANSAKHOM	2006/07/12
CHECKED BY	DATE
PMEECHAI	2006/07/12
APPROVED BY	DATE
SVIRATJAPOL	2006/07/12
MATERIAL NO.	
SEE CHART	
SIZE	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

SCALE NTS	DESIGN UNITS INCH	THIRD ANGLE PROJECTION
TITLE		
FCB ROUND CONDUCTOR 2.54MM(.100)CENTERS PVC. 24AWG STR TINNED		
MOLEX MOLEX INCORPORATED		
MATERIAL NO.	DOCUMENT NO.	SHEET NO.
SEE CHART	SD-24226-001	1 OF 3

E

E

SPECIFICATIONS

PHYSICAL

CONDUCTOR SPACING 2.54 (.100") \bar{C} TO \bar{C}
 WIRE GAUGE 24 AWG (7/32) STRANDED TINNED
 INSULATION P.V.C GRAY (LEAD FREE)

AGENCY

U.L. STYLE NO. 2651
 TEMPERATURE RATING -20°C TO 105°C
 VOLTAGE RATING 300V.MAX.
 FLAMMABILITY RATING VW-1

ELECTRICAL

CONDUCTOR RESISTANCE (D.C.) 27 m OHMS/FT. MAX.
 CHARACTERISTIC IMPEDANCE 134 OHMS NOM. (GS)
 114 OHMS NOM. (GSG)
 CAPACITANCE 6.6 pF/FT. NOM. (GS)
 12.0 pF/FT. NOM. (GSG)
 PROPAGATION DELAY 1.4 ns/FT. NOM.
 INSULATION RESISTANCE 10 M OHMS (10FT. SAMPLE)
 DIELECTRIC WITHSTAND VOLTAGE 2000 VRMS/MINUTE

GENERAL

\triangle_{B_2} NON-OPERATING TEMPERATURE -20°C TO 105°C
 FAULTS AND/OR SPLICES 1/REEL MAX. 100⁺³₀ FT. (30.48^{+0.914}₀ M.)/REEL
 20FT. (6.096M.) MIN. LENGTH

D

D

C

C

B

B

A

A

SEE CHANGE DETAIL EC NO: THL2008-0015 DRWN: CPANSAKHOM 2007/11/28 CHKD: DNARINTARA 2007/11/29 APPR: SVIRATJAPOL 2007/12/04	DESCRIPTION REV	QUALITY SYMBOLS	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM/IN		SCALE NTS	DESIGN UNITS INCH	THIRD ANGLE PROJECTION		
		$\blacktriangledown =$ $\triangle =$	mm	INCH	DRAWN BY CPANSAKHOM	DATE 2006/07/12	TITLE FCB ROUND CONDUCTOR 2.54MM(.100)CENTERS PVC. 24AWG STR TINNED				
			4 PLACES	±----	±----	CHECKED BY PMEECHAI					DATE 2006/07/12
			3 PLACES	±----	±----	APPROVED BY SVIRATJAPOL	DATE 2006/07/12	MOLEX INCORPORATED		DOCUMENT NO. SD-24226-001	SHEET NO. 2 OF 3
			2 PLACES	±----	±----	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS					
1 PLACE	±----	±----	ANGULAR ±----°		SIZE \triangle_{A_4}		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION				

E

D

C

B

A

E

D

C

B

A

CHART A DIMENSIONS MM (INCHES)				SHIPPED ON 100FT REELS	
ENG. NO.	NO. OF COND.	DIMENSION S	DIM. W (REF)	ENGINEERING NO.	ORDER NO.
24226-2	2	2.54±0.10 (.100±.004)	5.08 (.200)	24226-02-100B	82-24-7702
24226-3	3	5.08±0.20 (.200±.008)	7.62 (.300)	24226-03-100B	82-24-7703
24226-4	4	7.62±0.30 (.300±.012)	10.16 (.400)	24226-04-100B	82-24-7704
24226-5	5	10.16±0.33 (.400±.013)	12.70 (.500)	24226-05-100B	82-24-7705
24226-6	6	12.70±0.33 (.500±.013)	15.24 (.600)	24226-06-100B	82-24-7706
24226-7	7	15.24±0.33 (.600±.013)	17.78 (.700)	24226-07-100B	82-24-7707
24226-8	8	17.78±0.33 (.700±.013)	20.32 (.800)	24226-08-100B	82-24-7708
24226-9	9	20.32±0.33 (.800±.013)	22.86 (.900)	24226-09-100B	82-24-7709
24226-10	10	22.86±0.33 (.900±.013)	25.40 (1.000)	24226-10-100B	82-24-7710
24226-11	11	25.40±0.33 (1.000±.013)	27.94 (1.100)	24226-11-100B	82-24-7711
24226-12	12	27.94±0.33 (1.100±.013)	30.48 (1.200)	24226-12-100B	82-24-7712
24226-13	13	30.48±0.33 (1.200±.013)	33.02 (1.300)	24226-13-100B	82-24-7713
24226-14	14	33.02±0.33 (1.300±.013)	35.56 (1.400)	24226-14-100B	82-24-7714
24226-15	15	35.56±0.33 (1.400±.013)	38.10 (1.500)	24226-15-100B	82-24-7715
24226-16	16	38.10±0.33 (1.500±.013)	40.64 (1.600)	24226-16-100B	82-24-7716
24226-17	17	40.64±0.33 (1.600±.013)	43.18 (1.700)	24226-17-100B	82-24-7717
24226-18	18	43.18±0.33 (1.700±.013)	45.72 (1.800)	24226-18-100B	82-24-7718
24226-19	19	45.72±0.33 (1.800±.013)	48.26 (1.900)	24226-19-100B	82-24-7719
24226-20	20	48.26±0.33 (1.900±.013)	50.80 (2.000)	24226-20-100B	82-24-7720

ENGINEERING NO.

24226-XX-XXXX

A B C D

A : CABLE 2.54mm. (.100") CENTERS 24 AWG STRANDED TINNED

B : CONDUCTOR SIZE (AVAILABILITY 2 THROUGH 20)

C : CABLE LENGTH 100FT. (30.48M.)

D : A = INCHES

B = FEET

SEE CHANGE DETAIL EC NO: THL2008-0015 DRWN: CPANSAKHOM 2007/11/28 CHKD: DNARINTARA 2007/11/29 APPR: SVIRATJAPOL 2007/12/04	DESCRIPTION REV	QUALITY SYMBOLS ▽ = ◁ =	GENERAL TOLERANCES (UNLESS SPECIFIED)	DIMENSION STYLE MM/IN	SCALE NTS	DESIGN UNITS INCH	THIRD ANGLE PROJECTION	
			mm INCH	DRAWN BY DATE CPANSAKHOM 2006/07/12	TITLE	FCB ROUND CONDUCTOR 2.54MM(.100)CENTERS PVC. 24AWG STR TINNED		
			4 PLACES ± --- ± --- 3 PLACES ± --- ± --- 2 PLACES ± --- ± --- 1 PLACE ± --- ± ---	CHECKED BY DATE PMEECHAI 2006/07/12	MOLEX MOLEX INCORPORATED			
			ANGULAR ± ---°	APPROVED BY DATE SVIRATJAPOL 2006/07/12	MATERIAL NO.	DOCUMENT NO.	SHEET NO.	
			DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	SEE CHART	SD-24226-001	3 OF 3		