
isc Silicon PNP Power Transistor — NJW0302GD


DESCRIPTION

- High Collector-Emitter Breakdown Voltage-
  : $V_{(BR)CEO}$= -350V(Min)
- Good Linearity of h_{FE}
- Complement to Type NJW0281GD
- Minimum Lot-to-Lot variations for robust device performance and reliable operation

APPLICATIONS

- Designed for high fidelity audio amplifier and other linear applications





DIM	mm MIN	MAX
A	15.45	15.75
B	13.45	13.75
C	9.45	9.75
D	19.80	20.20
E	2.00	2.20
F	2.95	3.25
G	13.70	14.10
H	1.40	1.60
I	18.45	18.75
J	4.70	4.90
K	0.50	0.70
L	2.20	2.60
M	1.20	1.60
P	1.80	2.20
Q	5.25	5.65

ABSOLUTE MAXIMUM RATINGS(Ta=25℃)

SYMBOL	PARAMETER	VALUE	UNIT
V_{CBO}	Collector-Base Voltage	-350	V
V_{CEO}	Collector-Emitter Voltage	-350	V
V_{EBO}	Emitter-Base Voltage	-5	V
I_{CM}	Collector Current-Continuous	-23	A
I_B	Base Current-Continuous	-1.5	A
P_C	Collector Power Dissipation @ T_C=25℃	120	W
T_J	Junction Temperature	150	℃
T_{stg}	Storage Temperature Range	-65~150	℃

Download from alldatasheet.com

isc Silicon PNP Power Transistor NJW0302GD

ELECTRICAL CHARACTERISTICS

T_C=25℃ unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT
$V_{(BR)CEO}$	Collector-Emitter Breakdown Voltage	I_C= -30mA ; I_B= 0	-350			V
$V_{CE(sat)}$	Collector-Emitter Saturation Voltage	I_C= -5.0A; I_B= -0.5A			-1.0	V
$V_{BE(on)}$	Base−Emitter On Voltage	I_C = -5.0 A, V_{CE} = -5.0 V			-1.2	V
I_{CBO}	Collector Cutoff Current	V_{CB}= -300V ; I_E= 0			-100	μA
I_{EBO}	Emitter Cutoff Current	V_{EB}= -5V; I_C= 0			-100	μA
h_{FE-1}	DC Current Gain	I_C= -0.5A ; V_{CE}= -5V	30		60	
h_{FE-2}	DC Current Gain	I_C= -1A ; V_{CE}= 5V	30		60	

NOTICE：

ISC reserves the rights to make changes of the content herein the datasheet at any time without notification. The information contained herein is presented only as a guide for the applications of our products.

ISC products are intended for usage in general electronic equipment. The products are not designed for use in equipment which require specialized quality and/or reliability, or in equipment which could have applications in hazardous environments, aerospace industry, or medical field. Please contact us if you intend our products to be used in these special applications.

ISC makes no warranty or guarantee regarding the suitability of its products for any particular purpose, nor does ISC assume any liability arising from the application or use of any products, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.

Download from alldatasheet.com