
Single Phase Glass Passivated Silicon Bridge Rectifier

V_{RRM} = 50 V - 400 V
I_O = 35 A

Features

- Integrally molded heat sink provides low thermal resistance for maximum heat dissipation
- High surge current capability
- Universal 3-way terminals: snap on, wire-around, or P.C board mounting
- High temperature soldering guaranteed: 260^{0}C/ 10 seconds at 5 lbs (2.3 kg) tension
- Not ESD Sensitive

GBPC-T/W Package





Mechanical Data

Case: Molded plastic with heat sink integrally mounted in the bridge encapsulation

Terminals: Either nickel plated 0.25". Faston lugs or copper leads 0.040" diameter.

Polarity: Polarrity symbols marked on the body

Mounting position: Bolt down on heat-sink with silicone thermal compound between bridge and mounting surface

Weight: 15 grams or 0.53 ounces

Mounting torque: 20 inch-lbs max

Maximum ratings at Tc = 25 °C, unless otherwise specified (GBPCXXXXT uses GBPC-T package while GBPCXXXXW uses GBPC-W package)

Parameter	Symbol	Conditions	GBPC35005T/W	GBPC3501T/W	GBPC3502T/W	GBPC3504T/W	Unit
Repetitive peak reverse voltage	V_{RRM}		50	100	200	400	V
RMS reverse voltage	V_{RMS}		35	70	140	280	V
DC blocking voltage	V_{DC}		50	100	200	400	V
Operating temperature	T_j		-55 to 150	-55 to 150	-55 to 150	-55 to 150	°C
Storage temperature	T_{stg}		-55 to 150	-55 to 150	-55 to 150	-55 to 150	°C

Electrical characteristics at Tc = 25 °C, unless otherwise specified

Single phase, half sine wave, 60 Hz, resistive or inductive load

For capacitive load derate current by 20%

Parameter	Symbol	Conditions	GBPC35005T/W	GBPC3501T/W	GBPC3502T/W	GBPC3504T/W	Unit
Maximum average forward rectified current	I_O	T_c = 50 °C	35.0	35.0	35.0	35.0	A
Peak forward surge current	I_{FSM}	single sine-wave	400	400	400	400	A
Maximum instantaneous forward voltage drop per leg	V_F	I_F = 17.5 A	1.1	1.1	1.1	1.1	V
Maximum DC reverse current at rated DC blocking voltage per leg	I_R	T_a = 25 °C T_a = 125 °C	5 500	5 500	5 500	5 500	µA
Rating for fusing	I^2t	1 ms < t_m < 8.3 ms	660	660	660	660	A^2sec
RMS isolation voltage from case to leads	V_{ISO}		2500	2500	2500	2500	V
Typical junction capacitance	C_j		300	300	300	300	pF
Typical thermal resistance	$R_{\theta JC}$		1.4	1.4	1.4	1.4	°C/W

FIG.1-MAXIMUM OUTPUT RECTIFIED CURRENT




FIG.2-MAXIMUM OUTPUT RECTIFIED CURRENT




FIG.3-MAXIMUM POWER DISSIPATION




FIG.4-MAXIMUM NON-REPEITIVE PEAK FORWARD




FIG.5-TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS PER LEG




FIG.6-TYPICAL REVERSE CHARACTERISTICS




FIG.7-TYPICAL JUNCTION CAPACITANCE PER LEG






FIG.8-TYPICAL TRANSIENT THERMAL IMPEDANCE



Package dimensions and terminal configuration

Product is marked with part number and terminal configuration.



Dimensions in inches and (millimeters)

