

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:

0901430040

Status:

Active

Overview:

C-Grid III™

Description:

2.54mm (.100") Pitch C-Grid III™ Modular Crimp Housing, Dual Row, 40 Circuits

Documents:

3D Model

Drawing (PDF)


RoHS Certificate of Compliance (PDF)

General	
Product Family	Crimp Housings
Series	90143
Comments	No Buttons
Overview	C-Grid III™
Product Name	C-Grid III™
Physical	
Breakaway	No
Circuits (maximum)	40
Circuits Detail	No Voided Circuits
Color - Resin	Black
Gender	Female
Glow-Wire Compliant	No
Keying to Mating Part	None
Lock to Mating Part	No
Material - Resin	PPO
Number of Rows	2
Packaging Type	Bag
Panel Mount	No
Pitch - Mating Interface (in)	0.100 In
Pitch - Mating Interface (mm)	2.54 mm
Pitch - Term. Interface (in)	0.100 In
Pitch - Term. Interface (mm)	2.54 mm
Polarized to Mating Part	No
Ports	1
Stackable	Yes
Temperature Range - Operating	-55°C to +105°C

Electrical	
Current - Maximum per Contact	3A

Material Info

Reference - Drawing Numbers	
Sales Drawing	SD-90143



EU RoHS

ELV and RoHS Compliant

REACH SVHC

Not Reviewed

Halogen-Free

Status

Not Reviewed

China RoHS



Need more information on product environmental compliance?

Email productcompliance@molex.com
For a multiple part number RoHS Certificate of Compliance, [click here](#)

Please visit the [Contact Us](#) section for any non-product compliance questions.

Search Parts in this Series

90143Series


Mates With

C-Grid III™ Header, Dual Row 90122 , 90130 , 90131

Use With

C-Grid III™ Crimp Terminal 90119


PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION



NON-VOIDED OPTIONS					
NO. OF CKTS	PART NUMBER		DIM A	DIM B	DIM C
	NO BUTTONS	WITH BUTTONS			
4	90 I43-0004	90 I43-0104	(2.54)/0.100	(5.08)/0.200	————
6	90 I43-0006	90 I43-0106	(5.08)/0.200	(7.62)/0.300	(2.54)/0.100
8	90 I43-0008	90 I43-0108	(7.62)/0.300	(10.16)/0.400	(5.08)/0.200
10	90 I43-0010	90 I43-0110	(10.16)/0.400	(12.70)/0.500	(7.62)/0.300
12	90 I43-0012	90 I43-0112	(12.70)/0.500	(15.24)/0.600	(10.16)/0.400
14	90 I43-0014	90 I43-0114	(15.24)/0.600	(17.78)/0.700	(12.70)/0.500
16	90 I43-0016	90 I43-0116	(17.78)/0.700	(20.32)/0.800	(15.24)/0.600
18	90 I43-0018	90 I43-0118	(20.32)/0.800	(22.86)/0.900	(17.78)/0.700
20	90 I43-0020	90 I43-0120	(22.86)/0.900	(25.40)/1.000	(20.32)/0.800
22	90 I43-0022	90 I43-0122	(25.40)/1.000	(27.94)/1.100	(22.86)/0.900
24	90 I43-0024	90 I43-0124	(27.94)/1.100	(30.48)/1.200	(25.40)/1.000
26	90 I43-0026	90 I43-0126	(30.48)/1.200	(33.02)/1.300	(27.94)/1.100
28	90 I43-0028	90 I43-0128	(33.02)/1.300	(35.56)/1.400	(30.48)/1.200
30	90 I43-0030	90 I43-0130	(35.56)/1.400	(38.10)/1.500	(33.02)/1.300
32	90 I43-0032	90 I43-0132	(38.10)/1.500	(40.64)/1.600	(35.56)/1.400
34	90 I43-0034	90 I43-0134	(40.64)/1.600	(43.18)/1.700	(38.10)/1.500
36	90 I43-0036	90 I43-0136	(43.18)/1.700	(45.72)/1.800	(40.64)/1.600
38	90 I43-0038	90 I43-0138	(45.72)/1.800	(48.26)/1.900	(43.18)/1.700
40	90 I43-0040	90 I43-0140	(48.26)/1.900	(50.80)/2.000	(45.72)/1.800
42	90 I43-0042	90 I43-0142	(50.80)/2.000	(53.34)/2.100	(48.26)/1.900
44	90 I43-0044	90 I43-0144	(53.34)/2.100	(55.88)/2.200	(50.80)/2.000
46	90 I43-0046	90 I43-0146	(55.88)/2.200	(58.42)/2.300	(53.34)/2.100
48	90 I43-0048	90 I43-0148	(58.42)/2.300	(60.96)/2.400	(55.88)/2.200
50	90 I43-0050	90 I43-0150	(60.96)/2.400	(63.50)/2.500	(58.42)/2.300
52	90 I43-0052	90 I43-0152	(63.50)/2.500	(66.04)/2.600	(60.96)/2.400
54	90 I43-0054	90 I43-0154	(66.04)/2.600	(68.58)/2.700	(63.50)/2.500
56	90 I43-0056	90 I43-0156	(68.58)/2.700	(71.12)/2.800	(66.04)/2.600
58	90 I43-0058	90 I43-0158	(71.12)/2.800	(73.66)/2.900	(68.58)/2.700
60	90 I43-0060	90 I43-0160	(73.66)/2.900	(76.20)/3.000	(71.12)/2.800
62	90 I43-0062	90 I43-0162	(76.20)/3.000	(78.74)/3.100	(73.66)/2.900
64	90 I43-0064	90 I43-0164	(78.74)/3.100	(81.28)/3.200	(76.20)/3.000

1. MATERIAL: POLYPHENYLENE OXIDE 94 VI COLOUR BLACK.
2. 12 CIRCUIT PART SHOWN AS EXAMPLE
3. PRODUCT SPECIFICATION: PS-99020-0001

- INDICATES No. OF CIRCUITS
- INDICATES No. OF POLARISING BUTTONS
 - 0 -- NO BUTTONS
 - 1 -- WITH BUTTONS (4 CKT - 2 BUTTONS)
(6 TO 64 CKT - 4 BUTTONS)
- INDICATES HOUSING TYPE
 - 0 -- INDICATES NO VOIDED CIRCUITS
 - 9 -- INDICATES VOIDED CIRCUIT OPTION



POLARISING BUTTON VERSION
(90143-*|** VERSION)

<div>ADDED NOTE 3</div> <div>EC NO: E2008-0466</div> <div>2008/03/12</div> <div>2008/03/18</div> <div>2008/03/18</div> <div>DRWN: KIERMAN</div> <div>CHKD:</div> <div>APPR: BMAGUIRE</div>		QUALITY SYMBOLS	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM ONLY		SCALE 5:1	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION		
		DESCRIPTION	<div>▽=0</div> <div>▽=0</div>		mmINCH	DRAWN BYDATE		TITLE			
				4 PLACES	± --- ± ---	DB1987/10/06		C-GRID MODR CRP HSG			
				3 PLACES	± --- ± ---	CHECKED BYDATE		DR W/O POL BTTN			
				2 PLACES	± --- ± .004	GMSWEENEY2005/08/31					
				1 PLACE	± 0.1 ± ---	APPROVED BYDATE					
				ANGULAR ± 2 °		JDENNEHY2005/08/31		molex		MOLEX INCORPORATED	
				DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		MATERIAL NO.		DOCUMENT NO.		SHEET NO.	
						SEE CHART		SD-90143		1 OF 1	
		REV				SIZE A?		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION			