


XMS5003X



Sales Region	Worldwide (except Japan)
Series	XMS
Model	XMS500
Status	Production
Feature	for Medical instruments 2MOPP
Options	U channel Class I input Fan supply
Option Lineup	Please refer to here.
Recommended EMC Filter	
Accessories	Please refer to the catalog



Electrical Characteristics	
Input	Single-phase
Input Voltage Range[AC]	90 to 264Vac
Input Voltage Range[DC]	
Efficiency	92% Typ.
Rated Output Voltage[DC]	12Vdc
Output Voltage Range[DC]	
Maximum Output Current	41.6A
Maximum Output Power	500W

Package Type & Size	
Package / Mounting	Open frame
Width(W)	180mm Nom. (7.09in Nom.)
Height(H)	39.5mm Nom. (1.56in Nom.)
Depth(D)	107mm Nom. (4.21in Nom.)
Weight	

Other	
Operating Temp. Range	0 to 50°C
Cooling	Forced air Convection

Safety Standard(Certified)	IEC60601-1
	CSA60601-1
	EN60601-1
	ES60601-1
	UL60601-1
	IEC60950-1
	CSA60950-1
	EN60950-1
	UL60950-1
Safety Standard(Conformed)	IEC60065
	CSA60065
	EN60065
	UL60065
	IEC61010-1
	EN61010-1
Remarks	This page only shows representative characteristics. Please refer to the technical data for detailed specifications and conditions.

! Images are for reference only and show exemplary products.
! This PDF document was created based on the data listed on the TDK Corporation website.
! All specifications are subject to change without notice.