



Recommended PCB Layout

SPECIFICATIONS

- 1.RATING: DC30V 1.0A
- 2.MECHANICAL LIFE: 5,000 CYCLES.
- 3.PACKAGING: 1000PCS/REEL

| ITEM | PART NAME | TER'NO. | QTY. | MATERIAL | FINISHING | REMARK |
|------|-----------|---------|------|-----------------|-----------|--------|
| ③ | Shell | --- | 1 | Phosphor Bronze | Ag Plated | --- |
| ② | Contact | --- | 5 | Phosphor Bronze | Au Plated | --- |
| ① | Housing | --- | 1 | LCP | Black | --- |

| APPROVALS | DATE | TITLE: |
|---------------|-----------|---------------|
| DRAWN JKUNJLU | 2015/6/17 | USB CONNECTOR |
| CHECKED | | |
| APPROVALS | | |

| TOLERANCES ARE | | ANGLE | UNIT: | SCALE: | PROJ: |
|----------------|-------|-------|-------|--------|-------|
| 30~Ø以上 | ±0.30 | | mm | 1:1 | 1 |
| 10~30 | ±0.25 | | | | |
| 5~10 | ±0.20 | ±2' | | | |
| ~5 | ±0.15 | | | | |

| ECN NO. | REV. | DATE. | DESCRIPTION. | CHANGE. | CHECK. | APPRO. |
|---------|------|-------|--------------|---------|--------|--------|
| | A | | NEW | | | |



ELECTRONICS CO.,LTD

