

4

3

2

1

used for:

D-SUB

SW 5
e=5.77

4-40 UNC

5

13

4-40 UNC

SCREW

WASHER $\phi 6/3 \times 0.8$

SPRING RING DIN127 A3

NUT 4-40 UNC
SW 5x2.2

1 SET CONSISTS OF:
2 SCREWS
2 WASHERS
2 SPRING RINGS
2 NUTS

Directive 2002/95/EC
„RoHS“
Compliant

THIS DRAWING MAY NOT BE COPIED OR
REPRODUCED IN ANY WAY, AND MAY NOT
BE PASSED ON TO A THIRD PARTY WITHOUT
WRITTEN PERMISSION.
OWNERSHIP AND COPYRIGHT OF CONEC GmbH

DO NOT ALTER CAD DRAWING BY HAND

CONEC CORPORATION
BRAMPTON, ONTARIO

tolerance



scale:

5:1

material:

COPPER ALLOY
NICKEL PLATED

title:

SCREW LOCKING
Type 1 / 4-40 UNC / 13mm

dwg no:

AutoCAD 2000

DIN-A

16K1A166A

4

sh: 1/1

part no:

160X10359X

				2001	date	name
				drawn	22.03.	Parei
				appd.	22.03.	E. Mickenbecker
				norm		
				d-old		

rev.	description	date	name
------	-------------	------	------

CONEC[®]

4

3

2

1