General Cable

Product Data Sheet

RoHS Compliant Directive 2002/95/EC

Part Number: C9132A Revision Date: 12/12/2012

6C 18 AWG 16/30 TC PVC / OAS / PVC

EXZEL™ EXCEPTIONAL PERFORMANCE

A. CONSTRUCTION

		DIAMETERS
Conductor:	#18 AWG 16/30 Tinned Copper	.046" Nom
Insulation:	.016" Polyvinyl Chloride (PVC)	.078" Nom
Cable Core:	Cable 6/C @ 3.50" LHL w/ clear polyester wrap	.244" Nom
Shield:	18AWG 16/30 TC Drain wire, Aluminum / Polyester foil facing in, 100% coverage	
Jacket:	.032" Polyvinyl Chloride (PVC) jacket Ripcord under Jacket"	.308" Nom
Print Legend:	***CAROL® EXZEL™ -- C9132A -- 6C 18 AWG SHIELDED E105765-H (UL) TYPE CM 105C OR AWM 2464 80C 300V VW-1 --- LL69381 CSA TYPE CMG 105C FT4 -- CE -- -- ROHS -- MADE IN USA (DATE CODE) (TRUMARK SEQUENTIAL FOOTAGE)***	

B. INDUSTRY APPROVALS

National Electrical Code	Article 800
UL Standard 444	Type CM
UL Standard 758	AWM Style 2464
CSA International	Type CMG

C. ELECTRICAL PROPERTIES

Temperature:	CM/CMG: 105C, AWM: 80C
Suggested Working Voltage:	300V
Conductor DCR:	6.81 Ohms/M' @ 20°C
Mutual Capacitance:	32.9 pF/ft. @ 1 kHz

D. COLOR CODE

ITEM	COLOR
1	BLACK
2	RED
3	WHITE
4	GREEN
5	ORANGE
6	BLUE

Note: Data subject to change without notice. Contact your Customer Service representative for latest information.