



KTPS65 Series

65 Watt Universal Input, Desktop Adapter

INPUT SPECIFICATIONS

All specifications are typical at nominal input, full load.

INPUT SPECIFICATIONS

Input Voltage	AC 100 – 240VAC
Input Frequency	50 – 60Hz
Input Current	1.4A Max
Protection	Internal Primary Current Fuse Inrush Limiting

OUTPUT SPECIFICATIONS

Output Voltage	See Chart
Efficiency	CEC Level V, ErP Stage 2, MEPS
Protection	Short Circuit Protection Over Current Protection Over Voltage Protection
Ripple	1 - 2 % Vp-p (max)
Hold-Up Time	10 mS (min)
Transient Response	0.5mS for 50% Load Change(typ)
Load Regulation	± 5% (typ)
Leakage Current	0.25mA @ 2 pin 3.5mA @ 3 pin

GENERAL SPECIFICATIONS

MTBF(Calculated)	50,000 Calculated hours at 25°C by MIL-HDBK-217F
Dielectric Withstanding Voltage	3,000 VAC Primary – Secondary
EMI Conduction & Radiation	Compliance to EN55022 Class B
Harmonic Current	Compliance to EN61000-3-2,3
EMS Immunity	Compliance to EN61000-4- 2,3,4,5,6,8,11
Safety Approvals	UL/cUL/CE/CB/GS/PSE/FCC



FEATURES

- UNIVERSAL INPUT (AC100-240V)
- CEC LEVEL V
- OVER VOLTAGE PROTECTION
- OVER CURRENT PROTECTION
- SHORT CIRCUIT PROTECTION
- ROHS COMPLIANT

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	0°C~+40°C
Storage Temperature	-20°C ~ +80°C
Cooling.	Convection
Operating Humidity	20 – 80% Rh
Storage Humidity	10 – 90% Rh

MECHANICAL SPECIFICATIONS

Case Dimension	L115 x W53 x H38(mm)
Input Configuration	IEC320-C14 (Optional C6 & C8)
DC Cord	18AWG (Optional 16 AWG)
Output Connector	5.5 x 2.1 x 9.5 mm C+



KTPS65 Series

Model Number	Output Voltage	Output Current	Max Output Power
KTPS65-1250DT-3P	12.0V	5.00A	60W
KTPS65-1543DT-3P	15.0V	4.30A	65W
KTPS65-1640DT-3P	16.0V	4.00A	64W
KTPS65-1836DT-3P	18.0V	3.60A	65W
KTPS65-1934DT-3P	19.0V	3.40A	65W
KTPS65-2032DT-3P	20.0V	3.25A	65W
KTPS65-2427DT-3P	24.0V	2.70A	65W

Mechanical Drawing:

