

Y distributor - SAC-4P-Y/2XFS B S21 SCO - 1409204

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Y distributor, 5-position, Plug straight M12 SPEEDCON, A-coded, on Socket straight M12 SPEEDCON, A-coded, PIN 2+4 bridged and Socket straight M12 SPEEDCON, A-coded, PIN 2+4 bridged



Key Commercial Data

Packing unit	1 STK
Minimum order quantity	5 STK
Weight per Piece (excluding packing)	32.0 g
Custom tariff number	85366990
Country of origin	Poland

Technical data

Dimensions

Center distance	21 mm
-----------------	-------

Ambient conditions

Degree of protection	IP65
	IP67

General

Rated current at 40°C	4 A
Rated voltage	60 V
Number of positions	5
Insulation resistance	≥ 100 MΩ
Coding	A - standard
Standards/regulations	M12 connector IEC 61076-2-101
Status display	No

Y distributor - SAC-4P-Y/2XFS B S21 SCO - 1409204

Technical data

General

Overvoltage category	II
Degree of pollution	3
Insertion/withdrawal cycles	≥ 100
Torque	0.4 Nm (M12 connector)

Material


Flammability rating according to UL 94	HB
Contact material	CuZn
Contact surface material	Ni/Au
Contact carrier material	TPU GF
Material of grip body	TPU, hardly inflammable, self-extinguishing
Material, knurls	Zinc die-cast, nickel-plated
Sealing material	NBR

Standards and Regulations

Standard designation	M12 connector
Standards/regulations	IEC 61076-2-101
Flammability rating according to UL 94	HB


Drawings

Schematic diagram




Pin assignment M12 male connector, 5-pos., A-coded, male side

Schematic diagram




Pin assignment M12 socket, 5-pos., PIN 2+4 bridged, A-coded, socket side view

Dimensional drawing



Plug M12 x 1, Y distributor, inner gauge of 21 mm


Circuit diagram



Contact assignment of the M12 Y distributor

Y distributor - SAC-4P-Y/2XFS B S21 SCO - 1409204

Schematic diagram



Layout of connector pin assignments

Classifications

eCl@ss

eCl@ss 4.0	eCl@ss 4.0	27060306
eCl@ss 4.1	eCl@ss 4.1	27060306
eCl@ss 5.0	eCl@ss 5.0	27061801
eCl@ss 5.1	eCl@ss 5.1	27061801
eCl@ss 6.0	eCl@ss 6.0	27061801
eCl@ss 7.0	eCl@ss 7.0	27061801
eCl@ss 8.0	eCl@ss 8.0	27440104
eCl@ss 9.0	eCl@ss 9.0	27440102

ETIM

ETIM 4.0	ETIM 4.0	EC001855
ETIM 5.0	ETIM 5.0	EC002062

UNSPSC

UNSPSC 6.01	UNSPSC 6.01	31251501
UNSPSC 7.0901	UNSPSC 7.0901	31251501
UNSPSC 11	UNSPSC 11	31251501
UNSPSC 12.01	UNSPSC 12.01	31251501
UNSPSC 13.2	UNSPSC 13.2	31251501

Approvals

Approvals

Approvals

UL Listed

Y distributor - SAC-4P-Y/2XFS B S21 SCO - 1409204

Approvals

Ex Approvals

Approvals submitted

Approval details

UL Listed	
Nominal current I _N	4 A
Nominal voltage U _N	30 V

Accessories

Accessories

Protective cap

Screw plug - PROT-MS SCO - 1553129



M12 screw plug with SPEEDCON quick locking for unoccupied M12 sockets of the sensor/actuator cables, boxes and flush-type connectors

Sealing cap - PROT-M12 FS - 1560251



M12 sealing cap for unoccupied M12 plugs of the sensor/actuator cable, flush-type plugs and I/O devices in the field

Screw plug - PROT-M12 MS-PA-CHAIN - 1430899

M12 sealing cap with fixing band, for sensor cables, for free M12 sockets



Y distributor - SAC-4P-Y/2XFS B S21 SCO - 1409204

Accessories

Sealing cap - PROT-M12 FS-PA-CHAIN - 1430873

M12 sealing cap made of plastic with fixing band, for sensor cables, for free M12 sockets



Screwdriver tools

Tool - SAC BIT M12-D15 - 1208432



Nut for assembling sensor/actuator cables with M12 connector and M12 connectors for assembly, with a knurl diameter of 15 mm, for 4 mm hexagonal drive

Torque tool

Torque screwdriver - TSD 04 SAC - 1208429



Torque screwdriver, with preset torque of 0.4 Nm and 4 mm hexagonal drive for M12 connectors