


NT7701H3 TAB Pin assignment

Pin No.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
Name	Dummy	VOL	V12L	V43L	V5L	VSS	L/R	VDD	S/C	EIO2	D0	D1	D2	D3	D4	D5

NT7702N TAB Pin Assignment


Pin No.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
Name	Dummy	VOL	V12L	V43L	V5L	VSS	VDD	S/C	EIO2	D0	D1	D2	D3	D4	D5	D6

- NOTES:
1. SPECIAL CHARACTERISTIC
  2. SAFETY CHARACTERISTIC
  3. CRITICAL DIMENSION
  4. REFERENCE DIMENSION



VARTTRONIX LIMITED

ISSUE	AMENDMENT	DATE



(DOT SIZE FOR CUSTOMER REFERENCE)

Display Type	Reflective, B&W, ZBD
Display Resolution	320x240
Viewing Angle	3 O'CLOCK
Max ratio and bias level	TBD
ICD Controller/Driver	NT7701H3 TAB x 2, NT7702N4 TAB
Logic Voltage (V)	3.3V-5V
LCD Driving Voltage	1.5 ~ 20V
Operation Temperature	0C° to +40 C°
Storage Temperature	-20 C° to +70 C°

TITLE: JCM Module Specification  
 PROJECT NO.: ZBD320240C-01  
 CUSTOMER REF.: XXXXXXXXXXXX-XX

TOLERANCE UNLESS OTHERWISE SPECIFIED:	XX ±0.3
	XXX ±0.1
DIMENSIONS IN MM	ANGULAR ±1°
MATERIAL: N/A	FINISH: N/A
SCALE: 1:1 (NOT IN SCALE)	OVERALL THK: N/A

THIRD ANGLE PROJECTION	NAME	SIGN	DATE
<input checked="" type="checkbox"/>	W.F.S		06.01.13
<input type="checkbox"/>	CHECKED: DANIEL.POOD		
<input type="checkbox"/>	APPROVED: K.P.H		
ITEM NO.: ZBD320240C-01			

DESCRIPTION: ZBD320240C-01 SPEC.  
 FILE NO.: ZBD320240C-01 REV: 0  
 SHEET 1 OF 1