

# Product data sheet

## Characteristics

# 8910DP32V02Y135

Contacteur, Definite Purpose, 30A, 2 pole, 110/120 VAC 50/60 Hz coil, open, DIN rail mount

Product availability : Stock - Normally stocked in distribution facility



Price\* : 111.95 USD



### Main

Product or component type	Definite Purpose Contactor
Line Rated Current	30 A
Number of Poles	2P
Pole contact composition	2 NO
Range of product	DP

### Complementary

Maximum Horse Power Rating	2 hp 115 V AC, 1 phase 5 hp 230 V AC, 1 phase
Locked rotor rated current	125 A 460 V AC 100 A 575 V AC 150 A 277 V AC
[Ue] rated operational voltage	600 V AC
[Uc] control circuit voltage	120 V AC 60 Hz 110 V AC 50 Hz
Phase	1 phase
Electrical connection	Binder head Quick connect terminals
Mounting support	35 mm DIN rail

### Environment

Product certifications	UL Recognized CSA
------------------------	----------------------

### Ordering and shipping details

Category	21356 - 8910 DP 32
----------	--------------------

\* Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Discount Schedule	CP1B
GTIN	00785901192626
Nbr. of units in pkg.	1
Package weight(Lbs)	1 lb(US) (0.45 kg)
Returnability	No
Country of origin	CN

### Packing Units

Package 1 Height	3.20 in (8.128 cm)
Package 1 width	3.50 in (8.890 cm)
Package 1 Length	2.40 in (6.096 cm)

### Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information.

### Contractual warranty

Warranty	18 months
----------	-----------