



Sales Region	Worldwide	
Series	ZWS-BAF	
Status	Production	
Feature		
Option	With chassis model	
Option Lineup	Please refer to here.	
Recommended EMC F	ilter Please refer to here.	
Accessories	Please refer to the catalog	



Electrical Characteristics		
Input Voltage Range[AC]	85 to 265V	
Input Voltage Range[DC]	120 to 370V	
Efficiency	90% Тур.	
Rated Output Voltage[DC]	24V	
Output Voltage Range[DC]	21.6 to 26.4V	
Maximum Output Current	6.3A	
Maximum Output Power	151.2W	

Cases Shape & Size		
Case' ] shape	PC board	
Width(W)	85mm Nom.	
Height(H)	47mm Nom.	
Depth(D)	188mm Nom.	
Weight	560g Typ.	

Other		
Operating Temp. Range	-10 to 70°C	
Cooling	Convection cooling	
	UL60950-1	
Cofety (Cortified)	CSA C22.2 No.60950-1	
Safety Standard(Certified)	EN60950-1	
	EN50178 (OV II)	
Safety Standard(Conformed)	ndard(Conformed) Den-an	
Demortes	This page only shows representative characteristics. Please refer to the	
Remarks	technical data for detailed specifications and conditions.	

! Images are for reference only and show exemplary products. ! This PDF document was created based on the data listed on the TDK Corporation website.

! All specifications are subject to change without notice.