

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [0533250360](#)
Status: **Active**
Description: 2.00mm (.079") Pitch Mi II™ System Wire-to-Board Header, Single Row, Right Angle, Lead-free, 3 Circuits

Documents:
[3D Model](#)
[Drawing \(PDF\)](#)
[Product Specification PS-51090-016 \(PDF\)](#)
[Product Specification PS-52484-021 \(PDF\)](#)
[RoHS Certificate of Compliance \(PDF\)](#)

Agency Certification


CSA LR19980
UL E29179

General

Product Family PCB Headers
Series [53325](#)
Application Wire-to-Board
Product Name Mi II™

Physical

Breakaway No
Circuits (Loaded) 3
Circuits (maximum) 3
Color - Resin Natural
Durability (mating cycles max) 30
First Mate / Last Break No
Flammability 94V-0
Glow-Wire Compliant No
Guide to Mating Part No
Keying to Mating Part None
Lock to Mating Part Yes
Material - Metal Brass
Material - Plating Mating Tin
Material - Plating Termination Tin
Material - Resin Polyester
Number of Rows 1
Orientation Right Angle
PC Tail Length (in) 0.138 In
PC Tail Length (mm) 3.50 mm
PCB Locator No
PCB Retention Yes
PCB Thickness Recommended (in) 0.062 In
PCB Thickness Recommended (mm) 1.60 mm
Packaging Type Tray
Pitch - Mating Interface (in) 0.079 In
Pitch - Mating Interface (mm) 2.00 mm
Plating min: Mating (µin) 40
Plating min: Mating (µm) 1.00
Plating min: Termination (µin) 40
Plating min: Termination (µm) 1.00
Polarized to PCB No
Shrouded Fully
Stackable No
Surface Mount Compatible (SMC) No
Temperature Range - Operating -40°C to +105°C



Series

image - Reference only

EU RoHS
ELV and RoHS
Compliant
REACH SVHC
Contains SVHC: No
Halogen-Free
Status

China RoHS



Need more information on product environmental compliance?

Email productcompliance@molex.com
For a multiple part number RoHS Certificate of Compliance, [click here](#)

Please visit the [Contact Us](#) section for any non-product compliance questions.

Search Parts in this Series
[53325Series](#)

Mates With
[52484](#) Wire-to-Board IDT Recpetacle.,
[51090](#) Crimp Terminal

Termination Interface: Style	Through Hole
Electrical	
Current - Maximum per Contact	2A
Voltage - Maximum	125V
Material Info	
Reference - Drawing Numbers	
Product Specification	PS-51090-016, PS-52484-021, RPS-51090-001, RPS-51090-002, RPS-51090-013, RPS-51090-015, RPS-51090-017, RPS-51090-022, RPS-52484-019, RPS-52484-022, RPS-52484-023, RPS-52484-025, RPS-52484-026, RPS-53324-001
Sales Drawing	SD-53325-002

This document was generated on 04/16/2010

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

DWG. NO. SD-53325-002

E

D

Δ

C

B

DO NOT SCALE DRAWING

8

7

6

5

4

3

2

1

F



E

D

C

B

A




注 記 NOTES

1. 嵌合相手 : 51090-***00, 52484-***1*
MATES WITH
2. 材質
MATERIAL
ウエハー : PBT (ガラス15%入り)
UL94V-0
WAFER : PBT (G.F. 15%), UL94V-0
ピン : 黄銅、スズメッキ
PIN : BRASS, PRE-TINNED
3. キンクは全ピンに交互に付加。2極はキンク無し。
SET KINK ALTERNATELY TO ALL CIRCUITS.
CIRCUIT 2 HAS NO KINK.
4. 製品番号
MATERIAL NO.
53325-***6*
極数CIRCUIT SIZE 色COLOR

無鉛
LEAD FREE

15	33.3	32.1	28	53325-156*	53325-***6*
14	31.3	30.1	26	-146*	
13	29.3	28.1	24	-136*	
12	27.3	26.1	22	-126*	
11	25.3	24.1	20	-116*	
10	23.3	22.1	18	-106*	
9	21.3	20.1	16	-096*	
8	19.3	18.1	14	-086*	
7	17.3	16.1	12	-076*	
6	15.3	14.1	10	-066*	
5	13.3	12.1	8	-056*	
4	11.3	10.1	6	-046*	
3	9.3	8.1	4	-036*	
2	7.3	6.1	2	53325-026*	
極数CKT.	C	B	A	4. MATERIAL NO.	MODEL NO.

<div>1734NO.</div> <div>DRWN:</div> <div>CHK:</div> <div>APPR:</div>				<div>1733NO.</div> <div>DRWN:</div> <div>CHK:</div> <div>APPR:</div>				<div>1732NO.</div> <div>DRWN:</div> <div>CHK:</div> <div>APPR:</div>				<div>1731NO.</div> <div>DRWN:</div> <div>CHK:</div> <div>APPR:</div>				<div>1730NO. J2003-1741</div> <div>DRWN: S.SHIBATA</div> <div>CHK: T.KANEKO</div> <div>APPR: YO. ITO</div> <div>02/12/25</div> <div>02/12/25</div> <div>02/12/25</div>				<div>DESCRIPTION</div>	<div>MATERIAL</div> <div>材料</div> <div>注記参照</div> <div>SEE NOTES</div>				<div>GENERAL TOLERANCES:</div> <div>(UNLESS SPECIFIED)</div> <div>一般公差</div>				<div>SCALE</div> <div>5-1</div>		<div>DESIGN UNITS</div> <div>☒mm ☐INCH</div>		<div> 3RD ANGLE PROJECTION</div>		<div>☐mm ☐INCH</div> <div>☐mm ☐mm</div> <div>☒mm ONLY</div>		<div>OTHER ON CAD ONLY</div>	
																					<div>10 UNDER</div> <div>未 満</div>		<div>±0.2</div>		<div>DRAWN BY & DATE</div> <div>S. Shibata</div> <div>02/12/25</div>		<div>TITLE:</div> <div>2.0 WIRE TO BOARD CONN.</div> <div>WAFER ASS'Y (R/A)</div>											
																	<div>10 OVER</div> <div>以 上</div>		<div>30 UNDER</div> <div>未 満</div>		<div>±0.25</div>		<div>CHECKED BY & DATE</div> <div>J. Miyazawa</div> <div>02/12/25</div>															
																					<div>30 OVER</div> <div>以 上</div>		<div>±0.3</div>		<div>APPROVED BY & DATE</div> <div>Y. Ito</div> <div>02/12/25</div>		<div> MOLEX INCORPORATED</div>											
																					<div>WIRE RANGE</div> <div>適用 電線 範囲</div> <div>— # —</div>		<div>ANGLE</div> <div>角度</div>		<div>±3°</div>		<div>CAD FILENAME</div> <div>SD-53325-002.DGN</div>		<div>MATERIAL NO.</div> <div>SEE CHART</div>		<div>DRAWING NO.</div> <div>SD-53325-002</div>		<div>SHEET NO.</div> <div>1 OF 1</div>					
								<div>A</div>				<div>REV</div>	<div>INS. RANGE</div> <div>被 覆 外 径</div> <div>— # —</div>								<div>THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.</div>						<div>SIZE</div> <div>B</div>											