

# MJE243 - NPN, MJE253 - PNP

## Complementary Silicon Power Plastic Transistors

These devices are designed for low power audio amplifier and low-current, high-speed switching applications.

### Features

- High Collector-Emitter Sustaining Voltage –  
 $V_{CE(sus)} = 100 \text{ Vdc (Min)}$
- High DC Current Gain @  $I_C = 200 \text{ mAdc}$   
 $h_{FE} = 40 - 200$   
 $= 40 - 120$
- Low Collector-Emitter Saturation Voltage –  
 $V_{CE(sat)} = 0.3 \text{ Vdc (Max) @ } I_C = 500 \text{ mAdc}$
- High Current Gain Bandwidth Product –  
 $f_T = 40 \text{ MHz (Min) @ } I_C = 100 \text{ mAdc}$
- Annular Construction for Low Leakages  
 $I_{CBO} = 100 \text{ nAdc (Max) @ Rated } V_{CB}$
- Pb-Free Packages are Available\*

### MAXIMUM RATINGS

| Rating                                                                                | Symbol         | Value       | Unit                      |
|---------------------------------------------------------------------------------------|----------------|-------------|---------------------------|
| Collector-Emitter Voltage                                                             | $V_{CEO}$      | 100         | Vdc                       |
| Collector-Base Voltage                                                                | $V_{CB}$       | 100         | Vdc                       |
| Emitter-Base Voltage                                                                  | $V_{EB}$       | 7.0         | Vdc                       |
| Collector Current – Continuous<br>– Peak                                              | $I_C$          | 4.0<br>8.0  | Adc                       |
| Base Current                                                                          | $I_B$          | 10          | Adc                       |
| Total Power Dissipation @ $T_C = 25^\circ\text{C}$<br>Derate above $25^\circ\text{C}$ | $P_D$          | 15<br>120   | W<br>mW/ $^\circ\text{C}$ |
| Total Power Dissipation @ $T_A = 25^\circ\text{C}$<br>Derate above $25^\circ\text{C}$ | $P_D$          | 1.5<br>12   | W<br>mW/ $^\circ\text{C}$ |
| Operating and Storage Junction<br>Temperature Range                                   | $T_J, T_{stg}$ | -65 to +150 | $^\circ\text{C}$          |

### THERMAL CHARACTERISTICS

| Characteristic                             | Symbol        | Max  | Unit               |
|--------------------------------------------|---------------|------|--------------------|
| Thermal Resistance, Junction-to-Case       | $\theta_{JC}$ | 8.34 | $^\circ\text{C/W}$ |
| Thermal Resistance,<br>Junction-to-Ambient | $\theta_{JA}$ | 83.4 | $^\circ\text{C/W}$ |

Maximum ratings are those values beyond which device damage can occur. Maximum ratings applied to the device are individual stress limit values (not normal operating conditions) and are not valid simultaneously. If these limits are exceeded, device functional operation is not implied, damage may occur and reliability may be affected.


\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.



ON Semiconductor®


<http://onsemi.com>

**4.0 AMPERES  
POWER TRANSISTORS  
COMPLEMENTARY SILICON  
100 VOLTS, 15 WATTS**



TO-225  
CASE 77  
STYLE 1

### MARKING DIAGRAM



Y = Year  
WW = Work Week  
JE2x3 = Device Code  
x = 4 or 5  
G = Pb-Free Package

### ORDERING INFORMATION

| Device  | Package             | Shipping      |
|---------|---------------------|---------------|
| MJE243  | TO-225              | 500 Units/Box |
| MJE243G | TO-225<br>(Pb-Free) | 500 Units/Box |
| MJE253  | TO-225              | 500 Units/Box |
| MJE253G | TO-225<br>(Pb-Free) | 500 Units/Box |

Preferred devices are recommended choices for future use and best overall value.

# MJE243 – NPN,      MJE253 – PNP

## ELECTRICAL CHARACTERISTICS (T<sub>C</sub> = 25°C unless otherwise noted)

| Characteristic                                                                                                                                         | Symbol                | Min      | Max        | Unit     |
|--------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------|----------|------------|----------|
| <b>OFF CHARACTERISTICS</b>                                                                                                                             |                       |          |            |          |
| Collector–Emitter Sustaining Voltage<br>(I <sub>C</sub> = 10 mAdc, I <sub>B</sub> = 0)                                                                 | V <sub>CEO(sus)</sub> | 100      | –          | V        |
| Collector Cutoff Current<br>(V <sub>CB</sub> = 100 Vdc, I <sub>E</sub> = 0)<br>(V <sub>CE</sub> = 100 Vdc, I <sub>E</sub> = 0, T <sub>C</sub> = 125°C) | I <sub>CBO</sub>      | –<br>–   | 0.1<br>0.1 | μA<br>mA |
| Emitter Cutoff Current (V <sub>BE</sub> = 7.0 Vdc, I <sub>C</sub> = 0)                                                                                 | I <sub>EBO</sub>      | –        | 0.1        | μAdc     |
| <b>ON CHARACTERISTICS</b>                                                                                                                              |                       |          |            |          |
| DC Current Gain<br>(I <sub>C</sub> = 200 mAdc, V <sub>CE</sub> = 1.0 Vdc)<br>(I <sub>C</sub> = 1.0 Adc, V <sub>CE</sub> = 1.0 Vdc)                     | h <sub>FE</sub>       | 40<br>15 | 180<br>–   | –        |
| Collector–Emitter Saturation Voltage<br>(I <sub>C</sub> = 500 mAdc, I <sub>B</sub> = 50 mAdc)<br>(I <sub>C</sub> = 1.0 Adc, I <sub>B</sub> = 100 mAdc) | V <sub>CE(sat)</sub>  | –<br>–   | 0.3<br>0.6 | V        |
| Base–Emitter Saturation Voltage<br>(I <sub>C</sub> = 2.0 Adc, I <sub>B</sub> = 200 mAdc)                                                               | V <sub>BE(sat)</sub>  | –        | 1.8        | V        |
| Base–Emitter On Voltage<br>(I <sub>C</sub> = 500 mAdc, V <sub>CE</sub> = 1.0 Vdc)                                                                      | V <sub>BE(on)</sub>   | –        | 1.5        | V        |
| <b>DYNAMIC CHARACTERISTICS</b>                                                                                                                         |                       |          |            |          |
| Current–Gain – Bandwidth Product<br>(I <sub>C</sub> = 100 mAdc, V <sub>CE</sub> = 10 Vdc, f <sub>test</sub> = 10 MHz)                                  | f <sub>T</sub>        | 40       | –          | MHz      |
| Output Capacitance<br>(V <sub>CB</sub> = 10 Vdc, I <sub>E</sub> = 0, f = 0.1 MHz)                                                                      | C <sub>ob</sub>       | –        | 50         | pF       |

# MJE243 – NPN, MJE253 – PNP




Figure 1. Power Derating




Figure 2. Switching Time Test Circuit




Figure 3. Turn-On Time




Figure 4. Thermal Response




Figure 5. Active Region Safe Operating Area




Figure 6. Turn-Off Time




Figure 7. Capacitance

There are two limitations on the power handling ability of a transistor: average junction temperature and second breakdown. Safe operating area curves indicate  $I_C - V_{CE}$  limits of the transistor that must be observed for reliable operation; i.e., the transistor must not be subjected to greater dissipation than the curves indicate.

The data of Figure 5 is based on  $T_{J(pk)} = 150^\circ\text{C}$ ;  $T_C$  is variable depending on conditions. Second breakdown pulse limits are valid for duty cycles to 10% provided  $T_{J(pk)} \leq 150^\circ\text{C}$ .  $T_{J(pk)}$  may be calculated from the data in Figure 4. At high case temperatures, thermal limitations will reduce the power that can be handled to values less than the limitations imposed by second breakdown.



NPN  
MJE243PNP  
MJE253

Figure 8. DC Current Gain





Figure 9. "On" Voltages






Figure 10. Temperature Coefficients

# MJE243 – NPN, MJE253 – PNP

## PACKAGE DIMENSIONS

TO-225  
CASE 77-09  
ISSUE Z



### NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. 077-01 THRU -08 OBSOLETE, NEW STANDARD 077-09.

| DIM | INCHES    |       | MILLIMETERS |       |
|-----|-----------|-------|-------------|-------|
|     | MIN       | MAX   | MIN         | MAX   |
| A   | 0.425     | 0.435 | 10.80       | 11.04 |
| B   | 0.295     | 0.305 | 7.50        | 7.74  |
| C   | 0.095     | 0.105 | 2.42        | 2.66  |
| D   | 0.020     | 0.026 | 0.51        | 0.66  |
| F   | 0.115     | 0.130 | 2.93        | 3.30  |
| G   | 0.094 BSC |       | 2.39 BSC    |       |
| H   | 0.050     | 0.095 | 1.27        | 2.41  |
| J   | 0.015     | 0.025 | 0.39        | 0.63  |
| K   | 0.575     | 0.655 | 14.61       | 16.63 |
| M   | 5° TYP    |       | 5° TYP      |       |
| Q   | 0.148     | 0.158 | 3.76        | 4.01  |
| R   | 0.045     | 0.065 | 1.15        | 1.65  |
| S   | 0.025     | 0.035 | 0.64        | 0.88  |
| U   | 0.145     | 0.155 | 3.69        | 3.93  |
| V   | 0.040     | ---   | 1.02        | ---   |

### STYLE 1:

1. EMITTER
2. COLLECTOR
3. BASE

ON Semiconductor and  are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## PUBLICATION ORDERING INFORMATION

### LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor  
P.O. Box 5163, Denver, Colorado 80217 USA  
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada  
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada  
Email: [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

N. American Technical Support: 800-282-9855 Toll Free  
USA/Canada  
Europe, Middle East and Africa Technical Support:  
Phone: 421 33 790 2910  
Japan Customer Focus Center  
Phone: 81-3-5773-3850

ON Semiconductor Website: [www.onsemi.com](http://www.onsemi.com)

Order Literature: <http://www.onsemi.com/orderlit>

For additional information, please contact your local Sales Representative