2N6426, 2N6427

2N6426 is a Preferred Device

Darlington Transistors


NPN Silicon

Features


- These are Pb−Free Devices*

ON Semiconductor®

http://onsemi.com



TO−92
CASE 29
STYLE 1



STRAIGHT LEAD
BULK PACK

BENT LEAD
TAPE & REEL
AMMO PACK

MAXIMUM RATINGS

Rating	Symbol	Value	Unit
Collector − Emitter Voltage	V_{CEO}	40	Vdc
Collector − Base Voltage	V_{CBO}	40	Vdc
Emitter − Base Voltage	V_{EBO}	12	Vdc
Collector Current − Continuous	I_C	500	mAdc
Total Device Dissipation @ T_A = 25°C Derate above 25°C	P_D	625 5.0	mW mW/°C
Total Device Dissipation @ T_C = 25°C Derate above 25°C	P_D	1.5 12	W mW/°C
Operating and Storage Junction Temperature Range	T_J, T_{stg}	−55 to +150	°C


THERMAL CHARACTERISTICS

Characteristic	Symbol	Max	Unit
Thermal Resistance, Junction−to−Ambient	$R_{\theta JA}$	200	°C/W
Thermal Resistance, Junction−to−Case	$R_{\theta JC}$	83.3	°C/W

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

*For additional information on our Pb−Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

MARKING DIAGRAM



x = 6 or 7
A = Assembly Location
Y = Year
WW = Work Week
▪ = Pb−Free Package

(Note: Microdot may be in either location)

ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 5 of this data sheet.

Preferred devices are recommended choices for future use and best overall value.

© Semiconductor Components Industries, LLC, 2007

ELECTRICAL CHARACTERISTICS (T_A = 25°C unless otherwise noted)

Characteristic		Symbol	Min	Typ	Max	Unit
OFF CHARACTERISTICS						
Collector−Emitter Breakdown Voltage, (Note 1) (I_C = 10 mAdc, V_{BE} = 0)		$V_{(BR)CEO}$	40	−	−	Vdc
Collector−Base Breakdown Voltage (I_C = 100 μAdc, I_E = 0)		$V_{(BR)CBO}$	40	−	−	Vdc
Emitter−Base Breakdown Voltage (I_E = 10 μAdc, I_C = 0)		$V_{(BR)EBO}$	12	−	−	Vdc
Collector Cutoff Current (V_{CE} = 25 Vdc, I_B = 0)		I_{CES}	−	−	1.0	μAdc
Collector Cutoff Current (V_{CB}= 30 Vdc, I_E = 0)		I_{CBO}	−	−	50	nAdc
Emitter Cutoff Current (V_{EB}= 10 Vdc, I_C = 0)		I_{EBO}	−	−	50	nAdc
ON CHARACTERISTICS						
DC Current Gain, (Note 1)		h_{FE}				−
(I_C = 10 mAdc, V_{CE} = 5.0 Vdc)	2N6426		20,000	−	200,000	
	2N6427		10,000	−	100,000	
(I_C = 100 mAdc, V_{CE} = 5.0 Vdc)	2N6426		30,000	−	300,000	
	2N6427		20,000	−	200,000	
(I_C = 500 mAdc, V_{CE} = 5.0 Vdc)	2N6426		20,000	−	200,000	
	2N6427		14,000	−	140,000	
Collector−Emitter Saturation Voltage		$V_{CE(sat)}$				Vdc
(I_C = 50 mAdc, I_B = 0.5 mAdc)			−	0.71	1.2	
(I_C = 500 mAdc, I_B = 0.5 mAdc			−	0.9	1.5	
Base−Emitter Saturation Voltage (I_C = 500 mAdc, I_B = 0.5 mAdc)		$V_{BE(sat)}$	−	1.52	2.0	Vdc
Base−Emitter On Voltage (I_C = 50 mAdc, V_{CE} = 5.0 Vdc)		$V_{BE(on)}$	−	1.24	1.75	Vdc
SMALL−SIGNAL CHARACTERISTICS						
Output Capacitance (V_{CB} = 10 Vdc, I_E = 0, f = 1.0 MHz)		C_{obo}	−	5.4	7.0	pF
Input Capacitance (V_{EB} = 1.0 Vdc, I_C = 0, f = 1.0 MHz)		C_{ibo}	−	10	15	pF
Input Impedance		h_{ie}				kΩ
(I_C = 10 mAdc, V_{CE} = 5.0 Vdc, f = 1.0 kHz)	2N6426		100	−	2000	
	2N6427		50	−	1000	
Small−Signal Current Gain		hfe				−
(I_C = 10 mAdc, V_{CE} = 5.0 Vdc, f = 1.0 kHz)	2N6426		20,000	−	−	
	2N6427		10,000	−	−	
Current−Gain − High Frequency		$\|h_{fe}\|$				−
(I_C = 10 mAdc, V_{CE} = 5.0 Vdc, f = 100 MHz)	2N6426		1.5	2.4	−	
	2N6427		1.3	2.4	−	
Output Admittance (I_C = 10 mAdc, V_{CE} = 5.0 Vdc, f = 1.0 kHz)		h_{oe}	−	−	1000	μmhos
Noise Figure (I_C = 1.0 mAdc, V_{CE} = 5.0 Vdc, R_S = 100 kΩ, f = 1.0 kHz)		NF	−	3.0	10	dB

1. Pulse Test: Pulse Width ≤ 300 μs; Duty Cycle ≤ 2.0%.




Figure 1. Transistor Noise Model

NOISE CHARACTERISTICS

(V_{CE} = 5.0 Vdc, T_A = 25°C)




Figure 2. Noise Voltage




Figure 3. Noise Current




Figure 4. Total Wideband Noise Voltage




Figure 5. Wideband Noise Figure

SMALL−SIGNALCHARACTERISTICS




Figure 6. Capacitance




Figure 7. High Frequency Current Gain




Figure 8. DC Current Gain




Figure 9. Collector Saturation Region




Figure 10. “On” Voltages




Figure 11. Temperature Coefficients




Figure 12. Thermal Response





Figure 13. Active Region Safe Operating Area



Design Note: Use of Transient Thermal Resistance Data


ORDERING INFORMATION

Device	Package	Shipping†
2N6426G	TO−92 (Pb−Free)	5,000 Units / Bulk
2N6426RLRAG	TO−92 (Pb−Free)	2,000 / Tape & Ammo
2N6427G	TO−92 (Pb−Free)	5,000 Units / Bulk
2N6427RLRAG	TO−92 (Pb−Free)	2,000 / Tape & Ammo


†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

PACKAGE DIMENSIONS

TO−92 (TO−226)
CASE 29−11
ISSUE AM




STRAIGHT LEAD
BULK PACK




SECTION X−X

NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. CONTOUR OF PACKAGE BEYOND DIMENSION R IS UNCONTROLLED.
4. LEAD DIMENSION IS UNCONTROLLED IN P AND BEYOND DIMENSION K MINIMUM.

	INCHES		MILLIMETERS	
DIM	MIN	MAX	MIN	MAX
A	0.175	0.205	4.45	5.20
B	0.170	0.210	4.32	5.33
C	0.125	0.165	3.18	4.19
D	0.016	0.021	0.407	0.533
G	0.045	0.055	1.15	1.39
H	0.095	0.105	2.42	2.66
J	0.015	0.020	0.39	0.50
K	0.500	---	12.70	---
L	0.250	---	6.35	---
N	0.080	0.105	2.04	2.66
P	---	0.100	---	2.54
R	0.115	---	2.93	---
V	0.135	---	3.43	---



BENT LEAD
TAPE & REEL
AMMO PACK



SECTION X−X

NOTES:
1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: MILLIMETERS.
3. CONTOUR OF PACKAGE BEYOND DIMENSION R IS UNCONTROLLED.
4. LEAD DIMENSION IS UNCONTROLLED IN P AND BEYOND DIMENSION K MINIMUM.

	MILLIMETERS	
DIM	MIN	MAX
A	4.45	5.20
B	4.32	5.33
C	3.18	4.19
D	0.40	0.54
G	2.40	2.80
J	0.39	0.50
K	12.70	---
N	2.04	2.66
P	1.50	4.00
R	2.93	---
V	3.43	---

STYLE 1:
PIN 1. EMITTER
2. BASE
3. COLLECTOR

ON Semiconductor and ON are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. “Typical” parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including “Typicals” must be validated for each customer application by customer’s technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:
Literature Distribution Center for ON Semiconductor
P.O. Box 5163, Denver, Colorado 80217 USA
Phone: 303−675−2175 or 800−344−3860 Toll Free USA/Canada
Fax: 303−675−2176 or 800−344−3867 Toll Free USA/Canada
Email: orderlit@onsemi.com

N. American Technical Support: 800−282−9855 Toll Free USA/Canada
Europe, Middle East and Africa Technical Support:
Phone: 421 33 790 2910
Japan Customer Focus Center
Phone: 81−3−5773−3850

ON Semiconductor Website: **www.onsemi.com**

Order Literature: http://www.onsemi.com/orderlit

For additional information, please contact your local Sales Representative

2N6426/D