





Rev	AWO #	Description	Date	Appr
-		RELEASED	10/01/10	

APPROVED: _____
 DATE: _____ TITLE: _____



SPECIFICATIONS:
 Material: PBT, rated UL 94V-0
 Insulator color: Black
 Contacts: Brass
 Plating: Gold flash over Nickel underplate overall

Electrical:
 Operating voltage: 250 VAC max.
 Current rating: 1 Amp max.
 Contact resistance: 20 mohms max. initial
 Insulation resistance: 5,000 Mohms min.
 Dielectric withstanding voltage: 500 VAC for 1 minute

Temperature Rating:
 Operating temperature: -40°C to +105°C
 Environmental:
 Lead free, RoHS compliant
 Recommended soldering temp: 235°C for 5 seconds



Positions: 8, 10, 20, 26, 30, 34, 40, 44, 50, 60, 68, 80, 100
 A = .050 [1.27] x No. of Spaces
 B = .050 [1.27] x No. of Spaces + .366 [9.29]

UNLESS OTHERWISE SPECIFIED
 ALL DIMENSIONS ARE INCHES [MM]
 TOLERANCES: EXCEPT AS NOTED

INCHES	HOLDS	±	±
.10	ØXX	± .10	
.020	ØXX	± .015	
.015	ØXXX	± .010	

APPROVALS

DATE	DATE
10/01/10	

ADAM TECH
 909 Railway Avenue, Union, NJ 07083
 Phone: 908-687-5000 Fax: 908-687-5710

TITLE: .050" x .100" BOX HEADER, GOLD PLATED, RIGHT ANGLE MOUNT, PCB TYPE

DRAWN	DATE
DY	10/01/10

CHECKED	DATE

APPROVED	DATE

SIZE	PART NO.	REV.
X	HBHR-A1-XX-H-G	-

REF.	SCALE	SHEET
S0004TT	NTS	1 OF 1