
PIN Silicon Photodiode
Type OP993





Features

- Wide receiving angle
- Linear response vs. irradiance
- Fast switching time
- TO-18 equivalent package style

Description

The OP993 photodiode consists of a PIN silicon photodiode mounted in a dark blue plastic injection molded shell package. The wide receiving angle provides excellent on-axis coupling. The sensors are 100% production tested for close correlation with Optek emitters.

Optek's packaging process provides excellent optical and mechanical axis alignment. The shell also provides excellent optical lens surface, control of chip placement, and consistency of external package dimensions.


Absolute Maximum Ratings (T_A = 25° C unless otherwise noted)

Reverse Breakdown Voltage . . . . . 60 V
Storage and Operating Temperature Range . . . . . -40° C to +100° C
Lead Soldering Temperature [1/16 inch (1.6 mm) from case for 5 sec. with soldering iron] . . . . . 260° C(1)
Power Dissipation . . . . . 100 mW(2)

Notes:
(1) RMA flux is recommended. Duration can be extended to 10 sec. max. when flow soldering. Max. 20 grams force may be applied to leads when soldering.
(2) Derate linearly 1.67 mW/° C above 25° C.
(3) Light source is an unfiltered GaAlAs emitting diode operating at peak emission wavelength of 890nm and $E_{e(APT)}$ of 1.7 mW/cm^2 average within a .250" dia. aperture.
(4) This dimension is held to within ± 0.005" on the flange edge and may vary up to ± 0.020" in the area of the leads.


Typical Performance Curves

Relative Response vs. Wavelength



λ - Wavelength - nm

Coupling Characteristics OP993 and OP293



Distance Between Lens tips - inches

Type OP993


Electrical Characteristics (T_A = 25° C unless otherwise noted)

SYMBOL	PARAMETER	MIN	TYP	MAX	UNITS	TEST CONDITIONS
I_L	Reverse Light Current	12.5		28.5	µA	V_R = 5 V, E_e = 1.7 mW/cm^2(3)
I_D	Reverse Dark Current		1	60	nA	V_R = 30 V, E_e = 0
$V_{(BR)}$	Reverse Breakdown Voltage	60			V	I_R = 100 µA
V_F	Forward Voltage			1.2	V	I_F = 1 mA
C_T	Total Capacitance		4		pF	V_R = 20 V, E_e = 0, f = 1.0 MHz
t_r, t_f	Rise Time, Fall Time		5		ns	V_R = 20 V, λ = 850 nm, R_L = 50 Ω


PHOTOSENSORS

Typical Performance Curves


Normalized Light Current vs Reverse Voltage




Total Capacitance vs Reverse Voltage




Normalized Light and Dark Current vs Ambient Temperature




Light Current vs. Irradiance



Switching Time Test Circuit



Light Current vs. Angular Displacement



Optek reserves the right to make changes at any time in order to improve design and to supply the best product possible.

Optek Technology, Inc. 1215 W. Crosby Road Carrollton, Texas 75006 (972)323-2200 Fax (972)323-2396