

IEC C14 to IEC C15 Power Cable - Heavy Duty, 15A, 250V, 14 AWG, 3 ft., Green

MODEL NUMBER: P018-003-AGN



Connects a PDU or UPS system with a C14 input port to network hardware, such as computers, servers and storage drives, with C15 power connectors.

Description

The P018-003-AGN Heavy-Duty Computer Power Cord features a green SJT jacket and fully molded green ends, allowing you to easily identify your connections in a crowded rack or workstation. It features a C14 male connector on one end and a C15 female connector on the other for attaching a high-voltage computer, server or storage drive to a PDU or UPS system.

This three-foot 15A cord supports voltages up to 250V. It's UL-listed and features a flexible SJT jacket and 14 AWG wire for easy routing through tight areas. The P018-003-AGN is recommended for Cisco, HP and other hardware that use C15 power connectors.

Features

Safe, Reliable Power Solution

- Connects PDU or UPS system with C14 input to network hardware with C15 power connectors
- Ideal for replacing an old or lost cord
- Recommended for Cisco, HP and other C15-compatible hardware

Color-Coded Cable and Connectors

- Colored green for easy identification in crowded rack or workstation

Optimum Construction

- 14 AWG wire
- Flexible SJT jacket
- 250V/15A rating

Highlights

- Easy-to-identify green SJT jacket and fully molded green ends
- Flexible 14 AWG wire for easy routing
- 250V/15A rating
- UL-listed
- Recommended for Cisco®, HP and other C15-compatible hardware

Package Includes

- P018-003-AGN Heavy-Duty Computer Power Cord, Green, 3 ft.



- UL-listed

Specifications

| OVERVIEW | |
|------------------------------------|------------------------------|
| UPC Code | 037332199119 |
| Country/Region | North America |
| INPUT | |
| Maximum Input Amps | 15 |
| Cable Length (ft.) | 3 |
| Cable Length (m) | 0.9 |
| Cable Length (in.) | 36 |
| Voltage Compatibility (VAC) | 250 |
| Cable Length (cm) | 91.44 |
| PHYSICAL | |
| Power Cord Jacket Type | SJT |
| Wire Gauge (AWG) | 14 |
| Wire Gauge (OD - mm ²) | 2.08 |
| Shipping Dimensions (hwd / in.) | 9.90 x 7.00 x 0.50 |
| Shipping Dimensions (hwd / cm) | 25.15 x 17.78 x 1.27 |
| Shipping Weight (lbs.) | 0.44 |
| Shipping Weight (kg) | 0.20 |
| Color | Green |
| Number of Conductors | 3 |
| ENVIRONMENTAL | |
| Operating Temperature Range | -4 F to 221 F (-20 TO 105 C) |
| Storage Temperature Range | -4 F to 221 F (-20 TO 105 C) |
| Operating Humidity Range | 10-85% RH |
| Storage Humidity Range | 10-85% RH |
| CONNECTIONS | |
| Side A - Connector 1 | IEC-320-C14 |
| Side B - Connector 1 | IEC-320-C15 |



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

| SPECIAL FEATURES | |
|-------------------------------------|---------------------------|
| High Voltage | Yes |
| Heavy-Duty | Yes |
| Locking Plug | No |
| WARRANTY | |
| Product Warranty Period (Worldwide) | Lifetime limited warranty |

© 2019 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>