



RECOMMENDE PCB LAYOUT
TDP VIEW<XX±0.05>

- NOTES:
- 1.0 MAIN BODY PART MATERIAL INSULATOR: THERMOPLASTIC UL 94V-0 CONTACT TERMINAL: COPPER ALLOY SHELL: STAINLESS STEEL
 - 2.0 RATING:
 - 2.1 VOLTAGE:10 VAC (rms)
 - 2.2 CURRENT: 0.5 AMPERES MAX. PER CONTACT
 - 2.3 OPERATION TEMPERATURERANGE:-25~+90
 - 3.0 ELECTRIC CHARACTERISTIC:
 - 3.1 CONTACT RESISTANCE:100mΩ MAX.
 - 3.2 INSULATION RESISTANCE: 1000MΩ MIN.
 - 3.3 DIELECTRIC WITHSTANDING VOLTAGE:500V AC FOR 1 MINUTE
 - 4.0 OPERATION LIFE: 10000 CYCLES
 - 5.0 PLATING OF CONTACT: CONTACT AREA Au 5u" Min. TERMINATION AREA Gold Flash. UNDERPLATED NICKEL 50u"~100u" MIN.
 - 6.0 PACKING: TAPE&REEL



TOLERANCE TABLE

.0	±0.25
.00	±0.2
.000	±0.1

APPROVED:	DATE:	 深圳市如科盟实业有限公司 CHANKUANGMENG INDUSTRIAL CO., LTD
CHECKED:	DATE:	
DRAWN:	DATE:	TITLE:
hh-H	2019-02-19	SIM-6P 卡座 2.5H 全塑
PROD. P/N		UNIT
mm		SCALE
free		REV. A
FILE NO.		