

Multi-Frequency Processor

BIS V-6110-063-C002
Order Code: BIS00U9





1) Tightening torque

Basic features

Approval/Conformity	CE EAC cULus WEEE
EN 55011	Size 1, Cl. A
EN 55016-2-3	EN61000-6-4
Principle of operation	Processor unit

Display/Operation

Function indicator	Run EtherCAT, LED green Ready, LED green Error EtherCAT, LED red Link/Activity ECAT Out, LED green Link/Activity ECAT In, LED green

Electrical connection

Connection (COM 1)	ECAT In: M12x1-Female, 4-pin, D-coded
Connection (COM 2)	ECAT Out: M12x1-Female, 4-pin, D-coded
Connection (IO-Link/Service)	M12x1-Female, 5-pin, A-coded
Connection (supply voltage IN)	7/8"-Male, 5-pin
Connection slots	H1: M12x1-Female, 5-pin H2: M12x1-Female, 5-pin H3: M12x1-Female, 5-pin H4: M12x1-Female, 5-pin
Connector port 01, note type	for all VU/VM/VL-3… with connector, 4-pin

Multi-Frequency Processor

BIS V-6110-063-C002
Order Code: BIS00U9

Electrical data

Current consumption typ. at 24 V DC	150 mA
EN 61000-4-2/3/4/5/6	Severity level 4A/3A/4A/2A/3A
EN 61000-4-2/4/5/6	Severity level 2B/3B/2A/3A
IO-Link function	Master (max. 500 mA)
Nominal voltage	24 VDC
Operating voltage Ub	24 V DC LPS Class 2
Residual ripple max.	10 %

Environmental conditions

Ambient temperature	0 °C...60 °C
Continuous shock load	yes
EN 60068-2-27, Shock	yes
EN 60068-2-32 Free fall	yes
EN 60068-2-6, Vibration	yes
EN 61000-4-3 (1400...2000 MHz)	Severity level 3A
EN 61000-4-3 (2000...2700MHz)	Severity level 2A
EN 61000-4-3, 80...1000 MHz	Severity level 3A
IP rating	IP65, with connector

Functional safety

MTTF (40 °C)	33.1 a

Interface

Interface	EtherCAT IO-Link 1.1

Material

Housing material	Zinc, Die casting

Mechanical data


Application weight	750.00 g
Dimension	48 x 62 x 172 mm

Remarks

When installing, the technical standards and regulations of the corresponding countries must be observed.
Values are under rated conditions unless otherwise specified.
Current consumption when 4 read/write heads and IO-Link device are connected to the IO-Link port max. 2 A
For more information about MTTF and B10d see MTTF / B10d Certificate

Indication of the MTTF- / B10d value does not represent a binding composition and/or life expectancy assurance; these are simply experiential values with no warranty implications. These declared values also do not extend the expiration period for defect claims or affect it in any way.

Connector Drawings




1) 2)

IO-Link/ Service

1 — VP (+ 24V DC)
2 — USB-
3 — 0V
4 — Q/C (IO/Link)
5 — USB+

1) View towards connector
2) Female 5-pin/ Function




1) 2)

H1...H4

1 — VP (+24V DC)
2 — A (RS485)
3 — 0V
4 — B (RS485)
5 — N.C.

1) View towards connector
2) Female 5-pin/ Function




2)

POWER

1 — 0V
2 — 0V
3 — FE
4 — + 24V DC
5 — n.c

1) View towards connector
2) Male 5-pin/ Function



ECAT In/Out

2)

1 — +TX
2 — +RX
3 — -TX
4 — -RX

1) View towards connector
2) Female
3) Coding D