

DPX15-24WS3P3



Sales Region	Worldwide (except Japan)
Series	DPX
Model	DPX15
Status	Production
Option	
Option Lineup	Please refer to here.
Recommended EMC Filter	
Accessories	Please refer to the catalog



Electrical Characteristics

Nominal Input Voltage[DC]	24Vdc
Input Voltage Range[DC]	9.5 to 36Vdc
Efficiency	84% Typ.
Rated Output Voltage[DC]	3.3Vdc
Output Voltage Range[DC]	3.234 to 3.366Vdc
Output Current Range	0 to 4.5A
Maximum Ripple Noise	50mV
Maximum Output Power	15W
Withstanding Voltage1	Input - Case: 1600VDC: 1min.
Withstanding Voltage2	Input - Output: 1600VDC: 1min.
Withstanding Voltage3	Output - Case: 1600VDC: 1min.

Package Type & Size

Package / Mounting	DIN rail
Width(W)	125mm Nom. (4.92in Nom.)
Height(H)	57.6mm Nom. (2.27in Nom.)
Depth(D)	24.5mm Nom. (0.96in Nom.)
Weight	147.5g Typ.
Industry Standard Size	
Terminal Style	Block terminal

Other

Operating Temp. Range	-40 to 95°C
Isolation	Isolated
Feature	MIL-STD-810F EN55022 Class B
Safety Standard(Certified)	IEC60950-1 EN60950-1 UL60950-1

Remarks

This page only shows representative characteristics. Please refer to the technical data for detailed specifications and conditions.