



额定负荷 Rating	DC 12V/50mA
接触电阻 Contact Resistance	100mΩ max.
绝缘电阻 Insulation resistance	DC100V 60S 100MΩ min.
抗电强度 Dielectric strength	AC250V(50-60HZ) 60S min.
操作力 Operation force	160±30gf ▶250±50gf
寿命试验 Operating Life	100,000 cycles 70,000 cycles
行程 Travels	0.25±0.1mm

10
9.0
8.5
8.0
7.5
7.0
6.5
6.0
5.5
5.0
4.5
4.3
高度G(mm)

F	盖板	2IC1	PPA 黑	1	
E	按钮	2ID1	PPA 黑	1	
D	防水垫	2IF1	硅橡胶	1	
C	簧片	HE12	进口不锈钢覆银	1	
B	底座	2IB1	PPA 黑	1	
A	卡件	2IA2	黄铜0.3	1	镀银
序号	名称	料号	材料	数量	备注

>0.5~2	±0.05	±0.10	±0.15
>2~5	±0.15	±0.20	±0.25
>5~10	±0.25	±0.28	±0.30
角度 ANGLE	±0.5°		
未注尺寸公差(mm)			

第一视角	设计 Jack Jin	图面 单位 MM	A4
	审核 Jacky Zhong	比例 重量	
	批准 Tony Meng	页码 版次	1/1 A/0

东莞市美韩电子科技有限公司			
Dongguan Usakro Electronic Technology Co., Ltd.			
1:1	DWG NO.	型号:UK-B02123-CJ-250	SIZE A4
1 of 1	PART NO.	规格: 6.2*6.2*7 防水插件	VER R