

CC30-2412SFP-E



Sales Region	Worldwide
Series	CC-P-E
Status	Production
Option	DIP type Parallel operation
Option Lineup	Please refer to here.
Recommended EMC Filter	Please refer to here.
Accessories	Please refer to the catalog



Electrical Characteristics

Rated Input Voltage[DC]	24V
Input Voltage Range[DC]	18 to 36V
Efficiency	92% Typ.
Rated Output Voltage[DC]	12V
Output Voltage Range[DC]	Fixed
Maximum Output Current	
Maximum Ripple Noise	150mV
Maximum Output Power	30W
Withstanding Voltage1	Input - Output: 1000VDC: 1min.
Withstanding Voltage2	Input - Case: 500VDC: 1min.
Withstanding Voltage3	Output - Case: 500VDC: 1min.

Cases Shape & Size

Case'□' shape	On board/Power module
Width(W)	38.2mm Nom.
Height(H)	8.3mm Nom.
Depth(D)	33.5mm Nom.
Weight	20g Typ.
Industry Standard Size	
Terminal Style	DIP

Other

Operating Temp. Range	-40 to 85°C
Isolated / Non-isolated	Isolated
Feature	
Safety Standard(Certified)	UL60950-1 CSA C22.2 No.60950-1 (C-UL) EN60950-1 (NEMKO)
Safety Standard(Conformed)	

