



15 Watt Interchangeable Plug Series



Features

- Double Insulated
- Class B EMI
- Level VI Efficiency Compliant
- Limited Power Source (LPS)

Applications

- Wireless Communications
- Network Equipment
- Peripherals
- Gaming

Safety Approvals

- CE
- RCM
- cUL/UL

Mechanical Characteristics

- Length: 71.7mm (2.82in)
- Width: 50mm (1.97in)
- Height: 33.2mm (1.31in)
- Weight: 115g (4.06oz)

Output Specifications

Model	DC Output Voltage	Load		Ripple ⁽¹⁾ P-P (max.)
		Min.	Max.	
PSC15R-050	5V	0A	3.000A	100mV
PSC15R-060	5.9V	0A	2.500A	100mV
PSC15R-075	7.5V	0A	2.000A	100mV
PSC15R-090	9V	0A	1.67A	120mV
PSA15R-120P6	12V	0A	1.250A	100mV
PSA15R-150P6	15V	0A	1.000A	100mV
PSA15R-240P6	24V	0A	0.65A	200mV
PSA15R-480P6	48V	0A	0.313A	400mV

Note (1): Ripple measured by using a 12-inch twisted pair terminated with 10uF capacitor and 0.1uF ceramic in parallel with oscilloscope set to 20Mhz measured after a warm-up of 10minutes.

Phihong is not responsible for any error, and reserves the right to make changes without notice. Please visit our website at www.phihong.com for the most up-to-date specifications and contact information.

INPUT:**Input Voltage Rating**

100 to 240VAC

AC Input Voltage Range

90 to 264VAC

AC Input Current

0.5A (RMS), 120VAC at maximum load
 0.25A (RMS), 240VAC at maximum load

AC Input Frequency

47 to 63Hz

In-rush Current

<40A for 120VAC at maximum load
 <60A for 240VAC at maximum load
 (cold start at ambient 25°C)

Leakage Current

0.25mA maximum

Input Power Saving

100mW max @ 230V

OUTPUT**Output Power**

15W

Efficiency

US DoE Level VI; EU CoC Ver5 Tier1

Hold up time

8mS minimum at maximum load, 120VAC

ENVIRONMENTAL:**Temperature**

Operation	0°C to +40°C
Non-operation	-40°C to +85°C
Humidity	20 to 90%

EMI

FCC class B, EN55032 Class B

Immunity

EN61000-4-2
 EN61000-4-3
 EN61000-4-4
 EN61000-4-5 Level 3
 EN61000-4-6
 EN61000-4-11

Isolation (HI-POT test)

Input to Output: 3000VAC for 1 minute, 10mA

Insulation Resistance

Input to Output: 500VDC 500M Ohm minimum

FEATURES:**Over Current Protection**

>2A Short Circuit Auto-restart

Short Circuit Protection

Output can be shorted without damage

Over Voltage Protection

<13V

Dielectric Withstand (Hi-pot) Test

Pri. to Sec.: 3000V AC for 1 min., 10mA

DC Cord

1500mm (18~24AWG)

DC Output Connector (Tuning Fork Type)

5.5mm x 2.1mm x 10mm Center Positive

Interchangeable AC Clips

(Sold Separately)

RPA – US
 RPB – Brazil
 RPC – China
 RPE – Europe
 RPH – Korea
 RPI – India
 RPK – UK
 RPN – Argentina
 RPS – Australia
 RPX – IEC320 C8

