

S3PDB40


Three Phase Rectifier Modules





Type	V_{RSM} V	V_{RRM} V
S3PDB40N08	900	800
S3PDB40N12	1300	1200
S3PDB40N14	1500	1400
S3PDB40N16	1700	1600
S3PDB40N18	1900	1800

Dimensions in mm (1mm=0.0394")



Symbol	Test Conditions		Maximum Ratings	Unit
I_{dav} I_{dav}	T_C=110°C, module T_A=45°C (R_{thCA}=0.6K/W), module		40 32	A
I_{FSM}	T_{VJ}=45°C V_R=0	t=10ms (50Hz), sine t=8.3ms (60Hz), sine	370 400	A
	T_{VJ}=T_{VJM} V_R=0	t=10ms(50Hz), sine t=8.3ms(60Hz), sine	340 370	
I^2t	T_{VJ}=45°C V_R=0	t=10ms (50Hz), sine t=8.3ms (60Hz), sine	1010 1010	A^2s
	T_{VJ}=T_{VJM} V_R=0	t=10ms(50Hz), sine t=8.3ms(60Hz), sine	830 830	
T_{VJ} T_{VJM} T_{stg}			-40...+150 150 -40...+125	°C
V_{ISOL}	50/60Hz, RMS I_{ISOL}≤1mA	t=1min t=1s	2500 3000	V~
M_d	Mounting torque (M5) Terminal connection torque (M5)		5 ± 15% 5 ± 15%	Nm
Weight	typ.		160	g

Sirectifier®

S3PDB40

Three Phase Rectifier Modules

Symbol	Test Conditions	Characteristic Values	Unit
I_R	$V_R=V_{RRM}$; $T_{VJ}=25^oC$ $V_R=V_{RRM}$; $T_{VJ}=T_{VJM}$	≤ 0.3 ≤ 5	mA
V_F	I_F=150A; $T_{VJ}=25^oC$	≤ 1.8	V
V_{TO}	For power-loss calculations only	0.8	V
r_T	$T_{VJ}=T_{VJM}$	8	mΩ
R_{thJC}	per diode per module	1.45 0.24	K/W
R_{thJK}	per diode per module	1.87 0.31	K/W
d_S	Creeping distance on surface	10	mm
d_A	Creepage distance in air	9.4	mm
a	Max. allowable acceleration	50	m/s^2

FEATURES

* Package with screw terminals
* Isolation voltage 3000 V~
* Planar passivated chips
* Blocking voltage up to 1800 V
* Low forward voltage drop

APPLICATIONS

* Supplies for DC power equipment
* Input rectifiers for PWM inverter
* Battery DC power supplies
* Field supply for DC motors

ADVANTAGES

* Easy to mount with two screws
* Space and weight savings
* Improved temperature and power cycling