

Product data sheet

Specifications

SQUARE D



NEMA Contactor, Type S, reversing, horizontal, Size 1, 27A, 10 HP at 575 VAC, 2 phase, 4 pole, 120 VAC coil, open style

8702SCO10V02S

Product availability : Non-Stock - Not normally stocked in distribution facility

Main

Product Type	Contactor
Product Range	Type S
Contactor Type	Reversing

Complementary

NEMA Size	1
Rated Current	27 A
Number of Poles	4P
Mounting Orientation	Horizontal
Wiring Mode	4 wires
Maximum Voltage Rating	600 V AC
Phase	2 phases
Horsepower Rating	7.5 HP 200 V AC 7.5 HP 230 V AC 10 HP 460 V AC 10 HP 575 V AC

SCCR	Circuit-breaker 70 A maximum, SCCR: 100 kA at 480 V AC Fuse J 60 A maximum, SCCR: 100 kA at 600 V AC Fuse T 60 A maximum, SCCR: 100 kA at 600 V AC Fuse RK1 60 A maximum, SCCR: 100 kA at 600 V AC Fuse RK5 60 A maximum, SCCR: 100 kA at 600 V AC
------	--

Coil Voltage	110 V AC 50 Hz 120 V AC 60 Hz
--------------	----------------------------------

Control Circuit Type	Separate control circuit
----------------------	--------------------------

Control Units	No control units
---------------	------------------

Pilot Light	No indicator
-------------	--------------

Other Equipment	Fuse not supplied
-----------------	-------------------

Terminal Type	Screw clamp terminals
---------------	-----------------------

Environment

Enclosure Type	Not rated (open device)
----------------	-------------------------

Certifications	UL Listed CSA
----------------	------------------

Ordering and shipping details

Category	21272 - 8702,36 SC,SD(NOT S*R,T,W)
Discount Schedule	CP1
GTIN	785901178958
Nbr. of units in pkg.	1
Package weight(Lbs)	11 lb(US) (4.99 kg)
Returnability	No
Country of origin	MX

Offer Sustainability

EU RoHS Directive	Not compliant
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.

Contractual warranty

Warranty	18 months
----------	-----------