
G601 THRU G610

Surface Mount Standard Rectifiers


FEATURES

- High current capability
- Low forward voltage drop
- Low power loss, high efficiency
- High surge capability
- High temperature soldering guaranteed
- Mounting position: any

TO-251(I-PAK)



TO-252(D-PAK)





MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25℃ ambient temperature unless otherwise specified.

CHARACTERISTICS	TO-251 / TO-252	G601VS / G601DS	G602VS / G602DS	G604VS / G604DS	G606VS / G606DS	G608VS / G608DS	G610VS / G610DS	UNIT
Maximum Recurrent Peak Reverse Voltage	V_{RRM}	100	200	400	600	800	1000	V
Maximum RMS Voltage	V_{RMS}	70	140	280	420	560	700	V
Maximum DC Blocking Voltage	V_{DC}	100	200	400	600	800	1000	V
Maximum Average Forward Rectified Current	$I_{(AV)}$	6.0						A
Peak Forward Surage Current 8.3ms Single Half Sine-Wave Super Imposed on Rated Load (JEDEC Method)	I_{FSM}	160						A
Maximum Forward Voltage at 5.0A DC	V_F	1.1						V
Maximum DC Reverse Current T_J=25℃ at Rated DC Blocking Voltage T_J=125℃	I_R	5.0 500						uA
Typical Junction Capacitance Per Element (Note1)	C_J	50						pF
Typical Thermal Resistance (Note2)	$R_{\theta JC}$	25						℃/W
Operating Temperature Range	T_J	-55 to +150						℃
Storage Temperature Range	T_{STG}	-55 to +150						℃

NOTES: 1.Measured at 1.0MHz and applied reverse voltage of 4.0V DC.

2.Mounted on 10cm x 10cm x 1mm copper pad area

http://www.trr-jx.com
Download from alldatasheet.com
广东钜兴电子科技有限公司
GUANGDONG JUXING ELECTRONICE TECHNOLOGY., LTD

G601 THRU G610

Surface Mount Standard Rectifiers

Characteristic Curves (T_A=25 ℃ unless otherwise noted)

FIG.1- FORWARD CURRENT DERATING CURVE




FIG.2- MAXIMUM NON-REPETITIVE SURGE CURRENT




FIG.3- TYPICAL JUNCTION CAPACITANCE




FIG.4- TYPICAL FORWORD CHARACTERISTICS





FIG.5- TYPICAL REVERSE CHARACTERISTICS




http://www.trr-jx.com
Download from alldatasheet.com
广东钜兴电子科技有限公司
GUANGDONG JUXING ELECTRONICE TECHNOLOGY., LTD

G601 THRU G610

Surface Mount Standard Rectifiers


TO-252(D-PAK) Package Outline Dimensions



TO-252(D-PAK) mechanical data

UNIT		A	B	b	C	D	E	F	G	H	L	L1	L2	L3	S	M	N	J	K	T
mm	max	6.7	5.5	0.8	2.5	6.3	0.6	1.8	2.29 TYPICAL	0.55	3.1	1.2	1.0	1.75	0.1	1.8 TYPICAL	1.3 TYPICAL	3.16 ref.	1.80 ref.	4.83 ref.
	min	6.3	5.1	0.3	2.1	5.9	0.4	1.3		0.45	2.7	0.8	0.6	1.40	0.0					
mil	max	264	217	31	98	248	24	71	90 TYPICAL	22	122	47	39	69	4	71 TYPICAL	51 TYPICAL	124 ref.	71 ref.	190 ref.
	min	248	201	12	83	232	16	51		18	106	31	24	55	0					

TO-251(I-PAK) Package Outline Dimensions



TO-251(I-PAK) mechanical data

UNIT		A	B	b	b1	C	D	E	F	G	H	L	L1	M	N
mm	max	6.70	5.50	0.80	0.90	2.50	6.30	0.60	1.80	2.29 TYPICAL	0.55	4.30	1.20	1.8 TYPICAL	1.3 TYPICAL
	min	6.30	5.10	0.30	0.76	2.10	5.90	0.40	1.30		0.45	3.90	0.80		
mil	max	264	217	31	35	98	248	24	71	90 TYPICAL	22	169	47	71 TYPICAL	51 TYPICAL
	min	248	201	12	30	83	232	16	51		18	154	31		

http://www.trr-jx.com
Download from alldatasheet.com
广东钜兴电子科技有限公司
GUANGDONG JUXING ELECTRONICE TECHNOLOGY., LTD