



UT110N03

Power MOSFET

N-CHANNEL ENHANCEMENT MODE



DESCRIPTION

The **UT110N03** uses advanced trench technology to provide excellent $R_{DS(ON)}$, low gate charge and operation with low gate voltages. This device is suitable for use as a load switch or in PWM applications.

FEATURES

- * $V_{DS}(V)=26V$
- * $I_D=110A$
- * $R_{DS(ON)}=4.8m\Omega@V_{GS}=10V$
- * $R_{DS(ON)}=7.0m\Omega@V_{GS}=4.5V$

SYMBOL



TO-220

ORDERING INFORMATION

Ordering Number		Package	Pin Assignment			Packing
Lead Free	Halogen Free		1	2	3	
UT110N03L-TA3-T	UT110N03G-TA3-T	TO-220	G	D	S	Tube

UT110N03L-TA3-T (1) Packing Type (2) Package Type (3) Lead Free		(1) T: Tube (2) TA3: TO-220 (3) G: Halogen Free, L: Lead Free
---	--	--

■ ABSOLUTE MAXIMUM RATINGS ($T_C = 25^\circ\text{C}$, unless otherwise specified)

PARAMETER	SYMBOL	RATINGS	UNIT
Drain-Source Voltage	V_{DSS}	30	V
Gate-Source Voltage	V_{GSS}	± 20	V
Continuous Drain Current	I_D	110	A
Pulsed Drain Current (Note 2)	I_{DM}	440	A
Single Pulsed Avalanche Current (Note 3)	I_{AS}	35	A
Single Pulsed Avalanche Energy (Note 3)	E_{AS}	875	mJ
Power Dissipation	P_D	100	W
Junction Temperature	T_J	+175	$^\circ\text{C}$
Storage Temperature	T_{STG}	-55 ~ +175	$^\circ\text{C}$

Notes: 1. Absolute maximum ratings are those values beyond which the device could be permanently damaged.

Absolute maximum ratings are stress ratings only and functional device operation is not implied.

2. Pulse width limited by maximum junction temperature

3. $L = 0.5\text{mH}$, $I_{AS} = 35\text{A}$, $V_{DD} = 25\text{V}$, $R_G = 25\Omega$, Starting $T_J = 25^\circ\text{C}$.

■ THERMAL DATA

PARAMETER	SYMBOL	RATINGS	UNIT
Junction to Ambient	θ_{JA}	62.5	$^\circ\text{C/W}$
Junction to Case	θ_{JC}	1.5	$^\circ\text{C/W}$


■ ELECTRICAL CHARACTERISTICS ($T_J = 25^\circ\text{C}$, unless otherwise noted)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
OFF CHARACTERISTICS						
Drain-Source Breakdown Voltage	BV _{DSS}	V _{GS} =0V, I _D =250 μA	30			V
Drain-Source Leakage Current	I _{DSS}	V _{DS} =26V, V _{GS} =0 V			1	μA
Gate-Source Leakage Current	I _{GSS}	V _{DS} =0V, V _{GS} =±20 V			±100	nA
ON CHARACTERISTICS(Note1)						
Gate Threshold Voltage	V _{GS(TH)}	V _{DS} =V _{GS} , I _D =250 μA	1		3	V
Static Drain-Source On-Resistance	R _{DS(ON)}	V _{GS} =10V, I _D =50 A		3.9	4.8	mΩ
		V _{GS} =4.5V, I _D =40 A		5.2	7.0	mΩ
DYNAMIC PARAMETERS (Note 2)						
Input Capacitance	C _{ISS}	V _{DS} =15V, V _{GS} =0V, f=1.0MHz		9500		pF
Output Capacitance	C _{OSS}			800		pF
Reverse Transfer Capacitance	C _{RSS}			300		pF
SWITCHING PARAMETERS(Note 2)						
Total Gate Charge	Q _G	V _{DS} =15V, V _{GS} =5V, I _D =16A		50	65	nC
Gate Source Charge	Q _{GS}			20.8		nC
Gate Drain Charge	Q _{GD}			19		nC
Turn-ON Delay Time	t _{D(ON)}	V _{DD} =15V, I _D =1A, R _{GEN} =6Ω V _{GS} =10 V		25.7	50	ns
Turn-ON Rise Time	t _R			10	20	ns
Turn-OFF Delay Time	t _{D(OFF)}			128	200	ns
Turn-OFF Fall-Time	t _F			34	70	ns
SOURCE- DRAIN DIODE RATINGS AND CHARACTERISTICS						
Drain-Source Diode Forward Voltage	V _{SD}	I _S =20 A, V _{GS} =0 V			1.5	V
Drain-Source Diode Forward Current	I _S				90	A


Notes: 1. Pulse Test: Pulse Width $< 300\mu\text{s}$, Duty Cycle $< 2\%$

2. Guaranteed by design, not subject to production testing.

■ TEST CIRCUIT AND WAVEFORM







Switching Time Test Circuit



Switching Waveforms

■ TYPICAL CHARACTERISTICS



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.