

Is Now Part of



ON Semiconductor®

To learn more about ON Semiconductor, please visit our website at
www.onsemi.com

Please note: As part of the Fairchild Semiconductor integration, some of the Fairchild orderable part numbers will need to change in order to meet ON Semiconductor's system requirements. Since the ON Semiconductor product management systems do not have the ability to manage part nomenclature that utilizes an underscore (_), the underscore (_) in the Fairchild part numbers will be changed to a dash (-). This document may contain device numbers with an underscore (_). Please check the ON Semiconductor website to verify the updated device numbers. The most current and up-to-date ordering information can be found at www.onsemi.com. Please email any questions regarding the system integration to Fairchild_questions@onsemi.com.

ON Semiconductor and the ON Semiconductor logo are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

April 2016

FDMD8540L

Dual N-Channel PowerTrench® MOSFET

Q1: 40 V, 156 A, 1.5 mΩ Q2: 40 V, 156 A, 1.5 mΩ

Features

Q1: N-Channel

- Max $r_{DS(on)}$ = 1.5 mΩ at V_{GS} = 10 V, I_D = 33 A
- Max $r_{DS(on)}$ = 2.2 mΩ at V_{GS} = 4.5 V, I_D = 26 A

Q2: N-Channel

- Max $r_{DS(on)}$ = 1.5 mΩ at V_{GS} = 10 V, I_D = 33 A
- Max $r_{DS(on)}$ = 2.2 mΩ at V_{GS} = 4.5 V, I_D = 26 A
- Ideal for Flexible Layout in Primary Side of Bridge Topology
- 100% UIL Tested
- Kelvin High Side MOSFET Drive Pin-out Capability
- RoHS Compliant


General Description

This device includes two 40V N-Channel MOSFETs in a dual Power (5 mm X 6 mm) package. HS source and LS drain internally connected for half/full bridge, low source inductance package, low $r_{DS(on)}$/Qg FOM silicon.


Applications


- POL Synchronous Dual
- One Phase Motor Half Bridge
- Half/Full Bridge Secondary Synchronous Rectification

Top



Bottom





Power 5 x 6

MOSFET Maximum Ratings T_A = 25 °C unless otherwise noted.

Symbol	Parameter				Q1	Q2	Units
V_{DS}	Drain to Source Voltage				40	40	V
V_{GS}	Gate to Source Voltage				±20	±20	V
I_D	Drain Current	-Continuous	T_C = 25 °C	(Note 5)	156	156	A
		-Continuous	T_C = 100 °C	(Note 5)	99	99	
		-Continuous	T_A = 25 °C		33[1a]	33[1b]	
		-Pulsed		(Note 4)	886	886	
E_{AS}	Single Pulse Avalanche Energy			(Note 3)	541	541	mJ
P_D	Power Dissipation		T_C = 25 °C		62	62	W
	Power Dissipation		T_A = 25 °C		2.3[1a]	2.3[1b]	
T_J, T_{STG}	Operating and Storage Junction Temperature Range				-55 to +150		°C

Thermal Characteristics

$R_{\theta JC}$	Thermal Resistance, Junction-to-Case	2.0	2.0	°C/W
$R_{\theta JA}$	Thermal Resistance, Junction-to-Ambient	55[1a]	55 [1b]	

Package Marking and Ordering Information

Device Marking	Device	Package	Reel Size	Tape Width	Quantity
FDMD8540L	FDMD8540L	Power 5 x 6	13 ”	12 mm	3000 units

©2015 Fairchild Semiconductor Corporation

Electrical Characteristics T_J = 25 °C unless otherwise noted.

Symbol	Parameter	Test Conditions	Type	Min.	Typ.	Max.	Units
Off Characteristics							
BV_{DSS}	Drain to Source Breakdown Voltage	I_D = 250 μA, V_{GS} = 0 V	Q1 Q2	40 40			V
$\frac{\Delta BV_{DSS}}{\Delta T_J}$	Breakdown Voltage Temperature Coefficient	I_D = 250 μA, referenced to 25 °C	Q1 Q2		20 20		mV/°C
I_{DSS}	Zero Gate Voltage Drain Current	V_{DS} = 32 V, V_{GS} = 0 V	Q1 Q2			1 1	μA
I_{GSS}	Gate to Source Leakage Current	V_{GS} = ±20 V, V_{DS} = 0 V	Q1 Q2			±100 ±100	nA
On Characteristics							
$V_{GS(th)}$	Gate to Source Threshold Voltage	V_{GS} = V_{DS}, I_D = 250 μA	Q1 Q2	1.0 1.0	1.8 1.8	3.0 3.0	V
$\frac{\Delta V_{GS(th)}}{\Delta T_J}$	Gate to Source Threshold Voltage Temperature Coefficient	I_D = 250 μA, referenced to 25 °C	Q1 Q2		-6 -6		mV/°C
$r_{DS(on)}$	Static Drain to Source On Resistance	V_{GS} = 10 V, I_D = 33 A	Q1		1.25	1.5	mΩ
		V_{GS} = 4.5 V, I_D = 26 A			1.65	2.2	
		V_{GS} = 10 V, I_D = 33 A, T_J = 125 °C			1.7	2.1	
		V_{GS} = 10 V, I_D = 33 A	Q2		1.25	1.5	
		V_{GS} = 4.5 V, I_D = 26 A			1.65	2.2	
		V_{GS} = 10 V, I_D = 33 A, T_J = 125 °C			1.7	2.1	
g_{FS}	Forward Transconductance	V_{DD} = 5 V, I_D = 33 A	Q1 Q2		178 178		S
Dynamic Characteristics							
C_{iss}	Input Capacitance	V_{DS} = 20 V, V_{GS} = 0 V f = 1 MHz	Q1 Q2		5670 5670	7940 7940	pF
C_{oss}	Output Capacitance		Q1 Q2		1668 1668	2335 2335	pF
C_{rss}	Reverse Transfer Capacitance		Q1 Q2		75 75	135 135	pF
R_g	Gate Resistance		Q1 Q2	0.1 0.1	1.6 1.6	3.2 3.2	Ω
Switching Characteristics							
$t_{d(on)}$	Turn-On Delay Time	V_{DD} = 20 V, I_D = 33 A V_{GS} = 10 V, R_{GEN} = 6 Ω	Q1 Q2		15 15	28 28	ns
t_r	Rise Time		Q1 Q2		13 13	24 24	ns
$t_{d(off)}$	Turn-Off Delay Time		Q1 Q2		51 51	81 81	ns
t_f	Fall Time		Q1 Q2		14 14	25 25	ns
$Q_{g(TOT)}$	Total Gate Charge	V_{GS} = 0 V to 10 V; V_{DD} = 20 V, I_D =33 A	Q1 Q2		81 81	113 113	nC
$Q_{g(TOT)}$	Total Gate Charge	V_{GS} = 0 V to 4.5 V; V_{DD} = 20 V, I_D =33 A	Q1 Q2		38 38	54 54	nC
Q_{gs}	Gate to Source Charge	V_{DD} = 20 V, I_D =33 A	Q1 Q2		15 15		nC
Q_{gd}	Gate to Drain “Miller” Charge	V_{DD} = 20 V, I_D =33 A	Q1 Q2		11 11		nC


©2015 Fairchild Semiconductor Corporation

Electrical Characteristics T_J = 25 °C unless otherwise noted.


Symbol	Parameter	Test Conditions	Type	Min.	Typ.	Max.	Units
Drain-Source Diode Characteristics							
V_{SD}	Source to Drain Diode Forward Voltage	V_{GS} = 0 V, I_S = 33 A (Note 2)	Q1 Q2		0.8 0.8	1.3 1.3	V
V_{SD}	Source to Drain Diode Forward Voltage	V_{GS} = 0 V, I_S = 2 A (Note 2)	Q1 Q2		0.7 0.7	1.2 1.2	V
t_{rr}	Reverse Recovery Time	I_F = 33 A, di/dt = 100 A/μs	Q1 Q2		54 54	86 86	ns
Q_{rr}	Reverse Recovery Charge		Q1 Q2		38 38	60 60	nC

NOTES:


1. $R_{\theta JA}$ is determined with the device mounted on a 1 in^2 pad 2 oz copper pad on a 1.5 x 1.5 in. board of FR-4 material. $R_{\theta JC}$ is guaranteed by design while $R_{\theta CA}$ is determined by the user's board design.




a. 55 °C/W when mounted on a 1 in^2 pad of 2 oz copper



b. 55 °C/W when mounted on a 1 in^2 pad of 2 oz copper



c. 155 °C/W when mounted on a minimum pad of 2 oz copper



d. 155 °C/W when mounted on a minimum pad of 2 oz copper

2. Pulse Test: Pulse Width < 300 μs, Duty cycle < 2.0 %.
3. Q1: E_{AS} of 541 mJ is based on starting T_J = 25 °C, L = 3 mH, I_{AS} = 19 A, V_{DD} = 40 V, V_{GS} = 10 V. 100% tested at L = 0.1 mH, I_{AS} = 59 A.
   Q2: E_{AS} of 541 mJ is based on starting T_J = 25 °C, L = 3 mH, I_{AS} = 19 A, V_{DD} = 40 V, V_{GS} = 10 V. 100% tested at L = 0.1 mH, I_{AS} = 59 A.
4. Pulsed Id please refer to Fig 11 and Fig 24 SOA graph for more details.
5. Computed continuous current limited to Max Junction Temperature only, actual continuous current will be limited by thermal & electro-mechanical application board design.

©2015 Fairchild Semiconductor Corporation

Typical Characteristics (Q1 N-Channel) T_J = 25°C unless otherwise noted.




Figure 1. On Region Characteristics




Figure 2. Normalized On-Resistance vs. Drain Current and Gate Voltage




Figure 3. Normalized On Resistance vs. Junction Temperature




Figure 4. On-Resistance vs. Gate to Source Voltage




Figure 5. Transfer Characteristics




Figure 6. Source to Drain Diode Forward Voltage vs. Source Current

Typical Characteristics (Q1 N-Channel) T_J = 25°C unless otherwise noted.




Figure 7. Gate Charge Characteristics




Figure 8. Capacitance vs. Drain to Source Voltage




Figure 9. Unclamped Inductive Switching Capability




Figure 10. Maximum Continuous Drain Current vs. Case Temperature




Figure 11. Forward Bias Safe Operating Area




Figure 12. Single Pulse Maximum Power Dissipation

Typical Characteristics (Q1 N-Channel) T_J = 25°C unless otherwise noted.




Figure 13. Junction-to-Case Transient Thermal Response Curve

Typical Characteristics (Q2 N-Channel) T_J = 25 °C unless otherwise noted.




Figure 14. On- Region Characteristics




Figure 15. Normalized on-Resistance vs. Drain Current and Gate Voltage




Figure 16. Normalized On-Resistance vs. Junction Temperature




Figure 17. On-Resistance vs. Gate to Source Voltage




Figure 18. Transfer Characteristics




Figure 19. Source to Drain Diode Forward Voltage vs. Source Current

Typical Characteristics (Q2 N-Channel) T_J = 25°C unless otherwise noted.




Figure 20. Gate Charge Characteristics




Figure 21. Capacitance vs. Drain to Source Voltage




Figure 22. Unclamped Inductive Switching Capability




Figure 23. Maximum Continuous Drain Current vs. Case Temperature




Figure 24. Forward Bias Safe Operating Area




Figure 25. Single Pulse Maximum Power Dissipation

Typical Characteristics (Q2 N-Channel) T_J = 25 °C unless otherwise noted.







Figure 26. Junction-to-Case Transient Thermal Response Curve




TOP VIEW




RECOMMENDED LAND PATTERN



SIDE VIEW



DETAIL 'A'
(SCALE: 2X)



BOTTOM VIEW

NOTES: UNLESS OTHERWISE SPECIFIED

A) PACKAGE STANDARD REFERENCE: JEDEC REGISTRATION, MO-240, VARIATION AA.

B) ALL DIMENSIONS ARE IN MILLIMETERS.

C) DIMENSIONS DO NOT INCLUDE BURRS OR MOLD FLASH. MOLD FLASH OR BURRS DOES NOT EXCEED 0.10MM.

D) DIMENSIONING AND TOLERANCING PER ASME Y14.5M-2009.

E) IT IS RECOMMENDED TO HAVE NO TRACES OR VIAS WITHIN THE KEEP OUT AREA.

F) DRAWING FILE NAME: MKT-PQFN08QREV2

FAIRCHILD™

ON Semiconductor and ON are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:
Literature Distribution Center for ON Semiconductor
19521 E. 32nd Pkwy, Aurora, Colorado 80011 USA
Phone: 303−675−2175 or 800−344−3860 Toll Free USA/Canada
Fax: 303−675−2176 or 800−344−3867 Toll Free USA/Canada
Email: orderlit@onsemi.com

N. American Technical Support: 800−282−9855 Toll Free USA/Canada
Europe, Middle East and Africa Technical Support:
Phone: 421 33 790 2910
Japan Customer Focus Center
Phone: 81−3−5817−1050

ON Semiconductor Website: **www.onsemi.com**

Order Literature: http://www.onsemi.com/orderlit

For additional information, please contact your local Sales Representative