



TC64X/TC64XB Fan Control Evaluation Board User's Guide

Note the following details of the code protection feature on Microchip devices:

- Microchip products meet the specification contained in their particular Microchip Data Sheet.
- Microchip believes that its family of products is one of the most secure families of its kind on the market today, when used in the intended manner and under normal conditions.
- There are dishonest and possibly illegal methods used to breach the code protection feature. All of these methods, to our knowledge, require using the Microchip products in a manner outside the operating specifications contained in Microchip's Data Sheets. Most likely, the person doing so is engaged in theft of intellectual property.
- Microchip is willing to work with the customer who is concerned about the integrity of their code.
- Neither Microchip nor any other semiconductor manufacturer can guarantee the security of their code. Code protection does not mean that we are guaranteeing the product as "unbreakable."

Code protection is constantly evolving. We at Microchip are committed to continuously improving the code protection features of our products. Attempts to break microchip's code protection feature may be a violation of the Digital Millennium Copyright Act. If such acts allow unauthorized access to your software or other copyrighted work, you may have a right to sue for relief under that Act.

Information contained in this publication regarding device applications and the like is intended through suggestion only and may be superseded by updates. It is your responsibility to ensure that your application meets with your specifications. No representation or warranty is given and no liability is assumed by Microchip Technology Incorporated with respect to the accuracy or use of such information, or infringement of patents or other intellectual property rights arising from such use or otherwise. Use of Microchip's products as critical components in life support systems is not authorized except with express written approval by Microchip. No licenses are conveyed, implicitly or otherwise, under any intellectual property rights.

Trademarks

The Microchip name and logo, the Microchip logo, Accuron, dsPIC, KEELOQ, MPLAB, PIC, PICmicro, PICSTART, PRO MATE and PowerSmart are registered trademarks of Microchip Technology Incorporated in the U.S.A. and other countries.

Amplab, FilterLab, microID, MXDEV, MXLAB, PICMASTER, SEEVAL and The Embedded Control Solutions Company are registered trademarks of Microchip Technology Incorporated in the U.S.A.


Application Maestro, dsPICDEM, dsPICDEM.net, ECAN, ECONOMONITOR, FanSense, FlexROM, fuzzyLAB, In-Circuit Serial Programming, ICSP, ICEPIC, microPort, Migratable Memory, MPASM, MPLIB, MPLINK, MPSIM, PICKit, PICDEM, PICDEM.net, PowerCal, PowerInfo, PowerMate, PowerTool, rLAB, rPIC, Select Mode, SmartSensor, SmartShunt, SmartTel and Total Endurance are trademarks of Microchip Technology Incorporated in the U.S.A. and other countries.

Serialized Quick Turn Programming (SQTP) is a service mark of Microchip Technology Incorporated in the U.S.A.

All other trademarks mentioned herein are property of their respective companies.

© 2003, Microchip Technology Incorporated, Printed in the U.S.A., All Rights Reserved.

 Printed on recycled paper.



Microchip received QS-9000 quality system certification for its worldwide headquarters, design and wafer fabrication facilities in Chandler and Tempe, Arizona in July 1999 and Mountain View, California in March 2002. The Company's quality system processes and procedures are QS-9000 compliant for its PICmicro® 8-bit MCUs, KEELOQ® code hopping devices, Serial EEPROMs, microperipherals, non-volatile memory and analog products. In addition, Microchip's quality system for the design and manufacture of development systems is ISO 9001 certified.



TC64X/TC64XB FAN CONTROL EVALUATION BOARD USER'S GUIDE

Table of Contents

Chapter 1. General Information

1.1 Introduction	1
1.2 The TC64X/TC64XB Fan Control Evaluation Board	2
1.3 Reference Documents	4

Chapter 2. Getting Started

2.1 TC64X/TC64XB Fan Control Evaluation Board Functional Description	5
2.2 Implementing The TC64X/TC64XB Fan Control Evaluation Board	7
2.3 Operation In The Adjustable Output Voltage Mode	8

Appendix A. Board Layout and Schematic

A.1 Introduction	9
A.2 Board Layout and Schematics	9

Appendix B. Bill-of-Materials (BOM)

B.1 TC64X/TC64XB Fan Control Evaluation Board Components	11
--	----

Worldwide Sales and Service	12
-----------------------------------	----

TC64X/TC64XB Fan Control Evaluation Board User's Guide

NOTES:



TC64X/TC64XB FAN CONTROL EVALUATION BOARD USER'S GUIDE

Chapter 1. General Information

1.1 INTRODUCTION

Thank you for purchasing the TC64X/TC64XB Fan Control Evaluation Board from Microchip Technology Inc. The TC64X/TC64XB Fan Control Evaluation Board allows the user to evaluate and prototype brushless DC fan control circuits using one of the following Microchip BDC fan controllers.

These devices will be referred to as "TC64X" in this document:

- TC642
- TC646
- TC647
- TC648
- TC649

These devices will be referred to as TC64XB in this document:

- TC642B
- TC646B
- TC647B
- TC648B
- TC649B

The fan speed control signal can be provided by an external sensor or voltage signal, or from the on-board control voltage potentiometer.

Minimum speed setting devices are:

- TC642/2B
- TC647/7B

Auto-shutdown threshold devices are:

- TC646/6B
- TC648/8B
- TC649/9B

The minimum speed setting and auto-shutdown threshold devices are conveniently set by an on-board potentiometer.

The TC64X/TC64XB Fan Control Evaluation Board has the following features:

1. Capacity for complete evaluation and prototyping for TC64X and TC64XB BDC fan controllers.
2. Works with any BDC fan.
3. User prototyping area is provided for dedicated circuitry and other user-specific circuits.
4. Jumper blocks allow users to quickly configure output stage and input signal source.
5. External or internal control voltage.
6. Convenient user test points provide easy access for instrument readings at critical nodes.

TC64X/TC64XB Fan Control Evaluation Board User's Guide

1.2 THE TC64X/TC64XB FAN CONTROL EVALUATION BOARD

The TC64X/TC64XB Fan Control Evaluation Board (Figure 1-1) measures 4" x 6". The circuit board is populated with an 8-pin PDIP socket that can accommodate any of the TC64X and TC64XB devices. While the evaluation kit is pre-configured for a 100 mA, 12V fan, it can be custom-configured for a user-specific combination of control and fan requirements. A LED status indicator is also provided to give a visual indication of a fan fault condition.

The TC64X/TC64XB Fan Control Evaluation Board is powered from an external power supply (5V, 50 mA). The fan speed control signal can be provided by an external sensor, an external voltage signal or the on-board potentiometer. Minimum speed setting and auto-shutdown thresholds are conveniently set by a second potentiometer. Also included are jumper-configurable options for setting the output stage configuration, the modulation frequency and the input signal source. A SHDN/RESET switch is also available for manually shutting down the fan or resetting the system.




FIGURE 1-1: TC64X/TC64XB Fan Control Evaluation Board Kit

The TC64X/TC64XB Evaluation Kit includes the following:

1. 4" x 6" printed circuit board with components installed.
2. TC64X/TC64XB Fan Control Evaluation Board User's Guide (DS21403).
3. Sample Devices:

Device	Part Number	
	PDIP	SOIC
TC642B	TC642BEPA	TC642BEOA
TC646B	TC646BEPA	TC646BEOA
TC647	TC647VPA	TC647VOA
TC647B	TC647BEPA	TC647BEOA
TC648	TC648VPA	TC648VOA
TC648B	TC648BEPA	TC648BEOA
TC649	TC649VPA	TC649VOA
TC649B	TC649BEPA	TC649BEOA

If any of these items are damaged or missing, please contact your nearest Microchip sales office, listed on the back of this publication.

Certain items must be provided by the user to implement the TC64X/TC64XB Evaluation Kit:

1. A 5.0V, 50 mA regulated power supply
2. A 12.0V regulated power supply capable of supplying the required fan current
3. Small, flat-bladed screwdriver for adjusting the speed control and minimum speed/auto-shutdown potentiometers
4. Digital volt meter
5. General-purpose oscilloscope
6. Clip leads for power supply and fan connections
7. 12V, 75 mA to 100 mA brushless DC fan

Note: The TC64X and TC64XB will work with any BDC fan. A 12V, 75 mA to 100 mA fan is recommended for initial start-up since the evaluation board is preconfigured for this fan rating. If a 12V, 75 mA to 100 mA BDC fan is not available, the configuration settings of the TC64X/TC64XB Fan Control Evaluation Board must be modified accordingly.

1.3 REFERENCE DOCUMENTS

Other Reference Documents may be obtained by contacting your nearest Microchip sales office or by visiting the Microchip web site at www.microchip.com.

- *Technical Library CD-ROM*, DS00161
- *Analog & Interface Families Data Book 2002*, DS00207
- *2002 Technical Documentation Analog & Interface Product Families CD-ROM*, DS51205
- AN768, "*Redundant Fan Systems Using the TC642 Fan Manager*", DS00768, Microchip Technology Inc., 2002
- AN770, "*Linear Voltage Fan Speed Control Using Microchip's TC64x Family*", DS00770, Microchip Technology Inc., 2003
- AN771, "*Suppressing Acoustic Noise in Pulse Width Modulation (PWM) Fan Speed Control Systems*", DS00771, Microchip Technology Inc., 2003
- AN772, "*Speed Error in Pulse Width Modulation (PWM) Fan Control Systems*", DS00772, Microchip Technology Inc., 2003
- *TC642 Fan Speed Control Module for TC64X Family* Sell Sheet, DS51251
- *TC642EV, Evaluation Kit for Brushless DC Fan Controllers*, DS21403
- *TC64X, TC64XB* Sell Sheet, DS51252

Other reference documents may be obtained by contacting your nearest Microchip sales office (listed on the back of this document).

The Microchip web site (www.microchip.com) also contains a wealth of documentation. Individual data sheets, application notes, tutorials and user's guides are all available for easy download.



TC64X/TC64XB FAN CONTROL EVALUATION BOARD USER'S GUIDE

Chapter 2. Getting Started

This Chapter describes how the TC64X/TC64XB Fan Control Evaluation Board functions and how to use the various features.

The development system demonstrates the ability of the TC64X and TC64XB families to interface with virtually any brushless DC fan, control the speed of the fan according to external temperature input, indicate overtemperature conditions, and detect fan failure. A variety of test points and a user prototyping area are provided for easy and complete design evaluation. The TC64X/TC64XB Evaluation Kit's versatility and ease-of-use helps speed up prototyping and development.

2.1 TC64X/TC64XB FAN CONTROL EVALUATION BOARD FUNCTIONAL DESCRIPTION

2.1.1 Hardware Description

Various jumper options and sites for user-installed components allow the TC64X/TC64XB Fan Control Evaluation Board to operate with virtually any BDC fan.

As shown in Figure A-1 of **Appendix A. "Board Layout and Schematic"**, the TC64X/TC64XB Fan Control Evaluation Board operates with any of the TC64X and TC64XB devices installed in the 8-pin DIP socket.

The TC646/646B/648/648B/649/649B devices have an auto-shutdown mode, whereby the fan is shut off when measured temperature is below a prescribed minimum.

The TC642/2B/647/7B devices operate the fan continuously at a minimum speed when the measured temperature is low. For details, please refer to the data sheets for these devices. Shipped from the factory, the TC64X/TC64XB Fan Control Evaluation Board is configured to operate as a TC642/2B/647/7B that drives a 12V BDC fan having a 100 mA maximum operating current.

The TC64X and TC64XB devices modulate fan speed in direct proportion to the control signal applied to pin 1 (V_{IN}). This input can be supplied by an off-board sensor, or from the on-board speed control (Potentiometer 1), depending on the setting of the INT/EXT switch. The minimum fan operating speed (TC642/2B/647/7B) or auto-shutdown temperature setting (TC646/6B/648/8B/649/9B) is determined by the setting of Potentiometer 2. Additionally, the TC64X and TC64XB devices can be manually shut down (or reset) by pushing the SHDN/RESET switch or by applying a short between the two terminals of TB₄. Be sure JB₄ is set to match the TC64X and TC64XB devices currently in service. The BDC fan modulation frequency should be between 15 Hz to 30 Hz. This frequency is determined either by capacitor C₁, or the user-installed capacitor C₂, and the setting of JB₁. The default operating frequency is 30 Hz (see the TC64X and TC64XB data sheets for details).

TC64X/TC64XB Fan Control Evaluation Board User's Guide

The output drive device can be either a SOT-23, TO-92 or a TO-220 transistor/MOSFET, depending on the fan operating current and application. Resistor R_2 sets the base drive current for this transistor. The configuration, as shipped from the factory, consists of a 2N2222A transistor and a 1.1 k Ω base resistor, which will drive a BDC fan with an operating current of 100 mA or less. Larger fans can be driven with a different combination of base resistor and output transistor. Fan commutation pulses are sensed by pin 5 of the TC64X and TC64XB devices through R_3 and C_5 . Table 2-2 shows suggested values for R_3 for various fan current ratings. The TC64X/TC64XB Evaluation Kit is shipped from the factory with a 4.7 Ω resistor installed for R_3 and a 0.1 μ F capacitor installed for C_5 .

A fault visual indicator is also provided to facilitate experimentation. The FAULT LED is driven active by Q_4 whenever the FAULT output of the TC64X/TC64XB device goes low. The various jumper blocks and options are summarized in Table 2-1.

TABLE 2-1: TC64X/TC64XB EVALUATION BOARD JUMPER OPTIONS

Jumper Block	Shorting Block Installed	Function	Factory Setting
JB ₁	1 to 2	TC64X/TC64XB, 30 Hz timebase enabled.	Shorted
	3 to 4	TC64X/TC64XB timebase determined by user-installed capacitor C_2 .	Open
JB ₂	1 to 2	4.7 Ω sense resistor selected.	Shorted
	3 to 4	User-installed sense resistor R_4 selected.	Open
JB ₃	1 to 2	0.1 μ F sense capacitor selected (adequate for nearly all BDC fans).	Shorted
	3 to 4	User-installed sense capacitor C_4 selected.	Open
JB ₄	2 to TC642	TC64X/TC64XB Fan Control Evaluation Board configured for TC642/2B, TC647/7B.	Shorted
	2 to TC646	TC64X/TC64XB Fan Control Evaluation Board configured for TC646/6B, TC648/8B, TC649/9B.	Open

2.2 IMPLEMENTING THE TC64X/TC64XB FAN CONTROL EVALUATION BOARD

Initial start-up of the TC64X/TC64XB Fan Control Evaluation Board is simplified by using a 12V BDC fan with an operating current between 75 mA to 100 mA. The TC64X/TC64XB Fan Control Evaluation Board is shipped pre-configured for such a fan. If such a fan is available, please proceed to Step 1 below.

If such a fan is unavailable, the TC64X/TC64XB Fan Control Evaluation Board will require modification to certain component values and jumper settings. Proceed to **Section 2.3, "Operation in the Adjustable Output Voltage"**.

1. The TC64X/TC64XB Fan Control Evaluation Board is shipped from the factory configured as outlined in Table 2-1. Inspect the jumper settings on the board to ensure they match those listed in Table 2-1. Also be sure that a 4.7 Ω resistor is installed for R₃, a 1.1 k Ω resistor is installed for R₂, a 0.1 μ F capacitor is installed for C₅ and a 2N2222A transistor is installed for Q₂.
2. Connect the positive side of a 5V DC supply to V_{DD} (BP₁) and the negative side of the supply to GND (BP₂).
3. Connect the positive lead of a 12V, 100 mA (max) BDC fan to the FAN + terminal. Connect the negative lead of the fan to the FAN - terminal.
4. Connect the positive lead of a 12V DC supply to V_{FAN} (BP₃). Connect the negative lead from the 12V DC supply to ground (BP₂).
5. Set the INT/EXT switch to INT (Internal Control Voltage). Turn Potentiometer 1 (Speed Control) fully clockwise. Turn Potentiometer 2 (min speed/auto-shutdown level) fully clockwise.
6. Turn both DC supplies on. The fan should immediately run to full speed and the FAULT LED should be lit. If this is not the case, check the configuration settings and repeat steps 1 through 5.
7. Connect the positive lead of a DC voltmeter to test point TP₁ and the negative voltmeter lead to ground. This is the minimum speed setting voltage. Adjust Potentiometer 2 until a reading of 1.9V is achieved. This voltage corresponds to a minimum speed setting of approximately 40 percent of full speed.
8. Verify proper operation of the TC642/2B/647/7B by rotating Potentiometer 1 counterclockwise. The fan speed decreases and the FAULT LED goes off. Fan speed will decrease as Potentiometer 1 is rotated counterclockwise until the voltage on the wiper of Potentiometer 1 is less than the voltage on the wiper of Potentiometer 2, at which time the fan will operate continuously at 40 percent of full speed. Verify the minimum speed circuit is operating by adjusting Potentiometer 2 clockwise, while Potentiometer 1 is fully counterclockwise.
9. Verify open fan detection by disconnecting one lead of the fan while it is running. The FAULT LED will light after a disconnect time of about two seconds.
10. Verify locked rotor detection by stopping the fan blades during operation. The FAULT LED will light approximately two seconds after the fan blades are stopped.

The TC64X/TC64XB circuit board may now be custom-configured for your particular combination of control and fan requirements.

TC64X/TC64XB Fan Control Evaluation Board User's Guide

2.3 OPERATION IN THE ADJUSTABLE OUTPUT VOLTAGE MODE

2.3.1 Output Driver

Transistors such as 2N2222A are recommended for use as the output driver. These transistors are low cost, multiple sourced and have a high enough Beta for BDC fan applications of 200 mA or less operating current. If a single transistor is used, care must be taken to select a transistor having a minimum h_{FE} of 50 to ensure that the minimum output current specification (5 mA) of the TC64X and TC64XB devices are not exceeded. For large BDC fans, a logic level MOSFET is a good choice for the drive device. All component selections should be made based on information in the "Applications" section of the TC64X and TC64XB data sheets.

Table 2-2 provides a list of typical fan module operating configurations for 12V fan applications. The values in Table 2-2 assume the use of low-cost, bipolar transistors (such as the 2N2222A).

Substituting a logic level MOSFET, such as a BS170, for Q_2 , results in lower system voltage losses and significantly reduces output loading on the TC64X and TC64XB devices. The low $R_{DS(on)}$ of the MOSFET (1Ω in the case of the BS170) enables it to be used in place of the Darlington in high current fan applications (See the TC64X and TC64XB individual data sheets' "Applications" section for details). The pinout of many logic level MOSFETs is reversed from that of bipolar junction transistors, so care must be taken to properly orient the MOSFET.

TABLE 2-2: OUTPUT DRIVE DEVICE CONFIGURATIONS

Full Speed Fan Motor Current	Darlington Pair/MOSFET*	Single Transistor	R_2 (Ω)	R_3 (Ω)
50 mA	—	X	2.4 k	9.1
100 mA	—	X	1.1 k	4.7
150 mA	—	X	750	3.0
200 mA	—	X	620	2.4
200 mA	X	—	5.6 k	2.4
250 mA	X	—	4.7 k	2.0
300 mA	X	—	3.9 k	1.8
350 mA	X	—	3.3 k	1.5
400 mA	X	—	3.0 k	1.3
450 mA	X	—	2.4 k	1.2

* R_2 is not necessary when using a MOSFET as the drive device.

2.3.2 Sensor Interface Circuit

The TC64X and TC64XB data sheets provide detailed information relating to the design of a temperature sensor based on a low cost thermistor.



TC64X/TC64XB FAN CONTROL EVALUATION BOARD USER'S GUIDE

Appendix A. Board Layout and Schematic

A.1 INTRODUCTION

This appendix contains general information concerning the layout, schematic and components associated with the TC64X/TC64XB Fan Control Evaluation Board.

A.2 BOARD LAYOUT AND SCHEMATICS

Figure A-1 depicts the layout for the TC64X/TC64XB Fan Control Evaluation Board. Figure A-2 shows the schematic for the Fan Control Module.




FIGURE A-1: TC64X/TC64XB Fan Control Evaluation Board Layout

TC64X/TC64XB Fan Control Evaluation Board User's Guide




FIGURE A-2: Fan Control Module Schematic



TC64X/TC64XB FAN CONTROL EVALUATION BOARD USER'S GUIDE

Appendix B. Bill-of-Materials (BOM)

B.1 TC64X/TC64XB FAN CONTROL EVALUATION BOARD COMPONENTS

Table B-1 lists typical components and associated values that comprise the TC64X/TC64XB Fan Control Evaluation Board.

TABLE B-1: FAN CONTROL MODULE COMPONENTS

Component	Typical Value
BP1 – BP3	Banana receptacle
C ₁	1 μ F tantalum capacitor.
C ₂	Not installed
C ₃	1 μ F tantalum capacitor
C ₄	Not installed
C ₅	0.1 μ F ceramic capacitor
C ₆ , C ₇	0.01 μ F ceramic capacitor
C ₈	4.7 μ F tantalum capacitor
JB ₁ – JB ₄	SIP header terminal strips
LED -1	Miniature LED
Pot 1, Pot 2	1 k Ω , on-board potentiometer
Q ₁	Not installed (SOT-23 site)
Q ₂	2N2222A NPN bipolar transistor
Q ₃	Not installed (TO-220 site)
Q ₄	2N3906 PNP bipolar transistor
R ₁	620 Ω , 1/4 watt, 5% carbon resistor
R ₂	1.1 k Ω , 1/4 watt, 5% carbon resistor
R ₃	4.7 Ω , 1/4 watt, 5% carbon resistor
R ₄	Not installed
R ₅	30 k Ω , 1/4 watt, 5% carbon resistor
REF-1	LM385, 1.2V reference
REG-1	TC55RP3002EZB 3.0V, 2% regulator
SW-1	Miniature SPDT toggle switch (INT/EXT Switch)
SW-2	Miniature SPDT push button switch (SHDN/RESET switch)
U1	TC642B, TC646B, TC647/7B, TC648/8B, TC649/9B (Two, each provided as samples)



WORLDWIDE SALES AND SERVICE

AMERICAS

Corporate Office

2355 West Chandler Blvd.
Chandler, AZ 85224-6199
Tel: 480-792-7200
Fax: 480-792-7277
Technical Support: 480-792-7627
Web Address: <http://www.microchip.com>

Atlanta

3780 Mansell Road, Suite 130
Alpharetta, GA 30022
Tel: 770-640-0034
Fax: 770-640-0307

Boston

2 Lan Drive, Suite 120
Westford, MA 01886
Tel: 978-692-3848
Fax: 978-692-3821

Chicago

333 Pierce Road, Suite 180
Itasca, IL 60143
Tel: 630-285-0071
Fax: 630-285-0075

Dallas

4570 Westgrove Drive, Suite 160
Addison, TX 75001
Tel: 972-818-7423
Fax: 972-818-2924

Detroit

Tri-Atria Office Building
32255 Northwestern Highway, Suite 190
Farmington Hills, MI 48334
Tel: 248-538-2250
Fax: 248-538-2260

Kokomo

2767 S. Albright Road
Kokomo, IN 46902
Tel: 765-864-8360
Fax: 765-864-8387

Los Angeles

18201 Von Karman, Suite 1090
Irvine, CA 92612
Tel: 949-263-1888
Fax: 949-263-1338

Phoenix

2355 West Chandler Blvd.
Chandler, AZ 85224-6199
Tel: 480-792-7966
Fax: 480-792-4338

San Jose

2107 North First Street, Suite 590
San Jose, CA 95131
Tel: 408-436-7950
Fax: 408-436-7955

Toronto

6285 Northam Drive, Suite 108
Mississauga, Ontario L4V 1X5, Canada
Tel: 905-673-0699
Fax: 905-673-6509

ASIA/PACIFIC

Australia

Suite 22, 41 Rawson Street
Epping 2121, NSW
Australia
Tel: 61-2-9868-6733
Fax: 61-2-9868-6755

China - Beijing

Unit 915
Bei Hai Wan Tai Bldg.
No. 6 Chaoyangmen Beidajie
Beijing, 100027, No. China
Tel: 86-10-85282100
Fax: 86-10-85282104

China - Chengdu

Rm. 2401-2402, 24th Floor,
Ming Xing Financial Tower
No. 88 TIDU Street
Chengdu 610016, China
Tel: 86-28-86766200
Fax: 86-28-86766599

China - Fuzhou

Unit 28F, World Trade Plaza
No. 71 Wusi Road
Fuzhou 350001, China
Tel: 86-591-7503506
Fax: 86-591-7503521

China - Hong Kong SAR

Unit 901-6, Tower 2, Metroplaza
223 Hing Fong Road
Kwai Fong, N.T., Hong Kong
Tel: 852-2401-1200
Fax: 852-2401-3431

China - Shanghai

Room 701, Bldg. B
Far East International Plaza
No. 317 Xian Xia Road
Shanghai, 200051
Tel: 86-21-6275-5700
Fax: 86-21-6275-5060

China - Shenzhen

Rm. 1812, 18/F, Building A, United Plaza
No. 5022 Binhe Road, Futian District
Shenzhen 518033, China
Tel: 86-755-82901380
Fax: 86-755-8295-1393

China - Shunde

Room 401, Hongjian Building
No. 2 Fengxiangnan Road, Ronggui Town
Shunde City, Guangdong 528303, China
Tel: 86-765-8395507 Fax: 86-765-8395571

China - Qingdao

Rm. B505A, Fullhope Plaza,
No. 12 Hong Kong Central Rd.
Qingdao 266071, China
Tel: 86-532-5027355 Fax: 86-532-5027205

India

Divyasree Chambers
1 Floor, Wing A (A3/A4)
No. 11, O'Shaughnessy Road
Bangalore, 560 025, India
Tel: 91-80-2290061 Fax: 91-80-2290062

Japan

Benex S-1 6F
3-18-20, Shinyokohama
Kohoku-Ku, Yokohama-shi
Kanagawa, 222-0033, Japan
Tel: 81-45-471-6166 Fax: 81-45-471-6122

Korea

168-1, Youngbo Bldg. 3 Floor
Samsung-Dong, Kangnam-Ku
Seoul, Korea 135-882
Tel: 82-2-554-7200 Fax: 82-2-558-5932 or
82-2-558-5934

Singapore

200 Middle Road
#07-02 Prime Centre
Singapore, 188980
Tel: 65-6334-8870 Fax: 65-6334-8850

Taiwan

Kaohsiung Branch
30F - 1 No. 8
Min Chuan 2nd Road
Kaohsiung 806, Taiwan
Tel: 886-7-536-4818
Fax: 886-7-536-4803

Taiwan

Taiwan Branch
11F-3, No. 207
Tung Hua North Road
Taipei, 105, Taiwan
Tel: 886-2-2717-7175 Fax: 886-2-2545-0139

EUROPE

Austria

Durisolstrasse 2
A-4600 Wels
Austria
Tel: 43-7242-2244-399
Fax: 43-7242-2244-393

Denmark

Regus Business Centre
Lautrup høj 1-3
Ballerup DK-2750 Denmark
Tel: 45-4420-9895 Fax: 45-4420-9910

France

Parc d'Activite du Moulin de Massy
43 Rue du Saule Trapu
Batiment A - 1er Etage
91300 Massy, France
Tel: 33-1-69-53-63-20
Fax: 33-1-69-30-90-79

Germany

Steinheilstrasse 10
D-85737 Ismaning, Germany
Tel: 49-89-627-144-0
Fax: 49-89-627-144-44

Italy

Via Quasimodo, 12
20025 Legnano (MI)
Milan, Italy
Tel: 39-0331-742611
Fax: 39-0331-466781

Netherlands

P. A. De Biesbosch 14
NL-5152 SC Drunen, Netherlands
Tel: 31-416-690399
Fax: 31-416-690340

United Kingdom

505 Eskdale Road
Winnersh Triangle
Wokingham
Berkshire, England RG41 5TU
Tel: 44-118-921-5869
Fax: 44-118-921-5820

07/28/03