

General Description

The MIC2141 is a micropower boost switching regulator that can operate from 3- or 4-cell nickel-metal-hydride batteries or a single Li-ion cell. This regulator employs a constant 330kHz, fixed 18% duty-cycle, gated-oscillator architecture.

The MIC2141 can be used in applications where the output voltage must be dynamically adjusted. The device features a control signal input which is used to proportionally adjust the output voltage. The control signal input has a gain of 6, allowing a 0.8V to 3.6V control signal to vary a 4.8V to 22V output.

The MIC2141 requires only three external components to operate and is available in a tiny 5-pin SOT-23 package for space and power-sensitive portable applications. The MIC2141 draws only 70 μ A of quiescent current and can operate with an efficiency exceeding 85%.

Data sheets and support documentation can be found on Micrel's web site at: www.micrel.com.



Features

- Implements low-power boost, SEPIC, or flyback
- 2.2V to 14V input voltage
- 330kHz switching frequency
- <2 μ A shutdown current
- 70 μ A quiescent current
- 1.24V bandgap reference
- Typical output current 1mA to 10mA
- SOT23-5 package

Applications

- LCD bias supply
- CCD digital camera supply

Typical Application




DAC-Controlled LCD Bias Voltage Supply

Ordering Information


Part Number		Marking*		Voltage	Ambient Temperature Range	Package
Standard	Pb-Free	Standard	Pb-Free			
MIC2141BM5	MIC2141YM5	SAAA	<u>S</u> AAA	Adj.	–40° to +85°C	5-Pin SOT23

* Under bar symbol () may not be to scale.

Pin Configuration



5-Pin SOT23 (BM5)



5-Pin SOT23 (YM5)

Pin Description

Pin Number	Pin Name	Pin Function
1	IN	Input: +2.5V to +14V supply for internal circuitry.
2	GND	Ground: Return for internal circuitry and internal MOSFET (switch) source.
3	SW	Switch Node (Input): Internal MOSFET drain; 22V maximum.
4	FB	Feedback (Input): Output voltage sense node. Compared to VC control input voltage.
5	VC	Control (Input): Output voltage control signal input. Input voltage of 0.8V to 3.6V is proportional to 4.8V to 22V output voltage (gain of 6). If the pin is not connected, the output voltage will be $V_{IN} - 0.5V$.

Absolute Maximum Ratings⁽¹⁾

Supply Voltage (V_{IN})	18V
Switch Voltage (V_{SW})	24V
Feedback Voltage (V_{FB})	24V
Control Input Voltage (V_C) ⁽³⁾	$V_{IN} - 200\text{mV} \leq V_C \leq 4\text{V}$
ESD Rating ⁽⁴⁾	2kV

Operating Ratings⁽²⁾

Supply Voltage (V_{IN})	2.5V to 14V
Switch Voltage (V_{SW})	3V to 22V
Ambient Temperature (T_A)	-40°C to +85°C
Junction Temperature Range (T_J)	-40°C to +125°C
Package Thermal Impedance	
SOT23-5 (θ_{JA})	220°C/W

Electrical Characteristics












$V_{IN} = 3.6\text{V}$; $V_{OUT} = 5\text{V}$; $I_{OUT} = 1\text{mA}$; $T_J = 25^\circ\text{C}$, **bold** values indicate $-40^\circ\text{C} \leq T_A \leq +85^\circ\text{C}$, unless noted.

Parameter	Condition	Min	Typ	Max	Units
Input Voltage		2.5		14	V
Quiescent Current	Switch off, $V_{IN} = 3.6\text{V}$		70	100	μA
Comparator Hysteresis			10		mV
Control Voltage Gain (V_{OUT}/V_C)	$2.5\text{V} \leq V_{IN} \leq 12\text{V}$, $V_{OUT} = 15\text{V}$		6		
Controlled Output Voltage, Note 3	$V_C = 0.8\text{V}$; $2.5\text{V} \leq V_{IN} \leq 4.2\text{V}$	4.85	5	5.15	V
	$V_C = 2.5\text{V}$; $2.7\text{V} \leq V_{IN} \leq 12\text{V}$	14.55	15	15.45	V
	$V_C = 3.4\text{V}$; $3.6\text{V} \leq V_{IN} \leq 12\text{V}$	19.4	20	20.6	V
Load Regulation	$100\mu\text{A} \leq I_{OUT} \leq 1\text{mA}$, $V_{OUT} = 15\text{V}$		0.25	1	%
Line Regulation	$2.5\text{V} \leq V_{IN} \leq 12\text{V}$; $I_{OUT} \leq 1\text{mA}$		0.05	0.2	%/V
Switch on Resistance	$I_{SW} = 100\text{mA}$, $V_{IN} = 3.6\text{V}$		4		Ω
	$I_{SW} = 100\text{mA}$, $V_{IN} = 12\text{V}$		2.5		Ω
Oscillator Frequency		300	330	360	kHz
Oscillator Duty Cycle		15	18		%










Notes:

- Exceeding the absolute maximum rating may damage the device.
- The device is not guaranteed to function outside its operating rating
- $V_C = 4\text{V}$ sets V_{OUT} to 24V (absolute maximum level on V_{SW}); V_C must be $\leq V_{IN} - 200\text{mV}$.
- Devices are ESD sensitive. Handling precautions recommended.


Typical Characteristics



Typical Characteristics (cont.)



Functional Diagram



Functional Description

See “Applications Information” for component selection and pre-designed circuits.

Overview

This MIC2141 is a fixed-duty-cycle, constant-frequency, gated-oscillator, micropower, switch-mode power supply controller. Quiescent current for the MIC2141 is only 70µA in the switch off state, and since a MOSFET output switch is used, additional current needed for switch drive is minimized. Efficiencies above 85% throughout most operating conditions can be realized.

Regulation

Regulation is performed by a hysteretic comparator which regulates the output voltage by gating the internal oscillator. The user applies a programming voltage to the V_C pin. (For a fixed or adjustable output regulator, with an internal reference, use the MIC2142.) The output voltage is divided down internally and then compared to the V_C , the control input voltage, forcing the output voltage to 6 times the V_C . The comparator has hysteresis built into it, which determines the amount of low frequency ripple that will be present on the output. Once the feedback input to the comparator exceeds the control voltage by 10mV, the high-frequency oscillator drive is removed from the output switch. As the feedback input to the comparator returns to the control voltage level, the comparator is reset and the high-frequency oscillator is again gated to the output switch. Typically 10mV of hysteresis seen at the comparator will correspond to 60mV of low-frequency ripple at the output. Applications, which require continuous adjustment of the output voltage, can do so by adjustment of the V_C control pin.

Output

The maximum output voltage is limited by the voltage capability of the output switch. Output voltages up to 22V can be achieved with a standard boost circuit. Higher output voltages require a flyback configuration.

Output Voltage Control

The internal hysteretic comparator disables the output drive once the output voltage exceeds the nominal by 30mV. The drive is then enabled once the output voltage drops below the nominal by 30mV.

The reference level, which actually programs the output voltage, is set by the V_C control input. The output is 6 times the control voltage (V_C) and the output ripple will be 6 times the comparator hysteresis. Therefore, with 10mV of hysteresis, there will be ± 30 mV variation in the output around the nominal value. See the “Typical Characteristics: Control Voltage vs. Output Voltage” for a graph of input-to-output behavior.

The common-mode range of the comparator requires that the maximum control voltage (V_C) be held to 200mV less than V_{IN} . When programming for a 20V output, a minimum V_{IN} of 3.5V will be required. See the “Typical Characteristics: Gain vs. Output Voltage” for a graph of gain behavior. To achieve 20V output at lower input voltages, the external resistive divider (R1 and R2) shown in Figure 2 can be added. This circuit will increase the control-to-output gain, while limiting the error introduced by the tolerance of the internal resistor feedback network.

Application Information

Pre-designed circuit information is at the end of this section.

Component Selection

Boost Inductor

Maximum power is delivered to the load when the oscillator is gated on 100% of the time. Total output power and circuit efficiency must be considered when determining the maximum inductor. The largest inductor possible is preferable in order to minimize the peak current and output ripple. Efficiency can vary from 80% to 90% depending upon input voltage, output voltage, load current, inductor, and output diode.

Equation 1 solves for the output current capability for a given inductor value and expected efficiency. Figures 5 through 9; graph estimates for maximum output current, assuming the minimum duty cycle, maximum frequency, and 85% efficiency. To determine the required inductance, find the intersection between the output voltage and current and select the value of the inductor curve just above the intersection. If the efficiency is expected to be other than the 85% used for the graph, Equation 1 can then be used to better determine the maximum output capability.

$$(1) \quad I_{O(max)} = \frac{(V_{IN(min)} t_{ON})^2}{2L_{MAX} T_S} \times \frac{1}{\frac{V_O}{eff} - V_{IN(min)}}$$

The peak inductor and switch current can be calculated from Equation 2 or read from the graph in Figure 10. The peak current shown in Figure 10 is derived assuming a maximum duty cycle and a minimum frequency. The selected inductor and diode peak current capability must exceed this value. The peak current seen by the inductor is calculated at the maximum input voltage. A wider input voltage range will result in a higher worst-case peak current in the inductor. This effect can be seen in Table 4 by comparing the difference between the peak current at $V_{IN(min)}$ and $V_{IN(max)}$.

$$(2) \quad I_{PK} = \frac{t_{ON(max)} V_{IN(max)}}{L_{MIN}}$$

DCM/CCM Boundary

Equation 3 solves for the point at which the inductor current will transition from DCM (discontinuous conduction mode) to CCM (continuous conduction mode). As the input voltage is raised above this level the inductor has a potential for developing a dc component while the oscillator is gated on. Table 1 displays the input points at which the inductor current can possibly operate in the CCM region. Operation in this region can result in a peak current slightly higher than displayed on Table 4.

V_{OUT}	$V_{IN(CCM)}$
3.3V	3.04V
5.0V	4.40V
9.0V	7.60V
12.0V	10.0V
15.0V	12.4V
16.0V	13.2V
20.0V	16.4V
22.0V	18.0V

Table 1. DCM/CCM Boundary

$$(3) \quad V_{IN(ccm)} = (V_{OUT} + V_{FWD}) + (1 - D)$$

Table 2 lists common inductors suitable for most applications. Table 6 lists minimum inductor sizes versus input and output voltage. In low-cost, low-peak-current applications, RF-type leaded inductors may be sufficient. All inductors listed in Table 4 can be found within the selection of CR32- or LQH4C-series inductors from either Sumida or muRata.

Manufacturer	Series	Device Type
MuRata	LQH1C/C3/C4	surface mount
Sumida	CR32	surface mount
J.W. Miller	78F	axial leaded
Coilcraft	90	axial leaded

Table 2. Inductor Examples

Boost Output Diode

Speed, forward voltage, and reverse current are very important in selecting the output diode. In the boost configuration, the average diode current is the same as the average load current. (The peak current is the same as the peak inductor current and can be derived from Equation 2 or Figure 10.) Care must be taken to make sure that the peak current is evaluated at the maximum input voltage.

Diode	75°C V_{FWD} at 100mA	25°C V_{FWD} at 100mA	Room Temp. Leakage at 15V	75°C Leakage at 15V	Package
MBR0530	0.275V	0.325V	2.5μA	90μA	SOD123 SMT
1N4148	0.6V (175°C)	0.95V	25nA (20V)	0.2μA (20V)	leaded and SMT
BAT54	0.4V (85°C)	0.45V	10nA (25V)	1μA (20V)	SMT
BAT85	0.54V (85°C)	0.56V	0.4μA	2μA (85°C)	DO-34 leaded

Table 3. Diode Examples

As can be seen in the “Typical Characteristics: Efficiency” graph, the output diode type can have an effect on circuit efficiency. The BAT54- and BAT85-series diodes are low-current Schottky diodes available from On Semiconductor and Phillips, respectively. They are suitable for peak repetitive currents of 300mA or less with good reverse current characteristics. For applications that are cost driven, the 1N4148, or equivalent, will provide sufficient switching speed with greater forward drop and reduced cost. Other acceptable diodes are On Semiconductor’s MBR0530 or Vishay’s B0530, although they can have reverse currents that exceed 1mA at very high junction temperatures. Table 3 summarizes some typical performance characteristics of various suitable diodes.

Output Capacitor

If the availability of tantalum capacitors is limited, ceramic capacitors and inexpensive electrolytics may be necessary. Selection of the capacitor value will depend upon on the peak inductor current and inductor size. MuRata offers the GRM series with up to 10μF at 25V, with a Y5V temperature coefficient, in a 1210 surface-mount package. Low-cost applications can use M-series leaded electrolytic capacitors from Panasonic. In general, ceramic, electrolytic, or tantalum values ranging from 10μF to 47μF can be used for the output capacitor.

Manufacturer	Series	Type	Package
MuRata	GRM	ceramic Y5V	surface mount
Vishay	594	tantalum	surface mount
Panasonic	M-series	Electrolytic	leaded

Table 4. Capacitor Examples

Design Example

Given a design requirement of 12V output and 1mA load with a minimum input voltage of 2.5V, Equation 1 can be used to calculate to maximum inductance or it can be read from the graph in Figure 4. Once the maximum inductance has been determined, the peak current can be determined using Equation 2 or Figure 9.

$$V_{OUT} = 12V$$

$$I_{OUT} = 1mA$$

$$V_{IN} = 4.8V \text{ to } 2.5V$$

$$L_{MAX} = \frac{V_{IN(min)}^2 \cdot t_{ON(min)}^2}{I_{O(max)} \left(\frac{V_O}{eff} - V_{IN(min)} \right) \cdot 2 \cdot T_{S(min)}}$$

$$L_{MAX} = 17\mu H$$

Select 15μH ±10%.

$$I_{PEAK} = \frac{t_{ON(max)} \cdot V_{IN(max)}}{L_{MIN}} = 0.767\mu s \frac{4.8V}{13.5\mu H}$$

$$I_{PEAK} = 272mA$$

Select a BAT54 diode and CR32 inductor.

Always check the peak current to insure that it is within the limits specified in the load line shown in Figure 10 for all input and output voltages.

Gain Boost

Use Figure 2 to increase the voltage gain of the system. The typical gain can easily be increased from the nominal gain of 6 to a value of 8 or 10. Figure 2 shows a gain of 8 so that with 2.5V applied to V_C , V_{OUT} will be 20V.

Bootstrap

The bootstrap configuration is used to increase the maximum output current for a given input voltage. This is most effective when the input voltage is less than 5V. Output current can typically be tripled by using this technique. See Table 4a. for bootstrap-ready-built component values.




Figure 1. Basic Configuration




Figure 2. Gain-Boost Configuration






Figure 3. Bootstrap Configuration

Inductor Selection Guides

Figure 4. Inductor Selection for $V_{IN} = 2.5V$ Figure 5. Inductor Selection for $V_{IN} = 3.3V$




Figure 6. Inductor Selection for $V_{IN} = 5V$




Figure 7. Inductor Selection for $V_{IN} = 9V$




Figure 8. Inductor Selection for $V_{IN} = 12V$




Figure 9. Peak Inductor Current vs. Input Voltage

Pre-designed Circuit Values

$V_{IN(min)}$	$V_{IN(max)}$	V_{OUT}	$I_{OUT(max)}$	L1	CR1	I_{PEAK} ($V_{IN} = V_{OUT} - 0.5V$) or 14V	I_{PEAK} ($V_{IN} = V_{IN(MIN)}$)
2.5V	4.5V	5.0V	4mA 3mA 2mA 1mA 0.5mA	15μH 18μH 27μH 56μH 120μH	BAT54 BAT54 BAT54 BAT54 BAT54	230mA 192mA 128mA 62mA 29mA	128mA 106mA 71mA 34mA 16mA
		5V bootstrap	14.8mA	3.9μH	MBR0530	890mA	500mA
2.5V	11.5V	12V	1mA 0.5mA 0.2mA	15μH 33μH 82μH	MBR0530 BAT54 BAT54	588mA 267mA 108mA	128mA 58mA 23mA
2.5V	4.7V	12V bootstrap	3.5mA	4.7μH	MBR0530	750mA	500mA
2.5V	4.7V	12V bootstrap	4.3mA	3.9μH	MBR0530	900mA	500mA
2.5V	14V	15V	0.8mA 0.5mA 0.2mA	15μH 27μH 68μH	MBR0530 MBR0530 BAT54	741mA 412mA 163mA	128mA 71mA 28mA
2.5V	14V	16V	0.8mA 0.5mA 0.2mA	15μH 22μH 56μH	MBR0530 MBR0530 BAT54	710mA 456mA 190mA	128mA 87mA 34mA
2.5V	14V	22V	0.5mA 0.2mA 0.1mA	15μH 39μH 82μH	MBR0530 BAT54 BAT54	590mA 247mA 130mA	128mA 49mA 23mA
3.0V user for Li-ion battery range	4.5V	5V	10mA 3.6mA 0.8mA	12μH 27μH 120μH	BAT54 BAT54 BAT54	288mA 128mA 29mA	190mA 85mA 19mA
		5V bootstrap	20mA	4.7μH	MBR0530	730mA	450mA
3.0V user for Li-ion battery range	8.5V	9V	3mA 1.7mA 0.8mA	12μH 22μH 47μH	MBR0530 MBR0530 MBR0530	652mA 296mA 139mA	190mA 103mA 49mA
3.0V user for Li-ion battery range	4.7V	9V bootstrap	8mA	4.7μH	MBR0530	750mA	450mA
3.0V user for Li-ion battery range	11.5V	12V	2.1mA 1.7mA 1mA 0.45mA	12μH 15μH 27μH 56μH	MBR0530 MBR0530 MBR0530 BAT54	882mA 588mA 327mA 157mA	190mA 156mA 85mA 40mA
3.0V user for Li-ion battery range	4.7V	12V bootstrap	5.4mA	4.7μH	MBR0530	750mA	450mA
3.0V user for Li-ion battery range	14V	15V	1.6mA 0.87mA 0.41mA	12μH 22μH 47μH	MBR0530 MBR0530 BAT54	926mA 505mA 237mA	190mA 103mA 49mA
3.0V user for Li-ion battery range	4.7V	15V bootstrap	4mA	4.7μH	MBR0530	750mA	450mA
3.0V user for Li-ion battery range	14V	22V	1mA 0.8mA 0.46mA 0.2mA	10μH 15μH 27μH 68μH	MBR0530 MBR0530 MBR0530 BAT54	1071mA 714mA 400mA 157mA	190mA 152mA 85mA 3.3mA

Table 4a. Typical Configurations for Wide-Range Inputs—2.5V to 3.0V Minimum Input

V _{IN(min)}	V _{IN(max)}	V _{OUT}	I _{OUT(max)}	L1	CR1	I _{PEAK} (V _{IN} = V _{OUT} – 0.5V) or 14V	I _{PEAK} (V _{IN} = V _{IN(MIN)})
5.0V	8.5V	9V	17mA	8.2μH	MBR0530	795mA	467mA
			15mA	10μH	MBR0530	652mA	838mA
			10mA	12μH	MBR0530	643mA	319mA
			5mA	27μH	BAT54	241mA	142mA
			1mA	120μH	BAT54	54mA	32mA
5.0V	11.5V	12V	10mA	8.2μH	MBR0530	1075mA	467mA
			5mA	18μH	MBR0530	490mA	213mA
			2mA	39μH	BAT54	226mA	98mA
			1mA	82μH	BAT54	108mA	47mA
5.0V	14V	15V	7mA	8.2μH	MBR0530	1356mA	467mA
			5mA	12μH	MBR0530	926mA	319mA
			2mA	27μH	MBR0530	412mA	142mA
			1mA	56μH	BAT54	199mA	68mA
5.0V	14V	16V	2.5mA	22μH	MBR0530	986mA	174mA
			1mA	56μH	BAT54	190mA	68mA
			0.5mA	120μH	BAT54	90mA	32mA
5.0V	14V	22V	1.7mA	22μH	MBR0530	486mA	174mA
			1.0mA	39μH	BAT54	274mA	98mA
			0.5mA	82μH	BAT54	130mA	47mA
			0.1mA	180μH	BAT54	60mA	21mA
9.0V	11.5V	12V	33mA	15μH	MBR0530	588mA	460mA
			20mA	22μH	MBR0530	401mA	256mA
			10mA	47μH	BAT54	188mA	123mA
			5mA	100μH	BAT54	88mA	46mA
			1mA	470μH	BAT54	19mA	26mA
9.0V	14V	15V	20mA	15μH	MBR0530	741mA	460mA
			10mA	27μH	MBR0530	412mA	256mA
			5mA	56μH	BAT54	199mA	123mA
			2mA	150μH	BAT54	74mA	46mA
			1mA	270μH	BAT54	41mA	26mA
9.0V	14V	20V	4.5mA	39μH	BAT54	215mA	177mA
			2mA	68μH	BAT54	131mA	84mA
			1mA	150μH	BAT54	72mA	46mA
9.0V	14V	22V	4mA	39μH	BAT54	275mA	177mA
			2mA	68μH	BAT54	157mA	101mA
			1mA	150μH	BAT54	72mA	46mA
12V	14V	15V	45mA	18μH	MBR0530	618mA	511mA
			20mA	39μH	BAT54	285mA	236mA
			10mA	82μH	BAT54	136mA	112mA
			5mA	150μH	BAT54	74mA	61mA
			1.7mA	470μH	BAT54	24mA	20mA
12V	14V	20V	8mA	47μH	BAT54	230mA	196mA
			5mA	68μH	BAT54	158mA	135mA
			2mA	120μH	BAT54	90mA	77mA
			1mA	390μH	BAT54	27mA	24mA
12V	21.5V	22V	7mA	47μH	BAT54	228mA	196mA
			5mA	68μH	BAT54	157mA	135mA
			2mA	150μH	BAT54	69mA	61mA
			1mA	220μH	BAT54	47mA	42mA

Table 4b. Typical Configurations for Wide-Range Inputs—5V to 15V Minimum Input

V_{IN}	V_{OUT}	I_{OUT}	L1	CR1	I_{PEAK} (typical)
3.3V±5%	5V	13mA	10μH	BAT54	253mA
	9V	5mA	10μH	BAT54	253mA
	12V	3mA	10μH	BAT54	253mA
	15V	2.3mA	10μH	BAT54	253mA
	20V	1.7mA	10μH	BAT54	253mA
5V±5%	9V	17mA	8.2μH	MBR0530	467mA
	12V	10.4mA	8.2μH	MBR0530	467mA
	15V	7.5mA	8.2μH	MBR0530	467mA
	20V	2.2mA	22μH	MBR0530	174mA
12V±5%	15V	44mA	18μH	MBR0530	511mA
	20V	8.3mA	47μH	BAT54	196mA

Table 5. Typical Maximum Power Configurations for Regulated Inputs


V_{IN}	Output Voltage	
	16V to 22V	4.5V to 15V
2.5V	15μH	15μH
3.0V	12μH	12μH
3.3V	10μH	10μH
3.5V	8.2μH	8.2μH
4.0V	27μH	6.8μH
4.5V	27μH	6.8μH
5.0V	22μH	8.2μH
6.0V	27μH	10μH
7.0V	27μH	10μH
8.0V	33μH	12μH
9.0V	39μH	15μH
10V	39μH	15μH
11V	47μH	18μH
12V	47μH	18μH
13V	56μH	22μH
14V	56μH	22μH
15V	56μH	27μH
16V	68μH	27μH

Table 6. Minimum Inductance

Manufacturer	Web Address
MuRata	www.murata.com
Sumida	www.sumida.com
Coilcraft	www.coilcraft.com
J.W. Miller	www.jwmiller.com
Micrel	www.micre.com
Vishay	www.vishay.com
Panasonic	www.panasonic.com

Table 7. Component Supplier Websites

Package Information



5-Pin SOT23 (M)

MICREL, INC. 2180 FORTUNE DRIVE SAN JOSE, CA 95131 USA

TEL +1 (408) 944-0800 FAX +1 (408) 474-1000 WEB <http://www.micrel.com>

The information furnished by Micrel in this data sheet is believed to be accurate and reliable. However, no responsibility is assumed by Micrel for its use. Micrel reserves the right to change circuitry and specifications at any time without notification to the customer.

Micrel Products are not designed or authorized for use as components in life support appliances, devices or systems where malfunction of a product can reasonably be expected to result in personal injury. Life support devices or systems are devices or systems that (a) are intended for surgical implant into the body or (b) support or sustain life, and whose failure to perform can be reasonably expected to result in a significant injury to the user. A Purchaser's use or sale of Micrel Products for use in life support appliances, devices or systems is a Purchaser's own risk and Purchaser agrees to fully indemnify Micrel for any damages resulting from such use or sale.

© 2000 Micrel, Incorporated.