

# OPAx990 40-V Rail-to-Rail Input/Output, Low Offset Voltage, Low Power Op Amp

## 1 Features

- Low offset voltage:  $\pm 300\ \mu\text{V}$
- Low offset voltage drift:  $\pm 0.6\ \mu\text{V}/^\circ\text{C}$
- Low noise:  $30\ \text{nV}/\sqrt{\text{Hz}}$  at 1 kHz
- High common-mode rejection: 115 dB
- Low bias current:  $\pm 10\ \text{pA}$
- Rail-to-rail input and output
- MUX-friendly/comparator inputs
  - Amplifier operates with differential inputs up to supply rail
  - Amplifier can be used in open-loop or as comparator
- Wide bandwidth: 1.1-MHz GBW
- High slew rate:  $4.5\ \text{V}/\mu\text{s}$
- Low quiescent current:  $120\ \mu\text{A}$  per amplifier
- Wide supply:  $\pm 1.35\ \text{V}$  to  $\pm 20\ \text{V}$ ,  $2.7\ \text{V}$  to  $40\ \text{V}$
- Robust EMIRR performance: 78 dB at 1.8 GHz
- Differential and common-mode input voltage range to supply rail

## 2 Applications

- Multiplexed data-acquisition systems
- Test and measurement equipment
- Motor drive: power stage and control modules
- Power delivery: UPS, server, and merchant network power
- ADC driver and reference buffer amplifier
- Programmable logic controllers
- Analog input and output modules
- High-side and low-side current sensing
- High precision comparator

## 3 Description

The OPAx990 family (OPA990, OPA2990, and OPA4990) is a family of high voltage (40-V) general purpose operational amplifiers. These devices offer excellent DC precision and AC performance, including rail-to-rail input/output, low offset ( $\pm 300\ \mu\text{V}$ , typ), and low offset drift ( $\pm 0.6\ \mu\text{V}/^\circ\text{C}$ , typ).

Unique features such as differential and common-mode input voltage range to the supply rail, high short-circuit current ( $\pm 80\ \text{mA}$ ), high slew rate ( $4.5\ \text{V}/\mu\text{s}$ ), and shutdown make the OPAx990 an extremely flexible, robust, and high-performance op amp for high-voltage industrial applications.

The OPAx990 family of op amps is available in *micro*-size packages (such as X2QFN, WSON, and SOT-553), as well as standard packages (such as SOT-23, SOIC, and TSSOP), and is specified from  $-40^\circ\text{C}$  to  $125^\circ\text{C}$ .


**Device Information<sup>(1)</sup>**

| PART NUMBER | PACKAGE                    | BODY SIZE (NOM)   |
|-------------|----------------------------|-------------------|
| OPA990      | SOT-23 (5)                 | 2.90 mm × 1.60 mm |
|             | SOT-23 (6)                 | 2.90 mm × 1.60 mm |
|             | SC70 (5)                   | 2.00 mm × 1.25 mm |
|             | SOT-553 (5) <sup>(2)</sup> | 1.60 mm × 1.20 mm |
| OPA2990     | SOIC (8)                   | 4.90 mm × 3.90 mm |
|             | SOT-23 (8) <sup>(2)</sup>  | 2.90 mm × 1.60 mm |
|             | TSSOP (8)                  | 3.00 mm × 4.40 mm |
|             | VSSOP (8) <sup>(2)</sup>   | 3.00 mm × 3.00 mm |
|             | WSON (8)                   | 2.00 mm × 2.00 mm |
|             | X2QFN (10)                 | 2.00 mm × 1.50 mm |
| OPA4990     | SOIC (14)                  | 8.65 mm × 3.90 mm |
|             | TSSOP (14)                 | 5.00 mm × 4.40 mm |
|             | WQFN (16) <sup>(2)</sup>   | 3.00 mm × 3.00 mm |
|             | X2QFN (14) <sup>(2)</sup>  | 2.00 mm × 2.00 mm |

(1) For all available packages, see the orderable addendum at the end of the data sheet.

(2) This package is preview only.

## OPAx990 in a High-Voltage, Multiplexed, Data-Acquisition System



## Table of Contents

|                                                  |           |                                                                  |           |
|--------------------------------------------------|-----------|------------------------------------------------------------------|-----------|
| <b>1 Features</b> .....                          | <b>1</b>  | 7.4 Device Functional Modes.....                                 | <b>31</b> |
| <b>2 Applications</b> .....                      | <b>1</b>  | <b>8 Application and Implementation</b> .....                    | <b>32</b> |
| <b>3 Description</b> .....                       | <b>1</b>  | 8.1 Application Information.....                                 | <b>32</b> |
| <b>4 Revision History</b> .....                  | <b>2</b>  | 8.2 Typical Applications .....                                   | <b>32</b> |
| <b>5 Pin Configuration and Functions</b> .....   | <b>4</b>  | <b>9 Power Supply Recommendations</b> .....                      | <b>34</b> |
| <b>6 Specifications</b> .....                    | <b>10</b> | <b>10 Layout</b> .....                                           | <b>34</b> |
| 6.1 Absolute Maximum Ratings .....               | 10        | 10.1 Layout Guidelines .....                                     | 34        |
| 6.2 ESD Ratings.....                             | 10        | 10.2 Layout Example .....                                        | 34        |
| 6.3 Recommended Operating Conditions.....        | 10        | <b>11 Device and Documentation Support</b> .....                 | <b>37</b> |
| 6.4 Thermal Information for Single Channel ..... | 10        | 11.1 Device Support.....                                         | 37        |
| 6.5 Thermal Information for Dual Channel.....    | 11        | 11.2 Documentation Support .....                                 | 37        |
| 6.6 Thermal Information for Quad Channel .....   | 11        | 11.3 Related Links .....                                         | 37        |
| 6.7 Electrical Characteristics.....              | 12        | 11.4 Receiving Notification of Documentation Updates             | 38        |
| 6.8 Typical Characteristics.....                 | 15        | 11.5 Support Resources .....                                     | 38        |
| <b>7 Detailed Description</b> .....              | <b>23</b> | 11.6 Trademarks .....                                            | 38        |
| 7.1 Overview .....                               | 23        | 11.7 Electrostatic Discharge Caution.....                        | 38        |
| 7.2 Functional Block Diagram .....               | 23        | 11.8 Glossary .....                                              | 38        |
| 7.3 Feature Description.....                     | 24        | <b>12 Mechanical, Packaging, and Orderable Information</b> ..... | <b>38</b> |

## 4 Revision History

NOTE: Page numbers for previous revisions may differ from page numbers in the current version.

| <b>Changes from Revision E (December 2019) to Revision F</b>                                                           | <b>Page</b> |
|------------------------------------------------------------------------------------------------------------------------|-------------|
| Removed preview notation from OPA2990 X2QFN (10) package from <i>Device Information</i> table .....                    | <b>1</b>    |
| Removed preview notation from OPA2990S RUG package (X2QFN) in the <i>Pin Configuration and Functions</i> section ..... | <b>6</b>    |
| Changed RUG (X2QFN) in <i>Thermal Information for Dual Channel</i> section.....                                        | <b>10</b>   |

| <b>Changes from Revision D (July 2019) to Revision E</b>                                                                          | <b>Page</b> |
|-----------------------------------------------------------------------------------------------------------------------------------|-------------|
| Changed the OPA990 and OPA4990 device statuses from <i>Advance Information</i> to <i>Production Data</i> .....                    | <b>1</b>    |
| Removed preview notation from OPA990 SOT-23 (5) package from <i>Device Information</i> table .....                                | <b>1</b>    |
| Removed preview notation from OPA990S SOT-23 (6) package from <i>Device Information</i> table.....                                | <b>1</b>    |
| Removed preview notation from OPA990 SC70 (5) package from <i>Device Information</i> table.....                                   | <b>1</b>    |
| Removed preview notation from OPA4990 SOIC (14) package from <i>Device Information</i> table.....                                 | <b>1</b>    |
| Removed preview notation from OPA4990 TSSOP (14) package from <i>Device Information</i> table .....                               | <b>1</b>    |
| Removed preview notation from OPA990 DBV package (SOT-23) in the <i>Pin Configuration and Functions</i> section .....             | <b>4</b>    |
| Removed preview notation from OPA990 DCK package (SC70) in the <i>Pin Configuration and Functions</i> section .....               | <b>4</b>    |
| Removed preview notation from OPA990S DBV package (SOT-23) in the <i>Pin Configuration and Functions</i> section.....             | <b>4</b>    |
| Removed preview notation from OPA4990 D (SOIC) and TSSOP (PW) packages in the <i>Pin Configuration and Functions</i> section..... | <b>7</b>    |

| <b>Changes from Revision C (May 2019) to Revision D</b>                                                              | <b>Page</b> |
|----------------------------------------------------------------------------------------------------------------------|-------------|
| Removed preview notation from OPA2990 WSON (8) package from <i>Device Information</i> table .....                    | <b>1</b>    |
| Removed preview notation from OPA2990 DSG package (WSON) in the <i>Pin Configuration and Functions</i> section ..... | <b>5</b>    |
| Added SHUTDOWN to Electrical Characteristics table.....                                                              | <b>13</b>   |
| Added <i>Shutdown</i> section to the <i>Detailed Description</i> section.....                                        | <b>31</b>   |

---

**Changes from Revision B (April 2019) to Revision C**
**Page**


---

- Removed preview notation from OPA2990 TSSOP (8) package from *Device Information* table ..... [1](#)
  - Removed preview notation from OPA2990 PW package (TSSOP) in the *Pin Configuration and Functions* section..... [5](#)
- 

---

**Changes from Revision A (March 2019) to Revision B**
**Page**


---

- Removed preview notation from OPA2990 SOIC (8) package from *Device Information* table..... [1](#)
  - Removed preview notation from OPA2990 D package (SOIC) in the *Pin Configuration and Functions* section..... [5](#)
- 

---


**Changes from Original (February 2019) to Revision A**
**Page**


---

- Changed the OPA2990 device status from *Advance Information* to *Production Data*..... [1](#)
-


## 5 Pin Configuration and Functions

**OPA990 DBV and DRL Package<sup>(1)</sup>**  
5-Pin SOT-23 and SOT-553  
Top View



(1) DRL package is preview only.


**OPA990 DCK Package**  
5-Pin SC70  
Top View



**Pin Functions: OPA990**

| NAME | PIN         |     | I/O | DESCRIPTION                     |
|------|-------------|-----|-----|---------------------------------|
|      | DBV and DRL | DCK |     |                                 |
| IN+  | 3           | 1   | I   | Noninverting input              |
| IN–  | 4           | 3   | I   | Inverting input                 |
| OUT  | 1           | 4   | O   | Output                          |
| V+   | 5           | 5   | —   | Positive (highest) power supply |
| V–   | 2           | 2   | —   | Negative (lowest) power supply  |

**OPA990S DBV and DRL Package<sup>(1)</sup>**  
6-Pin SOT-23 and SOT-563  
Top View




(1) DRL package is preview only.

**Pin Functions: OPA990S**


| NAME                     | PIN         |  | I/O | DESCRIPTION                                                                                                              |
|--------------------------|-------------|--|-----|--------------------------------------------------------------------------------------------------------------------------|
|                          | DBV and DRL |  |     |                                                                                                                          |
| IN+                      | 3           |  | I   | Noninverting input                                                                                                       |
| IN–                      | 4           |  | I   | Inverting input                                                                                                          |
| OUT                      | 1           |  | O   | Output                                                                                                                   |
| $\overline{\text{SHDN}}$ | 5           |  | I   | Shutdown: low = amplifier enabled, high = amplifier disabled. See <a href="#">Shutdown</a> section for more information. |
| V+                       | 6           |  | —   | Positive (highest) power supply                                                                                          |
| V–                       | 2           |  | —   | Negative (lowest) power supply                                                                                           |

**OPA2990 D, DDF, DGK, and PW Packages<sup>(1)</sup>**  
**8-Pin SOIC, SOT-23-8, TSSOP, and VSSOP**  
**Top View**



(1) DDF and DGK packages are preview only.


**OPA2990 DSG Package<sup>(1)</sup>**  
**8-Pin WSON With Exposed Thermal Pad**  
**Top View**




(1) Connect thermal pad to V-. See [Packages With an Exposed Thermal Pad](#) section for more information.

**Pin Functions: OPA2990**

| PIN  |                              | I/O | DESCRIPTION                     |
|------|------------------------------|-----|---------------------------------|
| NAME | SOIC, TSSOP, VSSOP, and WSON |     |                                 |
| IN1+ | 3                            | I   | Noninverting input, channel 1   |
| IN1– | 2                            | I   | Inverting input, channel 1      |
| IN2+ | 5                            | I   | Noninverting input, channel 2   |
| IN2– | 6                            | I   | Inverting input, channel 2      |
| OUT1 | 1                            | O   | Output, channel 1               |
| OUT2 | 7                            | O   | Output, channel 2               |
| V+   | 8                            | —   | Positive (highest) power supply |
| V–   | 4                            | —   | Negative (lowest) power supply  |




(1) Package is preview only.




### Pin Functions: OPA2990S

| PIN                       |       |       | I/O | DESCRIPTION                                                                                                                         |
|---------------------------|-------|-------|-----|-------------------------------------------------------------------------------------------------------------------------------------|
| NAME                      | VSSOP | X2QFN |     |                                                                                                                                     |
| IN1+                      | 3     | 10    | I   | Noninverting input, channel 1                                                                                                       |
| IN1–                      | 2     | 9     | I   | Inverting input, channel 1                                                                                                          |
| IN2+                      | 7     | 4     | I   | Noninverting input, channel 2                                                                                                       |
| IN2–                      | 8     | 5     | I   | Inverting input, channel 2                                                                                                          |
| OUT1                      | 1     | 8     | O   | Output, channel 1                                                                                                                   |
| OUT2                      | 9     | 6     | O   | Output, channel 2                                                                                                                   |
| $\overline{\text{SHDN}}1$ | 5     | 2     | I   | Shutdown, channel 1: low = amplifier enabled, high = amplifier disabled. See <a href="#">Shutdown</a> section for more information. |
| $\overline{\text{SHDN}}2$ | 6     | 3     | I   | Shutdown, channel 2: low = amplifier enabled, high = amplifier disabled. See <a href="#">Shutdown</a> section for more information. |
| V+                        | 10    | 7     | —   | Positive (highest) power supply                                                                                                     |
| V–                        | 4     | 1     | —   | Negative (lowest) power supply                                                                                                      |


**OPA4990 D and PW Packages**  
**14-Pin SOIC and TSSOP**  
**Top View**



**OPA4990 RUC Packages<sup>(1)</sup>**  
**14-Pin X2QFN With Exposed Thermal Pad**  
**Top View**



**OPA4990 RTE Package<sup>(1)(2)</sup>**  
**16-Pin WQFN With Exposed Thermal Pad**  
**Top View**



(1) Package is preview only.

- (1) Connect thermal pad to V-. See [Packages With an Exposed Thermal Pad](#) section for more information.
- (2) Package is preview only.


### Pin Functions: OPA4990

| NAME | PIN            |      |       | I/O | DESCRIPTION                   |
|------|----------------|------|-------|-----|-------------------------------|
|      | SOIC and TSSOP | WQFN | X2QFN |     |                               |
| IN1+ | 3              | 1    | 2     | I   | Noninverting input, channel 1 |
| IN1- | 2              | 16   | 1     | I   | Inverting input, channel 1    |
| IN2+ | 5              | 3    | 4     | I   | Noninverting input, channel 2 |
| IN2- | 6              | 4    | 5     | I   | Inverting input, channel 2    |
| IN3+ | 10             | 10   | 9     | I   | Noninverting input, channel 3 |
| IN3- | 9              | 9    | 8     | I   | Inverting input, channel 3    |

**Pin Functions: OPA4990 (continued)**

| PIN  |                |      |       | I/O | DESCRIPTION                     |
|------|----------------|------|-------|-----|---------------------------------|
| NAME | SOIC and TSSOP | WQFN | X2QFN |     |                                 |
| IN4+ | 12             | 12   | 11    | I   | Noninverting input, channel 4   |
| IN4– | 13             | 13   | 12    | I   | Inverting input, channel 4      |
| NC   | —              | 6, 7 | —     | —   | Do not connect                  |
| OUT1 | 1              | 15   | 14    | O   | Output, channel 1               |
| OUT2 | 7              | 5    | 6     | O   | Output, channel 2               |
| OUT3 | 8              | 8    | 7     | O   | Output, channel 3               |
| OUT4 | 14             | 14   | 13    | O   | Output, channel 4               |
| V+   | 4              | 2    | 3     | —   | Positive (highest) power supply |
| V–   | 11             | 11   | 10    | —   | Negative (lowest) power supply  |

**OPA4990S RTE Package<sup>(1)</sup>  
16-Pin WQFN With Exposed Thermal Pad  
Top View**



- (1) Connect thermal pad to V–. See [Packages With an Exposed Thermal Pad](#) section for more information.
- (2) Package is preview only.

**Pin Functions: OPA4990S**

| PIN                        |      | I/O | DESCRIPTION                                                                                                                                  |
|----------------------------|------|-----|----------------------------------------------------------------------------------------------------------------------------------------------|
| NAME                       | WQFN |     |                                                                                                                                              |
| IN1+                       | 1    | I   | Noninverting input, channel 1                                                                                                                |
| IN1–                       | 16   | I   | Inverting input, channel 1                                                                                                                   |
| IN2+                       | 3    | I   | Noninverting input, channel 2                                                                                                                |
| IN2–                       | 4    | I   | Inverting input, channel 2                                                                                                                   |
| IN3+                       | 10   | I   | Noninverting input, channel 3                                                                                                                |
| IN3–                       | 9    | I   | Inverting input, channel 3                                                                                                                   |
| IN4+                       | 12   | I   | Noninverting input, channel 4                                                                                                                |
| IN4–                       | 13   | I   | Inverting input, channel 4                                                                                                                   |
| OUT1                       | 15   | O   | Output, channel 1                                                                                                                            |
| OUT2                       | 5    | O   | Output, channel 2                                                                                                                            |
| OUT3                       | 8    | O   | Output, channel 3                                                                                                                            |
| OUT4                       | 14   | O   | Output, channel 4                                                                                                                            |
| $\overline{\text{SHDN12}}$ | 6    | I   | Shutdown, channels 1 and 2: low = amplifiers enabled, high = amplifiers disabled. See <a href="#">Shutdown</a> section for more information. |
| $\overline{\text{SHDN34}}$ | 7    | I   | Shutdown, channels 3 and 4: low = amplifiers enabled, high = amplifiers disabled. See <a href="#">Shutdown</a> section for more information. |
| VCC+                       | 2    | —   | Positive (highest) power supply                                                                                                              |
| VCC–                       | 11   | —   | Negative (lowest) power supply                                                                                                               |

## 6 Specifications

### 6.1 Absolute Maximum Ratings

over operating ambient temperature range (unless otherwise noted)<sup>(1)</sup>

|                                      |                                     | MIN          | MAX          | UNIT |
|--------------------------------------|-------------------------------------|--------------|--------------|------|
| Supply voltage, $V_S = (V+) - (V-)$  |                                     | 0            | 42           | V    |
| Signal input pins                    | Common-mode voltage <sup>(2)</sup>  | $(V-) - 0.5$ | $(V+) + 0.5$ | V    |
|                                      | Differential voltage <sup>(2)</sup> |              | $V_S + 0.2$  | V    |
|                                      | Current <sup>(2)</sup>              | -10          | 10           | mA   |
| Output short-circuit <sup>(3)</sup>  |                                     | Continuous   |              |      |
| Operating ambient temperature, $T_A$ |                                     | -55          | 150          | °C   |
| Junction temperature, $T_J$          |                                     |              | 150          | °C   |
| Storage temperature, $T_{stg}$       |                                     | -65          | 150          | °C   |

- (1) Stresses beyond those listed under *Absolute Maximum Ratings* may cause permanent damage to the device. These are stress ratings only, which do not imply functional operation of the device at these or any other conditions beyond those indicated under *Recommended Operating Conditions*. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.
- (2) Input pins are diode-clamped to the power-supply rails. Input signals that may swing more than 0.5 V beyond the supply rails must be current limited to 10 mA or less.
- (3) Short-circuit to ground, one amplifier per package. Extended short-circuit current, especially with higher supply voltage, can cause excessive heating and eventual destruction. See the [Thermal Protection](#) section for more information.

### 6.2 ESD Ratings

|             |                         |                                                                                | VALUE | UNIT |
|-------------|-------------------------|--------------------------------------------------------------------------------|-------|------|
| $V_{(ESD)}$ | Electrostatic discharge | Human body model (HBM), per ANSI/ESDA/JEDEC JS-001 <sup>(1)</sup>              | ±2000 | V    |
|             |                         | Charged device model (CDM), per JEDEC specification JESD22-C101 <sup>(2)</sup> | ±1000 |      |

- (1) JEDEC document JEP155 states that 500-V HBM allows safe manufacturing with a standard ESD control process.
- (2) JEDEC document JEP157 states that 250-V CDM allows safe manufacturing with a standard ESD control process.

### 6.3 Recommended Operating Conditions

over operating ambient temperature range (unless otherwise noted)

|          |                                                              | MIN          | MAX                 | UNIT |
|----------|--------------------------------------------------------------|--------------|---------------------|------|
| $V_S$    | Supply voltage, $(V+) - (V-)$                                | 2.7          | 40                  | V    |
| $V_I$    | Input voltage range                                          | $(V-) - 0.2$ | $(V+) + 0.2$        | V    |
| $V_{IH}$ | High level input voltage at shutdown pin (amplifier enabled) | $(V-) + 1.1$ | $(V-) + 20 V^{(1)}$ | V    |
| $V_{IL}$ | Low level input voltage at shutdown pin (amplifier disabled) | $(V-)$       | $(V-) + 0.2$        | V    |
| $T_A$    | Specified temperature                                        | -40          | 125                 | °C   |

- (1) Cannot exceed  $V+$ .

### 6.4 Thermal Information for Single Channel

| THERMAL METRIC <sup>(1)</sup> |                                              | OPA990, OPA990S |        |               |                                 |        | UNIT |
|-------------------------------|----------------------------------------------|-----------------|--------|---------------|---------------------------------|--------|------|
|                               |                                              | DBV<br>(SOT-23) |        | DCK<br>(SC70) | DRL <sup>(2)</sup><br>(SOT-553) |        |      |
|                               |                                              | 5 PINS          | 6 PINS | 5 PINS        | 5 PINS                          | 6 PINS |      |
| R <sub>θJA</sub>              | Junction-to-ambient thermal resistance       | 192.1           | 1174.5 | 204.6         | TBD                             | TBD    | °C/W |
| R <sub>θJC(top)</sub>         | Junction-to-case (top) thermal resistance    | 113.6           | 113.4  | 116.5         | TBD                             | TBD    | °C/W |
| R <sub>θJB</sub>              | Junction-to-board thermal resistance         | 60.5            | 55.8   | 51.8          | TBD                             | TBD    | °C/W |
| Ψ <sub>JT</sub>               | Junction-to-top characterization parameter   | 37.2            | 39.6   | 24.9          | TBD                             | TBD    | °C/W |
| Ψ <sub>JB</sub>               | Junction-to-board characterization parameter | 60.3            | 55.6   | 51.5          | TBD                             | TBD    | °C/W |
| R <sub>θJC(bot)</sub>         | Junction-to-case (bottom) thermal resistance | N/A             | N/A    | N/A           | TBD                             | TBD    | °C/W |

- (1) For more information about traditional and new thermal metrics, see the *Semiconductor and IC Package Thermal Metrics* application report, [SPRA953](#).
- (2) This package option is preview for OPA990.

## 6.5 Thermal Information for Dual Channel

| THERMAL METRIC <sup>(1)</sup> |                                              | OPA2990, OPA2990S |                                  |                               |                               |               |               |                | UNIT |
|-------------------------------|----------------------------------------------|-------------------|----------------------------------|-------------------------------|-------------------------------|---------------|---------------|----------------|------|
|                               |                                              | D<br>(SOIC)       | DDF <sup>(2)</sup><br>(SOT-23-8) | DGK <sup>(2)</sup><br>(VSSOP) | DGS <sup>(2)</sup><br>(VSSOP) | DSG<br>(WSON) | PW<br>(TSSOP) | RUG<br>(X2QFN) |      |
|                               |                                              | 8 PINS            | 8 PINS                           | 8 PINS                        | 10 PINS                       | 8 PINS        | 8 PINS        | 10 PINS        |      |
| R <sub>θJA</sub>              | Junction-to-ambient thermal resistance       | 138.7             | TBD                              | 189.3                         | 152.2                         | 81.6          | 188.4         | 149.6          | °C/W |
| R <sub>θJC(top)</sub>         | Junction-to-case (top) thermal resistance    | 78.7              | TBD                              | 75.8                          | 67.3                          | 101.6         | 77.1          | 58.3           | °C/W |
| R <sub>θJB</sub>              | Junction-to-board thermal resistance         | 82.2              | TBD                              | 111.0                         | 95.5                          | 48.3          | 119.1         | 77.7           | °C/W |
| ψ <sub>JT</sub>               | Junction-to-top characterization parameter   | 27.8              | TBD                              | 15.4                          | 67.9                          | 6.0           | 14.2          | 1.3            | °C/W |
| ψ <sub>JB</sub>               | Junction-to-board characterization parameter | 81.4              | TBD                              | 109.3                         | 94.3                          | 48.3          | 117.4         | 77.5           | °C/W |
| R <sub>θJC(bot)</sub>         | Junction-to-case (bottom) thermal resistance | N/A               | TBD                              | N/A                           | N/A                           | 22.8          | N/A           | N/A            | °C/W |

- (1) For more information about traditional and new thermal metrics, see the *Semiconductor and IC Package Thermal Metrics* application report, [SPRA953](#).
- (2) This package option is preview for OPA2990.

## 6.6 Thermal Information for Quad Channel

| THERMAL METRIC <sup>(1)</sup> |                                              | OPA4990, OPA4990S |               |                              |                              | UNIT |
|-------------------------------|----------------------------------------------|-------------------|---------------|------------------------------|------------------------------|------|
|                               |                                              | D<br>(SOIC)       | PW<br>(TSSOP) | RTE <sup>(2)</sup><br>(WQFN) | RUC <sup>(2)</sup><br>(WQFN) |      |
|                               |                                              | 14 PINS           | 14 PINS       | 16 PINS                      | 14 PINS                      |      |
| R <sub>θJA</sub>              | Junction-to-ambient thermal resistance       | 105.2             | 134.7         | 53.5                         | 143.0                        | °C/W |
| R <sub>θJC(top)</sub>         | Junction-to-case (top) thermal resistance    | 61.2              | 55.0          | 58.3                         | 46.4                         | °C/W |
| R <sub>θJB</sub>              | Junction-to-board thermal resistance         | 61.1              | 79.0          | 28.6                         | 81.8                         | °C/W |
| ψ <sub>JT</sub>               | Junction-to-top characterization parameter   | 21.4              | 9.2           | 2.1                          | 1.0                          | °C/W |
| ψ <sub>JB</sub>               | Junction-to-board characterization parameter | 60.7              | 78.1          | 28.6                         | 81.5                         | °C/W |
| R <sub>θJC(bot)</sub>         | Junction-to-case (bottom) thermal resistance | N/A               | N/A           | 12.6                         | N/A                          | °C/W |

- (1) For more information about traditional and new thermal metrics, see the *Semiconductor and IC Package Thermal Metrics* application report, [SPRA953](#).
- (2) This package option is preview for OPA4990.

## 6.7 Electrical Characteristics

For  $V_S = (V+) - (V-) = 2.7\text{ V to }40\text{ V}$  ( $\pm 1.35\text{ V to } \pm 20\text{ V}$ ) at  $T_A = 25^\circ\text{C}$ ,  $R_L = 10\text{ k}\Omega$  connected to  $V_S / 2$ ,  $V_{CM} = V_S / 2$ , and  $V_{OUT} = V_S / 2$ , unless otherwise noted.

| PARAMETER            |                                          | TEST CONDITIONS                                                                                                                                     |                                 | MIN                                                                                                  | TYP                     | MAX               | UNIT |
|----------------------|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------|------------------------------------------------------------------------------------------------------|-------------------------|-------------------|------|
| OFFSET VOLTAGE       |                                          |                                                                                                                                                     |                                 |                                                                                                      |                         |                   |      |
| V <sub>OS</sub>      | Input offset voltage                     | V <sub>CM</sub> = V <sub>−</sub>                                                                                                                    |                                 | ±0.3                                                                                                 | ±1.5                    | mV                |      |
|                      |                                          |                                                                                                                                                     | T <sub>A</sub> = −40°C to 125°C | ±1.75                                                                                                |                         |                   |      |
| dV <sub>OS</sub> /dT | Input offset voltage drift               |                                                                                                                                                     | T <sub>A</sub> = −40°C to 125°C | ±0.6                                                                                                 |                         | μV/°C             |      |
| PSRR                 | Input offset voltage versus power supply | V <sub>CM</sub> = V <sub>−</sub> , V <sub>S</sub> = 4 V to 40 V                                                                                     | T <sub>A</sub> = −40°C to 125°C | ±0.1                                                                                                 | ±1.3                    | μV/V              |      |
|                      |                                          | V <sub>CM</sub> = V <sub>−</sub> , V <sub>S</sub> = 2.7 V to 40 V <sup>(1)</sup>                                                                    |                                 | ±0.75                                                                                                | ±6.6                    |                   |      |
|                      | Channel separation                       | f = 0 Hz                                                                                                                                            |                                 | 5                                                                                                    |                         | μV/V              |      |
| INPUT BIAS CURRENT   |                                          |                                                                                                                                                     |                                 |                                                                                                      |                         |                   |      |
| I <sub>B</sub>       | Input bias current                       |                                                                                                                                                     |                                 | ±10                                                                                                  |                         | pA                |      |
| I <sub>OS</sub>      | Input offset current                     |                                                                                                                                                     |                                 | ±5                                                                                                   |                         | pA                |      |
| NOISE                |                                          |                                                                                                                                                     |                                 |                                                                                                      |                         |                   |      |
| E <sub>N</sub>       | Input voltage noise                      | f = 0.1 Hz to 10 Hz                                                                                                                                 |                                 | 6                                                                                                    |                         | μV <sub>PP</sub>  |      |
|                      |                                          |                                                                                                                                                     |                                 | 1                                                                                                    |                         | μV <sub>RMS</sub> |      |
| e <sub>N</sub>       | Input voltage noise density              | f = 1 kHz                                                                                                                                           |                                 | 30                                                                                                   |                         | nV/√Hz            |      |
|                      |                                          | f = 10 kHz                                                                                                                                          |                                 | 28                                                                                                   |                         |                   |      |
| i <sub>N</sub>       | Input current noise                      | f = 1 kHz                                                                                                                                           |                                 | 2                                                                                                    |                         | fA/√Hz            |      |
| INPUT VOLTAGE RANGE  |                                          |                                                                                                                                                     |                                 |                                                                                                      |                         |                   |      |
| V <sub>CM</sub>      | Common-mode voltage range                |                                                                                                                                                     |                                 | (V <sub>−</sub> ) − 0.2                                                                              | (V <sub>+</sub> ) + 0.2 | V                 |      |
| CMRR                 | Common-mode rejection ratio              | V <sub>S</sub> = 40 V, (V <sub>−</sub> ) − 0.1 V < V <sub>CM</sub> < (V <sub>+</sub> ) − 2 V (PMOS pair)                                            | T <sub>A</sub> = −40°C to 125°C | 100                                                                                                  | 115                     | dB                |      |
|                      |                                          | V <sub>S</sub> = 4 V, (V <sub>−</sub> ) − 0.1 V < V <sub>CM</sub> < (V <sub>+</sub> ) − 2 V (PMOS pair)                                             |                                 | 75                                                                                                   | 90                      |                   |      |
|                      |                                          | V <sub>S</sub> = 2.7 V, (V <sub>−</sub> ) − 0.1 V < V <sub>CM</sub> < (V <sub>+</sub> ) − 2 V (PMOS pair) <sup>(1)</sup>                            |                                 | 70                                                                                                   | 90                      |                   |      |
|                      |                                          | V <sub>S</sub> = 2.7 − 40 V, (V <sub>+</sub> ) − 1 V < V <sub>CM</sub> < (V <sub>+</sub> ) + 0.1 V (NMOS pair)                                      |                                 | 80                                                                                                   |                         |                   |      |
|                      |                                          | (V <sub>+</sub> ) − 2 V < V <sub>CM</sub> < (V <sub>+</sub> ) − 1 V                                                                                 |                                 | See <a href="#">Offset Voltage (Transition Region)</a> in the <i>Typical Characteristics</i> section |                         |                   |      |
| INPUT CAPACITANCE    |                                          |                                                                                                                                                     |                                 |                                                                                                      |                         |                   |      |
| Z <sub>ID</sub>      | Differential                             |                                                                                                                                                     |                                 | 100    3                                                                                             |                         | MΩ    pF          |      |
| Z <sub>ICM</sub>     | Common-mode                              |                                                                                                                                                     |                                 | 6    1                                                                                               |                         | TΩ    pF          |      |
| OPEN-LOOP GAIN       |                                          |                                                                                                                                                     |                                 |                                                                                                      |                         |                   |      |
| A <sub>OL</sub>      | Open-loop voltage gain                   | V <sub>S</sub> = 40 V, V <sub>CM</sub> = V <sub>S</sub> / 2, (V <sub>−</sub> ) + 0.1 V < V <sub>O</sub> < (V <sub>+</sub> ) − 0.1 V                 | T <sub>A</sub> = −40°C to 125°C | 120                                                                                                  | 145                     | dB                |      |
|                      |                                          | V <sub>S</sub> = 4 V, V <sub>CM</sub> = V <sub>S</sub> / 2, (V <sub>−</sub> ) + 0.1 V < V <sub>O</sub> < (V <sub>+</sub> ) − 0.1 V                  | T <sub>A</sub> = −40°C to 125°C | 104                                                                                                  | 130                     |                   |      |
|                      |                                          | V <sub>S</sub> = 2.7 V, V <sub>CM</sub> = V <sub>S</sub> / 2, (V <sub>−</sub> ) + 0.1 V < V <sub>O</sub> < (V <sub>+</sub> ) − 0.1 V <sup>(1)</sup> | T <sub>A</sub> = −40°C to 125°C | 101                                                                                                  | 118                     | dB                |      |
|                      |                                          | V <sub>S</sub> = 2.7 V, V <sub>CM</sub> = V <sub>S</sub> / 2, (V <sub>−</sub> ) + 0.1 V < V <sub>O</sub> < (V <sub>+</sub> ) − 0.1 V <sup>(1)</sup> | T <sub>A</sub> = −40°C to 125°C | 101                                                                                                  | 117                     | dB                |      |

(1) Specified by characterization only.

## Electrical Characteristics (continued)

For  $V_S = (V_+) - (V_-) = 2.7\text{ V to }40\text{ V}$  ( $\pm 1.35\text{ V to } \pm 20\text{ V}$ ) at  $T_A = 25^\circ\text{C}$ ,  $R_L = 10\text{ k}\Omega$  connected to  $V_S / 2$ ,  $V_{CM} = V_S / 2$ , and  $V_{OUT} = V_S / 2$ , unless otherwise noted.

| PARAMETER                 |                                                   | TEST CONDITIONS                                                                                         | MIN                                                 | TYP                    | MAX | UNIT             |
|---------------------------|---------------------------------------------------|---------------------------------------------------------------------------------------------------------|-----------------------------------------------------|------------------------|-----|------------------|
| <b>FREQUENCY RESPONSE</b> |                                                   |                                                                                                         |                                                     |                        |     |                  |
| GBW                       | Gain-bandwidth product                            |                                                                                                         |                                                     | 1.1                    |     | MHz              |
| SR                        | Slew rate                                         | $V_S = 40\text{ V}$ , $G = +1$ , $C_L = 20\text{ pF}$                                                   |                                                     | 4.5                    |     | V/ $\mu\text{s}$ |
| $t_S$                     | Settling time                                     | To 0.1%, $V_S = 40\text{ V}$ , $V_{STEP} = 10\text{ V}$ , $G = +1$ , $C_L = 20\text{ pF}$               |                                                     | 4                      |     | $\mu\text{s}$    |
|                           |                                                   | To 0.1%, $V_S = 40\text{ V}$ , $V_{STEP} = 2\text{ V}$ , $G = +1$ , $C_L = 20\text{ pF}$                |                                                     | 2                      |     |                  |
|                           |                                                   | To 0.01%, $V_S = 40\text{ V}$ , $V_{STEP} = 10\text{ V}$ , $G = +1$ , $C_L = 20\text{ pF}$              |                                                     | 5                      |     |                  |
|                           |                                                   | To 0.01%, $V_S = 40\text{ V}$ , $V_{STEP} = 2\text{ V}$ , $G = +1$ , $C_L = 20\text{ pF}$               |                                                     | 3                      |     |                  |
|                           | Phase margin                                      | $G = +1$ , $R_L = 10\text{ k}\Omega$ , $C_L = 20\text{ pF}$                                             |                                                     | 60                     |     | $^\circ$         |
|                           | Overload recovery time                            | $V_{IN} \times \text{gain} > V_S$                                                                       |                                                     | 600                    |     | ns               |
| THD+N                     | Total harmonic distortion + noise                 | $V_S = 40\text{ V}$ , $V_O = 1\text{ V}_{RMS}$ , $G = 1$ , $f = 1\text{ kHz}$                           |                                                     | 0.00162%               |     |                  |
| <b>OUTPUT</b>             |                                                   |                                                                                                         |                                                     |                        |     |                  |
|                           | Voltage output swing from rail                    | Positive and negative rail headroom                                                                     | $V_S = 40\text{ V}$ , $R_L = \text{no load}$        | 2                      |     | mV               |
|                           |                                                   |                                                                                                         | $V_S = 40\text{ V}$ , $R_L = 10\text{ k}\Omega$     | 45                     | 60  |                  |
|                           |                                                   |                                                                                                         | $V_S = 40\text{ V}$ , $R_L = 2\text{ k}\Omega$      | 200                    | 300 |                  |
|                           |                                                   |                                                                                                         | $V_S = 2.7\text{ V}$ , $R_L = \text{no load}$       | 1                      |     |                  |
|                           |                                                   |                                                                                                         | $V_S = 2.7\text{ V}$ , $R_L = 10\text{ k}\Omega$    | 5                      | 20  |                  |
|                           |                                                   |                                                                                                         | $V_S = 2.7\text{ V}$ , $R_L = 2\text{ k}\Omega$     | 25                     | 50  |                  |
| $I_{SC}$                  | Short-circuit current                             |                                                                                                         |                                                     | $\pm 80$               |     | mA               |
| $C_{LOAD}$                | Capacitive load drive                             |                                                                                                         | See <a href="#">Typical Characteristics</a> section |                        |     |                  |
| $Z_O$                     | Open-loop output impedance                        | $f = 1\text{ MHz}$ , $I_O = 0\text{ A}$                                                                 |                                                     | 575                    |     | $\Omega$         |
| <b>POWER SUPPLY</b>       |                                                   |                                                                                                         |                                                     |                        |     |                  |
| $I_Q$                     | Quiescent current per amplifier                   | OPA2990, OPA4990, $I_O = 0\text{ A}$                                                                    |                                                     | 120                    | 150 | $\mu\text{A}$    |
|                           |                                                   |                                                                                                         | $T_A = -40^\circ\text{C to } 125^\circ\text{C}$     |                        | 160 |                  |
|                           |                                                   | OPA990, $I_O = 0\text{ A}$                                                                              |                                                     | 130                    | 170 |                  |
|                           |                                                   |                                                                                                         | $T_A = -40^\circ\text{C to } 125^\circ\text{C}$     |                        | 175 |                  |
|                           | Turn-on time                                      | At $T_A = 25^\circ\text{C}$ , $V_S = 40\text{ V}$ , $V_S$ ramp rate $> 0.3\text{ V}/\mu\text{s}$        |                                                     | 40                     |     | $\mu\text{s}$    |
| <b>SHUTDOWN</b>           |                                                   |                                                                                                         |                                                     |                        |     |                  |
| $I_{QSD}$                 | Quiescent current per amplifier                   | $V_S = 2.7\text{ V to } 40\text{ V}$ , all amplifiers disabled, $\text{SHDN} = V_- + 1\text{ V}$        |                                                     | 20                     | 30  | $\mu\text{A}$    |
| $Z_{SHDN}$                | Output impedance during shutdown                  | $V_S = 2.7\text{ V to } 40\text{ V}$ , amplifier disabled                                               |                                                     | 10    12               |     | G $\Omega$    pF |
| $V_{IH}$                  | Logic high threshold voltage (amplifier disabled) |                                                                                                         | $(V_-) + 1.1\text{ V}$                              |                        |     | V                |
| $V_{IL}$                  | Logic low threshold voltage (amplifier enabled)   |                                                                                                         |                                                     | $(V_-) + 0.2\text{ V}$ |     | V                |
| $t_{ON}$                  | Amplifier enable time <sup>(2)</sup>              | $G = +1$ , $V_{CM} = V_-$ , $V_O = 0.1 \times V_S / 2$                                                  |                                                     | 11                     |     | $\mu\text{s}$    |
| $t_{OFF}$                 | Amplifier disable time <sup>(2)</sup>             | $V_{CM} = V_-$ , $V_O = V_S / 2$                                                                        |                                                     | 2.5                    |     | $\mu\text{s}$    |
|                           | SHDN pin input bias current (per pin)             | $V_S = 2.7\text{ V to } 40\text{ V}$ , $(V_-) + 20\text{ V} \geq \text{SHDN} \geq (V_-) + 0.9\text{ V}$ |                                                     | 500                    |     | nA               |
|                           |                                                   | $V_S = 2.7\text{ V to } 40\text{ V}$ , $(V_-) \leq \text{SHDN} \leq (V_-) + 0.7\text{ V}$               |                                                     | 150                    |     |                  |


(2) Disable time ( $t_{OFF}$ ) and enable time ( $t_{ON}$ ) are defined as the time interval between the 50% point of the signal applied to the  $\overline{\text{SHDN}}$  pin and the point at which the output voltage reaches the 10% (disable) or 90% (enable) level.

**Table 1. Table of Graphs**

| DESCRIPTION                                                    | FIGURE                                                                                                        |
|----------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------|
| Offset Voltage Production Distribution                         | <a href="#">Figure 1</a>                                                                                      |
| Offset Voltage Drift Distribution                              | <a href="#">Figure 2</a>                                                                                      |
| Offset Voltage vs Temperature                                  | <a href="#">Figure 3</a> , <a href="#">Figure 4</a>                                                           |
| Offset Voltage vs Common-Mode Voltage                          | <a href="#">Figure 5</a> , <a href="#">Figure 6</a> , <a href="#">Figure 7</a> , <a href="#">Figure 8</a>     |
| Offset Voltage vs Power Supply                                 | <a href="#">Figure 9</a>                                                                                      |
| Open-Loop Gain and Phase vs Frequency                          | <a href="#">Figure 10</a>                                                                                     |
| Closed-Loop Gain and Phase vs Frequency                        | <a href="#">Figure 11</a>                                                                                     |
| Input Bias Current vs Common-Mode Voltage                      | <a href="#">Figure 12</a>                                                                                     |
| Input Bias Current vs Temperature                              | <a href="#">Figure 13</a>                                                                                     |
| Output Voltage Swing vs Output Current                         | <a href="#">Figure 14</a> , <a href="#">Figure 15</a> , <a href="#">Figure 16</a> , <a href="#">Figure 17</a> |
| CMRR and PSRR vs Frequency                                     | <a href="#">Figure 18</a>                                                                                     |
| CMRR vs Temperature                                            | <a href="#">Figure 19</a>                                                                                     |
| PSRR vs Temperature                                            | <a href="#">Figure 20</a>                                                                                     |
| 0.1-Hz to 10-Hz Noise                                          | <a href="#">Figure 21</a>                                                                                     |
| Input Voltage Noise Spectral Density vs Frequency              | <a href="#">Figure 22</a>                                                                                     |
| THD+N Ratio vs Frequency                                       | <a href="#">Figure 23</a>                                                                                     |
| THD+N vs Output Amplitude                                      | <a href="#">Figure 24</a>                                                                                     |
| Quiescent Current vs Supply Voltage                            | <a href="#">Figure 25</a>                                                                                     |
| Quiescent Current vs Temperature                               | <a href="#">Figure 26</a>                                                                                     |
| Open Loop Voltage Gain vs Temperature                          | <a href="#">Figure 27</a>                                                                                     |
| Open Loop Output Impedance vs Frequency                        | <a href="#">Figure 28</a>                                                                                     |
| Output Swing vs Supply Voltage                                 | <a href="#">Figure 29</a> , <a href="#">Figure 30</a> , <a href="#">Figure 31</a> , <a href="#">Figure 32</a> |
| Small Signal Overshoot vs Capacitive Load (100-mV Output Step) | <a href="#">Figure 33</a> , <a href="#">Figure 34</a>                                                         |
| Phase Margin vs Capacitive Load                                | <a href="#">Figure 35</a>                                                                                     |
| No Phase Reversal                                              | <a href="#">Figure 36</a>                                                                                     |
| Positive Overload Recovery                                     | <a href="#">Figure 37</a>                                                                                     |
| Negative Overload Recovery                                     | <a href="#">Figure 38</a>                                                                                     |
| Small-Signal Step Response (100 mV)                            | <a href="#">Figure 39</a> , <a href="#">Figure 40</a>                                                         |
| Large-Signal Step Response                                     | <a href="#">Figure 41</a> , <a href="#">Figure 42</a> , <a href="#">Figure 43</a>                             |
| Short-Circuit Current vs Temperature                           | <a href="#">Figure 44</a>                                                                                     |
| Maximum Output Voltage vs Frequency                            | <a href="#">Figure 45</a>                                                                                     |
| Channel Separation vs Frequency                                | <a href="#">Figure 46</a>                                                                                     |
| EMIRR vs Frequency                                             | <a href="#">Figure 47</a>                                                                                     |


## 6.8 Typical Characteristics

at  $T_A = 25^\circ\text{C}$ ,  $V_S = \pm 20\text{ V}$ ,  $V_{CM} = V_S / 2$ ,  $R_{LOAD} = 10\text{ k}\Omega$  connected to  $V_S / 2$ , and  $C_L = 10\text{ pF}$  (unless otherwise noted)



Distribution from 15526 amplifiers,  $T_A = 25^\circ\text{C}$

**Figure 1. Offset Voltage Production Distribution**



Distribution from 190 amplifiers

**Figure 2. Offset Voltage Drift Distribution**




**Figure 3. Offset Voltage vs Temperature**




**Figure 4. Offset Voltage vs Temperature**




**Figure 5. Offset Voltage vs Common-Mode Voltage**




**Figure 6. Offset Voltage vs Common-Mode Voltage (Transition Region)**

## Typical Characteristics (continued)

at  $T_A = 25^\circ\text{C}$ ,  $V_S = \pm 20\text{ V}$ ,  $V_{CM} = V_S / 2$ ,  $R_{LOAD} = 10\text{ k}\Omega$  connected to  $V_S / 2$ , and  $C_L = 10\text{ pF}$  (unless otherwise noted)




Figure 7. Offset Voltage vs Common-Mode Voltage




Figure 8. Offset Voltage vs Common-Mode Voltage




Figure 9. Offset Voltage vs Power Supply




Figure 10. Open-Loop Gain and Phase vs Frequency




Figure 11. Closed-Loop Gain vs Frequency




Figure 12. Input Bias Current vs Common-Mode Voltage

## Typical Characteristics (continued)

at  $T_A = 25^\circ\text{C}$ ,  $V_S = \pm 20\text{ V}$ ,  $V_{CM} = V_S / 2$ ,  $R_{LOAD} = 10\text{ k}\Omega$  connected to  $V_S / 2$ , and  $C_L = 10\text{ pF}$  (unless otherwise noted)




Figure 13. Input Bias Current vs Temperature




Figure 14. Output Voltage Swing vs Output Current (Sourcing)




Figure 15. Output Voltage Swing vs Output Current (Sinking)




Figure 16. Output Voltage Swing vs Output Current (Sourcing)




Figure 17. Output Voltage Swing vs Output Current (Sinking)




Figure 18. CMRR and PSRR vs Frequency

## Typical Characteristics (continued)

at  $T_A = 25^\circ\text{C}$ ,  $V_S = \pm 20\text{ V}$ ,  $V_{CM} = V_S / 2$ ,  $R_{LOAD} = 10\text{ k}\Omega$  connected to  $V_S / 2$ , and  $C_L = 10\text{ pF}$  (unless otherwise noted)




Figure 19. CMRR vs Temperature (dB)




Figure 20. PSRR vs Temperature (dB)




Figure 21. 0.1-Hz to 10-Hz Noise




Figure 22. Input Voltage Noise Spectral Density vs Frequency




Figure 23. THD+N Ratio vs Frequency




Figure 24. THD+N vs Output Amplitude

## Typical Characteristics (continued)

at  $T_A = 25^\circ\text{C}$ ,  $V_S = \pm 20\text{ V}$ ,  $V_{CM} = V_S / 2$ ,  $R_{LOAD} = 10\text{ k}\Omega$  connected to  $V_S / 2$ , and  $C_L = 10\text{ pF}$  (unless otherwise noted)




Figure 25. Quiescent Current vs Supply Voltage




Figure 26. Quiescent Current vs Temperature




Figure 27. Open-Loop Voltage Gain vs Temperature (dB)




Figure 28. Open-Loop Output Impedance vs Frequency




Figure 29. Output Swing vs Supply Voltage, Positive Swing




Figure 30. Output Swing vs Supply Voltage, Negative Swing

## Typical Characteristics (continued)

at  $T_A = 25^\circ\text{C}$ ,  $V_S = \pm 20\text{ V}$ ,  $V_{CM} = V_S / 2$ ,  $R_{LOAD} = 10\text{ k}\Omega$  connected to  $V_S / 2$ , and  $C_L = 10\text{ pF}$  (unless otherwise noted)




Figure 31. Output Swing vs Supply Voltage, Positive Swing




Figure 32. Output Swing vs Supply Voltage, Negative Swing




Figure 33. Small-Signal Overshoot vs Capacitive Load




Figure 34. Small-Signal Overshoot vs Capacitive Load




Figure 35. Phase Margin vs Capacitive Load





Figure 36. No Phase Reversal

## Typical Characteristics (continued)


at  $T_A = 25^\circ\text{C}$ ,  $V_S = \pm 20\text{ V}$ ,  $V_{CM} = V_S / 2$ ,  $R_{LOAD} = 10\text{ k}\Omega$  connected to  $V_S / 2$ , and  $C_L = 10\text{ pF}$  (unless otherwise noted)



$G = -10$

C018


Figure 37. Positive Overload Recovery



$G = -10$

C018


Figure 38. Negative Overload Recovery



$C_L = 20\text{ pF}$ ,  $G = 1$ , 20-mV step response

C010


Figure 39. Small-Signal Step Response



$C_L = 20\text{ pF}$ ,  $G = -1$ , 20-mV step response

C011


Figure 40. Small-Signal Step Response



$C_L = 20\text{ pF}$ ,  $G = 1$

C005

Figure 41. Large-Signal Step Response (Falling)




$C_L = 20\text{ pF}$ ,  $G = 1$

C005

Figure 42. Large-Signal Step Response (Rising)

## Typical Characteristics (continued)


at  $T_A = 25^\circ\text{C}$ ,  $V_S = \pm 20\text{ V}$ ,  $V_{CM} = V_S / 2$ ,  $R_{LOAD} = 10\text{ k}\Omega$  connected to  $V_S / 2$ , and  $C_L = 10\text{ pF}$  (unless otherwise noted)



$C_L = 20\text{ pF}$ ,  $G = -1$


C021

Figure 43. Large-Signal Step Response




D038

Figure 44. Short-Circuit Current vs Temperature




C020

Figure 45. Maximum Output Voltage vs Frequency



C014

Figure 46. Channel Separation vs Frequency



C004

Figure 47. EMIRR (Electromagnetic Interference Rejection Ratio) vs Frequency

## 7 Detailed Description


### 7.1 Overview

The OPAx990 family (OPA990, OPA2990, and OPA4990) is a family of high voltage (40-V) general purpose operational amplifiers.

These devices offer excellent DC precision and AC performance, including rail-to-rail input/output, low offset ( $\pm 300 \mu\text{V}$ , typ), and low offset drift ( $\pm 0.6 \mu\text{V}/^\circ\text{C}$ , typ).

Unique features such as differential and common-mode input voltage range to the supply rail, high short-circuit current ( $\pm 80 \text{ mA}$ ), high slew rate ( $4.5 \text{ V}/\mu\text{s}$ ), and shutdown make the OPAx990 an extremely flexible, robust, and high-performance operational amplifier for high-voltage industrial applications.

### 7.2 Functional Block Diagram



## 7.3 Feature Description

### 7.3.1 Input Protection Circuitry

The OPAx990 uses a unique input architecture to eliminate the requirement for input protection diodes but still provides robust input protection under transient conditions. Figure 48 shows conventional input diode protection schemes that are activated by fast transient step responses and introduce signal distortion and settling time delays because of alternate current paths, as shown in Figure 49. For low-gain circuits, these fast-ramping input signals forward-bias back-to-back diodes, causing an increase in input current and resulting in extended settling time.




Figure 48. OPAx990 Input Protection Does Not Limit Differential Input Capability




Figure 49. Back-to-Back Diodes Create Settling Issues

The OPAx990 family of operational amplifiers provides a true high-impedance differential input capability for high-voltage applications using a patented input protection architecture that does not introduce additional signal distortion or delayed settling time, making the device an optimal op amp for multichannel, high-switched, input applications. The OPA990 tolerates a maximum differential swing (voltage between inverting and non-inverting pins of the op amp) of up to 40 V, making the device suitable for use as a comparator or in applications with fast-ramping input signals such as data-acquisition systems; see the TI TechNote [MUX-Friendly Precision Operational Amplifiers](#) for more information.

## Feature Description (continued)

### 7.3.2 EMI Rejection

The OPAx990 uses integrated electromagnetic interference (EMI) filtering to reduce the effects of EMI from sources such as wireless communications and densely-populated boards with a mix of analog signal chain and digital components. EMI immunity can be improved with circuit design techniques; the OPAx990 benefits from these design improvements. Texas Instruments has developed the ability to accurately measure and quantify the immunity of an operational amplifier over a broad frequency spectrum extending from 10 MHz to 6 GHz. [Figure 50](#) shows the results of this testing on the OPAx990. [Table 2](#) shows the EMIRR IN+ values for the OPAx990 at particular frequencies commonly encountered in real-world applications. The *EMI Rejection Ratio of Operational Amplifiers* application report contains detailed information on the topic of EMIRR performance as it relates to op amps and is available for download from [www.ti.com](http://www.ti.com).




**Figure 50. EMIRR Testing**

**Table 2. OPA990 EMIRR IN+ For Frequencies of Interest**

| FREQUENCY | APPLICATION OR ALLOCATION                                                                                                                                                        | EMIRR IN+ |
|-----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------|
| 400 MHz   | Mobile radio, mobile satellite, space operation, weather, radar, ultra-high frequency (UHF) applications                                                                         | 59.5 dB   |
| 900 MHz   | Global system for mobile communications (GSM) applications, radio communication, navigation, GPS (to 1.6 GHz), GSM, aeronautical mobile, UHF applications                        | 68.9 dB   |
| 1.8 GHz   | GSM applications, mobile personal communications, broadband, satellite, L-band (1 GHz to 2 GHz)                                                                                  | 77.8 dB   |
| 2.4 GHz   | 802.11b, 802.11g, 802.11n, Bluetooth®, mobile personal communications, industrial, scientific and medical (ISM) radio band, amateur radio and satellite, S-band (2 GHz to 4 GHz) | 78.0 dB   |
| 3.6 GHz   | Radiolocation, aero communication and navigation, satellite, mobile, S-band                                                                                                      | 88.8 dB   |
| 5 GHz     | 802.11a, 802.11n, aero communication and navigation, mobile communication, space and satellite operation, C-band (4 GHz to 8 GHz)                                                | 87.6 dB   |

### 7.3.3 Thermal Protection

The internal power dissipation of any amplifier causes its internal (junction) temperature to rise. This phenomenon is called *self heating*. The absolute maximum junction temperature of the OPAx990 is 150°C. Exceeding this temperature causes damage to the device. The OPAx990 has a thermal protection feature that reduces damage from self heating. The protection works by monitoring the temperature of the device and turning off the op amp output drive for temperatures above 170°C. Figure 51 shows an application example for the OPA990 that has significant self heating because of its power dissipation (0.81 W). Thermal calculations indicate that for an ambient temperature of 65°C, the device junction temperature must reach 177°C. The actual device, however, turns off the output drive to recover towards a safe junction temperature. Figure 51 shows how the circuit behaves during thermal protection. During normal operation, the device acts as a buffer so the output is 3 V. When self heating causes the device junction temperature to increase above the internal limit, the thermal protection forces the output to a high-impedance state and the output is pulled to ground through resistor  $R_L$ . If the condition that caused excessive power dissipation is not removed, the amplifier will oscillate between a shutdown and enabled state until the output fault is corrected.




Figure 51. Thermal Protection

### 7.3.4 Capacitive Load and Stability

The OPAx990 features a resistive output stage capable of driving moderate capacitive loads, and by leveraging an isolation resistor, the device can easily be configured to drive large capacitive loads. Increasing the gain enhances the ability of the amplifier to drive greater capacitive loads; see Figure 52 and Figure 53. The particular op amp circuit configuration, layout, gain, and output loading are some of the factors to consider when establishing whether an amplifier will be stable in operation.




Figure 52. Small-Signal Overshoot vs Capacitive Load (10-mV Output Step,  $G = 1$ )




Figure 53. Small-Signal Overshoot vs Capacitive Load (10-mV Output Step,  $G = -1$ )

For additional drive capability in unity-gain configurations, improve capacitive load drive by inserting a small resistor,  $R_{ISO}$ , in series with the output, as shown in Figure 54. This resistor significantly reduces ringing and maintains DC performance for purely capacitive loads. However, if a resistive load is in parallel with the capacitive load, then a voltage divider is created, thus introducing a gain error at the output and slightly reducing the output swing. The error introduced is proportional to the ratio  $R_{ISO} / R_L$ , and is generally negligible at low output levels. A high capacitive load drive makes the OPAx990 well suited for applications such as reference buffers, MOSFET gate drives, and cable-shield drives. The circuit shown in Figure 54 uses an isolation resistor,  $R_{ISO}$ , to stabilize the output of an op amp.  $R_{ISO}$  modifies the open-loop gain of the system for increased phase margin.




**Figure 54. Extending Capacitive Load Drive With the OPA990**

### 7.3.5 Common-Mode Voltage Range

The OPAx990 is a 40-V, true rail-to-rail input operational amplifier with an input common-mode range that extends 200 mV beyond either supply rail. This wide range is achieved with paralleled complementary N-channel and P-channel differential input pairs, as shown in Figure 55. The N-channel pair is active for input voltages close to the positive rail, typically  $(V+) - 1\text{ V}$  to 100 mV above the positive supply. The P-channel pair is active for inputs from 100 mV below the negative supply to approximately  $(V+) - 2\text{ V}$ . There is a small transition region, typically  $(V+) - 2\text{ V}$  to  $(V+) - 1\text{ V}$  in which both input pairs are on. This transition region can vary modestly with process variation, and within this region PSRR, CMRR, offset voltage, offset drift, noise, and THD performance may be degraded compared to operation outside this region.

Figure 5 shows this transition region for a typical device in terms of input voltage offset in more detail.

For more information on common-mode voltage range and PMOS/NMOS pair interaction, see [Op Amps With Complementary-Pair Input Stages](#) application note.




**Figure 55. Rail-to-Rail Input Stage**

### 7.3.6 Phase Reversal Protection

The OPAx990 family has internal phase-reversal protection. Many op amps exhibit a phase reversal when the input is driven beyond its linear common-mode range. This condition is most often encountered in non-inverting circuits when the input is driven beyond the specified common-mode voltage range, causing the output to reverse into the opposite rail. The OPAx990 is a rail-to-rail input op amp; therefore, the common-mode range can extend up to the rails. Input signals beyond the rails do not cause phase reversal; instead, the output limits into the appropriate rail. This performance is shown in Figure 56. For more information on phase reversal, see [Op Amps With Complementary-Pair Input Stages](#) application note.




**Figure 56. No Phase Reversal**

### 7.3.7 Electrical Overstress

Designers often ask questions about the capability of an operational amplifier to withstand electrical overstress (EOS). These questions tend to focus on the device inputs, but may involve the supply voltage pins or even the output pin. Each of these different pin functions have electrical stress limits determined by the voltage breakdown characteristics of the particular semiconductor fabrication process and specific circuits connected to the pin. Additionally, internal electrostatic discharge (ESD) protection is built into these circuits to protect them from accidental ESD events both before and during product assembly.

Having a good understanding of this basic ESD circuitry and its relevance to an electrical overstress event is helpful. Figure 57 shows an illustration of the ESD circuits contained in the OPAx990 (indicated by the dashed line area). The ESD protection circuitry involves several current-steering diodes connected from the input and output pins and routed back to the internal power-supply lines, where the diodes meet at an absorption device or the power-supply ESD cell, internal to the operational amplifier. This protection circuitry is intended to remain inactive during normal circuit operation.




Figure 57. Equivalent Internal ESD Circuitry Relative to a Typical Circuit Application

An ESD event is very short in duration and very high voltage (for example; 1 kV, 100 ns), whereas an EOS event is long duration and lower voltage (for example; 50 V, 100 ms). The ESD diodes are designed for out-of-circuit ESD protection (that is, during assembly, test, and storage of the device before being soldered to the PCB). During an ESD event, the ESD signal is passed through the ESD steering diodes to an absorption circuit (labeled ESD power-supply circuit). The ESD absorption circuit clamps the supplies to a safe level.

Although this behavior is necessary for out-of-circuit protection, excessive current and damage is caused if activated in-circuit. A transient voltage suppressors (TVS) can be used to prevent against damage caused by turning on the ESD absorption circuit during an in-circuit ESD event. Using the appropriate current limiting resistors and TVS diodes allows for the use of device ESD diodes to protect against EOS events.

### 7.3.8 Overload Recovery

Overload recovery is defined as the time required for the op amp output to recover from a saturated state to a linear state. The output devices of the op amp enter a saturation region when the output voltage exceeds the rated operating voltage, either due to the high input voltage or the high gain. After the device enters the saturation region, the charge carriers in the output devices require time to return back to the linear state. After the charge carriers return back to the linear state, the device begins to slew at the specified slew rate. Thus, the propagation delay in case of an overload condition is the sum of the overload recovery time and the slew time. The overload recovery time for the OPAX990 is approximately 600 ns.

### 7.3.9 Typical Specifications and Distributions

Designers often have questions about a typical specification of an amplifier in order to design a more robust circuit. Due to natural variation in process technology and manufacturing procedures, every specification of an amplifier will exhibit some amount of deviation from the ideal value, like an amplifier's input offset voltage. These deviations often follow *Gaussian* ("bell curve"), or *normal* distributions, and circuit designers can leverage this information to guardband their system, even when there is not a minimum or maximum specification in the [Electrical Characteristics](#) table.




Figure 58. Ideal Gaussian Distribution

Figure 58 shows an example distribution, where  $\mu$ , or  $\mu$ , is the mean of the distribution, and where  $\sigma$ , or  $\sigma$ , is the standard deviation of a system. For a specification that exhibits this kind of distribution, approximately two-thirds (68.26%) of all units can be expected to have a value within one standard deviation, or one sigma, of the mean (from  $\mu - \sigma$  to  $\mu + \sigma$ ).

Depending on the specification, values listed in the *typical* column of the [Electrical Characteristics](#) table are represented in different ways. As a general rule of thumb, if a specification naturally has a nonzero mean (for example, like gain bandwidth), then the typical value is equal to the mean ( $\mu$ ). However, if a specification naturally has a mean near zero (like input offset voltage), then the typical value is equal to the mean plus one standard deviation ( $\mu + \sigma$ ) in order to most accurately represent the typical value.

You can use this chart to calculate approximate probability of a specification in a unit; for example, for OPAX990, the typical input voltage offset is 300  $\mu$ V, so 68.2% of all OPAX990 devices are expected to have an offset from  $-300 \mu$ V to  $+300 \mu$ V. At  $4 \sigma$  ( $\pm 1200 \mu$ V), 99.9937% of the distribution has an offset voltage less than  $\pm 1200 \mu$ V, which means 0.0063% of the population is outside of these limits, which corresponds to about 1 in 15,873 units.

Specifications with a value in the minimum or maximum column are assured by TI, and units outside these limits will be removed from production material. For example, the OPAX990 family has a maximum offset voltage of 1.5 mV at 25°C, and even though this corresponds to  $5\sigma$  ( $\approx 1$  in 1.7 million units), which is extremely unlikely, TI assures that any unit with larger offset than 1.5 mV will be removed from production material.

For specifications with no value in the minimum or maximum column, consider selecting a sigma value of sufficient guardband for your application, and design worst-case conditions using this value. For example, the  $6\sigma$  value corresponds to about 1 in 500 million units, which is an extremely unlikely chance, and could be an option as a wide guardband to design a system around. In this case, the OPAX990 family does not have a maximum or minimum for offset voltage drift, but based on [Figure 2](#) and the typical value of  $0.6\ \mu\text{V}/^\circ\text{C}$  in the [Electrical Characteristics](#) table, it can be calculated that the  $6\sigma$  value for offset voltage drift is about  $3.6\ \mu\text{V}/^\circ\text{C}$ . When designing for worst-case system conditions, this value can be used to estimate the worst possible offset across temperature without having an actual minimum or maximum value.

However, process variation and adjustments over time can shift typical means and standard deviations, and unless there is a value in the minimum or maximum specification column, TI cannot assure the performance of a device. This information should be used only to estimate the performance of a device.

### 7.3.10 Packages With an Exposed Thermal Pad

The OPAX990 family is available in packages such as the WSON-8 (DSG) and WQFN-16 (RTE) which feature an exposed thermal pad. Inside the package, the die is attached to this thermal pad using an electrically conductive compound. For this reason, when using a package with an exposed thermal pad, the thermal pad must either be connected to V– or left floating. Attaching the thermal pad to a potential other than V– is not allowed, and performance of the device is not assured when doing so.

### 7.3.11 Shutdown

The OPAX990S devices feature one or more shutdown pins (SHDN) that disable the op amp, placing it into a low-power standby mode. In this mode, the op amp typically consumes about 20  $\mu\text{A}$ . The SHDN pins are active high, meaning that shutdown mode is enabled when the input to the SHDN pin is a valid logic high.

The SHDN pins are referenced to the negative supply rail of the op amp. The threshold of the shutdown feature lies around 800 mV (typical) and does not change with respect to the supply voltage. Hysteresis has been included in the switching threshold to ensure smooth switching characteristics. To ensure optimal shutdown behavior, the SHDN pins should be driven with valid logic signals. A valid logic low is defined as a voltage between V– and V– + 0.4 V. A valid logic high is defined as a voltage between V– + 1.2 V and V– + 20 V. The shutdown pin circuitry includes a pull-down resistor, which will inherently pull the voltage of the pin to the negative supply rail if not driven. Thus, to enable the amplifier, the SHDN pins should either be left floating or driven to a valid logic low. To disable the amplifier, the SHDN pins must be driven to a valid logic high. The maximum voltage allowed at the SHDN pins is V– + 20 V. Exceeding this voltage level will damage the device.

The SHDN pins are high-impedance CMOS inputs. Channels of single and dual op amp packages are independently controlled, and channels of quad op amp packages are controlled in pairs. For battery-operated applications, this feature may be used to greatly reduce the average current and extend battery life. The typical enable time out of shutdown is 30  $\mu\text{s}$ ; disable time is 3  $\mu\text{s}$ . When disabled, the output assumes a high-impedance state. This architecture allows the OPAX990S family to operate as a gated amplifier, multiplexer, or programmable-gain amplifier. Shutdown time ( $t_{\text{OFF}}$ ) depends on loading conditions and increases as load resistance increases. To ensure shutdown (disable) within a specific shutdown time, the specified 10-k $\Omega$  load to midsupply ( $V_{\text{S}} / 2$ ) is required. If using the OPAX990S without a load, the resulting turnoff time significantly increases.

## 7.4 Device Functional Modes

The OPAX990 has a single functional mode and is operational when the power-supply voltage is greater than or equal to 2.7 V ( $\pm 1.35$  V). The maximum power supply voltage for the OPAX990 is 40 V ( $\pm 20$  V).

The OPAX990S devices feature a shutdown pin, which can be used to place the op amp into a low-power mode. See [Shutdown](#) section for more information.

## 8 Application and Implementation

### NOTE

Information in the following applications sections is not part of the TI component specification, and TI does not warrant its accuracy or completeness. TI's customers are responsible for determining suitability of components for their purposes. Customers should validate and test their design implementation to confirm system functionality.

### 8.1 Application Information

The OPAx990 family offers excellent DC precision and AC performance. These devices operate up to 40-V supply rails and offer true rail-to-rail input/output, low offset voltage and offset voltage drift, as well as 1.1-MHz bandwidth and high output drive. These features make the OPAx990 a robust, high-performance operational amplifier for high-voltage industrial applications.

### 8.2 Typical Applications

#### 8.2.1 High Voltage Buffered Multiplexer

The OPAx990S shutdown devices can be configured to create a high voltage, buffered multiplexer. Outputs can be connected together on a common bus and the shutdown pins can be used to select the desired channel to pass through. Since the amplifier circuitry has been designed such that disable transitions occur significantly faster than enable transitions, the amplifier naturally exhibits a "break before make" switch topology. Amplifier outputs enter a high impedance state when placed in shutdown, so there is no risk of bus contention when connecting multiple channel outputs together. Additionally, because outputs are isolated from inputs, there is no concern about the impedance at the input of each channel interacting undesirably with the impedance at the output, like an amplifier gain stage or ADC driver circuit. Also, because this topology uses amplifiers instead of MOSFET switches, other common issues with multiplexers such as charge injection or signal error due to  $R_{ON}$  effects are eliminated.

Figure 59 shows an example topology for a basic 2:1 multiplexer. When SEL is low, channel 1 is selected and active; when SEL is high, channel 2 is selected and active. For more information on how to use the OPAx990S shutdown function, see the shutdown section in the [Electrical Characteristics](#) table.




**Figure 59. High Voltage Buffered Multiplexer**

#### 8.2.2 Slew Rate Limit for Input Protection

In control systems for valves or motors, abrupt changes in voltages or currents can cause mechanical damages. By controlling the slew rate of the command voltages into the drive circuits, the load voltages ramps up and down at a safe rate. For symmetrical slew-rate applications (positive slew rate equals negative slew rate), one additional op amp provides slew-rate control for a given analog gain stage. The unique input protection and high output current and slew rate of the OPAx990 make the device an optimal amplifier to achieve slew rate control for both dual- and single-supply systems. Figure 60 shows the OPA990 in a slew-rate limit design.

## Typical Applications (continued)




**Figure 60. Slew Rate Limiter Uses One Op Amp**

## 9 Power Supply Recommendations

The OPAx990 is specified for operation from 2.7 V to 40 V ( $\pm 1.35$  V to  $\pm 20$  V); many specifications apply from  $-40^{\circ}\text{C}$  to  $125^{\circ}\text{C}$  or with specific supply voltages and test conditions. Parameters that can exhibit significant variance with regard to operating voltage or temperature are presented in the [Typical Characteristics](#) section.

### CAUTION

Supply voltages larger than 40 V can permanently damage the device; see the [Absolute Maximum Ratings](#).

Place 0.1- $\mu\text{F}$  bypass capacitors close to the power-supply pins to reduce errors coupling in from noisy or high-impedance power supplies. For more detailed information on bypass capacitor placement, refer to the [Layout](#) section.

## 10 Layout

### 10.1 Layout Guidelines

For best operational performance of the device, use good PCB layout practices, including:

- Noise can propagate into analog circuitry through the power pins of the circuit as a whole and op amp itself. Bypass capacitors are used to reduce the coupled noise by providing low-impedance power sources local to the analog circuitry.
  - Connect low-ESR, 0.1- $\mu\text{F}$  ceramic bypass capacitors between each supply pin and ground, placed as close to the device as possible. A single bypass capacitor from  $V+$  to ground is applicable for single-supply applications.
- Separate grounding for analog and digital portions of circuitry is one of the simplest and most-effective methods of noise suppression. One or more layers on multilayer PCBs are usually devoted to ground planes. A ground plane helps distribute heat and reduces EMI noise pickup. Make sure to physically separate digital and analog grounds paying attention to the flow of the ground current.
- In order to reduce parasitic coupling, run the input traces as far away from the supply or output traces as possible. If these traces cannot be kept separate, crossing the sensitive trace perpendicular is much better as opposed to in parallel with the noisy trace.
- Place the external components as close to the device as possible. As illustrated in [Figure 62](#), keeping  $R_F$  and  $R_G$  close to the inverting input minimizes parasitic capacitance.
- Keep the length of input traces as short as possible. Always remember that the input traces are the most sensitive part of the circuit.
- Consider a driven, low-impedance guard ring around the critical traces. A guard ring can significantly reduce leakage currents from nearby traces that are at different potentials.
- Cleaning the PCB following board assembly is recommended for best performance.
- Any precision integrated circuit may experience performance shifts due to moisture ingress into the plastic package. Following any aqueous PCB cleaning process, baking the PCB assembly is recommended to remove moisture introduced into the device packaging during the cleaning process. A low temperature, post cleaning bake at  $85^{\circ}\text{C}$  for 30 minutes is sufficient for most circumstances.

### 10.2 Layout Example




**Figure 61. Schematic Representation**

## Layout Example (continued)




**Figure 62. Operational Amplifier Board Layout for Noninverting Configuration**




**Figure 63. Example Layout for SC70 (DCK) Package**

## Layout Example (continued)




Figure 64. Example Layout for VSSOP-8 (DGK) Package




Figure 65. Example Layout for WSON-8 (DSG) Package

## 11 Device and Documentation Support

### 11.1 Device Support

#### 11.1.1 Development Support

##### 11.1.1.1 TINA-TI™ (Free Software Download)

TINA™ is a simple, powerful, and easy-to-use circuit simulation program based on a SPICE engine. TINA-TI is a free, fully-functional version of the TINA software, preloaded with a library of macro models in addition to a range of both passive and active models. TINA-TI provides all the conventional dc, transient, and frequency domain analysis of SPICE, as well as additional design capabilities.

Available as a [free download](#) from the Analog eLab Design Center, TINA-TI offers extensive post-processing capability that allows users to format results in a variety of ways. Virtual instruments offer the ability to select input waveforms and probe circuit nodes, voltages, and waveforms, creating a dynamic quick-start tool.

#### NOTE

These files require that either the TINA software (from DesignSoft™) or TINA-TI software be installed. Download the free TINA-TI software from the [TINA-TI folder](#).

### 11.2 Documentation Support

#### 11.2.1 Related Documentation

Texas Instruments, [Op Amps With Complementary-Pair Input Stages](#) application note

#### 11.3 Related Links

The table below lists quick access links. Categories include technical documents, support and community resources, tools and software, and quick access to order now.

**Table 3. Related Links**

| PARTS   | PRODUCT FOLDER             | ORDER NOW                  | TECHNICAL DOCUMENTS        | TOOLS & SOFTWARE           | SUPPORT & COMMUNITY        |
|---------|----------------------------|----------------------------|----------------------------|----------------------------|----------------------------|
| OPA990  | <a href="#">Click here</a> | <a href="#">Click here</a> | <a href="#">Click here</a> | <a href="#">Click here</a> | <a href="#">Click here</a> |
| OPA2990 | <a href="#">Click here</a> | <a href="#">Click here</a> | <a href="#">Click here</a> | <a href="#">Click here</a> | <a href="#">Click here</a> |
| OPA4990 | <a href="#">Click here</a> | <a href="#">Click here</a> | <a href="#">Click here</a> | <a href="#">Click here</a> | <a href="#">Click here</a> |

## 11.4 Receiving Notification of Documentation Updates

To receive notification of documentation updates, navigate to the device product folder on ti.com. In the upper right corner, click on *Alert me* to register and receive a weekly digest of any product information that has changed. For change details, review the revision history included in any revised document.

## 11.5 Support Resources

TI E2E™ support forums are an engineer's go-to source for fast, verified answers and design help — straight from the experts. Search existing answers or ask your own question to get the quick design help you need.

Linked content is provided "AS IS" by the respective contributors. They do not constitute TI specifications and do not necessarily reflect TI's views; see TI's [Terms of Use](#).

## 11.6 Trademarks

E2E is a trademark of Texas Instruments.

TINA-TI is a trademark of Texas Instruments, Inc and DesignSoft, Inc.

Bluetooth is a registered trademark of Bluetooth SIG, Inc.

TINA, DesignSoft are trademarks of DesignSoft, Inc.

All other trademarks are the property of their respective owners.

## 11.7 Electrostatic Discharge Caution



This integrated circuit can be damaged by ESD. Texas Instruments recommends that all integrated circuits be handled with appropriate precautions. Failure to observe proper handling and installation procedures can cause damage.

ESD damage can range from subtle performance degradation to complete device failure. Precision integrated circuits may be more susceptible to damage because very small parametric changes could cause the device not to meet its published specifications.

## 11.8 Glossary

[SLYZ022](#) — *TI Glossary*.

This glossary lists and explains terms, acronyms, and definitions.

## 12 Mechanical, Packaging, and Orderable Information

The following pages include mechanical, packaging, and orderable information. This information is the most current data available for the designated devices. This data is subject to change without notice and revision of this document. For browser-based versions of this data sheet, refer to the left-hand navigation.

**PACKAGING INFORMATION**

| Orderable Device | Status<br>(1) | Package Type | Package<br>Drawing | Pins | Package<br>Qty | Eco Plan<br>(2)            | Lead/Ball Finish<br>(6) | MSL Peak Temp<br>(3) | Op Temp (°C) | Device Marking<br>(4/5) | Samples                 |
|------------------|---------------|--------------|--------------------|------|----------------|----------------------------|-------------------------|----------------------|--------------|-------------------------|-------------------------|
| OPA2990IDDFR     | ACTIVE        | SOT-23-THIN  | DDF                | 8    | 3000           | Green (RoHS<br>& no Sb/Br) | NIPDAU                  | Level-1-260C-UNLIM   | -40 to 125   | O90F                    | <a href="#">Samples</a> |
| OPA2990IDR       | ACTIVE        | SOIC         | D                  | 8    | 2500           | Green (RoHS<br>& no Sb/Br) | NIPDAU                  | Level-2-260C-1 YEAR  | -40 to 125   | OP2990                  | <a href="#">Samples</a> |
| OPA2990IDSGR     | ACTIVE        | WSO          | DSG                | 8    | 3000           | Green (RoHS<br>& no Sb/Br) | NIPDAU                  | Level-2-260C-1 YEAR  | -40 to 125   | O29G                    | <a href="#">Samples</a> |
| OPA2990IPWR      | ACTIVE        | TSSOP        | PW                 | 8    | 2000           | Green (RoHS<br>& no Sb/Br) | NIPDAU                  | Level-2-260C-1 YEAR  | -40 to 125   | O2990P                  | <a href="#">Samples</a> |
| OPA2990SIDGSR    | ACTIVE        | VSSOP        | DGS                | 10   | 2500           | Green (RoHS<br>& no Sb/Br) | NIPDAUAG                | Level-2-260C-1 YEAR  | -40 to 125   | OP29                    | <a href="#">Samples</a> |
| OPA4990IDR       | ACTIVE        | SOIC         | D                  | 14   | 2500           | Green (RoHS<br>& no Sb/Br) | NIPDAU                  | Level-2-260C-1 YEAR  | -40 to 125   | OPA4990D                | <a href="#">Samples</a> |
| OPA4990IPWR      | PREVIEW       | TSSOP        | PW                 | 14   | 2000           | Green (RoHS<br>& no Sb/Br) | SN                      | Level-2-260C-1 YEAR  | -40 to 125   | OPA49PW                 |                         |
| OPA990IDBVR      | ACTIVE        | SOT-23       | DBV                | 5    | 3000           | Green (RoHS<br>& no Sb/Br) | NIPDAU                  | Level-1-260C-UNLIM   | -40 to 125   | O90V                    | <a href="#">Samples</a> |
| OPA990IDCKR      | PREVIEW       | SC70         | DCK                | 5    | 3000           | Green (RoHS<br>& no Sb/Br) | SN                      | Level-2-260C-1 YEAR  | -40 to 125   | 1FL                     |                         |
| OPA990SIDBVR     | ACTIVE        | SOT-23       | DBV                | 6    | 3000           | Green (RoHS<br>& no Sb/Br) | NIPDAU                  | Level-1-260C-UNLIM   | -40 to 125   | O90S                    | <a href="#">Samples</a> |
| POPA2990IDDFR    | ACTIVE        | SOT-23-THIN  | DDF                | 8    | 3000           | TBD                        | Call TI                 | Call TI              | -40 to 125   |                         | <a href="#">Samples</a> |
| POPA2990SIDGSR   | ACTIVE        | VSSOP        | DGS                | 10   | 2500           | TBD                        | Call TI                 | Call TI              | -40 to 125   |                         | <a href="#">Samples</a> |
| POPA4990IPWR     | ACTIVE        | TSSOP        | PW                 | 14   | 2000           | TBD                        | Call TI                 | Call TI              | -40 to 125   |                         | <a href="#">Samples</a> |
| POPA4990IRUCR    | ACTIVE        | QFN          | RUC                | 14   | 3000           | TBD                        | Call TI                 | Call TI              | -40 to 125   |                         | <a href="#">Samples</a> |
| POPA990IDCKR     | ACTIVE        | SC70         | DCK                | 5    | 3000           | TBD                        | Call TI                 | Call TI              | -40 to 125   |                         | <a href="#">Samples</a> |
| POPA990SIDBVR    | ACTIVE        | SOT-23       | DBV                | 6    | 3000           | TBD                        | Call TI                 | Call TI              | -40 to 125   |                         | <a href="#">Samples</a> |

<sup>(1)</sup> The marketing status values are defined as follows:

**ACTIVE:** Product device recommended for new designs.

**LIFEBUY:** TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.

**NRND:** Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.

---

**PREVIEW:** Device has been announced but is not in production. Samples may or may not be available.

**OBSOLETE:** TI has discontinued the production of the device.

<sup>(2)</sup> **RoHS:** TI defines "RoHS" to mean semiconductor products that are compliant with the current EU RoHS requirements for all 10 RoHS substances, including the requirement that RoHS substance do not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, "RoHS" products are suitable for use in specified lead-free processes. TI may reference these types of products as "Pb-Free".

**RoHS Exempt:** TI defines "RoHS Exempt" to mean products that contain lead but are compliant with EU RoHS pursuant to a specific EU RoHS exemption.

**Green:** TI defines "Green" to mean the content of Chlorine (Cl) and Bromine (Br) based flame retardants meet JS709B low halogen requirements of  $\leq 1000$ ppm threshold. Antimony trioxide based flame retardants must also meet the  $\leq 1000$ ppm threshold requirement.

<sup>(3)</sup> MSL, Peak Temp. - The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.


<sup>(4)</sup> There may be additional marking, which relates to the logo, the lot trace code information, or the environmental category on the device.

<sup>(5)</sup> Multiple Device Markings will be inside parentheses. Only one Device Marking contained in parentheses and separated by a "~" will appear on a device. If a line is indented then it is a continuation of the previous line and the two combined represent the entire Device Marking for that device.

<sup>(6)</sup> Lead/Ball Finish - Orderable Devices may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead/Ball Finish values may wrap to two lines if the finish value exceeds the maximum column width.

**Important Information and Disclaimer:** The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.


In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

**TAPE AND REEL INFORMATION**


\*All dimensions are nominal

| Device        | Package Type | Package Drawing | Pins | SPQ  | Reel Diameter (mm) | Reel Width W1 (mm) | A0 (mm) | B0 (mm) | K0 (mm) | P1 (mm) | W (mm) | Pin1 Quadrant |
|---------------|--------------|-----------------|------|------|--------------------|--------------------|---------|---------|---------|---------|--------|---------------|
| OPA2990IDDFR  | SOT-23-THIN  | DDF             | 8    | 3000 | 180.0              | 8.4                | 3.2     | 3.2     | 1.4     | 4.0     | 8.0    | Q3            |
| OPA2990IDR    | SOIC         | D               | 8    | 2500 | 330.0              | 12.4               | 6.4     | 5.2     | 2.1     | 8.0     | 12.0   | Q1            |
| OPA2990IDSGR  | WSON         | DSG             | 8    | 3000 | 180.0              | 8.4                | 2.3     | 2.3     | 1.15    | 4.0     | 8.0    | Q2            |
| OPA2990IPWR   | TSSOP        | PW              | 8    | 2000 | 330.0              | 12.4               | 7.0     | 3.6     | 1.6     | 8.0     | 12.0   | Q1            |
| OPA2990SIDGSR | VSSOP        | DGS             | 10   | 2500 | 330.0              | 12.4               | 5.3     | 3.4     | 1.4     | 8.0     | 12.0   | Q1            |
| OPA4990IDR    | SOIC         | D               | 14   | 2500 | 330.0              | 16.4               | 6.5     | 9.0     | 2.1     | 8.0     | 16.0   | Q1            |
| OPA990IDBVR   | SOT-23       | DBV             | 5    | 3000 | 180.0              | 8.4                | 3.2     | 3.2     | 1.4     | 4.0     | 8.0    | Q3            |
| OPA990SIDBVR  | SOT-23       | DBV             | 6    | 3000 | 180.0              | 8.4                | 3.2     | 3.2     | 1.4     | 4.0     | 8.0    | Q3            |

## TAPE AND REEL BOX DIMENSIONS



\*All dimensions are nominal

| Device        | Package Type | Package Drawing | Pins | SPQ  | Length (mm) | Width (mm) | Height (mm) |
|---------------|--------------|-----------------|------|------|-------------|------------|-------------|
| OPA2990IDDFR  | SOT-23-THIN  | DDF             | 8    | 3000 | 210.0       | 185.0      | 35.0        |
| OPA2990IDR    | SOIC         | D               | 8    | 2500 | 367.0       | 367.0      | 35.0        |
| OPA2990IDSGR  | WSON         | DSG             | 8    | 3000 | 210.0       | 185.0      | 35.0        |
| OPA2990IPWR   | TSSOP        | PW              | 8    | 2000 | 367.0       | 367.0      | 35.0        |
| OPA2990SIDGSR | VSSOP        | DGS             | 10   | 2500 | 366.0       | 364.0      | 50.0        |
| OPA4990IDR    | SOIC         | D               | 14   | 2500 | 367.0       | 367.0      | 38.0        |
| OPA990IDBVR   | SOT-23       | DBV             | 5    | 3000 | 210.0       | 185.0      | 35.0        |
| OPA990SIDBVR  | SOT-23       | DBV             | 6    | 3000 | 210.0       | 185.0      | 35.0        |




# EXAMPLE BOARD LAYOUT


DBV0006A

SOT-23 - 1.45 mm max height

SMALL OUTLINE TRANSISTOR



LAND PATTERN EXAMPLE  
EXPOSED METAL SHOWN  
SCALE:15X



SOLDER MASK DETAILS

4214840/B 03/2018

NOTES: (continued)

6. Publication IPC-7351 may have alternate designs.


7. Solder mask tolerances between and around signal pads can vary based on board fabrication site.

## EXAMPLE STENCIL DESIGN

DBV0006A

SOT-23 - 1.45 mm max height

SMALL OUTLINE TRANSISTOR



SOLDER PASTE EXAMPLE  
BASED ON 0.125 mm THICK STENCIL  
SCALE:15X

4214840/B 03/2018

NOTES: (continued)

8. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
9. Board assembly site may have different recommendations for stencil design.




DBV0005A

# PACKAGE OUTLINE

SOT-23 - 1.45 mm max height

SMALL OUTLINE TRANSISTOR



4214839/E 09/2019

## NOTES:


1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. Reference JEDEC MO-178.
4. Body dimensions do not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0.15 mm per side.

# EXAMPLE BOARD LAYOUT


DBV0005A

SOT-23 - 1.45 mm max height

SMALL OUTLINE TRANSISTOR



LAND PATTERN EXAMPLE  
EXPOSED METAL SHOWN  
SCALE:15X



SOLDER MASK DETAILS

4214839/E 09/2019

NOTES: (continued)


5. Publication IPC-7351 may have alternate designs.
6. Solder mask tolerances between and around signal pads can vary based on board fabrication site.

## EXAMPLE STENCIL DESIGN

DBV0005A

SOT-23 - 1.45 mm max height

SMALL OUTLINE TRANSISTOR




SOLDER PASTE EXAMPLE  
BASED ON 0.125 mm THICK STENCIL  
SCALE:15X

4214839/E 09/2019

NOTES: (continued)

7. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
8. Board assembly site may have different recommendations for stencil design.



4221984/A 05/2015

**NOTES:**


1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. This dimension does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0.15 mm per side.
4. This dimension does not include interlead flash. Interlead flash shall not exceed 0.25 mm per side.
5. Reference JEDEC registration MO-187, variation BA.

# EXAMPLE BOARD LAYOUT


DGS0010A

VSSOP - 1.1 mm max height


SMALL OUTLINE PACKAGE



LAND PATTERN EXAMPLE  
SCALE:10X



NON SOLDER MASK  
DEFINED



SOLDER MASK  
DEFINED

SOLDER MASK DETAILS  
NOT TO SCALE

4221984/A 05/2015

NOTES: (continued)

6. Publication IPC-7351 may have alternate designs.


7. Solder mask tolerances between and around signal pads can vary based on board fabrication site.

## EXAMPLE STENCIL DESIGN

DGS0010A

VSSOP - 1.1 mm max height

SMALL OUTLINE PACKAGE



SOLDER PASTE EXAMPLE  
BASED ON 0.125 mm THICK STENCIL  
SCALE:10X


4221984/A 05/2015

NOTES: (continued)

8. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
9. Board assembly site may have different recommendations for stencil design.

D (R-PDSO-G14)

PLASTIC SMALL OUTLINE




NOTES:

- A. All linear dimensions are in inches (millimeters).
- B. This drawing is subject to change without notice.
- C. Body length does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0.006 (0,15) each side.
- D. Body width does not include interlead flash. Interlead flash shall not exceed 0.017 (0,43) each side.
- E. Reference JEDEC MS-012 variation AB.

D (R-PDSO-G14)


PLASTIC SMALL OUTLINE



- NOTES:
- A. All linear dimensions are in millimeters.
  - B. This drawing is subject to change without notice.
  - C. Publication IPC-7351 is recommended for alternate designs.
  - D. Laser cutting apertures with trapezoidal walls and also rounding corners will offer better paste release. Customers should contact their board assembly site for stencil design recommendations. Refer to IPC-7525 for other stencil recommendations.
  - E. Customers should contact their board fabrication site for solder mask tolerances between and around signal pads.

PW (R-PDSO-G14)


PLASTIC SMALL OUTLINE




4040064-3/G 02/11

PW (R-PDSO-G14)

PLASTIC SMALL OUTLINE



- NOTES:
- All linear dimensions are in millimeters.
  - This drawing is subject to change without notice.
  - Publication IPC-7351 is recommended for alternate designs.
  - Laser cutting apertures with trapezoidal walls and also rounding corners will offer better paste release. Customers should contact their board assembly site for stencil design recommendations. Refer to IPC-7525 for other stencil recommendations.
  - Customers should contact their board fabrication site for solder mask tolerances between and around signal pads.




**D0008A**

# PACKAGE OUTLINE

**SOIC - 1.75 mm max height**

SMALL OUTLINE INTEGRATED CIRCUIT



4214825/C 02/2019

## NOTES:


1. Linear dimensions are in inches [millimeters]. Dimensions in parenthesis are for reference only. Controlling dimensions are in inches. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. This dimension does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed .006 [0.15] per side.
4. This dimension does not include interlead flash.
5. Reference JEDEC registration MS-012, variation AA.

# EXAMPLE BOARD LAYOUT


D0008A

SOIC - 1.75 mm max height

SMALL OUTLINE INTEGRATED CIRCUIT



LAND PATTERN EXAMPLE  
EXPOSED METAL SHOWN  
SCALE:8X



SOLDER MASK DETAILS

4214825/C 02/2019

NOTES: (continued)

6. Publication IPC-7351 may have alternate designs.


7. Solder mask tolerances between and around signal pads can vary based on board fabrication site.

## EXAMPLE STENCIL DESIGN

D0008A

SOIC - 1.75 mm max height

SMALL OUTLINE INTEGRATED CIRCUIT



SOLDER PASTE EXAMPLE  
BASED ON .005 INCH [0.125 MM] THICK STENCIL  
SCALE:8X

4214825/C 02/2019

NOTES: (continued)

8. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
9. Board assembly site may have different recommendations for stencil design.

## GENERIC PACKAGE VIEW


**DSG 8**

**WSON - 0.8 mm max height**



2 x 2, 0.5 mm pitch

PLASTIC SMALL OUTLINE - NO LEAD

This image is a representation of the package family, actual package may vary.  
Refer to the product data sheet for package details.



4224783/A



4218900/D 04/2020

## NOTES:


1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. The package thermal pad must be soldered to the printed circuit board for thermal and mechanical performance.

# EXAMPLE BOARD LAYOUT


DSG0008A

WSN - 0.8 mm max height

PLASTIC SMALL OUTLINE - NO LEAD



LAND PATTERN EXAMPLE  
SCALE:20X



SOLDER MASK DETAILS

4218900/D 04/2020


NOTES: (continued)

4. This package is designed to be soldered to a thermal pad on the board. For more information, see Texas Instruments literature number SLUA271 ([www.ti.com/lit/sluea271](http://www.ti.com/lit/sluea271)).
5. Vias are optional depending on application, refer to device data sheet. If any vias are implemented, refer to their locations shown on this view. It is recommended that vias under paste be filled, plugged or tented.

**DSG0008A**

**WSON - 0.8 mm max height**

PLASTIC SMALL OUTLINE - NO LEAD



## SOLDER PASTE EXAMPLE BASED ON 0.125 mm THICK STENCIL

EXPOSED PAD 9:  
87% PRINTED SOLDER COVERAGE BY AREA UNDER PACKAGE  
SCALE:25X

4218900/D 04/2020

NOTES: (continued)

6. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.


PW0008A



# PACKAGE OUTLINE

## TSSOP - 1.2 mm max height

SMALL OUTLINE PACKAGE



4221848/A 02/2015

### NOTES:


1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. This dimension does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0.15 mm per side.
4. This dimension does not include interlead flash. Interlead flash shall not exceed 0.25 mm per side.
5. Reference JEDEC registration MO-153, variation AA.

# EXAMPLE BOARD LAYOUT



PW0008A

TSSOP - 1.2 mm max height

SMALL OUTLINE PACKAGE



LAND PATTERN EXAMPLE  
SCALE:10X



SOLDER MASK DETAILS  
NOT TO SCALE

4221848/A 02/2015

NOTES: (continued)

6. Publication IPC-7351 may have alternate designs.


7. Solder mask tolerances between and around signal pads can vary based on board fabrication site.

## EXAMPLE STENCIL DESIGN

PW0008A

TSSOP - 1.2 mm max height

SMALL OUTLINE PACKAGE




SOLDER PASTE EXAMPLE  
BASED ON 0.125 mm THICK STENCIL  
SCALE:10X

4221848/A 02/2015

NOTES: (continued)


8. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
9. Board assembly site may have different recommendations for stencil design.




4220584/A 05/2019

## NOTES:

1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.



LAND PATTERN EXAMPLE  
EXPOSED METAL SHOWN  
SCALE: 23X



SOLDER MASK DETAILS

4220584/A 05/2019

NOTES: (continued)


- For more information, see Texas Instruments literature number SLUA271 ([www.ti.com/lit/sluea271](http://www.ti.com/lit/sluea271)).

## EXAMPLE STENCIL DESIGN

RUC0014A

X2QFN - 0.4 mm max height

PLASTIC QUAD FLAT PACK- NO LEAD



SOLDER PASTE EXAMPLE  
BASED ON 0.100mm THICK STENCIL  
SCALE: 23X


4220584/A 05/2019

NOTES: (continued)

4. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.

## DCK (R-PDSO-G5)

## PLASTIC SMALL-OUTLINE PACKAGE




4093553-3/G 01/2007



- NOTES:
- All linear dimensions are in millimeters.
  - This drawing is subject to change without notice.
  - Body dimensions do not include mold flash or protrusion. Mold flash and protrusion shall not exceed 0.15 per side.
  - Falls within JEDEC MO-203 variation AA.

DCK (R-PDSO-G5)

PLASTIC SMALL OUTLINE



- NOTES:
- A. All linear dimensions are in millimeters.
  - B. This drawing is subject to change without notice.
  - C. Customers should place a note on the circuit board fabrication drawing not to alter the center solder mask defined pad.
  - D. Publication IPC-7351 is recommended for alternate designs.
  - E. Laser cutting apertures with trapezoidal walls and also rounding corners will offer better paste release. Customers should contact their board assembly site for stencil design recommendations. Example stencil design based on a 50% volumetric metal load solder paste. Refer to IPC-7525 for other stencil recommendations.



4222047/B 11/2015

## NOTES:


1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. This dimension does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0.15 mm per side.

# EXAMPLE BOARD LAYOUT


DDF0008A

SOT-23 - 1.1 mm max height


PLASTIC SMALL OUTLINE



LAND PATTERN EXAMPLE  
SCALE:15X



NON SOLDER MASK  
DEFINED



SOLDER MASK  
DEFINED

SOLDER MASK DETAILS

4222047/B 11/2015

NOTES: (continued)


4. Publication IPC-7351 may have alternate designs.
5. Solder mask tolerances between and around signal pads can vary based on board fabrication site.

## EXAMPLE STENCIL DESIGN

DDF0008A

SOT-23 - 1.1 mm max height

PLASTIC SMALL OUTLINE



SOLDER PASTE EXAMPLE  
BASED ON 0.125 mm THICK STENCIL  
SCALE:15X

4222047/B 11/2015

NOTES: (continued)

6. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
7. Board assembly site may have different recommendations for stencil design.

## IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, or other requirements. These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you will fully indemnify TI and its representatives against, any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to TI's Terms of Sale ([www.ti.com/legal/termsofsale.html](http://www.ti.com/legal/termsofsale.html)) or other applicable terms available either on [ti.com](http://ti.com) or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products.

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265  
Copyright © 2020, Texas Instruments Incorporated