FDMS001N025DSD

PowerTrench® Power Clip

25 V Asymmetric Dual N−Channel MOSFET

ON Semiconductor®

www.onsemi.com



PQFN8
POWER CLIP
CASE 483AR

General Description

This device includes two specialized N−Channel MOSFETs in a dual package. The switch node has been internally connected to enable easy placement and routing of synchronous buck converters. The control MOSFET (Q1) and synchronous SyncFET (Q2) have been designed to provide optimal power efficiency.

Features

Q1: N−Channel

- Max $r_{DS(on)}$ = 3.25 mΩ at V_{GS} = 10 V, I_D = 19 A
- Max $r_{DS(on)}$ = 4 mΩ at V_{GS} = 4.5 V, I_D = 17 A

Q2: N−Channel

- Max $r_{DS(on)}$ = 0.92 mΩ at V_{GS} = 10 V, I_D = 38 A
- Max $r_{DS(on)}$ = 1.20 mΩ at V_{GS} = 4.5 V, I_D = 34 A
- Low Inductance Packaging Shortens Rise/Fall Times, Resulting in Lower Switching Losses
- MOSFET Integration Enables Optimum Layout for Lower Circuit Inductance and Reduced Switch Node Ringing
- These Devices are Pb−Free, Halogen Free/BFR Free and are RoHS Compliant

Applications

- Computing
- Communications
- General Purpose Point of Load



PIN ASSIGNMENT

Pin	Name	Description
1	HSG	High Side Gate
2	GR	Gate Return
3,4,9	V+(HSD)	High Side Drain
5,6,7	SW	Switching Node, Low Side Drain
8	LSG	Low Side Gate
10	GND(LSS)	Low Side Source

ORDERING INFORMATION

See detailed ordering and shipping information on page 3 of this data sheet.

© Semiconductor Components Industries, LLC, 2017

Table 1. MAXIMUM RATINGS T_A = 25°C unless otherwise noted

Symbol	Parameter		Q1	Q2	Units
V_{DS}	Drain to Source Voltage		25 (Note 1)	25	V
V_{GS}	Gate to Source Voltage		+16/−12V	+16/−12V	V
I_D	Drain Current −Continuous	T_C = 25°C (Note 2)	69	165	A
	−Continuous	T_C = 100°C (Note 2)	43	104	
	−Continuous	T_A = 25°C	19 (Note 7a)	38 (Note 7b)	
	−Pulsed	T_A = 25°C (Note 3)	381	1240	
E_{AS}	Single Pulse Avalanche Energy	(Note 4)	121	337	mJ
P_D	Power Dissipation for Single Operation	T_C = 25°C	26	42	W
	Power Dissipation for Single Operation	T_A = 25°C	2.1 (Note 7a)	2.3 (Note 7b)	
T_J, T_{STG}	Operating and Storage Junction Temperature Range		−55 to +150		°C

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

1. The continuous V_{DS} rating is 25 V; However, a pulse of 30 V peak voltage for no longer than 100 ns duration at 600 KHz frequency can be applied.
2. Computed continuous current limited to Max Junction Temperature only, actual continuous current will be limited by thermal & electro−mechanical application board design.
3. Pulsed Id please refer to Figure 11 and Figure 24 SOA graphs for more details.
4. Q1: E_{AS} of 121 mJ is based on starting T_J = 25°C; N−ch: L = 3 mH, I_{AS} = 9 A, V_{DD} = 25 V. 100% tested at L = 0.1 mH, I_{AS} = 29 A.
   Q2: E_{AS} of 337 mJ is based on starting T_J = 25°C; N−ch: L = 3 mH, I_{AS} = 15 A, V_{DD} = 25 V. 100% tested at L = 0.1 mH, I_{AS} = 48 A.

Table 2. THERMAL CHARACTERISTICS

Symbol	Parameter	Q1	Q2	Units
$R_{\theta JC}$	Thermal Resistance, Junction to Case	4.9	3.0	°C/W
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient	60 (Note 7a)	55 (Note 7b)	
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient	130 (Note 7c)	120 (Note 7d)	

Table 3. ELECTRICAL CHARACTERISTICS T_J = 25°C unless otherwise noted

Symbol	Parameter	Test Conditions	Type	Min	Typ	Max	Units
OFF CHARACTERISTICS							
BV_{DSS}	Drain to Source Breakdown Voltage	I_D = 1 mA, V_{GS} = 0 V I_D = 1 mA, V_{GS} = 0 V	Q1 Q2	25 25			V
$\Delta BV_{DSS}/\Delta T_J$	Breakdown Voltage Temperature Coefficient	I_D = 10 mA, referenced to 25°C I_D = 10 mA, referenced to 25°C	Q1 Q2		15 28		mV/°C
I_{DSS}	Zero Gate Voltage Drain Current	V_{DS} = 20 V, V_{GS} = 0 V V_{DS} = 20 V, V_{GS} = 0 V	Q1 Q2			1 500	μA μA
I_{GSS}	Gate to Source Leakage Current	V_{GS} = +16 V/−12 V, V_{DS} = 0 V V_{GS} = +16 V/−12 V, V_{DS} = 0 V	Q1 Q2			±100 ±100	nA nA
ON CHARACTERISTICS							
$V_{GS(th)}$	Gate to Source Threshold Voltage	V_{GS} = V_{DS}, I_D = 320 μA V_{GS} = V_{DS}, I_D = 1 mA	Q1 Q2	0.8 1.0	1.3 1.5	2.5 3.0	V
$\Delta V_{GS(th)}/\Delta T_J$	Gate to Source Threshold Voltage Temperature Coefficient	I_D = 1 mA, referenced to 25°C I_D = 10 mA, referenced to 25°C	Q1 Q2		−4 −3		mV/°C
$r_{DS(on)}$	Drain to Source On Resistance	V_{GS} = 10 V, I_D = 19 A V_{GS} = 4.5 V, I_D = 17 A V_{GS} = 10 V, I_D = 19 A,T_J =125°C	Q1		2.5 3.0 3.5	3.25 4.0 5.0	mΩ
		V_{GS} = 10 V, I_D = 38 A V_{GS} = 4.5 V, I_D = 34 A V_{GS} = 10 V, I_D = 38 A,T_J = 125°C	Q2		0.70 0.92 0.96	0.92 1.20 1.38	

Table 3. ELECTRICAL CHARACTERISTICS T_J = 25°C unless otherwise noted

Symbol	Parameter	Test Conditions	Type	Min	Typ	Max	Units
ON CHARACTERISTICS							
g_{FS}	Forward Transconductance	V_{DS} = 5 V, I_D = 19 A V_{DS} = 5 V, I_D = 38 A	Q1 Q2		98 262		S
DYNAMIC CHARACTERISTICS							
C_{iss}	Input Capacitance	Q1: V_{DS} = 13 V, V_{GS} = 0 V, f = 1 MHZ Q2: V_{DS} = 13 V, V_{GS} = 0 V, f = 1 MHZ	Q1 Q2		1370 5105		pF
C_{oss}	Output Capacitance		Q1 Q2		625 1810		pF
C_{rss}	Reverse Transfer Capacitance		Q1 Q2		44 173		pF
R_g	Gate Resistance		Q1 Q2	0.1 0.1	0.4 0.3	1.2 1.0	Ω
SWITCHING CHARACTERISTICS							
$t_{d(on)}$	Turn−On Delay Time	Q1: V_{DD} = 13 V, I_D = 19 A, R_{GEN} = 6 Ω Q2: V_{DD} = 13 V, I_D = 38 A, R_{GEN} = 6 Ω	Q1 Q2		8 15	16 26	ns
t_r	Rise Time		Q1 Q2		2 5	10 10	ns
$t_{d(off)}$	Turn−Off Delay Time		Q1 Q2		22 39	34 62	ns
t_f	Fall Time		Q1 Q2		2 4	10 10	ns
Q_g	Total Gate Charge	V_{GS} = 0 V to 10 V; Q1 V_{DD} = 13 V, I_D = 19 A; Q2 V_{DD} = 13 V, I_D = 38 A	Q1 Q2		21 75	30 104	nC
Q_g	Total Gate Charge	V_{GS} = 0 V to 4.5 V	Q1 Q2		9.7 35	14 49	nC
Q_{gs}	Gate to Source Gate Charge		Q1 Q2		2.9 12		nC
Q_{gd}	Gate to Drain “Miller” Charge		Q1 Q2		2.0 7.9		nC
DRAIN−SOURCE DIODE CHARACTERISTICS							
V_{SD}	Source to Drain Diode Forward Voltage	V_{GS} = 0 V, I_S = 19 A (Note 6) V_{GS} = 0 V, I_S = 38 A (Note 6)	Q1 Q2		0.8 0.8	1.2 1.2	V
I_S	Diode continuous forward current	T_C = 25°C (Note 2)	Q1 Q2			69 125	A
$I_{S,Pulse}$	Diode pulse current	T_C = 25°C (Note 3)	Q1 Q2			381 1240	A
t_{rr}	Reverse Recovery Time	Q1 I_F = 19 A, di/dt = 100 A/μs Q2 I_F = 38 A, di/dt = 300 A/μs	Q1 Q2		27 39	44 62	ns
Q_{rr}	Reverse Recovery Charge		Q1 Q2		12 55	21 87	nC

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

5. $R_{\theta JA}$ is determined with the device mounted on a 1 in^2 pad 2 oz copper pad on a 1.5 x 1.5 in. board of FR−4 material. $R_{\theta CA}$ is determined by the user’s board design.
6. Pulse Test: Pulse Width < 300 μs, Duty cycle < 2.0%.

PACKAGE MARKING AND ORDERING INFORMATION

Device Marking	Device	Package	Reel Size	Tape Width	Quantity
FDMS001N025DSD	FDMS001N025DSD	Power Clip 56	13”	12 mm	3000 units



(Note 7a)



(Note 7b)



(Note 7c)



(Note 7d)

7. a) 60°C/W when mounted on a 1 in^2 pad of 2 oz copper
   b) 55°C/W when mounted on a 1 in^2 pad of 2 oz copper
   c) 130°C/W when mounted on a minimum pad of 2 oz copper
   d) 120°C/W when mounted on a minimum pad of 2 oz copper

TYPICAL CHARACTERISTICS (Q1 N−Channel) T_J = 25°C unless otherwise noted



Figure 1. On Region Characteristics



Figure 2. Normalized On−Resistance vs. Drain Current and Gate Voltage



Figure 3. Normalized On Resistance vs. Junction Temperature



Figure 4. On−Resistance vs. Gate to Source Voltage



Figure 5. Transfer Characteristics



Figure 6. Source to Drain Diode Forward Voltage vs. Source Current

TYPICAL CHARACTERISTICS (Q1 N−Channel) T_J = 25°C unless otherwise noted



Figure 7. Gate Charge Characteristics



Figure 8. Capacitance vs. Drain to Source Voltage



Figure 9. Unclamped Inductive Switching Capability



Figure 10. Maximum Continuous Drain Current vs. Case Temperature



Figure 11. Forward Bias Safe Operating Area



Figure 12. Single Pulse Maximum Power Dissipation

TYPICAL CHARACTERISTICS (Q1 N−Channel) T_J = 25°C unless otherwise noted



Figure 13. Junction−to−Case Transient Thermal Response Curve

TYPICAL CHARACTERISTICS (Q2 N−Channel) T_J = 25°C unless otherwise noted



Figure 14. On Region Characteristics



Figure 15. Normalized On−Resistance vs. Drain Current and Gate Voltage



Figure 16. Normalized On Resistance vs. Junction Temperature



Figure 17. On−Resistance vs. Gate to Source Voltage



Figure 18. Transfer Characteristics



Figure 19. Source to Drain Diode Forward Voltage vs. Source Current

TYPICAL CHARACTERISTICS (Q2 N−Channel) T_J = 25°C unless otherwise noted



Figure 20. Gate Charge Characteristics



Figure 21. Capacitance vs. Drain to Source Voltage



Figure 22. Unclamped Inductive Switching Capability



Figure 23. Maximum Continuous Drain Current vs. Case Temperature



Figure 24. Forward Bias Safe Operating Area



Figure 25. Single Pulse Maximum Power Dissipation

TYPICAL CHARACTERISTICS (Q2 N−Channel) T_J = 25°C unless otherwise noted



Figure 26. Junction−to−Case Transient Thermal Response Curve

TYPICAL CHARACTERISTICS (continued)

ON Semiconductor's SyncFET process embeds a Schottky diode in parallel with PowerTrench MOSFET. This diode exhibits similar characteristics to a discrete external Schottky diode in parallel with a MOSFET. Figure 27 shows the reverses recovery characteristic of the FDMS001N025DSD.

Schottky barrier diodes exhibit significant leakage at high temperature and high reverse voltage. This will increase the power in the device.



Figure 27. FDMS001N025DSD SyncFET Body Diode Reverse Recovery Characteristic



Figure 28. SyncFET Body Diode Reverse Leakage vs. Drain−Source Voltage

PACKAGE DIMENSIONS

PQFN8 5X6, 1.27P
CASE 483AR
ISSUE O







NOTES: UNLESS OTHERWISE SPECIFIED

A) DOES NOT FULLY CONFORM TO JEDEC REGISTRATION, MO−229, DATED 11/2001.
B) ALL DIMENSIONS ARE IN MILLIMETERS.
C) DIMENSIONS DO NOT INCLUDE BURRS OR MOLD FLASH. MOLD FLASH OR BURRS DOES NOT EXCEED 0.10MM.
D) DIMENSIONING AND TOLERANCING PER ASME Y14.5M−1994.



DETAIL A
(SCALE: 2X)

PowerTrench is a registered trademark of Semiconductor Components Industries, LLC.

ON Semiconductor and are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:
Literature Distribution Center for ON Semiconductor
19521 E. 32nd Pkwy, Aurora, Colorado 80011 USA
Phone: 303−675−2175 or 800−344−3860 Toll Free USA/Canada
Fax: 303−675−2176 or 800−344−3867 Toll Free USA/Canada
Email: orderlit@onsemi.com

N. American Technical Support: 800−282−9855 Toll Free USA/Canada
Europe, Middle East and Africa Technical Support:
Phone: 421 33 790 2910
Japan Customer Focus Center
Phone: 81−3−5817−1050

ON Semiconductor Website: **www.onsemi.com**

Order Literature: http://www.onsemi.com/orderlit

For additional information, please contact your local Sales Representative