

# MHT2012N 2400-2500 MHz REFERENCE CIRCUIT

ORDERABLE PART NUMBER: **MHT2012N-2450**



PUBLIC




SECURE CONNECTIONS  
FOR A SMARTER WORLD

# License




- Open and read the License.pdf included in the same zip file as the document you are currently reading. By using the documentation materials included in this zip file, you indicate that you accept the terms of the agreement.

# Introduction



- The NXP MHT2012N is a 2400-2500 MHz, 12.5 W CW RF power LDMOS integrated circuit housed in a PQFN over-molded plastic package. It has 50 ohm input matching, inter-stage matching and no output matching.
  - Further details about the device, including its data sheet, are available [here](#).
- The following pages describe the 2400-2500 MHz reference circuit (evaluation board). Its typical applications are RF Energy and driver for RF cooking.
- The reference circuit can be ordered through NXP's distribution partners and etailers under part number MHT2012N-2450.



# Circuit Overview – 5.08 cm x 7.62 cm (2.0" x 3.0")



# Typical CW Performance




Typical Performance:  $V_{DD} = 28\text{ Vdc}$ ,  $P_{in} = 11\text{ dBm}$ ,  $I_{DQ1} = 15\text{ mA}$ ,  $I_{DQ2} = 75\text{ mA}$

Frequency (MHz)	Signal Type	$G_{ps}$ (dB)	PAE (%)	$P_{out}$ (W)
2400	CW	30.1	51.3	13.0
2450		30.0	51.4	12.7
2500		29.7	50.5	11.7




# Quick Start

1. Mount the reference circuit onto a heatsink capable of dissipating more than 10 W in order to provide enough thermal dissipation
2. Connect the ground.
3. Terminate the RF output with a 50 ohm load capable of handling more than 11 W.
4. Connect the RF input to a 50 ohm source with the RF off.
5. Connect the gate voltage, set to 0 V.
6. Connect the drain voltage ( $V_{DD}$ ) and raise it slowly to 28 V. Current should be 0 A.
7. Raise the gate voltage slowly until the drain current reaches the desired level (typical drain quiescent current for the first stage  $I_{DQ1} = 15$  mA, for the second stage  $I_{DQ2} = 75$  mA, with gate voltage typically around 4.8 V for both stages).
8. Raise the RF input slowly to 13 dBm.
9. Check the RF output power (typically 12 W), the drain current (around 1 A for this power level) and the temperature of the board.





# Component Placement Reference




# Bill of Materials

Part	Description	Part Number	Manufacturer
C1, C4, C9, C12	10 $\mu$ F Chip Capacitor	GRM32ER61H106KA12L	Murata
C2, C5, C8, C11	0.1 $\mu$ F Chip Capacitor	GRM32NR72A104KA01B	Murata
C3	0.5 pF Chip Capacitor	ATC600F0R5BT250XT	ATC
C6	1.6 pF Chip Capacitor	ATC600F1R6BT250XT	ATC
C7	4.7 pF Chip Capacitor	ATC600F4R7BT250XT	ATC
C10	220 $\mu$ F, 50 V Electrolytic Capacitor	227CKS050M	Illinois Capacitor
C13, C14, C15, C16, C17, C18, C19	5.6 pF Chip Capacitor	ATC600F5R6BT250XT	ATC
Q1	RF Power LDMOS Transistor	MHT2012N	NXP
R1, R2	4.7 k $\Omega$ , 1/4 W Chip Resistor	CRCW12064K70FKEA	Vishay
PCB	Rogers RT6035HTC, 0.030", $\epsilon_r = 3.5$	D103883	MTL



# Tuning Tips

Moving C6 closer to C7 increases efficiency



# Load Pull Performance

f (MHz)	$Z_{\text{source}}$ ( $\Omega$ )	$Z_{\text{in}}$ ( $\Omega$ )	Max Efficiency					
			P1dB					
			$Z_{\text{load}}^{(1)}$ ( $\Omega$ )	Gain (dB)	(dBm)	(W)	$\eta_D$ (%)	PAE (%)
2400	$40.9 + j23.6$	$58.6 - j22.8$	$4.19 - j1.25$	30.5	40.9	12	56.2	56.1
2450	$38.1 + j30.8$	$56.8 - j34.4$	$4.01 - j1.06$	30.2	41.0	13	56.8	56.7
2500	$32.9 + j30.7$	$48.5 - j37.7$	$3.63 - j1.34$	30.4	41.1	13	59.5	59.4

f (MHz)	$Z_{\text{source}}$ ( $\Omega$ )	$Z_{\text{in}}$ ( $\Omega$ )	Max Efficiency					
			P3dB					
			$Z_{\text{load}}^{(2)}$ ( $\Omega$ )	Gain (dB)	(dBm)	(W)	$\eta_D$ (%)	PAE (%)
2400	$40.9 + j23.6$	$51.9 - j26.8$	$4.28 - j1.45$	28.5	41.6	15	54.3	54.2
2450	$38.1 + j30.8$	$48.5 - j35.0$	$4.19 - j1.50$	28.2	41.9	15	55.2	55.1
2500	$32.9 + j30.7$	$40.4 - j36.5$	$3.94 - j1.74$	28.4	42.0	16	57.0	56.9

(1) Load impedance for optimum P1dB efficiency.


(2) Load impedance for optimum P3dB efficiency.

$Z_{\text{source}}$  = Measured impedance presented to the input of the device at the package reference plane.

$Z_{\text{in}}$  = Impedance as measured from gate contact to ground.

$Z_{\text{load}}$  = Measured impedance presented to the output of the device at the package reference plane.

**Note: Measurement made on a per side basis.**



# Revision History

- The following table summarizes revisions to the content of the MHT2012N 2450 MHz Reference Circuit zip file.

Revision	Date	Description
0	September 2019	• Initial Release



SECURE CONNECTIONS  
FOR A SMARTER WORLD