REVISIONS			
REV	DESCRIPTION	APPR	DATE



NOTES : Unless Otherwise Specified

1. MATERIAL : FR4 OR EQUIVALENT EPOXY, 2 OZ. COPPER CLAD
   THICKNESS .062 +/-.006 TOTAL OF 2 LAYERS
2. FINISH : ALL PLATED HOLES .001 MIN. / .0015 MAX. COPPER PLATE
   ELECTRODEPOSITED TIN-LEAD COMPOSITION
   BEFORE REFLOW , SOLDER MASK OVER BARE COPPER (SMOBC)
3. SOLDER MASK : BOTH SIDES USING GREEN SR1020 OR EQUIVALENT
4. SILKSCREEN : USING WHITE NON-CONDUCTIVE EPOXY INK
5. ALL DIMENSIONS ARE IN INCHES
6. SCORING:



SIZE	QTY	SYM	PLTD
20	30	+	PLTD
72	2	Y	NPLTD
95	5	Z	PLTD

Fabrication Drawing

APPROVALS		
	INIT	DATE
DRAWN		
CHECK		
DESIGN		
ENGR		
SCALE = NONE		

LINEAR TECHNOLOGY
1630 McCarthy Blvd.
Milpitas, CA 95035
PH: (408)432-1900

TITLE: 4.5A, 500kHz Step-Down Switching Regulator

SIZE	DEMO	REV.
A	DC238 LT1506CR	A

DES- 0280 | SHT 1 of 1