NTZS3151P

MOSFET – P-Channel, Small Signal, SOT-563

-20 V, -950 mA

Features

- Low $R_{DS(on)}$ Improving System Efficiency
- Low Threshold Voltage
- Small Footprint 1.6 x 1.6 mm
- These Devices are Pb−Free, Halogen Free/BFR Free and are RoHS Compliant

Applications

- Load/Power Switches
- Battery Management
- Cell Phones, Digital Cameras, PDAs, Pagers, etc.

MAXIMUM RATINGS (T_J = 25°C unless otherwise noted.)

Parameter			Symbol	Value	Unit
Drain−to−Source Voltage			V_{DSS}	−20	V
Gate−to−Source Voltage			V_{GS}	±8.0	V
Continuous Drain Current (Note 1)	Steady State	T_A = 25°C	I_D	−860	mA
		T_A = 70°C		−690	
Power Dissipation (Note 1)	Steady State		P_D	170	mW
Continuous Drain Current (Note 1)	t ≤ 5 s	T_A = 25°C	I_D	−950	mA
		T_A = 70°C		−760	
Power Dissipation (Note 1)	t ≤ 5 s		P_D	210	mW
Pulsed Drain Current	t_p = 10 μs		I_{DM}	−4.0	A
Operating Junction and Storage Temperature			T_J, T_{STG}	−55 to 150	°C
Source Current (Body Diode)			I_S	−360	mA
Lead Temperature for Soldering Purposes (1/8″ from case for 10 s)			T_L	260	°C

THERMAL RESISTANCE RATINGS

Parameter	Symbol	Max	Unit
Junction−to−Ambient − Steady State (Note 1)	$R_{\theta JA}$	720	°C/W
Junction−to−Ambient − t ≤ 5 s (Note 1)	$R_{\theta JA}$	600	

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.


1. Surface−mounted on FR4 board using 1 in. sq. pad size (Cu. area = 1.127 in. sq. [1 oz.] including traces).


ON Semiconductor®

http://onsemi.com

$V_{(BR)DSS}$	$R_{DS(on)}$ Typ	I_D Max
−20 V	120 mΩ @ −4.5 V	−950 mA
	144 mΩ @ −2.5 V	
	195 mΩ @ −1.8 V	

P−Channel MOSFET






SOT−563−6
CASE 463A

MARKING DIAGRAM



TX = Specific Device Code
M = Date Code
▪ = Pb−Free Package
(Note: Microdot may be in either location)

PINOUT: SOT−563



Top View

ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 4 of this data sheet.

© Semiconductor Components Industries, LLC, 2013

ELECTRICAL CHARACTERISTICS (T_J = 25°C unless otherwise noted.)

Parameter	Symbol	Test Condition		Min	Typ	Max	Unit
OFF CHARACTERISTICS							
Drain−to−Source Breakdown Voltage	$V_{(BR)DSS}$	V_{GS} = 0 V, I_D = −250 μA		−20			V
Drain−to−Source Breakdown Voltage Temperature Coefficient	$V_{(BR)DSS}/T_J$				−13		mV/°C
Zero Gate Voltage Drain Current	I_{DSS}	V_{GS} = 0 V	T_J = 25°C			−1.0	μA
		V_{DS} = −20 V	T_J = 125°C			−5.0	
Gate−to−Source Leakage Current	I_{GSS}	V_{DS} = 0 V, V_{GS} = ±8.0 V				±100	nA
ON CHARACTERISTICS (Note 2)							
Gate Threshold Voltage	$V_{GS(TH)}$	V_{GS} = V_{DS}, I_D = −250 μA		−0.45		−1.0	V
Negative Threshold Temperature Coefficient	$V_{GS(TH)}/T_J$				2.4		mV/°C
Drain−to−Source On Resistance	$R_{DS(on)}$	V_{GS} = −4.5 V, I_D = −950 mA			120	150	mΩ
		V_{GS} = −4.5 V, I_D = −770 mA			112	142	
		V_{GS} = −2.5 V, I_D = −670 mA			144	200	
		V_{GS} = −1.8 V, I_D = −200 mA			195	240	
Forward Transconductance	g_{FS}	V_{DS} = −10 V, I_D = −810 mA			3.1		S
CHARGES AND CAPACITANCES							
Input Capacitance	C_{ISS}	V_{GS} = 0 V, f = 1.0 MHz, V_{DS} = −16 V			458		pF
Output Capacitance	C_{OSS}				61		
Reverse Transfer Capacitance	C_{RSS}				38		
Total Gate Charge	$Q_{G(TOT)}$	V_{GS} = −4.5 V, V_{DS} = −10 V; I_D = −770 mA			5.6		nC
Threshold Gate Charge	$Q_{G(TH)}$				0.6		
Gate−to−Source Charge	Q_{GS}				0.9		
Gate−to−Drain Charge	Q_{GD}				1.2		
SWITCHING CHARACTERISTICS (Note 3)							
Turn−On Delay Time	$t_{d(ON)}$	V_{GS} = −4.5 V, V_{DD} = −10 V, I_D = −950 mA, R_G = 6.0 Ω			5.0		ns
Rise Time	t_r				12		
Turn−Off Delay Time	$t_{d(OFF)}$				23.7		
Fall Time	t_f				18		
DRAIN−SOURCE DIODE CHARACTERISTICS							
Forward Diode Voltage	V_{SD}	V_{GS} = 0 V, I_S = −360 mA	T_J = 25°C		−0.64	−0.9	V
			T_J = 125°C		−0.5		
Reverse Recovery Time	t_{RR}	V_{GS} = 0 V, dI_S/dt = 100 A/μs, I_S = −360 mA			10.5		ns

2. Pulse Test: pulse width ≤ 300 μs, duty cycle ≤ 2%.
3. Switching characteristics are independent of operating junction temperatures.

TYPICAL PERFORMANCE CURVES (T_J = 25°C unless otherwise noted)




Figure 1. On−Region Characteristics




Figure 2. Transfer Characteristics




Figure 3. On−Resistance vs. Drain Current and Temperature




Figure 4. On−Resistance vs. Drain Current and Gate Voltage




Figure 5. On−Resistance Variation with Temperature




Figure 6. Drain−to−Source Leakage Current vs. Voltage

TYPICAL PERFORMANCE CURVES (T_J = 25°C unless otherwise noted)




Figure 7. Capacitance Variation




Figure 8. Gate−to−Source and Drain−to−Source Voltage vs. Total Charge




Figure 9. Resistive Switching Time Variation vs. Gate Resistance




Figure 10. Diode Forward Voltage vs. Current


ORDERING INFORMATION

Device	Package	Shipping
NTZS3151PT1G	SOT−563 (Pb−Free)	4000 / Tape & Reel
NTZS3151PT1H	SOT−563 (Pb−Free)	4000 / Tape & Reel
NTZS3151PT5G	SOT−563 (Pb−Free)	8000 / Tape & Reel

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

PACKAGE DIMENSIONS


SOT−563, 6 LEAD
CASE 463A
ISSUE F



NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETERS
3. MAXIMUM LEAD THICKNESS INCLUDES LEAD FINISH THICKNESS. MINIMUM LEAD THICKNESS IS THE MINIMUM THICKNESS OF BASE MATERIAL.

	MILLIMETERS			INCHES		
DIM	MIN	NOM	MAX	MIN	NOM	MAX
A	0.50	0.55	0.60	0.020	0.021	0.023
b	0.17	0.22	0.27	0.007	0.009	0.011
C	0.08	0.12	0.18	0.003	0.005	0.007
D	1.50	1.60	1.70	0.059	0.062	0.066
E	1.10	1.20	1.30	0.043	0.047	0.051
e	0.5 BSC			0.02 BSC		
L	0.10	0.20	0.30	0.004	0.008	0.012
H_E	1.50	1.60	1.70	0.059	0.062	0.066

SOLDERING FOOTPRINT*



*For additional information on our Pb−Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

ON Semiconductor and ON are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of SCILLC's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:
Literature Distribution Center for ON Semiconductor
P.O. Box 5163, Denver, Colorado 80217 USA
Phone: 303−675−2175 or 800−344−3860 Toll Free USA/Canada
Fax: 303−675−2176 or 800−344−3867 Toll Free USA/Canada
Email: orderlit@onsemi.com

N. American Technical Support: 800−282−9855 Toll Free USA/Canada
Europe, Middle East and Africa Technical Support:
Phone: 421 33 790 2910
Japan Customer Focus Center
Phone: 81−3−5817−1050

ON Semiconductor Website: **www.onsemi.com**

Order Literature: http://www.onsemi.com/orderlit

For additional information, please contact your local Sales Representative

NTSZ3151P/D