
High Efficiency Thyristor

V_{RRM}	=	1200 V
I_{TAV}	=	30 A
V_T	=	1.27 V


Single Thyristor

Part number

CLA30E1200PB



Backside: anode



Features / Advantages:

- Thyristor for line frequency
- Planar passivated chip
- Long-term stability

Applications:

- Line rectifying 50/60 Hz
- Softstart AC motor control
- DC Motor control
- Power converter
- AC power control
- Lighting and temperature control

Package: TO-220

- Industry standard outline
- RoHS compliant
- Epoxy meets UL 94V-0

Disclaimer Notice

Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at www.littelfuse.com/disclaimer-electronics.

© 2019 IXYS all rights reserved


Thyristor

Symbol	Definition	Conditions		Ratings min.	typ.	max.	Unit
$V_{RSM/DSM}$	*max. non-repetitive reverse/forward blocking voltage*		T_{VJ} = 25°C			1300	V
$V_{RRM/DRM}$	*max. repetitive reverse/forward blocking voltage*		T_{VJ} = 25°C			1200	V
$I_{R/D}$	*reverse current, drain current*	$V_{R/D}$ = 1200 V	T_{VJ} = 25°C			10	µA
		$V_{R/D}$ = 1200 V	T_{VJ} = 125°C			2	mA
V_T	*forward voltage drop*	I_T = 30 A	T_{VJ} = 25°C			1.30	V
		I_T = 60 A				1.59	V
		I_T = 30 A	T_{VJ} = 125°C			1.27	V
		I_T = 60 A				1.65	V
I_{TAV}	*average forward current*	T_C = 115°C	T_{VJ} = 150°C			30	A
$I_{T(RMS)}$	*RMS forward current*	180° sine				47	A
V_{T0}	*threshold voltage* } *for power loss calculation only*		T_{VJ} = 150°C			0.86	V
r_T	*slope resistance* }					13.2	mΩ
R_{thJC}	*thermal resistance junction to case*					0.5	K/W
R_{thCH}	*thermal resistance case to heatsink*				0.5		K/W
P_{tot}	*total power dissipation*		T_C = 25°C			250	W
I_{TSM}	*max. forward surge current*	t = 10 ms; (50 Hz), sine	T_{VJ} = 45°C			300	A
		t = 8,3 ms; (60 Hz), sine	V_R = 0 V			325	A
		t = 10 ms; (50 Hz), sine	T_{VJ} = 150°C			255	A
		t = 8,3 ms; (60 Hz), sine	V_R = 0 V			275	A
I^2t	*value for fusing*	t = 10 ms; (50 Hz), sine	T_{VJ} = 45°C			450	A²s
		t = 8,3 ms; (60 Hz), sine	V_R = 0 V			440	A²s
		t = 10 ms; (50 Hz), sine	T_{VJ} = 150°C			325	A²s
		t = 8,3 ms; (60 Hz), sine	V_R = 0 V			315	A²s
C_J	*junction capacitance*	V_R = 400 V f = 1 MHz	T_{VJ} = 25°C		13		pF
P_{GM}	*max. gate power dissipation*	t_P = 30 µs	T_C = 150°C			10	W
		t_P = 300 µs				5	W
P_{GAV}	*average gate power dissipation*					0.5	W
$(di/dt)_{cr}$	*critical rate of rise of current*	T_{VJ} = 150°C; f = 50 Hz	repetitive, I_T = 90 A			150	A/µs
		t_P = 200 µs; di_G/dt = 0.3 A/µs;					
		I_G = 0.3 A; V = ⅔ V_{DRM}	non-repet., I_T = 30 A			500	A/µs
$(dv/dt)_{cr}$	*critical rate of rise of voltage*	V = ⅔ V_{DRM}	T_{VJ} = 150°C			500	V/µs
		R_{GK} = ∞; method 1 (linear voltage rise)					
V_{GT}	*gate trigger voltage*	V_D = 6 V	T_{VJ} = 25°C			1.3	V
			T_{VJ} = -40°C			1.6	V
I_{GT}	*gate trigger current*	V_D = 6 V	T_{VJ} = 25°C			30	mA
			T_{VJ} = -40°C			50	mA
V_{GD}	*gate non-trigger voltage*	V_D = ⅔ V_{DRM}	T_{VJ} = 150°C			0.2	V
I_{GD}	*gate non-trigger current*					1	mA
I_L	*latching current*	t_p = 10 µs	T_{VJ} = 25°C			90	mA
		I_G = 0.3 A; di_G/dt = 0.3 A/µs					
I_H	*holding current*	V_D = 6 V R_{GK} = ∞	T_{VJ} = 25°C			60	mA
t_{gd}	*gate controlled delay time*	V_D = ½ V_{DRM}	T_{VJ} = 25°C			2	µs
		I_G = 0.3 A; di_G/dt = 0.3 A/µs					
t_q	*turn-off time*	V_R = 100 V; I_T = 30A; V = ⅔ V_{DRM}	T_{VJ} = 125 °C		150		µs
		di/dt = 10 A/µs dv/dt = 20 V/µs t_p = 200 µs					

© 2019 IXYS all rights reserved

Package TO-220			Ratings			
Symbol	**Definition**	**Conditions**	**min.**	**typ.**	**max.**	**Unit**
I_{RMS}	*RMS current*	per terminal			35	A
T_{VJ}	*virtual junction temperature*		-40		150	°C
T_{op}	*operation temperature*		-40		125	°C
T_{stg}	*storage temperature*		-40		150	°C
Weight				2		g
M_D	*mounting torque*		0.4		0.6	Nm
F_C	*mounting force with clip*		20		60	N

Product Marking



Part description

C = Thyristor (SCR)
L = High Efficiency Thyristor
A = (up to 1200V)
30 = Current Rating [A]
E = Single Thyristor
1200 = Reverse Voltage [V]
PB = TO-220AB (3)


Ordering	Ordering Number	Marking on Product	Delivery Mode	Quantity	Code No.
Standard	CLA30E1200PB	CLA30E1200PB	Tube	50	508228

Similar Part	Package	Voltage class
CLA30E1200HB	TO-247AD (3)	1200
CLA30E1200PC	TO-263AB (D2Pak) (2)	1200
CS22-12io1M	TO-220ABFP (3)	1200
CS22-08io1M	TO-220ABFP (3)	800

CMA30E1600PN	TO-220ABFP (3)	1600
CMA30E1600PB	TO-220AB (3)	1600

Equivalent Circuits for Simulation

** on die level* $T_{VJ} = 150°C$




Thyristor


$V_{0\,max}$	*threshold voltage*	0.86	V
$R_{0\,max}$	*slope resistance **	10	mΩ

© 2019 IXYS all rights reserved

Outlines TO-220



Dim.	Millimeter		Inches	
	Min.	Max.	Min.	Max.
A	4.32	4.82	0.170	0.190
A1	1.14	1.39	0.045	0.055
A2	2.29	2.79	0.090	0.110
b	0.64	1.01	0.025	0.040
b2	1.15	1.65	0.045	0.065
C	0.35	0.56	0.014	0.022
D	14.73	16.00	0.580	0.630
E	9.91	10.66	0.390	0.420
e	2.54	BSC	0.100	BSC
H1	5.85	6.85	0.230	0.270
L	12.70	13.97	0.500	0.550
L1	2.79	5.84	0.110	0.230
ØP	3.54	4.08	0.139	0.161
Q	2.54	3.18	0.100	0.125



© 2019 IXYS all rights reserved

Thyristor




Fig. 1 Forward characteristics




Fig. 2 Surge overload current
I_{TSM}: crest value, t: duration




Fig. 3 I^2t versus time (1-10 s)




Fig. 4 Gate voltage & gate current
Triggering: A = no; B = possible; C = safe




Fig. 5 Gate controlled delay time t_{gd}




Fig. 6 Max. forward current at case temperature





Fig. 7a Power dissipation versus direct output current
Fig. 7b and ambient temperature



i	R_{thi} (K/W)	t_i (s)
1	0.08	0.01
2	0.06	0.0001
3	0.2	0.02
4	0.05	0.2
5	0.11	0.11

Fig. 7 Transient thermal impedance junction to case

© 2019 IXYS all rights reserved

© 2019 IXYS all rights reserved