MBT3946DW1T1G, SMBT3946DW1T1G

Complementary General Purpose Transistor

The MBT3946DW1T1G device is a spin-off of our popular SOT−23/SOT−323 three-leaded device. It is designed for general purpose amplifier applications and is housed in the SOT−363−6 surface mount package. By putting two discrete devices in one package, this device is ideal for low-power surface mount applications where board space is at a premium.

Features

- h_{FE}, 100−300
- Low $V_{CE(sat)}$, ≤ 0.4 V
- Simplifies Circuit Design
- Reduces Board Space
- Reduces Component Count
- S Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC−Q101 Qualified and PPAP Capable
- These Devices are Pb-Free, Halogen Free/BFR Free and are RoHS Compliant

Table 1. MAXIMUM RATINGS

Rating	Symbol	Value	Unit
Collector − Emitter Voltage (NPN) (PNP)	V_{CEO}	 40 −40	Vdc
Collector − Base Voltage (NPN) (PNP)	V_{CBO}	 60 −40	Vdc
Emitter − Base Voltage (NPN) (PNP)	V_{EBO}	 6.0 −5.0	Vdc
Collector Current − Continuous (NPN) (PNP)	I_C	 200 −200	mAdc
Electrostatic Discharge	ESD	HBM Class 2 MM Class B	

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

Table 2. THERMAL CHARACTERISTICS

Characteristic	Symbol	Max	Unit
Total Package Dissipation (Note 1) T_A = 25°C	P_D	150	mW
Thermal Resistance, Junction-to-Ambient	$R_{\theta JA}$	833	°C/W
Junction and Storage Temperature Range	T_J, T_{stg}	−55 to +150	°C


1. Device mounted on FR4 glass epoxy printed circuit board using the minimum recommended footprint.

ON Semiconductor®

http://onsemi.com




SOT−363/SC−88
CASE 419B
STYLE 1



MBT3946DW1T1*

*Q1 PNP
Q2 NPN

MARKING DIAGRAM



46 = Specific Device Code
M = Date Code
▪ = Pb-Free Package

(Note: Microdot may be in either location)

ORDERING INFORMATION

Device	Package	Shipping†
MBT3946DW1T1G	SC−88 (Pb-Free)	3,000 / Tape & Reel
SMBT3946DW1T1G	SC−88 (Pb-Free)	3,000 / Tape & Reel
MBT3946DW1T2G	SC−88 (Pb-Free)	3,000 / Tape & Reel

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

© Semiconductor Components Industries, LLC, 2012

Table 3. ELECTRICAL CHARACTERISTICS (T_A = 25°C unless otherwise noted)

Characteristic		Symbol	Min	Max	Unit
OFF CHARACTERISTICS					
Collector – Emitter Breakdown Voltage (Note 2)		$V_{(BR)CEO}$			Vdc
(I_C = 1.0 mAdc, I_B = 0)	(NPN)		40	–	
(I_C = −1.0 mAdc, I_B = 0)	(PNP)		−40	–	
Collector – Base Breakdown Voltage		$V_{(BR)CBO}$			Vdc
(I_C = 10 μAdc, I_E = 0)	(NPN)		60	–	
(I_C = −10 μAdc, I_E = 0)	(PNP)		−40	–	
Emitter – Base Breakdown Voltage		$V_{(BR)EBO}$			Vdc
(I_E = 10 μAdc, I_C = 0)	(NPN)		6.0	–	
(I_E = −10 μAdc, I_C = 0)	(PNP)		−5.0	–	
Base Cutoff Current		I_{BL}			nAdc
(V_{CE} = 30 Vdc, V_{EB} = 3.0 Vdc)	(NPN)		–	50	
(V_{CE} = −30 Vdc, V_{EB} = −3.0 Vdc)	(PNP)		–	−50	
Collector Cutoff Current		I_{CEX}			nAdc
(V_{CE} = 30 Vdc, V_{EB} = 3.0 Vdc)	(NPN)		–	50	
(V_{CE} = −30 Vdc, V_{EB} = −3.0 Vdc)	(PNP)		–	−50	
ON CHARACTERISTICS (Note 2)					
DC Current Gain		h_{FE}			–
(I_C = 0.1 mAdc, V_{CE} = 1.0 Vdc)	(NPN)		40	–	
(I_C = 1.0 mAdc, V_{CE} = 1.0 Vdc)			70	–	
(I_C = 10 mAdc, V_{CE} = 1.0 Vdc)			100	300	
(I_C = 50 mAdc, V_{CE} = 1.0 Vdc)			60	–	
(I_C = 100 mAdc, V_{CE} = 1.0 Vdc)			30	–	
(I_C = −0.1 mAdc, V_{CE} = −1.0 Vdc)	(PNP)		60	–	
(I_C = −1.0 mAdc, V_{CE} = −1.0 Vdc)			80	–	
(I_C = −10 mAdc, V_{CE} = −1.0 Vdc)			100	300	
(I_C = −50 mAdc, V_{CE} = −1.0 Vdc)			60	–	
(I_C = −100 mAdc, V_{CE} = −1.0 Vdc)			30	–	
Collector – Emitter Saturation Voltage		$V_{CE(sat)}$			Vdc
(I_C = 10 mAdc, I_B = 1.0 mAdc)	(NPN)		–	0.2	
(I_C = 50 mAdc, I_B = 5.0 mAdc)			–	0.3	
(I_C = −10 mAdc, I_B = −1.0 mAdc)	(PNP)		–	−0.25	
(I_C = −50 mAdc, I_B = −5.0 mAdc)			–	−0.4	
Base – Emitter Saturation Voltage		$V_{BE(sat)}$			Vdc
(I_C = 10 mAdc, I_B = 1.0 mAdc)	(NPN)		0.65	0.85	
(I_C = 50 mAdc, I_B = 5.0 mAdc)			–	0.95	
(I_C = −10 mAdc, I_B = −1.0 mAdc)	(PNP)		−0.65	−0.85	
(I_C = −50 mAdc, I_B = −5.0 mAdc)			–	−0.95	
SMALL-SIGNAL CHARACTERISTICS					
Current – Gain – Bandwidth Product		f_T			MHz
(I_C = 10 mAdc, V_{CE} = 20 Vdc, f = 100 MHz)	(NPN)		300	–	
(I_C = −10 mAdc, V_{CE} = −20 Vdc, f = 100 MHz)	(PNP)		250	–	
Output Capacitance		C_{obo}			pF
(V_{CB} = 5.0 Vdc, I_E = 0, f = 1.0 MHz)	(NPN)		–	4.0	
(V_{CB} = −5.0 Vdc, I_E = 0, f = 1.0 MHz)	(PNP)		–	4.5	
Input Capacitance		C_{ibo}			pF
(V_{EB} = 0.5 Vdc, I_C = 0, f = 1.0 MHz)	(NPN)		–	8.0	
(V_{EB} = −0.5 Vdc, I_C = 0, f = 1.0 MHz)	(PNP)		–	10.0	
Input Impedance		h_{ie}			kΩ
(V_{CE} = 10 Vdc, I_C = 1.0 mAdc, f = 1.0 kHz)	(NPN)		1.0	10	
(V_{CE} = −10 Vdc, I_C = −1.0 mAdc, f = 1.0 kHz)	(PNP)		2.0	12	
Voltage Feedback Ratio		h_{re}			X 10^{-4}
(V_{CE} = 10 Vdc, I_C = 1.0 mAdc, f = 1.0 kHz)	(NPN)		0.5	8.0	
(V_{CE} = −10 Vdc, I_C = −1.0 mAdc, f = 1.0 kHz)	(PNP)		0.1	10	
Small – Signal Current Gain		h_{fe}			–
(V_{CE} = 10 Vdc, I_C = 1.0 mAdc, f = 1.0 kHz)	(NPN)		100	400	
(V_{CE} = −10 Vdc, I_C = −1.0 mAdc, f = 1.0 kHz)	(PNP)		100	400	

Table 4. ELECTRICAL CHARACTERISTICS (T_A = 25°C unless otherwise noted) (continued)

Characteristic		Symbol	Min	Max	Unit
Output Admittance		h_{oe}			μmhos
(V_{CE} = 10 Vdc, I_C = 1.0 mAdc, f = 1.0 kHz)	(NPN)		1.0	40	
(V_{CE} = −10 Vdc, I_C = −1.0 mAdc, f = 1.0 kHz)	(PNP)		3.0	60	
Noise Figure		NF			dB
(V_{CE} = 5.0 Vdc, I_C = 100 μAdc, R_S = 1.0 kΩ, f = 1.0 kHz)	(NPN)		–	5.0	
(V_{CE} = −5.0 Vdc, I_C = −100 μAdc, R_S = 1.0 kΩ, f = 1.0 kHz)	(PNP)		–	4.0	

SWITCHING CHARACTERISTICS

Delay Time	(V_{CC} = 3.0 Vdc, V_{BE} = −0.5 Vdc)	(NPN)	t_d	–	35	ns
	(V_{CC} = −3.0 Vdc, V_{BE} = 0.5 Vdc)	(PNP)		–	35	
Rise Time	(I_C = 10 mAdc, I_{B1} = 1.0 mAdc)	(NPN)	t_r	–	35	
	(I_C = −10 mAdc, I_{B1} = −1.0 mAdc)	(PNP)		–	35	
Storage Time	(V_{CC} = 3.0 Vdc, I_C = 10 mAdc)	(NPN)	t_s	–	200	ns
	(V_{CC} = −3.0 Vdc, I_C = −10 mAdc)	(PNP)		–	225	
Fall Time	(I_{B1} = I_{B2} = 1.0 mAdc)	(NPN)	t_f	–	50	
	(I_{B1} = I_{B2} = −1.0 mAdc)	(PNP)		–	75	

2. Pulse Test: Pulse Width ≤ 300 μs; Duty Cycle ≤ 2.0%.

(NPN)




Figure 1. Delay and Rise Time Equivalent Test Circuit




Figure 2. Storage and Fall Time Equivalent Test Circuit

* Total shunt capacitance of test jig and connectors

TYPICAL TRANSIENT CHARACTERISTICS




Figure 3. Capacitance




Figure 4. Charge Data

(NPN)




Figure 5. Turn-On Time




Figure 6. Rise Time




Figure 7. Storage Time




Figure 8. Fall Time

TYPICAL AUDIO SMALL-SIGNAL CHARACTERISTICS
NOISE FIGURE VARIATIONS

(V_{CE} = 5.0 Vdc, T_A = 25°C, Bandwidth = 1.0 Hz)




Figure 9. Noise Figure




Figure 10. Noise Figure

(NPN)
h PARAMETERS
(V_{CE} = 10 Vdc, f = 1.0 kHz, T_A = 25°C)




Figure 11. Current Gain




Figure 12. Output Admittance




Figure 13. Input Impedance




Figure 14. Voltage Feedback Ratio




Figure 15. Safe Operating Area

(NPN)
TYPICAL STATIC CHARACTERISTICS




Figure 16. DC Current Gain




Figure 17. Collector Saturation Region




Figure 18. "ON" Voltages




Figure 19. Temperature Coefficients

(PNP)




Figure 20. Delay and Rise Time Equivalent Test Circuit




Figure 21. Storage and Fall Time Equivalent Test Circuit

* Total shunt capacitance of test jig and connectors

TYPICAL TRANSIENT CHARACTERISTICS




Figure 22. Capacitance




Figure 23. Charge Data




Figure 24. Turn-On Time




Figure 25. Fall Time

(PNP)

TYPICAL AUDIO SMALL-SIGNAL CHARACTERISTICS
NOISE FIGURE VARIATIONS

(V_{CE} = −5.0 Vdc, T_A = 25°C, Bandwidth = 1.0 Hz)




Figure 26.




Figure 27.

h PARAMETERS

(V_{CE} = −10 Vdc, f = 1.0 kHz, T_A = 25°C)




Figure 28. Current Gain




Figure 29. Output Admittance




Figure 30. Input Impedance




Figure 31. Voltage Feedback Ratio

(PNP)

TYPICAL STATIC CHARACTERISTICS




Figure 32. DC Current Gain




Figure 33. Collector Saturation Region




Figure 34. “ON” Voltages




Figure 35. Temperature Coefficients






Figure 36. Safe Operating Area

PACKAGE DIMENSIONS

SC−88/SC70−6/SOT−363
CASE 419B−02
ISSUE W






NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. 419B−01 OBSOLETE, NEW STANDARD 419B−02.

	MILLIMETERS			INCHES		
DIM	MIN	NOM	MAX	MIN	NOM	MAX
A	0.80	0.95	1.10	0.031	0.037	0.043
A1	0.00	0.05	0.10	0.000	0.002	0.004
A3		0.20 REF			0.008 REF	
b	0.10	0.21	0.30	0.004	0.008	0.012
C	0.10	0.14	0.25	0.004	0.005	0.010
D	1.80	2.00	2.20	0.070	0.078	0.086
E	1.15	1.25	1.35	0.045	0.049	0.053
e		0.65 BSC			0.026 BSC	
L	0.10	0.20	0.30	0.004	0.008	0.012
H_E	2.00	2.10	2.20	0.078	0.082	0.086

STYLE 1:
PIN 1. EMITTER 2
2. BASE 2
3. COLLECTOR 1
4. EMITTER 1
5. BASE 1
6. COLLECTOR 2

SOLDERING FOOTPRINT*



*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

ON Semiconductor and ON are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of SCILLC's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:
Literature Distribution Center for ON Semiconductor
P.O. Box 5163, Denver, Colorado 80217 USA
Phone: 303−675−2175 or 800−344−3860 Toll Free USA/Canada
Fax: 303−675−2176 or 800−344−3867 Toll Free USA/Canada
Email: orderlit@onsemi.com

N. American Technical Support: 800−282−9855 Toll Free USA/Canada
Europe, Middle East and Africa Technical Support:
Phone: 421 33 790 2910
Japan Customer Focus Center
Phone: 81−3−5817−1050

ON Semiconductor Website: **www.onsemi.com**

Order Literature: http://www.onsemi.com/orderlit

For additional information, please contact your local Sales Representative