P2N2907A

Amplifier Transistor

PNP Silicon

ON Semiconductor®

http://onsemi.com

Features

- These are Pb-Free Devices*



TO-92
CASE 29
STYLE 17



STRAIGHT LEAD
BULK PACK

BENT LEAD
TAPE & REEL
AMMO PACK

MAXIMUM RATINGS

Rating	Symbol	Value	Unit
Collector-Emitter Voltage	V_{CEO}	-60	Vdc
Collector-Base Voltage	V_{CBO}	-60	Vdc
Emitter-Base Voltage	V_{EBO}	-5.0	Vdc
Collector Current - Continuous	I_C	-600	mAdc
Total Device Dissipation @ T_A = 25°C Derate above 25°C	P_D	625 5.0	mW mW/°C
Total Device Dissipation @ T_C = 25°C Derate above 25°C	P_D	1.5 12	W mW/°C
Operating and Storage Junction Temperature Range	T_J, T_{stg}	-55 to +150	°C

THERMAL CHARACTERISTICS

Characteristic	Symbol	Max	Unit
Thermal Resistance, Junction to Ambient	$R_{\theta JA}$	200	°C/W
Thermal Resistance, Junction to Case	$R_{\theta JC}$	83.3	°C/W

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

MARKING DIAGRAM



A = Assembly Location
Y = Year
WW = Work Week
▪ = Pb-Free Package
(Note: Microdot may be in either location)

ORDERING INFORMATION

Device	Package	Shipping†
P2N2907AG	TO-92 (Pb-Free)	5000 Units / Bulk
P2N2907ARL1G	TO-92 (Pb-Free)	2000 / Tape & Reel

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specification Brochure, BRD8011/D.

*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

© Semiconductor Components Industries, LLC, 2007

ELECTRICAL CHARACTERISTICS (T_A = 25°C unless otherwise noted)

Characteristic	Symbol	Min	Max	Unit
OFF CHARACTERISTICS				
Collector−Emitter Breakdown Voltage (Note 1) (I_C = −10 mAdc, I_B = 0)	$V_{(BR)CEO}$	−60	−	Vdc
Collector−Base Breakdown Voltage (I_C = −10 μAdc, I_E = 0)	$V_{(BR)CBO}$	−60	−	Vdc
Emitter−Base Breakdown Voltage (I_E = −10 μAdc, I_C = 0)	$V_{(BR)EBO}$	−5.0	−	Vdc
Collector Cutoff Current (V_{CE} = −30 Vdc, $V_{EB(off)}$ = −0.5 Vdc)	I_{CEX}	−	−50	nAdc
Collector Cutoff Current (V_{CB} = −50 Vdc, I_E = 0) (V_{CB} = −50 Vdc, I_E = 0, T_A = 150°C)	I_{CBO}	− −	−0.01 −10	μAdc
Emitter Cutoff Current (V_{EB} = −3.0 Vdc)	I_{EBO}	−	−10	nAdc
Collector Cutoff Current (V_{CE} = −10 V)	I_{CEO}	−	−10	nAdc
Base Cutoff Current (V_{CE} = −30 Vdc, $V_{EB(off)}$ = −0.5 Vdc)	I_{BEX}	−	−50	nAdc
ON CHARACTERISTICS				
DC Current Gain (I_C = −0.1 mAdc, V_{CE} = −10 Vdc) (I_C = −1.0 mAdc, V_{CE} = −10 Vdc) (I_C = −10 mAdc, V_{CE} = −10 Vdc) (I_C = −150 mAdc, V_{CE} = −10 Vdc) (Note 1) (I_C = −500 mAdc, V_{CE} = −10 Vdc) (Note 1)	h_{FE}	 75 100 100 100 50	 − − − 300 −	−
Collector−Emitter Saturation Voltage (Note 1) (I_C = −150 mAdc, I_B = −15 mAdc) (I_C = −500 mAdc, I_B = −50 mAdc)	$V_{CE(sat)}$	 − −	 −0.4 −1.6	Vdc
Base−Emitter Saturation Voltage (Note 1) (I_C = −150 mAdc, I_B = −15 mAdc) (I_C = −500 mAdc, I_B = −50 mAdc)	$V_{BE(sat)}$	 − −	 −1.3 −2.6	Vdc
SMALL−SIGNAL CHARACTERISTICS				
Current−Gain − Bandwidth Product (Notes 1 and 2) (I_C = −50 mAdc, V_{CE} = −20 Vdc, f = 100 MHz)	f_T	200	−	MHz
Output Capacitance (V_{CB} = −10 Vdc, I_E = 0, f = 1.0 MHz)	C_{obo}	−	8.0	pF
Input Capacitance (V_{EB} = −2.0 Vdc, I_C = 0, f = 1.0 MHz)	C_{ibo}	−	30	pF
SWITCHING CHARACTERISTICS				
Turn−On Time	(V_{CC} = −30 Vdc, I_C = −150 mAdc, I_{B1} = −15 mAdc) (Figures 1 and 5)	t_{on}	−	50	ns
Delay Time		t_d	−	10	ns
Rise Time		t_r	−	40	ns
Turn−Off Time	(V_{CC} = −6.0 Vdc, I_C = −150 mAdc, I_{B1} = I_{B2} = −15 mAdc) (Figure 2)	t_{off}	−	110	ns
Storage Time		t_s	−	80	ns
Fall Time		t_f	−	30	ns

1. Pulse Test: Pulse Width ≤ 300 μs, Duty Cycle ≤ 2.0%.
2. f_T is defined as the frequency at which $|h_{fe}|$ extrapolates to unity.



Figure 1. Delay and Rise Time Test Circuit



Figure 2. Storage and Fall Time Test Circuit

TYPICAL CHARACTERISTICS



Figure 3. DC Current Gain



Figure 4. Collector Saturation Region



Figure 5. Turn-On Time



Figure 6. Turn-Off Time

TYPICAL SMALL−SIGNAL CHARACTERISTICS

NOISE FIGURE

V_{CE} = 10 Vdc, T_A = 25°C



Figure 7. Frequency Effects



Figure 8. Source Resistance Effects



Figure 9. Capacitances



Figure 10. Current−Gain − Bandwidth Product



Figure 11. “On” Voltage



Figure 12. Temperature Coefficients

PACKAGE DIMENSIONS

TO−92 (TO−226)
CASE 29−11
ISSUE AM



STRAIGHT LEAD
BULK PACK



SECTION X−X

NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. CONTOUR OF PACKAGE BEYOND DIMENSION R IS UNCONTROLLED.
4. LEAD DIMENSION IS UNCONTROLLED IN P AND BEYOND DIMENSION K MINIMUM.

	INCHES		MILLIMETERS	
DIM	MIN	MAX	MIN	MAX
A	0.175	0.205	4.45	5.20
B	0.170	0.210	4.32	5.33
C	0.125	0.165	3.18	4.19
D	0.016	0.021	0.407	0.533
G	0.045	0.055	1.15	1.39
H	0.095	0.105	2.42	2.66
J	0.015	0.020	0.39	0.50
K	0.500	---	12.70	---
L	0.250	---	6.35	---
N	0.080	0.105	2.04	2.66
P	---	0.100	---	2.54
R	0.115	---	2.93	---
V	0.135	---	3.43	---



BENT LEAD
TAPE & REEL
AMMO PACK



SECTION X−X

NOTES:
1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: MILLIMETERS.
3. CONTOUR OF PACKAGE BEYOND DIMENSION R IS UNCONTROLLED.
4. LEAD DIMENSION IS UNCONTROLLED IN P AND BEYOND DIMENSION K MINIMUM.

	MILLIMETERS	
DIM	MIN	MAX
A	4.45	5.20
B	4.32	5.33
C	3.18	4.19
D	0.40	0.54
G	2.40	2.80
J	0.39	0.50
K	12.70	---
N	2.04	2.66
P	1.50	4.00
R	2.93	---
V	3.43	---

STYLE 17:
PIN 1. COLLECTOR
2. BASE
3. EMITTER

ON Semiconductor and ON are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. “Typical” parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including “Typicals” must be validated for each customer application by customer’s technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:
Literature Distribution Center for ON Semiconductor
P.O. Box 5163, Denver, Colorado 80217 USA
Phone: 303−675−2175 or 800−344−3860 Toll Free USA/Canada
Fax: 303−675−2176 or 800−344−3867 Toll Free USA/Canada
Email: orderlit@onsemi.com

N. American Technical Support: 800−282−9855 Toll Free USA/Canada
Europe, Middle East and Africa Technical Support:
Phone: 421 33 790 2910
Japan Customer Focus Center
Phone: 81−3−5773−3850

ON Semiconductor Website: **www.onsemi.com**

Order Literature: http://www.onsemi.com/orderlit

For additional information, please contact your local Sales Representative