
VND830ASP

DOUBLE CHANNEL HIGH SIDE SOLID STATE RELAY

TYPE	$R_{DS(on)}$	I_{OUT}	V_{CC}
VND830ASP	60 mΩ (*)	6 A (*)	36 V (*)

(*) Per channel

- DC SHORT CIRCUIT CURRENT: 6A
- CMOS COMPATIBLE INPUTS
- PROPORTIONAL LOAD CURRENT SENSE
- UNDERVOLTAGE AND OVERVOLTAGE SHUT-DOWN
- OVERVOLTAGE CLAMP
- THERMAL SHUT-DOWN
- CURRENT LIMITATION
- VERY LOW STAND-BY POWER DISSIPATION
- PROTECTION AGAINST:
  LOSS OF GROUND AND LOSS OF V_{CC}
- REVERSE BATTERY PROTECTION (**)




PowerSO-10™

ORDER CODES		
PACKAGE	**TUBE**	**T&R**
PowerSO-10™	VND830ASP	VND830ASP13TR

DESCRIPTION

The VND830ASP is a monolithic device made using STMicroelectronics VIPower M0-3 technology. It is intended for driving any kind of load with one side connected to ground. Active V_{CC} pin voltage clamp protects the device against low energy spikes (see ISO7637 transient compatibility table). This device has two channels in high side configuration; each channel has an analog sense output on which the sensing current is proportional (according to a known ratio) to the corresponding load current. Built-in thermal shut-down and outputs current limitation protect the chip from over temperature and short circuit. Device turns off in case of ground pin disconnection.

BLOCK DIAGRAM




(**) See application schematic at page 8

Obsolete Product(s) - Obsolete Product(s)


ABSOLUTE MAXIMUM RATING

Symbol	Parameter	Value	Unit
V_{CC}	DC Supply Voltage	41	V
$-V_{CC}$	Reverse Supply Voltage	- 0.3	V
$-I_{GND}$	DC Reverse Ground Pin Current	- 200	mA
I_{OUT}	Output Current	Internally Limited	A
I_R	Reverse Output Current	- 6	A
I_{IN}	Input Current	+/- 10	mA
V_{CSENSE}	Current Sense Maximum Voltage	-3 +15	V V
V_{ESD}	Electrostatic Discharge (Human Body Model: R=1.5Ω; C=100pF) - INPUT - CURRENT SENSE - OUTPUT - V_{CC}	 4000 2000 5000 5000	 V V V V
E_{MAX}	Maximum Switching Energy (L=1.8mH; R_L=0Ω; V_{bat}=13.5V; T_{jstart}=150ºC; I_L=9A)	100	mJ
P_{tot}	Power Dissipation at T_C=25°C	74	W
T_j	Junction Operating Temperature	Internally Limited	°C
T_c	Case Operating Temperature	- 40 to 150	°C
T_{stg}	Storage Temperature	- 55 to 150	°C

CONNECTION DIAGRAM (TOP VIEW)



CURRENT AND VOLTAGE CONVENTIONS



Obsolete Product(s) - Obsolete Product(s)

THERMAL DATA

Symbol	Parameter	Value	Unit
$R_{thj\text{-}case}$	Thermal Resistance Junction-case	1.2	°C/W
$R_{thj\text{-}amb}$	Thermal Resistance Junction-ambient	51.2 (*)	°C/W

(*) When mounted on a standard single-sided FR-4 board with 0.5cm^2 of Cu (at least 35µm thick). Horizontal mounting and no artificial air flow

ELECTRICAL CHARACTERISTICS (8V<V_{CC}<36V; -40°C< T_j <150°C, unless otherwise specified)

(Per each channel)

POWER OUTPUT

Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
V_{CC}	Operating Supply Voltage		5.5	13	36	V
V_{USD}	Undervoltage Shut-down		3	4	5.5	V
V_{OV}	Overvoltage Shut-down		36			V
R_{ON}	On State Resistance	I_{OUT} =2A; T_j=25°C I_{OUT} =2A; T_j=150°C			60 120	mΩ mΩ
V_{clamp}	Clamp voltage	I_{CC}=20 mA (see note 1)	41	48	55	V
I_S	Supply Current	Off State; V_{CC}=13V; $V_{IN=}V_{OUT}$=0V Off State; V_{CC}=13V; $V_{IN=}V_{OUT}$=0V; T_j =25°C On State; V_{IN}=5V; V_{CC}=13V; I_{OUT}=0A; R_{SENSE}=3.9KΩ		12 12	40 25 7	µA µA mA
$I_{L(off1)}$	Off State Output Current	V_{IN}=V_{OUT}=0V; V_{CC}=36V; T_j=125°C	0		50	µA
$I_{L(off2)}$	Off State Output Current	V_{IN}=0V; V_{OUT}=3.5V	-75		0	µA
$I_{L(off3)}$	Off State Output Current	V_{IN}=V_{OUT}=0V; V_{CC}=13V; T_j =125°C			5	µA
$I_{L(off4)}$	Off State Output Current	V_{IN}=V_{OUT}=0V; V_{CC}=13V; T_j =25°C			3	µA

SWITCHING (V_{CC} =13V)

Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
$t_{d(on)}$	Turn-on Delay Time	R_L=6.5Ω from V_{IN} rising edge to V_{OUT}=1.3V		30		µs
$t_{d(off)}$	Turn-off Delay Time	R_L=6.5Ω from V_{IN} falling edge to V_{OUT}=11.7V		30		µs
$dV_{OUT}/dt_{(on)}$	Turn-on Voltage Slope	R_L=6.5Ω from V_{OUT}=1.3V to V_{OUT}=10.4V		See relative diagram		V/µs
$dV_{OUT}/dt_{(off)}$	Turn-off Voltage Slope	R_L=6.5Ω from V_{OUT}=11.7V to V_{OUT}=1.3V		See relative diagram		V/µs

LOGIC INPUT (Channels 1,2)

Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
V_{IL}	Input low level voltage				1.25	V
I_{IL}	Low level input current	V_{IN}=1.25V	1			µA
V_{IH}	Input high level voltage		3.25			V
I_{IH}	High level input current	V_{IN}=3.25V			10	µA
$V_{I(hyst)}$	Input hysteresis voltage		0.5			V
V_{ICL}	Input clamp voltage	I_{IN}=1mA I_{IN}=-1mA	6	6.8 -0.7	8	V V

Note 1: V_{clamp} and V_{OV} are correlated. Typical difference is 5V.

Obsolete Product(s) - Obsolete Product(s)

ELECTRICAL CHARACTERISTICS (continued)

V_{CC} - OUTPUT DIODE

Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
V_F	Forward on Voltage	$-I_{OUT}$=2A; T_j=150°C			0.6	V

PROTECTIONS

Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
I_{lim}	Current limitation	Vcc=13V 5.5V<Vcc<36V	6	9	15 15	A A
T_{TSD}	Thermal shut-down temperature		150	175	200	°C
T_R	Thermal reset temperature		135			°C
T_{HYST}	Thermal hysteresis		7	15		°C
V_{demag}	Turn-off output voltage clamp	I_{OUT}=2A; V_{IN}=0V; L=6mH	V_{CC}-41	V_{CC}-48	V_{CC}-55	V
V_{ON}	Output voltage drop limitation	I_{OUT}=10mA		50		mV

CURRENT SENSE (9V≤V_{CC}≤16V) (See figure 1)

Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
K_0	I_{OUT}/I_{SENSE}	I_{OUT1} or I_{OUT2}=0.05A; V_{SENSE}=0.5V; other channels open; T_j= -40°C...150°C	600	1300	2000	
K_1	I_{OUT}/I_{SENSE}	I_{OUT1} or I_{OUT2}=0.25A; V_{SENSE}=0.5V; other channels open; T_j= -40°C...150°C	1000	1400	1900	
dK_1/K_1	Current Sense Ratio Drift	I_{OUT1} or I_{OUT2}=0.25A; V_{SENSE}=0.5V; other channels open; T_j= -40°C...150°C	-10		+10	%
K_2	I_{OUT}/I_{SENSE}	I_{OUT1} or I_{OUT2}=1.6A; V_{SENSE}=4V; other channels open; T_j=-40°C T_j=25°C...150°C	1280 1300	1500 1500	1800 1780	
dK_2/K_2	Current Sense Ratio Drift	I_{OUT1} or I_{OUT2}=1.6A; V_{SENSE}=4V; other channels open; T_j=-40°C...150°C	-6		+6	%
K_3	I_{OUT}/I_{SENSE}	I_{OUT1} or I_{OUT2}=2.5A; V_{SENSE}=4V; other channels open; T_j=-40°C T_j=25°C...150°C	1280 1340	1500 1500	1680 1600	
dK_3/K_3	Current Sense Ratio Drift	I_{OUT1} or I_{OUT2}=2.5A; V_{SENSE}=4V; other channels open; T_j=-40°C...150°C	-6		+6	%
I_{SENSE}	Analog Sense Leakage Current	V_{IN}=0V; I_{OUT}=0A; V_{SENSE}=0V; T_j=-40°C...150°C V_{IN}=5V; I_{OUT}=0A; V_{SENSE}=0V; T_j=-40°C...150°C	0 0		5 10	µA µA
V_{SENSE}	Max Analog Sense Output Voltage	V_{CC}=5.5V; $I_{OUT1,2}$=1.3A; R_{SENSE}=10kΩ V_{CC}>8V, $I_{OUT1,2}$=2.5A; R_{SENSE}=10kΩ	2 4			V V
V_{SENSEH}	Sense Voltage in Overtemperature conditions	V_{CC}=13V; R_{SENSE}=3.9kΩ		5.5		V
$R_{VSENSEH}$	Analog Sense Output Impedance in Overtemperature Condition	V_{CC}=13V; Tj>T_{TSD}; All Channels Open		400		Ω
t_{DSENSE}	Current sense delay response	to 90% I_{SENSE} (see note 2)			500	µs

Note 2: current sense signal delay after positive input slope.

Note: Sense pin doesn't have to be left floating.

Obsolete Product(s) - Obsolete Product(s)

TRUTH TABLE (per channel)

CONDITIONS	INPUT	OUTPUT	SENSE
Normal operation	L H	L H	0 Nominal
Overtemperature	L H	L L	0 V_{SENSEH}
Undervoltage	L H	L L	0 0
Overvoltage	L H	L L	0 0
Short circuit to GND	L H H	L L L	0 (T_j<T_{TSD}) 0 (T_j>T_{TSD}) V_{SENSEH}
Short circuit to V_{CC}	L H	H H	0 < Nominal
Negative output voltage clamp	L	L	0

ELECTRICAL TRANSIENT REQUIREMENTS

ISO T/R 7637/1 Test Pulse	TEST LEVELS				
	I	II	III	IV	Delays and Impedance
1	-25 V	-50 V	-75 V	-100 V	2 ms 10 Ω
2	+25 V	+50 V	+75 V	+100 V	0.2 ms 10 Ω
3a	-25 V	-50 V	-100 V	-150 V	0.1 µs 50 Ω
3b	+25 V	+50 V	+75 V	+100 V	0.1 µs 50 Ω
4	-4 V	-5 V	-6 V	-7 V	100 ms, 0.01 Ω
5	+26.5 V	+46.5 V	+66.5 V	+86.5 V	400 ms, 2 Ω

ISO T/R 7637/1 Test Pulse	TEST LEVELS RESULTS			
	I	II	III	IV
1	C	C	C	C
2	C	C	C	C
3a	C	C	C	C
3b	C	C	C	C
4	C	C	C	C
5	C	E	E	E

CLASS	CONTENTS
C	All functions of the device are performed as designed after exposure to disturbance.
E	One or more functions of the device is not performed as designed after exposure to disturbance and cannot be returned to proper operation without replacing the device.

Obsolete Product(s) - Obsolete Product(s)

Figure 1: I_{OUT}/I_{SENSE} versus I_{OUT}






Figure 2: Switching Characteristics (Resistive load R_L=6.5Ω)




Obsolete Product(s) - Obsolete Product(s)

Figure 3: Waveforms



Obsolete Product(s) - Obsolete Product(s)

APPLICATION SCHEMATIC



Obsolete Product(s) - Obsolete Product(s)

GND PROTECTION NETWORK AGAINST REVERSE BATTERY

Solution 1: Resistor in the ground line (R_{GND} only). This can be used with any type of load.

The following is an indication on how to dimension the R_{GND} resistor.

1) $R_{GND} \leq 600mV / I_{S(on)max}$.

2) $R_{GND} \geq (-V_{CC}) / (-I_{GND})$

where $-I_{GND}$ is the DC reverse ground pin current and can be found in the absolute maximum rating section of the device's datasheet.

Power Dissipation in R_{GND} (when V_{CC}<0: during reverse battery situations) is:

$P_D = (-V_{CC})^2/R_{GND}$

This resistor can be shared amongst several different HSD. Please note that the value of this resistor should be calculated with formula (1) where $I_{S(on)max}$ becomes the sum of the maximum on-state currents of the different devices.

Please note that if the microprocessor ground is not common with the device ground then the R_{GND} will produce a shift ($I_{S(on)max} * R_{GND}$) in the input thresholds and the status output values. This shift will vary depending on how many devices are ON in the case of several high side drivers sharing the same R_{GND}.

If the calculated power dissipation leads to a large resistor or several devices have to share the same resistor then the ST suggests to utilize Solution 2 (see below).

Solution 2: A diode (D_{GND}) in the ground line.

A resistor (R_{GND}=1kΩ) should be inserted in parallel to D_{GND} if the device will be driving an inductive load.

This small signal diode can be safely shared amongst several different HSDs. Also in this case, the presence of the ground network will produce a shift (≈600mV) in the input thresholds and the status output values if the microprocessor ground is not common with the device ground. This shift will not vary if more than one HSD shares the same diode/resistor network.

Series resistor in INPUT line is also required to prevent that, during battery voltage transient, the current exceeds the Absolute Maximum Rating.

Safest configuration for unused INPUT pin is to leave it unconnected, while unused SENSE pin has to be connected to Ground pin.

LOAD DUMP PROTECTION

D_{ld} is necessary (Voltage Transient Suppressor) if the load dump peak voltage exceeds V_{CC} max DC rating. The same applies if the device will be subject to transients on the V_{CC} line that are greater than the ones shown in the ISO T/R 7637/1 table.

µC I/Os PROTECTION:

If a ground protection network is used and negative transient are present on the V_{CC} line, the control pins will be pulled negative. ST suggests to insert a resistor (R_{prot}) in line to prevent the µC I/Os pins to latch-up.

The value of these resistors is a compromise between the leakage current of µC and the current required by the HSD I/Os (Input levels compatibility) with the latch-up limit of µC I/Os.

$$-V_{CCpeak}/I_{latchup} \leq R_{prot} \leq (V_{OH\mu C}-V_{IH}-V_{GND}) / I_{IHmax}$$

Calculation example:


For V_{CCpeak}= - 100V and $I_{latchup} \geq$ 20mA; $V_{OH\mu C} \geq$ 4.5V

$5k\Omega \leq R_{prot} \leq 65k\Omega$.


Recommended R_{prot} value is 10kΩ.

Obsolete Product(s) - Obsolete Product(s)


Off State Output Current




High Level Input Current




Input Clamp Voltage




Input High Level



Input Low Level




Input Hysteresis Voltage




Obsolete Product(s) - Obsolete Product(s)


Overvoltage Shutdown




I_{LIM} Vs T_{case}




Turn-on Voltage Slope




Turn-off Voltage Slope



On State Resistance Vs T_{case}




On State Resistance Vs V_{CC}




Obsolete Product(s) - Obsolete Product(s)

Maximum turn off current versus load inductance



A = Single Pulse at T_{Jstart}=150ºC
B= Repetitive pulse at T_{Jstart}=100ºC
C= Repetitive Pulse at T_{Jstart}=125ºC


Conditions:
V_{CC}=13.5V
Values are generated with R_L=0Ω
In case of repetitive pulses, T_{jstart} (at beginning of each demagnetization) of every pulse must not exceed the temperature specified above for curves B and C.



Obsolete Product(s) - Obsolete product(s)


PowerSO-10™ THERMAL DATA

PowerSO-10™ PC Board




Layout condition of R_{th} and Z_{th} measurements (PCB FR4 area= 58mm x 58mm, PCB thickness=2mm, Cu thickness=35µm, Copper areas: from minimum pad lay-out to 8cm^2).

$R_{thj\text{-}amb}$ Vs PCB copper area in open box free air condition




Obsolete Product(s) - Obsolete Product(s)

PowerSO-10 Thermal Impedance Junction Ambient Single Pulse



Obsolete Product(s) - Obsolete Product(s)

Thermal fitting model of a double channel HSD in PowerSO-10



Pulse calculation formula

$$Z_{TH\delta} = R_{TH} \cdot \delta + Z_{THtp}(1 - \delta)$$

where $\delta = t_p / T$


Thermal Parameter

Area/island (cm^2)	0.5	6
R1 (°C/W)	0.15	
R2 (°C/W)	0.8	
R3(°C/W)	0.7	
R4 (°C/W)	0.8	
R5 (°C/W)	12	
R6 (°C/W)	37	22
C1 (W.s/°C)	0.0006	
C2 (W.s/°C)	2.10E-03	
C3 (W.s/°C)	0.013	
C4 (W.s/°C)	0.3	
C5 (W.s/°C)	0.75	
C6 (W.s/°C)	3	5

PowerSO-10™ MECHANICAL DATA


DIM.	mm.			inch		
	MIN.	TYP	MAX.	MIN.	TYP.	MAX.
A	3.35		3.65	0.132		0.144
A (*)	3.4		3.6	0.134		0.142
A1	0.00		0.10	0.000		0.004
B	0.40		0.60	0.016		0.024
B (*)	0.37		0.53	0.014		0.021
C	0.35		0.55	0.013		0.022
C (*)	0.23		0.32	0.009		0.0126
D	9.40		9.60	0.370		0.378
D1	7.40		7.60	0.291		0.300
E	9.30		9.50	0.366		0.374
E2	7.20		7.60	0.283		300
E2 (*)	7.30		7.50	0.287		0.295
E4	5.90		6.10	0.232		0.240
E4 (*)	5.90		6.30	0.232		0.248
e		1.27			0.050	
F	1.25		1.35	0.049		0.053
F (*)	1.20		1.40	0.047		0.055
H	13.80		14.40	0.543		0.567
H (*)	13.85		14.35	0.545		0.565
h		0.50			0.002	
L	1.20		1.80	0.047		0.070
L (*)	0.80		1.10	0.031		0.043
α	0º		8º	0º		8º
α (*)	2º		8º	2º		8º

(*) Muar only POA P013P




Obsolete Product(s) - Obsolete Product(s)


PowerSO-10™ SUGGESTED PAD LAYOUT



TUBE SHIPMENT (no suffix)



CASABLANCA




MUAR

All dimensions are in mm.

	Base Q.ty	Bulk Q.ty	Tube length (± 0.5)	A	B	C (± 0.1)
Casablanca	50	1000	532	10.4	16.4	0.8
Muar	50	1000	532	4.9	17.2	0.8

TAPE AND REEL SHIPMENT (suffix "13TR")



REEL DIMENSIONS

Base Q.ty	600
Bulk Q.ty	600
A (max)	330
B (min)	1.5
C (± 0.2)	13
F	20.2
G (+ 2 / -0)	24.4
N (min)	60
T (max)	30.4


All dimensions are in mm.


TAPE DIMENSIONS


According to Electronic Industries Association (EIA) Standard 481 rev. A, Feb 1986

Tape width	**W**	24
Tape Hole Spacing	**P0 (± 0.1)**	4
Component Spacing	**P**	24
Hole Diameter	**D (± 0.1/-0)**	1.5
Hole Diameter	**D1 (min)**	1.5
Hole Position	**F (± 0.05)**	11.5
Compartment Depth	**K (max)**	6.5
Hole Spacing	**P1 (± 0.1)**	2

All dimensions are in mm.







Obsolete Product(s) - Obsolete Product(s)

Please Read Carefully:

Information in this document is provided solely in connection with ST products. STMicroelectronics NV and its subsidiaries (“ST”) reserve the right to make changes, corrections, modifications or improvements, to this document, and the products and services described herein at any time, without notice.

All ST products are sold pursuant to ST’s terms and conditions of sale.

Purchasers are solely responsible for the choice, selection and use of the ST products and services described herein, and ST assumes no liability whatsoever relating to the choice, selection or use of the ST products and services described herein.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted under this document. If any part of this document refers to any third party products or services it shall not be deemed a license grant by ST for the use of such third party products or services, or any intellectual property contained therein or considered as a warranty covering the use in any manner whatsoever of such third party products or services or any intellectual property contained therein.

UNLESS OTHERWISE SET FORTH IN ST’S TERMS AND CONDITIONS OF SALE ST DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY WITH RESPECT TO THE USE AND/OR SALE OF ST PRODUCTS INCLUDING WITHOUT LIMITATION IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION), OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT.

ST PRODUCTS ARE NOT DESIGNED OR AUTHORIZED FOR USE IN: (A) SAFETY CRITICAL APPLICATIONS SUCH AS LIFE SUPPORTING, ACTIVE IMPLANTED DEVICES OR SYSTEMS WITH PRODUCT FUNCTIONAL SAFETY REQUIREMENTS; (B) AERONAUTIC APPLICATIONS; (C) AUTOMOTIVE APPLICATIONS OR ENVIRONMENTS, AND/OR (D) AEROSPACE APPLICATIONS OR ENVIRONMENTS. WHERE ST PRODUCTS ARE NOT DESIGNED FOR SUCH USE, THE PURCHASER SHALL USE PRODUCTS AT PURCHASER’S SOLE RISK, EVEN IF ST HAS BEEN INFORMED IN WRITING OF SUCH USAGE, UNLESS A PRODUCT IS EXPRESSLY DESIGNATED BY ST AS BEING INTENDED FOR “AUTOMOTIVE, AUTOMOTIVE SAFETY OR MEDICAL” INDUSTRY DOMAINS ACCORDING TO ST PRODUCT DESIGN SPECIFICATIONS. PRODUCTS FORMALLY ESCC, QML OR JAN QUALIFIED ARE DEEMED SUITABLE FOR USE IN AEROSPACE BY THE CORRESPONDING GOVERNMENTAL AGENCY.

Resale of ST products with provisions different from the statements and/or technical features set forth in this document shall immediately void any warranty granted by ST for the ST product or service described herein and shall not create or extend in any manner whatsoever, any liability of ST.

ST and the ST logo are trademarks or registered trademarks of ST in various countries.
Information in this document supersedes and replaces all information previously supplied.
The ST logo is a registered trademark of STMicroelectronics. All other names are the property of their respective owners.

© 2013 STMicroelectronics - All rights reserved

STMicroelectronics group of companies

Australia - Belgium - Brazil - Canada - China - Czech Republic - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan - Malaysia - Malta - Morocco - Philippines - Singapore - Spain - Sweden - Switzerland - United Kingdom - United States of America

www.st.com

Obsolete Product(s) - Obsolete Product(s)