
M74HCT4051

SINGLE 8-CHANNEL ANALOG MULTIPLEXER/DEMULTIPLEXER

- LOW POWER DISSIPATION:
  I_{CC} = 4µA (MAX.) at T_A=25°C
- LOGIC LEVEL TRANSLATION TO ENABLE TTL LOGIC SIGNAL TO COMMUNICATE WITH ±5V ANALOG SIGNAL
- LOW "ON" RESISTANCE:
  70Ω TYP. (V_{CC} - V_{EE} = 4.5V)
  50Ω TYP. (V_{CC} - V_{EE} = 9V)
- WIDE ANALOG INPUT VOLTAGE RANGE: ±6V
- FAST SWITCHING:
  t_{pd} = 13ns (TYP.) at T_A = 25 °C
- LOW CROSSTALK BETWEEN SWITCHES
- HIGH ON/OFF OUTPUT VOLTAGE RATIO
- WIDE OPERATING SUPPLY VOLTAGE RANGE (V_{CC} - V_{EE}) = 2V TO 12V
- LOW SINE WAVE DISTORTION:
  0.02% at V_{CC} - V_{EE} = 9V
- COMPATIBLE WITH TTL OUTPUTS:
  V_{IH} = 2V(MIN.) V_{IL} = 0.8V (MAX.)
- PIN AND FUNCTION COMPATIBLE WITH 74 SERIES 4051



ORDER CODES


PACKAGE	TUBE	T & R
DIP	M74HCT4051B1R	
SOP	M74HCT4051M1R	M74HCT4051RM13TR
TSSOP		M74HCT4051TTR

DESCRIPTION

The M74HCT4051 is a single eight-channel analog MULTIPLEXER/DEMULTIPLEXER fabricated with silicon gate C^2MOS technology and it is pin to pin compatible with the equivalent metal gate CMOS4000B series.
It contains 8 bidirectional and digitally controlled analog switches.


A built-in level shifting is included to allow an input range up to ±6V (peak) for an analog signal with digital control signal of 0 to 6V.
V_{EE} supply pin is provided for analog input signals. It has an inhibit (INH) input terminal to disable all the switches when high, compatible with TTL output level. For operation as a digital multiplexer/demultiplexer, VEE is connected to GND. A, B and C control inputs select one channel out of eight channels; they are compatible with TTL output level.
All inputs are equipped with protection circuits against static discharge and transient excess voltage.

PIN CONNECTION AND IEC LOGIC SYMBOLS




Obsolete Product(s) - Obsolete Product(s)

CONTROL INPUT EQUIVALENT CIRCUIT



I/O EQUIVALENT CIRCUIT




PIN DESCRIPTION

PIN No	SYMBOL	NAME AND FUNCTION
3	COM OUT/IN	Common Output/Input
6	INH	INHIBIT Input
7	V_{EE}	Negative Supply Voltage
11, 10, 9	A, B, C	Select Inputs
13, 14, 15, 12, 1, 5, 2, 4	0 to 7	Independent Input/Outputs
8	GND	Ground (0V)
16	V_{CC}	Positive Supply Voltage

TRUTH TABLE

INPUT STATE				ON CHANNEL
INH	C	B	A	
L	L	L	L	0
L	L	L	H	1
L	L	H	L	2
L	L	H	H	3
L	H	L	L	4
L	H	L	H	5
L	H	H	L	6
L	H	H	H	7
H	X	X	X	NONE

FUNCTIONAL DIAGRAM



Obsolete Product(s) - Obsolete Product(s)

ABSOLUTE MAXIMUM RATINGS

Symbol	Parameter	Value	Unit
V_{CC}	Supply Voltage	-0.5 to +7	V
V_{CC} - V_{EE}	Supply Voltage	-0.5 to +13	V
V_I	Control Input Voltage	-0.5 to V_{CC} + 0.5	V
$V_{I/O}$	Switch I/O Voltage	V_{EE} -0.5 to V_{CC} + 0.5	V
I_{CK}	Control Input Diode Current	± 20	mA
I_{IOK}	I/O Diode Current	± 20	mA
I_T	Switch Through Current	± 25	mA
I_{CC} or I_{GND}	DC V_{CC} or Ground Current	± 50	mA
P_D	Power Dissipation	500(*)	mW
T_{stg}	Storage Temperature	-65 to +150	°C
T_L	Lead Temperature (10 sec)	300	°C

Absolute Maximum Ratings are those values beyond which damage to the device may occur. Functional operation under these conditions is not implied
(*) 500mW at 65 °C; derate to 300mW by 10mW/°C from 65°C to 85°C

RECOMMENDED OPERATING CONDITIONS

Symbol	Parameter		Value	Unit
V_{CC}	Supply Voltage		4.5 to 5.5	V
V_{EE}	Supply Voltage		-6 to 0	V
V_{CC} - V_{EE}	Supply Voltage		2 to 12	V
V_I	Input Voltage		0 to V_{CC}	V
$V_{I/O}$	I/O Voltage		V_{EE} to V_{CC}	V
T_{op}	Operating Temperature		-55 to 125	°C
t_r, t_f	Input Rise and Fall Time	V_{CC} = 4.5 to 5.5V	0 to 500	ns

Obsolete Product(s) - Obsolete Product(s)

DC SPECIFICATIONS

Symbol	Parameter	Test Condition			Value							Unit
		V_{CC} (V)	V_{EE} (V)		T_A = 25°C			-40 to 85°C		-55 to 125°C		
					Min.	Typ.	Max.	Min.	Max.	Min.	Max.	
V_{IHC}	High Level Input Voltage	4.5 to 5.5			2.0			2.0		2.0		V
V_{ILC}	Low Level Input Voltage	4.5 to 5.5					0.8		0.8		0.8	V
R_{ON}	ON Resistance	4.5	GND	$V_I = V_{IHC}$ or V_{ILC} $V_{I/O} = V_{CC}$ to V_{EE} $I_{I/O} \leq 2mA$		85	180		225		270	Ω
		4.5	-4.5			55	120		150		180	
		4.5	GND	$V_I = V_{IHC}$ or V_{ILC} $V_{I/O} = V_{CC}$ or V_{EE} $I_{I/O} \leq 2mA$		70	150		190		230	
		4.5	-4.5			50	100		125		150	
ΔR_{ON}	Difference of ON Resistance between switches	4.5	GND	$V_I = V_{IHC}$ or V_{ILC} $V_{I/O} = V_{CC}$ or V_{EE} $I_{I/O} \leq 2mA$		10	30		35		45	Ω
		4.5	-4.5			5	12		15		18	
I_{OFF}	Input/Output Leakage Current (SWITCH OFF)	5.5	GND	$V_{OS} = V_{CC}$ or GND V_{IS} = GND or V_{CC} $V_I = V_{ILC}$ or V_{IHC}			±0.06		± 0.6		± 1.0	µA
		5.5	-6.0				± 0.1		± 1		± 1	
I_{IZ}	Switch Input Leakage Current (SWITCH ON, OUTPUT OPEN)	5.5	GND	$V_{OS} = V_{CC}$ or GND $V_I = V_{IHC}$ or V_{ILC}			±0.06		± 0.6		± 1.0	µA
		5.5	-6.0				± 0.1		± 1		± 1	
I_I	Input Leakage Current	5.5	GND	$V_I = V_{CC}$ or GND			± 0.1		± 0.1		± 1	µA
I_{CC}	Quiescent Supply Current	5.5	GND	$V_I = V_{CC}$ or GND			4		40		80	µA
		5.5	-6.0				8		80		160	
ΔI_{CC}	Additional Quiescent Supply Current per input pin	4.5 to 5.5	GND	$V_I = V_{CC}$ - 2.1V other input at V_{CC} or GND		100	360		450		490	µA

Obsolete Product(s) - Obsolete Product(s)

AC ELECTRICAL CHARACTERISTICS (C_L = 50 pF, Input $t_r = t_f$ = 6ns)

Symbol	Parameter	Test Condition			Value							Unit
		V_{CC} (V)	V_{EE} (V)		T_A = 25°C			-40 to 85°C		-55 to 125°C		
					Min.	Typ.	Max.	Min.	Max.	Min.	Max.	
$\Phi_{I/O}$	Phase Difference Between Input and Output	4.5	GND	C_L = 50pF		5	12		15		18	ns
		4.5	-4.5			4	8		10		12	
t_{PZL} t_{PZH}	Output Enable Time	4.5	GND	R_L = 1KΩ C_L = 50pF		13	45		56		68	ns
		4.5	-4.5			11	34		43		51	
t_{PLZ} t_{PHZ}	Output Disable Time	4.5	GND	R_L = 1KΩ C_L = 50pF		25	38		48		58	ns
		4.5	-4.5			19	31		39		47	

CAPACITANCE CHARACTERISTICS

Symbol	Parameter	Test Condition			Value							Unit
		V_{CC} (V)	V_{EE} (V)		T_A = 25°C			-40 to 85°C		-55 to 125°C		
					Min.	Typ.	Max.	Min.	Max.	Min.	Max.	
C_{IN}	Input Capacitance	5.0				5	10		10		10	pF
$C_{I/O}$	Common Terminal Capacitance	5.0	-5.0			11	20		20		20	pF
$C_{I/O}$	Switch Terminal Capacitance	5.0	-5.0			7	15		15		15	pF
C_{IOS}	Feed Through Capacitance	5.0	-5.0			0.75	2		2		2	pF
C_{PD}	Power Dissipation Capacitance (note 1)	5.0	GND			67						pF

1) C_{PD} is defined as the value of the IC's internal equivalent capacitance which is calculated from the operating current consumption without load. (Refer to Test Circuit). Average operating current can be obtained by the following equation. $I_{CC(opr)} = C_{PD} \times V_{CC} \times f_{IN} + I_{CC}$

Obsolete Product(s) - Obsolete Product(s)

ANALOG SWITCH CHARACTERISTICS (GND = 0V;T_A = 25°C)


Symbol	Parameter	Test Condition				Value	Unit
		V_{CC} (V)	V_{EE} (V)	V_{IN} (V_{p-p})		Typ.	
	Sine Wave Distortion	2.25	-2.25	4	f_{IN} = 1 KHz R_L = 10 KΩ, C_L = 50 pF	0.025	%
		4.5	-4.5	8		0.020	
	Sine Wave Distortion	2.25	-2.25	4	f_{IN} = 10 KHz R_L = 10 KΩ, C_L = 50 pF	0.12	%
		4.5	-4.5	8		0.06	
f_{MAX}	Frequency Response (Switch ON) (*)	2.25	-2.25	Adjust f_{IN} voltage to obtain 0 dBm at V_{OS}. Increase f_{IN} Frequency until dB meter reads -3dB R_L = 50Ω, C_L = 10 pF, f_{IN} = 1KHz sine wave		120	MHz
		4.5	-4.5			190	
f_{MAX}	Frequency Response (Switch ON) (**)	2.25	-2.25	Adjust f_{IN} voltage to obtain 0 dBm at V_{OS}. Increase f_{IN} Frequency until dB meter reads -3dB R_L = 50Ω, C_L = 10 pF, f_{IN} = 1KHz sine wave		95	MHz
		4.5	-4.5			150	
		6.0	-6.0				
	Feed through Attenuation (Switch OFF)	2.25	-2.25	V_{IN} is centered at (V_{CC} - V_{EE})/2 Adjust input for 0 dBm R_L = 600Ω, C_L = 50 pF, f_{IN} = 1MHz sine wave		-50	dB
		4.5	-4.5			-50	
	Crosstalk (Control Input to Signal Output)	4.5	0	Adjust R_L at set up so that I_S = 0A. R_L = 600Ω, C_L = 50 pF, f_{IN} = 1MHz square wave between Vcc and GND tr=tf= 6 ns		60	mV
		4.5	-4.5			140	
	Crosstalk (between any two switches)	2.25	-2.25	Adjust V_{IN} to obtain 0dBm at input R_L = 600Ω, C_L = 50 pF, f_{IN} = 1MHz sine wave		-50	dB
		4.5	-4.5			-50	

(*) Input COMMON Terminal, and measured at SWITCH Terminal
(**) Input SWITCH Terminal, and measured at common Terminal
NOTE: These characteristics are determined by the design of the device.


Obsolete Product(s) - Obsolete Product(s)

SWITCHING CARACTERISTICS TEST CIRCUIT


t_{PLZ}, t_{PHZ}, t_{PZL}, t_{PZH}




CROSSTALK (control to output)




BANDWIDTH AND FEEDTHROUGH ATTENUATION



CROSSTALK BETWEEN ANY TWO SWITCHES




C_{I-O}, $C_{I/O}$




Obsolete Product(s) - Obsolete Product(s)


SWITCHING CHARACTERISTICS WAVEFORM



CHANNEL RESISTANCE (R_{ON})




I_{CC} (Opr.)



Obsolete Product(s) - Obsolete Product(s)

Plastic DIP-16 (0.25) MECHANICAL DATA

DIM.	mm.			inch		
	MIN.	TYP	MAX.	MIN.	TYP.	MAX.
a1	0.51			0.020		
B	0.77		1.65	0.030		0.065
b		0.5			0.020	
b1		0.25			0.010	
D			20			0.787
E		8.5			0.335	
e		2.54			0.100	
e3		17.78			0.700	
F			7.1			0.280
I			5.1			0.201
L		3.3			0.130	
Z			1.27			0.050




P001C

Obsolete Product(s) - Obsolete Product(s)

SO-16 MECHANICAL DATA

DIM.	mm.			inch		
	MIN.	TYP	MAX.	MIN.	TYP.	MAX.
A			1.75			0.068
a1	0.1		0.2	0.004		0.008
a2			1.65			0.064
b	0.35		0.46	0.013		0.018
b1	0.19		0.25	0.007		0.010
C		0.5			0.019	
c1	45° (typ.)					
D	9.8		10	0.385		0.393
E	5.8		6.2	0.228		0.244
e		1.27			0.050	
e3		8.89			0.350	
F	3.8		4.0	0.149		0.157
G	4.6		5.3	0.181		0.208
L	0.5		1.27	0.019		0.050
M			0.62			0.024
S	8° (max.)					




PO13H

Obsolete Product(s) - Obsolete Product(s)

TSSOP16 MECHANICAL DATA

DIM.	mm.			inch		
	MIN.	TYP	MAX.	MIN.	TYP.	MAX.
A			1.2			0.047
A1	0.05		0.15	0.002	0.004	0.006
A2	0.8	1	1.05	0.031	0.039	0.041
b	0.19		0.30	0.007		0.012
c	0.09		0.20	0.004		0.0079
D	4.9	5	5.1	0.193	0.197	0.201
E	6.2	6.4	6.6	0.244	0.252	0.260
E1	4.3	4.4	4.48	0.169	0.173	0.176
e		0.65 BSC			0.0256 BSC	
K	0°		8°	0°		8°
L	0.45	0.60	0.75	0.018	0.024	0.030




0080338D

Obsolete Product(s) - Obsolete Product(s)

Tape & Reel SO-16 MECHANICAL DATA


DIM.	mm.			inch		
	MIN.	TYP	MAX.	MIN.	TYP.	MAX.
A			330			12.992
C	12.8		13.2	0.504		0.519
D	20.2			0.795		
N	60			2.362		
T			22.4			0.882
Ao	6.45		6.65	0.254		0.262
Bo	10.3		10.5	0.406		0.414
Ko	2.1		2.3	0.082		0.090
Po	3.9		4.1	0.153		0.161
P	7.9		8.1	0.311		0.319



Obsolete Product(s) - Obsolete Product(s)

Tape & Reel TSSOP16 MECHANICAL DATA

DIM.	mm.			inch		
	MIN.	TYP	MAX.	MIN.	TYP.	MAX.
A			330			12.992
C	12.8		13.2	0.504		0.519
D	20.2			0.795		
N	60			2.362		
T			22.4			0.882
Ao	6.7		6.9	0.264		0.272
Bo	5.3		5.5	0.209		0.217
Ko	1.6		1.8	0.063		0.071
Po	3.9		4.1	0.153		0.161
P	7.9		8.1	0.311		0.319



Obsolete Product(s) - Obsolete Product(s)

Obsolete Product(s) - Obsolete Product(s)

Information furnished is believed to be accurate and reliable. However, STMicroelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of STMicroelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. STMicroelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of STMicroelectronics.

© The ST logo is a registered trademark of STMicroelectronics

© 2003 STMicroelectronics - Printed in Italy - All Rights Reserved
STMicroelectronics GROUP OF COMPANIES
Australia - Brazil - Canada - China - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan - Malaysia - Malta - Morocco
Singapore - Spain - Sweden - Switzerland - United Kingdom - United States.
© http://www.st.com