19-3377; Rev 0; 7/04

0.75Ω, Dual SPDT Audio Switch with Integrated Comparators

General Description

The MAX4855 dual, single-pole/double-throw (SPDT) switch operates from a single +2V to +5.5V supply and features rail-to-rail signal handling. The MAX4855 has low on-resistance (0.75Ω) with a +3V supply making it ideal for audio switching applications in portable devices. The device also integrates two internal comparators that can be used for headphone detection or mute/send key functions.

The MAX4855 is available in the space-saving (3mm x 3mm), 16-pin thin QFN package and operates over the extended temperature range of -40°C to +85°C.

Applications

Speaker Headset Switching

Audio-Signal Routing

Cellular Phones

Notebook Computers

PDAs and Other Handheld Devices

Features


- **Audio Signal Routing**
- **0.75Ω On-Resistance**
- **0.18Ω On-Resistance Flatness**
- **0.07Ω Channel-to-Channel Matching**
- **Rail-to-Rail Signal Handling**
- **2 Integrated Comparators**
- **1.8V Logic Compatible**
- **2V to 5.5V Supply Range**
- **Available in a Space-Saving (3mm x 3mm), 16-Pin TQFN Package**

Ordering Information

PART	TEMP RANGE	PIN-PACKAGE	TOP MARK
MAX4855ETE	-40°C to +85°C	16 TQFN-EP*	ABY

**EP = Exposed paddle.*


Block Diagram/Truth Table



MAX4855		
IN_	NO_	NC_
0	OFF	ON
1	ON	OFF

SWITCHES SHOWN FOR LOGIC 0 INPUT

Pin Configuration



THIN QFN

CONNECT EXPOSED PADDLE TO GROUND.

For pricing, delivery, and ordering information, please contact Maxim/Dallas Direct! at 1-888-629-4642, or visit Maxim's website at www.maxim-ic.com.

0.75Ω, Dual SPDT Audio Switch with Integrated Comparators

ABSOLUTE MAXIMUM RATINGS

V_{CC}, IN_, CIN_ to GND .....-0.3V to +6.0V
NO_, NC_, COM_, COUT_ (Note 1) .....-0.3V to (V_{CC} + 0.3V)
COUT_ Continuous Current.....±20mA
Closed Switch Continuous Current COM_, NO_, NC_.....±300mA
Peak Current COM_, NO_, NC_
(pulsed at 1ms, 50% duty cycle) .....±400mA
Peak Current COM_, NO_, NC_
(pulsed at 1ms, 10% duty cycle) .....±500mA

Continuous Power Dissipation (T_A = +70°C)
16-Pin Thin QFN (derate 20.8mW/°C above +70°C) 1667mW
Operating Temperature Range.....-40°C to +85°C
Junction Temperature.....+150°C
Storage Temperature Range .....-65°C to +150°C
Lead Temperature (soldering, 10s).....+300°C

Note 1: Signals on NO, NC, or COM exceeding V_{CC} or GND are clamped by internal diodes. Signals on IN exceeding GND are clamped by an internal diode. Limit forward-diode current to maximum current rating.

Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

ELECTRICAL CHARACTERISTICS

(V_{CC} = +2.7V to +5.5V, T_A = -40°C to +85°C, unless otherwise noted. Typical values are at V_{CC} = +3.0V, T_A = +25°C, unless otherwise noted.) (Note 2)

PARAMETER	SYMBOL	CONDITIONS		MIN	TYP	MAX	UNITS
Supply Voltage	V_{CC}			2		5.5	V
Supply Current	I_{CC}	V_{CC} = 5.5V, $V_{IN_}$ = 0V or V_{CC}			5	10	µA
ANALOG SWITCH							
Analog Signal Range	$V_{NO_}$, $V_{NC_}$, $V_{COM_}$			0		V_{CC}	V
On-Resistance (Note 3)	R_{ON}	V_{CC} = 2.7V, $I_{COM_}$ = 100mA, $V_{NC_}$ or $V_{NO_}$ = 0V to V_{CC}	T_A = +25°C		0.75	1	Ω
			T_A = -40°C to +85°C			1.1	
On-Resistance Match Between Channels (Notes 3, 4)	ΔR_{ON}	V_{CC} = 2.7V, I_{COM} = 100mA, $V_{NC_}$ or $V_{NO_}$ = 1.5V	T_A = +25°C		0.075	0.120	Ω
			T_A = -40°C to +85°C			0.135	
On-Resistance Flatness (Note 5)	R_{FLAT}	V_{CC} = 2.7V, $I_{COM_}$ = 100mA, $V_{NC_}$ or $V_{NO_}$ = 0.75V, 1.5V, 1.75V	T_A = +25°C		0.18	0.275	Ω
			T_A = -40°C to +85°C			0.3	
NO_/NC_ Off-Leakage Current (Note 2)	I_{OFF}	V_{CC} = 5.5V, $V_{NC_}$ or $V_{NO_}$ = 1V or 4.5V, $V_{COM_}$ = 4.5V or 1V	T_A = +25°C	-2		+2	nA
			T_A = -40°C to +85°C	-10		+10	
COM_ On-Leakage Current (Note 2)	I_{ON}	V_{CC} = 5.5V; $V_{NC_}$ or $V_{NO_}$ = 1V, 4.5V, or floating; $V_{COM_}$ = 1V, 4.5V, or floating	T_A = +25°C	-2		+2	nA
			T_A = -40°C to +85°C	-15		+15	
DYNAMIC CHARACTERISTICS							
Turn-On Time	t_{ON}	V_{CC} = 2.7V, $V_{NO_}$ or $V_{NC_}$ = 1.5V, R_L = 300Ω, C_L = 50pF (Figure 1)	T_A = +25°C		40	60	ns
			T_A = -40°C to +85°C			100	

ELECTRICAL CHARACTERISTICS (continued)

(V_{CC} = +2.7V to +5.5V, T_A = -40°C to +85°C, unless otherwise noted. Typical values are at V_{CC} = +3.0V, T_A = +25°C, unless otherwise noted.) (Note 2)

PARAMETER	SYMBOL	CONDITIONS		MIN	TYP	MAX	UNITS
Turn-Off Time	t_{OFF}	V_{CC} = 2.7V, $V_{NO_}$ or $V_{NC_}$ = 1.5V, R_L = 300Ω, C_L = 50pF (Figure 1)	T_A = +25°C		30	40	ns
			T_A = -40°C to +85°C			60	
Break-Before-Make Time Delay (Note 3)	t_D	V_{CC} = 2.7V, $V_{NO_}$ or $V_{NC_}$ = 1.5V, R_L = 50Ω, C_L = 50pF (Figure 2)	T_A = +25°C		15		ns
			T_A = -40°C to +85°C	2			
Charge Injection	Q	$V_{COM_}$ = 1.5V, R_S = 0Ω, C_L = 1.0nF (Figure 3)			170		pC
Off-Isolation (Note 6)		f = 100kHz, $V_{COM_}$ = $1V_{RMS}$, R_L = 50Ω, C_L = 5pF (Figure 4)			-75		dB
Crosstalk	V_{CT}	f = 100kHz, $V_{COM_}$ = $1V_{RMS}$, R_L = 50Ω, C_L = 5pF (Figure 4)			-93		dB
-3dB Bandwidth	BW	Signal = 0dBm, R_L = 50Ω, C_L = 5pF (Figure 4)			38		MHz
Total Harmonic Distortion	THD	f = 20Hz to 20kHz, $V_{COM_}$ = 1V + $2V_{P-P}$, R_L = 32Ω			0.07		%
NO_/NC_ Off-Capacitance	C_{OFF}	f = 1MHz (Figure 5)			50		pF
COM On-Capacitance	C_{ON}	f = 1MHz (Figure 5)			150		pF
DIGITAL I/O (IN_)							
Input-Logic High Voltage	V_{IH}	V_{CC} = 2V to 3.6V		1.4			V
		V_{CC} = 3.6V to 5.5V		1.8			
Input-Logic Low Voltage	V_{IL}	V_{CC} = 2V to 3.6V				0.5	V
		V_{CC} = 3.6V to 5.5V				0.8	
Input Leakage Current	I_{IN}	$V_{IN_}$ = 0 or 5.5V		-0.5		+0.5	µA
COMPARATOR							
Comparator Range				0		5.5	V
Comparator Threshold		V_{CC} = 2V to 5.5V, falling input		0.3 x V_{CC}	0.33 x V_{CC}	0.36 x V_{CC}	V
Comparator Hysteresis		V_{CC} = 2V to 5.5V			50		mV
Comparator Output High Voltage		I_{SOURCE} = 1mA		V_{CC} - 0.4V			V
Comparator Output Low Voltage		I_{SINK} = 1mA				0.4	V
Comparator Switching Time		Rising input (Figure 6)			2.5		µs
		Falling input (Figure 6)			0.5		

Note 2: Specifications are 100% tested at T_A = +85°C only, and guaranteed by design and characterization over the specified temperature range.

Note 3: Guaranteed by design and characterization; not production tested.

Note 4: $\Delta R_{ON} = R_{ON(MAX)} - R_{ON(MIN)}$.

Note 5: Flatness is defined as the difference between the maximum and minimum value of on-resistance as measured over the specified analog signal ranges.


Note 6: Off-Isolation = $20\log_{10} (V_{COM_} / V_{NO_})$, $V_{COM_}$ = output, $V_{NO_}$ = input to off switch.

0.75Ω, Dual SPDT Audio Switch with Integrated Comparators


Typical Operating Characteristics

(V_{CC} = 3.0V, T_A = +25°C, unless otherwise noted.)


ON-RESISTANCE vs. COM VOLTAGE




ON-RESISTANCE vs. COM VOLTAGE




ON-RESISTANCE vs. COM VOLTAGE




SUPPLY CURRENT vs. SUPPLY VOLTAGE




TURN-ON/TURN-OFF TIME vs. SUPPLY VOLTAGE




TURN-ON/TURN-OFF TIME vs. TEMPERATURE




LOGIC THRESHOLD vs. SUPPLY VOLTAGE



CHARGE INJECTION vs. COM VOLTAGE




LEAKAGE CURRENT vs. TEMPERATURE




Typical Operating Characteristics (continued)

(V_{CC} = 3.0V, T_A = +25°C, unless otherwise noted.)


FREQUENCY RESPONSE




TOTAL HARMONIC DISTORTION vs. FREQUENCY



COMPARATOR THRESHOLD vs. TEMPERATURE



COMPARATOR THRESHOLD vs. TEMPERATURE



0.75Ω, Dual SPDT Audio Switch with Integrated Comparators

Pin Description

PIN	NAME	FUNCTION
1, 8	N.C.	No Connection. Not internally connected.
2	CIN1	Inverting Input for Comparator 1
3	CIN2	Inverting Input for Comparator 2
4	COM1	Common Terminal for Analog Switch 1
5	NO1	Normally Open Terminal for Analog Switch 1
6	GND	Ground
7	NC2	Normally Closed Terminal for Analog Switch 2
9	IN2	Digital Control Input for Analog Switch 2. A logic LOW on IN2 connects COM2 to NC2 and a logic HIGH connects COM2 to NO2.
10	COM2	Common Terminal for Analog Switch 2
11	COUT1	Output for Comparator 1
12	NO2	Normally Open Terminal for Analog Switch 2
13	COUT2	Output for Comparator 2
14	V_{CC}	Supply Voltage. Bypass to GND with a 0.01µF capacitor as close to the pin as possible.
15	IN1	Digital Control Input for Analog Switch 1. A logic LOW on IN1 connects COM1 to NC1 and a logic HIGH connects COM1 to NO1.
16	NC1	Normally Closed Terminal for Analog Switch 1
EP	—	Exposed Paddle. Connect to PC board ground plane.

Detailed Description

The MAX4855 dual SPDT, low on-resistance, low-voltage, analog switch operates from a +2V to +5.5V supply and can handle signals up to the power rails. In addition, the MAX4855 integrates two internal comparators that can be used for headphone or mute detection. The comparator threshold is internally generated to be approximately 1/3 of V_{CC}.

Applications Information

Digital Control Inputs

The logic inputs (IN_) accept up to +5.5V even if the supply voltages are below this level. For example, with a +3.3V V_{CC} supply, IN_ can be driven low to GND and high to +5.5V allowing for mixing of logic levels in a system. Driving IN_ rail-to-rail minimizes power consumption. For a +2V supply voltage, the logic thresholds are 0.5V (low) and 1.4V (high); for a +5V supply voltage, the logic thresholds are 0.8V (low) and 1.8V (high).

Analog Signal Levels

The on-resistance of these switches changes very little for analog input signals across the entire supply voltage range (see the *Typical Operating Characteristics*). The switches are bidirectional, so the NO_, NC_, and COM_ pins can be either inputs or outputs.

Comparator

The positive terminal of the comparator is internally set to $V_{CC}/3$. When the negative terminal (CIN_) is below the threshold ($V_{CC}/3$), the comparator output (COUT_) is high. When CIN_ rises above $V_{CC}/3$, COUT_ is low.

The comparator threshold allows for detection of headphones since headphone audio signals are typically biased to $V_{CC}/2$.

Power-Supply Sequencing

Caution: Do not exceed the absolute maximum ratings because stresses beyond the listed ratings may cause permanent damage to the device.

Proper power-supply sequencing is recommended for all CMOS devices. Always apply V_{CC} before applying analog signals, especially if the analog signal is not current-limited.

Test Circuits/Timing Diagrams




Figure 1. Switching Time




Figure 2. Break-Before-Make Interval

0.75Ω, Dual SPDT Audio Switch with Integrated Comparators




Figure 3. Charge Injection




Figure 4. On-Loss, Off-Isolation, and Crosstalk




Figure 5. Channel Off-/On-Capacitance





Figure 6. Comparator Switching Time

Typical Operating Circuit



Chip Information


TRANSISTOR COUNT: 735

PROCESS: CMOS

0.75Ω, Dual SPDT Audio Switch with Integrated Comparators

Package Information

(The package drawing(s) in this data sheet may not reflect the most current specifications. For the latest package outline information go to **www.maxim-ic.com/packages**.)



PKG	12L 3x3			16L 3x3		
REF.	MIN.	NOM.	MAX.	MIN.	NOM.	MAX.
A	0.70	0.75	0.80	0.70	0.75	0.80
b	0.20	0.25	0.30	0.20	0.25	0.30
D	2.90	3.00	3.10	2.90	3.00	3.10
E	2.90	3.00	3.10	2.90	3.00	3.10
e	0.50 BSC.			0.50 BSC.		
L	0.45	0.55	0.65	0.30	0.40	0.50
N	12			16		
ND	3			4		
NE	3			4		
A1	0	0.02	0.05	0	0.02	0.05
A2	0.20 REF			0.20 REF		
k	0.25	-	-	0.25	-	-

EXPOSED PAD VARIATIONS

PKG. CODES	D2			E2			PIN ID	JEDEC	DOWN BONDS ALLOWED
	MIN.	NOM.	MAX.	MIN.	NOM.	MAX.			
T1233-1	0.95	1.10	1.25	0.95	1.10	1.25	0.35 x 45°	WEED-1	NO
T1233-3	0.95	1.10	1.25	0.95	1.10	1.25	0.35 x 45°	WEED-1	YES
T1633-1	0.95	1.10	1.25	0.95	1.10	1.25	0.35 x 45°	WEED-2	NO
T1633-2	0.95	1.10	1.25	0.95	1.10	1.25	0.35 x 45°	WEED-2	YES
T1633F-3	0.55	0.60	0.95	0.55	0.60	0.95	0.225 x 45°	WEED-2	N/A
T1633-4	0.95	1.10	1.25	0.95	1.10	1.25	0.35 x 45°	WEED-2	NO

NOTES:

1. DIMENSIONING & TOLERANCING CONFORM TO ASME Y14.5M-1994.
2. ALL DIMENSIONS ARE IN MILLIMETERS. ANGLES ARE IN DEGREES.
3. N IS THE TOTAL NUMBER OF TERMINALS.
4. THE TERMINAL #1 IDENTIFIER AND TERMINAL NUMBERING CONVENTION SHALL CONFORM TO JESD 95-1 SPP-012. DETAILS OF TERMINAL #1 IDENTIFIER ARE OPTIONAL, BUT MUST BE LOCATED WITHIN THE ZONE INDICATED. THE TERMINAL #1 IDENTIFIER MAY BE EITHER A MOLD OR MARKED FEATURE.
5. DIMENSION b APPLIES TO METALLIZED TERMINAL AND IS MEASURED BETWEEN 0.20 mm AND 0.25 mm FROM TERMINAL TIP.
6. ND AND NE REFER TO THE NUMBER OF TERMINALS ON EACH D AND E SIDE RESPECTIVELY.
7. DEPOPULATION IS POSSIBLE IN A SYMMETRICAL FASHION.
8. COPLANARITY APPLIES TO THE EXPOSED HEAT SINK SLUG AS WELL AS THE TERMINALS.
9. DRAWING CONFORMS TO JEDEC MO220 REVISION C.

DALLAS SEMICONDUCTOR MAXIM
PROPRIETARY INFORMATION
TITLE: PACKAGE OUTLINE 12, 16L, THIN QFN, 3x3x0.8mm
APPROVAL
DOCUMENT CONTROL NO. 21-0136
REV. E
2/2

Maxim cannot assume responsibility for use of any circuitry other than circuitry entirely embodied in a Maxim product. No circuit patent licenses are implied. Maxim reserves the right to change the circuitry and specifications without notice at any time.

© 2004 Maxim Integrated Products Printed USA MAXIM is a registered trademark of Maxim Integrated Products.