


SIZE	QTY	SYM	PLATED	TOL
70	2	+	NO	+/-0.0
40	6	X	YES	+/-0.0
95	8	□	YES	+/-0.0
6	46	◇	YES	+/-0.0
215	4	⊗	YES	+/-0.0

- ART01 = LAYER 1 (COMPONENT SIDE)
- ART02 = LAYER 2 (GND)
- ART03 = LAYER 3 (GND)
- ART04 = LAYER 4 (SOLDER SIDE)

NOTES: Unless Otherwise Specified:

- PCBS Are To Be RoHS Compliant
- Fab Per IPC-A-600
- Material: Epoxy Fiberglass, NEMA Grade FR-4, 4 Layers
.062 +/- .005 Inch Thickness With
2 OZ. Copper Finished On All Outer Layers,
1 OZ. Copper On All Internal Layers.
Flammability Rating: 94 V-2 Minimum.
- Size: Cut To Dimensions And Tolerances Shown.
0.00 Are Primary Datums.
- Finish: SMOBC Using Wet Mask, Or LPI Both Sides, Color Green.
Silkscreen Both Sides With White Non-conductive Ink.
Gold Immersion Both Sides (Not Required For Prototype Boards)
- Drilling: Drill Holes Per Schedule. Plate Through
Holes With Copper, .001 Inch Thick Min. All
Hole Sizes Are Specified After Plating.
Hole Location Tolerances Are +/- .003" In Relation To Center.
- Do Not Alter Artwork To Add Logo Or Date Code,
- Scoring: (Not Required For Prototype Boards)



9. DESIGN HAS SOLDER MASK DEFINED_PADS ON U1. U1 SOLDER MASK
SIZE IS 25 MIL AND PAD SIZE IS 29 MIL. DO NOT CHANGE ANY
SIZE ON THIS COMPONENT.

Fabrication Drawing

APPROVALS

DRAWN	INIT	DATE
CHECK	KL	
DESIGN		
ENGR		

1630 McCarthy Blvd.
Milpitas, CA 95035
PH: (408)432-1900

LTM8025EV
36V, 3A Step-Down μ Module[®] Regulator

SIZE	DEMO BRD	DC1379B	REV. B
A			

SCALE = NONE

SHT 1 of 1