

CSD18533Q5A 60 V N-Channel NexFET™ Power MOSFET

1 Features


- Ultra Low Qg and Qgd
- Low Thermal Resistance
- Avalanche Rated
- Logic Level
- Pb Free Terminal Plating
- RoHS Compliant
- Halogen Free
- SON 5 mm x 6 mm Plastic Package

2 Applications

- DC-DC Conversion
- Secondary Side Synchronous Rectifier
- Motor Control

3 Description

This 4.7 mΩ, 60 V, SON 5 x 6 mm NexFET™ power MOSFET is designed to minimize losses in power conversion applications.



Product Summary

| T _A = 25°C | | TYPICAL VALUE | | UNIT |
|-----------------------|-------------------------------|-------------------------|-----|------|
| V _{DS} | Drain-to-Source Voltage | 60 | | V |
| Q _g | Gate Charge Total (10 V) | 29 | | nC |
| Q _{gd} | Gate Charge Gate-to-Drain | 5.4 | | nC |
| R _{DS(on)} | Drain-to-Source On-Resistance | V _{GS} = 4.5 V | 6.5 | mΩ |
| | | V _{GS} = 10 V | 4.7 | mΩ |
| V _{GS(th)} | Threshold Voltage | 1.9 | | V |

Ordering Information⁽¹⁾

| Device | Qty | Media | Package | Ship |
|--------------|------|--------------|---------------------------------|---------------|
| CSD18533Q5A | 2500 | 13-Inch Reel | SON 5 mm x 6 mm Plastic Package | Tape and Reel |
| CSD18533Q5AT | 250 | 7-Inch Reel | | |

(1) For all available packages, see the orderable addendum at the end of the data sheet.

Absolute Maximum Ratings

| T _A = 25°C | | VALUE | UNIT |
|-----------------------------------|--|------------|------|
| V _{DS} | Drain-to-Source Voltage | 60 | V |
| V _{GS} | Gate-to-Source Voltage | ±20 | V |
| I _D | Continuous Drain Current (Package limited), T _C = 25°C | 100 | A |
| | Continuous Drain Current (Silicon limited), T _C = 25°C | 103 | |
| | Continuous Drain Current, T _A = 25°C ⁽¹⁾ | 17 | |
| I _{DM} | Pulsed Drain Current, T _A = 25°C ⁽²⁾ | 267 | A |
| P _D | Power Dissipation ⁽¹⁾ | 3.2 | W |
| | Power Dissipation, T _C = 25°C | 116 | |
| T _J , T _{stg} | Operating Junction and Storage Temperature Range | -55 to 150 | °C |
| E _{AS} | Avalanche Energy, single pulse I _D = 53 A, L = 0.1 mH, R _G = 25 Ω | 140 | mJ |

(1) Typical R_{θJA} = 40°C/W on a 1 inch², 2 oz. Cu pad on a 0.06 inch thick FR4 PCB.

(2) Max R_{θJC} = 1.3°C/W, pulse duration ≤ 100 μs, duty cycle ≤ 1%





Table of Contents

| | | | |
|---|----------|---|-----------|
| 1 Features | 1 | 6.1 Trademarks | 7 |
| 2 Applications | 1 | 6.2 Electrostatic Discharge Caution | 7 |
| 3 Description | 1 | 6.3 Glossary | 7 |
| 4 Revision History | 2 | 7 Mechanical, Packaging, and Orderable Information | 8 |
| 5 Specifications | 3 | 7.1 Q5A Package Dimensions | 8 |
| 5.1 Electrical Characteristics | 3 | 7.2 Recommended PCB Pattern | 9 |
| 5.2 Thermal Information | 3 | 7.3 Recommended Stencil Opening | 9 |
| 5.3 Typical MOSFET Characteristics | 4 | 7.4 Q5A Tape and Reel Information | 10 |
| 6 Device and Documentation Support | 7 | | |

4 Revision History

NOTE: Page numbers for previous revisions may differ from page numbers in the current version.

| Changes from Revision A (May 2013) to Revision B | Page |
|--|-------------|
| • Added part number to title | 1 |
| • Increased Pulsed Drain Current to 267 A | 1 |
| • Added line for max power dissipation with case temperature held to 25° C | 1 |
| • Updated pulsed current conditions | 1 |
| • Changed Figure 1 to normalized $R_{\theta JC}$ curve | 4 |
| • Updated SOA in Figure 10 | 6 |

| Changes from Original (September 2012) to Revision A | Page |
|--|-------------|
| • Changed the $R_{\theta JC}$ MAX value From: 2.3°C/W to 1.3°C/W | 3 |
| • Changed From: Max $R_{\theta JA}$ = 121°C/W To: Max $R_{\theta JA}$ = 125°C/W | 4 |
| • Changed Typ $R_{th JA}$ = 99°C/W To: $R_{th JA}$ = 100°C/W in Figure 1 | 4 |
| • Added the Recommended Stencil Opening section | 9 |

5 Specifications

5.1 Electrical Characteristics

 $(T_A = 25^\circ\text{C}$ unless otherwise stated)

| PARAMETER | | TEST CONDITIONS | MIN | TYP | MAX | UNIT |
|--------------------------------|----------------------------------|---|---|------|------|---------------|
| STATIC CHARACTERISTICS | | | | | | |
| V_{DSS} | Drain-to-Source Voltage | $V_{GS} = 0\text{ V}, I_D = 250\ \mu\text{A}$ | 60 | | | V |
| I_{DSS} | Drain-to-Source Leakage Current | $V_{GS} = 0\text{ V}, V_{DS} = 48\text{ V}$ | | | 1 | μA |
| I_{GSS} | Gate-to-Source Leakage Current | $V_{DS} = 0\text{ V}, V_{GS} = 20\text{ V}$ | | | 100 | nA |
| $V_{GS(th)}$ | Gate-to-Source Threshold Voltage | $V_{DS} = V_{GS}, I_D = 250\ \mu\text{A}$ | 1.5 | 1.9 | 2.3 | V |
| $R_{DS(on)}$ | Drain-to-Source On-Resistance | $V_{GS} = 4.5\text{ V}, I_D = 18\text{ A}$ | | 6.5 | 8.5 | m Ω |
| | | $V_{GS} = 10\text{ V}, I_D = 18\text{ A}$ | | 4.7 | 5.9 | m Ω |
| g_{fs} | Transconductance | $V_{DS} = 30\text{ V}, I_D = 18\text{ A}$ | | 122 | | S |
| DYNAMIC CHARACTERISTICS | | | | | | |
| C_{iss} | Input Capacitance | $V_{GS} = 0\text{ V}, V_{DS} = 30\text{ V}, f = 1\text{ MHz}$ | | 2200 | 2750 | pF |
| C_{oss} | Output Capacitance | | | 292 | 365 | pF |
| C_{rss} | Reverse Transfer Capacitance | | | 7 | 9 | pF |
| R_G | Series Gate Resistance | | | 1.3 | 2.6 | Ω |
| Q_g | Gate Charge Total (4.5 V) | $V_{DS} = 30\text{ V}, I_D = 18\text{ A}$ | | 14 | 18 | nC |
| Q_g | Gate Charge Total (10 V) | | | 29 | 36 | |
| Q_{gd} | Gate Charge Gate-to-Drain | | | 5.4 | | nC |
| Q_{gs} | Gate Charge Gate-to-Source | | | 6.6 | | nC |
| $Q_{g(th)}$ | Gate Charge at V_{th} | | | 4.7 | | nC |
| Q_{oss} | Output Charge | | $V_{DS} = 30\text{ V}, V_{GS} = 0\text{ V}$ | | 31 | |
| $t_{d(on)}$ | Turn On Delay Time | $V_{DS} = 30\text{ V}, V_{GS} = 10\text{ V}, I_{DS} = 18\text{ A}, R_G = 0\ \Omega$ | | 5.2 | | ns |
| t_r | Rise Time | | | 5.5 | | ns |
| $t_{d(off)}$ | Turn Off Delay Time | | | 15 | | ns |
| t_f | Fall Time | | | 2.0 | | ns |
| DIODE CHARACTERISTICS | | | | | | |
| V_{SD} | Diode Forward Voltage | $I_{SD} = 18\text{ A}, V_{GS} = 0\text{ V}$ | | 0.8 | 1 | V |
| Q_{rr} | Reverse Recovery Charge | $V_{DS} = 30\text{ V}, I_F = 18\text{ A}, di/dt = 300\text{ A}/\mu\text{s}$ | | 68 | | nC |
| t_{rr} | Reverse Recovery Time | | | 40 | | ns |

5.2 Thermal Information

 $(T_A = 25^\circ\text{C}$ unless otherwise stated)

| THERMAL METRIC | | MIN | TYP | MAX | UNIT |
|-----------------|--|-----|-----|-----|---------------------------|
| $R_{\theta JC}$ | Thermal Resistance Junction to Case ⁽¹⁾ | | | 1.3 | $^\circ\text{C}/\text{W}$ |
| $R_{\theta JA}$ | Thermal Resistance Junction to Ambient ⁽¹⁾⁽²⁾ | | | 50 | |

- (1) $R_{\theta JC}$ is determined with the device mounted on a 1 inch² (6.45 cm²), 2 oz. (0.071 mm thick) Cu pad on a 1.5 inch x 1.5 inch (3.81 cm x 3.81 cm), 0.06 inch (1.52 mm) thick FR4 PCB. $R_{\theta JC}$ is specified by design, whereas $R_{\theta JA}$ is determined by the user's board design.
- (2) Device mounted on FR4 material with 1 inch² (6.45 cm²), 2 oz. (0.071 mm thick) Cu.

CSD18533Q5A

SLPS388B – SEPTEMBER 2012 – REVISED JANUARY 2015

www.ti.com



Max $R_{\theta JA} = 50^{\circ}\text{C/W}$
when mounted on
1 inch² (6.45 cm²) of
2 oz. (0.071 mm thick)
Cu.



Max $R_{\theta JA} = 125^{\circ}\text{C/W}$
when mounted on a
minimum pad area of
2 oz. (0.071 mm thick)
Cu.

5.3 Typical MOSFET Characteristics

($T_A = 25^{\circ}\text{C}$ unless otherwise stated)




Figure 1. Transient Thermal Impedance

Typical MOSFET Characteristics (continued)

($T_A = 25^\circ\text{C}$ unless otherwise stated)




Figure 2. Saturation Characteristics




Figure 3. Transfer Characteristics




Figure 4. Gate Charge




Figure 5. Capacitance




Figure 6. Threshold Voltage vs Temperature




Figure 7. On-State Resistance vs Gate-to-Source Voltage

Typical MOSFET Characteristics (continued)

($T_A = 25^\circ\text{C}$ unless otherwise stated)




Figure 8. Normalized On-State Resistance vs Temperature




Figure 9. Typical Diode Forward Voltage




Figure 10. Maximum Safe Operating Area




Figure 11. Single Pulse Unclamped Inductive Switching




Figure 12. Maximum Drain Current vs Temperature

6 Device and Documentation Support

6.1 Trademarks

NexFET is a trademark of Texas Instruments.
All other trademarks are the property of their respective owners.

6.2 Electrostatic Discharge Caution



These devices have limited built-in ESD protection. The leads should be shorted together or the device placed in conductive foam during storage or handling to prevent electrostatic damage to the MOS gates.

6.3 Glossary


[SLYZ022](#) — *TI Glossary*.

This glossary lists and explains terms, acronyms, and definitions.

7 Mechanical, Packaging, and Orderable Information


The following pages include mechanical, packaging, and orderable information. This information is the most current data available for the designated devices. This data is subject to change without notice and revision of this document. For browser-based versions of this data sheet, refer to the left-hand navigation.

7.1 Q5A Package Dimensions



| DIM | MILLIMETERS | | |
|----------|-------------|------|------|
| | MIN | NOM | MAX |
| A | 0.90 | 1.00 | 1.10 |
| b | 0.33 | 0.41 | 0.51 |
| c | 0.20 | 0.25 | 0.34 |
| D1 | 4.80 | 4.90 | 5.00 |
| D2 | 3.61 | 3.81 | 4.02 |
| E | 5.90 | 6.00 | 6.10 |
| E1 | 5.70 | 5.75 | 5.80 |
| E2 | 3.38 | 3.58 | 3.78 |
| E3 | 3.03 | 3.13 | 3.23 |
| e | 1.17 | 1.27 | 1.37 |
| e1 | 0.27 | 0.37 | 0.47 |
| e2 | 0.15 | 0.25 | 0.35 |
| H | 0.41 | 0.56 | 0.71 |
| K | 1.10 | | |
| L | 0.51 | 0.61 | 0.71 |
| L1 | 0.06 | 0.13 | 0.20 |
| θ | 0° | | 12° |

7.2 Recommended PCB Pattern




Recommended PCB Pattern (continued)


| DIM | MILLIMETERS | | INCHES | |
|-----|-------------|-------|--------|-------|
| | MIN | MAX | MIN | MAX |
| F1 | 6.205 | 6.305 | 0.244 | 0.248 |
| F2 | 4.46 | 4.56 | 0.176 | 0.18 |
| F3 | 4.46 | 4.56 | 0.176 | 0.18 |
| F4 | 0.65 | 0.7 | 0.026 | 0.028 |
| F5 | 0.62 | 0.67 | 0.024 | 0.026 |
| F6 | 0.63 | 0.68 | 0.025 | 0.027 |
| F7 | 0.7 | 0.8 | 0.028 | 0.031 |
| F8 | 0.65 | 0.7 | 0.026 | 0.028 |
| F9 | 0.62 | 0.67 | 0.024 | 0.026 |
| F10 | 4.9 | 5 | 0.193 | 0.197 |
| F11 | 4.46 | 4.56 | 0.176 | 0.18 |

For recommended circuit layout for PCB designs, see application note [SLPA005 – Reducing Ringing Through PCB Layout Techniques](#).

7.3 Recommended Stencil Opening



7.4 Q5A Tape and Reel Information



M0138-01

Notes:

- 10-sprocket hole-pitch cumulative tolerance ± 0.2
- Camber not to exceed 1mm in 100mm, noncumulative over 250mm
- Material: black static-dissipative polystyrene
- All dimensions are in mm (unless otherwise specified)
- A_0 and B_0 measured on a plane 0.3mm above the bottom of the pocket

PACKAGING INFORMATION

| Orderable Device | Status (1) | Package Type | Package Drawing | Pins | Package Qty | Eco Plan (2) | Lead/Ball Finish (6) | MSL Peak Temp (3) | Op Temp (°C) | Device Marking (4/5) | Samples |
|------------------|---------------|--------------|-----------------|------|-------------|-------------------------|-------------------------|----------------------|--------------|-------------------------|-------------------------|
| CSD18533Q5A | ACTIVE | VSONP | DQJ | 8 | 2500 | Green (RoHS & no Sb/Br) | SN | Level-1-260C-UNLIM | -55 to 150 | CSD18533 | Samples |
| CSD18533Q5AT | ACTIVE | VSONP | DQJ | 8 | 250 | Green (RoHS & no Sb/Br) | SN | Level-1-260C-UNLIM | -55 to 150 | CSD18533 | Samples |

(1) The marketing status values are defined as follows:

ACTIVE: Product device recommended for new designs.

LIFEBUY: TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.

NRND: Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.

PREVIEW: Device has been announced but is not in production. Samples may or may not be available.

OBSOLETE: TI has discontinued the production of the device.

(2) **RoHS:** TI defines "RoHS" to mean semiconductor products that are compliant with the current EU RoHS requirements for all 10 RoHS substances, including the requirement that RoHS substance do not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, "RoHS" products are suitable for use in specified lead-free processes. TI may reference these types of products as "Pb-Free".

RoHS Exempt: TI defines "RoHS Exempt" to mean products that contain lead but are compliant with EU RoHS pursuant to a specific EU RoHS exemption.

Green: TI defines "Green" to mean the content of Chlorine (Cl) and Bromine (Br) based flame retardants meet JS709B low halogen requirements of <=1000ppm threshold. Antimony trioxide based flame retardants must also meet the <=1000ppm threshold requirement.

(3) MSL, Peak Temp. - The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.

(4) There may be additional marking, which relates to the logo, the lot trace code information, or the environmental category on the device.

(5) Multiple Device Markings will be inside parentheses. Only one Device Marking contained in parentheses and separated by a "~" will appear on a device. If a line is indented then it is a continuation of the previous line and the two combined represent the entire Device Marking for that device.

(6) Lead/Ball Finish - Orderable Devices may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead/Ball Finish values may wrap to two lines if the finish value exceeds the maximum column width.

Important Information and Disclaimer:The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, or other requirements. These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you will fully indemnify TI and its representatives against, any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to TI's Terms of Sale (www.ti.com/legal/termsofsale.html) or other applicable terms available either on ti.com or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products.

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265
Copyright © 2020, Texas Instruments Incorporated