STH140N8F7-2

N-channel 80 V, 3.3 mΩ typ., 90 A STripFET™ F7 Power MOSFET in a H2PAK-2 package

Datasheet - production data





Figure 1: Internal schematic diagram



Features

Order code	V_{DS}	$R_{DS(on)}$ max.	I_D	P_{TOT}
STH140N8F7-2	80 V	4 mΩ	90 A	200 W

- Among the lowest $R_{DS(on)}$ on the market
- Excellent figure of merit (FoM)
- Low C_{rss}/C_{iss} ratio for EMI immunity
- High avalanche ruggedness

Applications

- Switching applications

Description

This N-channel Power MOSFET utilizes STripFET™ F7 technology with an enhanced trench gate structure that results in very low on-state resistance, while also reducing internal capacitance and gate charge for faster and more efficient switching.

Table 1: Device summary

Order code	Marking	Package	Packaging
STH140N8F7-2	140N8F7	H^2PAK-2	Tape and reel

This is information on a product in full production.

www.st.com

Contents

1 Electrical ratings 3
2 Electrical characteristics 4
2.1 Electrical characteristics (curves) 5
3 Test circuit 7
4 Package mechanical data 8
4.1 H2PAK-2 mechanical data 9
5 Packaging mechanical data 12
6 Revision history 14

1 Electrical ratings

Table 2: Absolute maximum ratings

Symbol	Parameter	Value	Unit
V_{DS}	Drain-source voltage	80	V
V_{GS}	Gate-source voltage	± 20	V
I_D	Drain current (continuous) at T_C = 25 ° C	90 (1)	A
I_D	Drain current (continuous) at T_C = 100 ° C	90	A
I_{DM}(2)	Drain current (pulsed)	360	A
P_{TOT}	Total dissipation at T_C = 25 ° C	200	W
E_{AS}(3)	Single pulse avalanche energy	515	mJ
T_j	Operating junction temperature	- 55 to 175	° C
T_{stg}	Storage temperature		

Notes:

(1)Limited by package

(2)Pulse width is limited by safe operating area

(3)Starting Tj =25 ° C, Id = 18.5 A, Vdd = 50 V

Table 3: Thermal data

Symbol	Parameter	Value	Unit
$R_{thj\text{-}pcb}$ (1)	Thermal resistance junction-pcb	35	° C/W
$R_{thj\text{-}case}$	Thermal resistance junction-case	0.75	° C/W

Notes:

(1)When mounted on FR-4 board of 1inch² , 2oz Cu

2 Electrical characteristics

(T_{CASE} = 25 ° C unless otherwise specified)

Table 4: On/off states

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$V_{(BR)DSS}$	Drain-source breakdown voltage	V_{GS} = 0, I_D = 250 µA	80			V
I_{DSS}	Zero gate voltage Drain current	V_{GS} = 0, V_{DS} = 80 V			1	µA
		V_{GS} = 0, V_{DS} = 80 V, T_J=125 ° C			10	µA
I_{GSS}	Gate-source leakage current	V_{DS} = 0, V_{GS} = ± 20 V			± 100	nA
$V_{GS(th)}$	Gate threshold voltage	V_{DS} = V_{GS}, I_D = 250 µA	2.5		4.5	V
$R_{DS(on)}$	Static drain-source on-resistance	V_{GS}=10 V, I_D = 45 A		3.3	4	mΩ

Table 5: Dynamic

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
C_{iss}	Input capacitance	V_{GS} = 0, V_{DS} = 40 V, f = 1 MHz	-	6340	-	pF
C_{oss}	Output capacitance		-	1195	-	pF
C_{rss}	Reverse transfer capacitance		-	105	-	pF
Q_g	Total gate charge	V_{DD} = 40 V, I_D = 64 A, V_{GS} = 10 V	-	96	-	nC
Q_{gs}	Gate-source charge		-	30	-	nC
Q_{gd}	Gate-drain charge		-	26	-	nC

Table 6: Switching times

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$t_{d(on)}$	Turn-on delay time	V_{DD} = 40 V, I_D = 45 A R_G=4.7 Ω, V_{GS} = 10 V	-	26	-	ns
t_r	Rise time		-	51	-	ns
$t_{d(off)}$	Turn-off-delay time		-	82	-	ns
t_f	Fall time		-	44	-	ns

Table 7: Source drain diode

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
I_{SD}	Source-drain current		-		90	A
I_{SDM} (1)	Source-drain current (pulsed)		-		360	A
V_{SD} (2)	Forward on voltage	V_{GS} = 0, I_{SD} = 90 A	-		1.2	V
t_{rr}	Reverse recovery time	I_{SD} = 64 A, di/dt = 100 A/µs, V_{DD} = 60 V, T_j = 150 ° C	-	58		ns
Q_{rr}	Reverse recovery charge		-	92		nC
I_{RRM}	Reverse recovery current		-	3.2		A

Notes:

(1)Pulse width is limited by safe operating area

(2)Pulse test: pulse duration = 300 µ s, duty cycle 1.5%

2.1 Electrical characteristics (curves)

Figure 2: Safe operating area




Figure 3: Thermal impedance




Figure 4: Output characteristics




Figure 5: Transfer characteristics




Figure 6: Normalized V(BR)DSS vs. temperature




Figure 7: Static drain-source on resistance




Figure 8: Gate charge vs. gate-source voltage




Figure 9: Capacitance variations




Figure 10: Normalized gate threshold voltage vs. temperature




Figure 11: Normalized on resistance vs. temperature





Figure 12: Source-drain diode forward characteristics



3 Test circuit

Figure 13: Switching times test circuit for resistive load




Figure 14: Gate charge test circuit




Figure 15: Test circuit for inductive load switching and diode recovery times




Figure 16: Unclamped inductive load test circuit




Figure 17: Unclamped inductive waveform





Figure 18: Switching time waveform



4 Package mechanical data

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK® packages, depending on their level of environmental compliance. ECOPACK® specifications, grade definitions and product status are available at: ***www.st.com***. ECOPACK® is an ST trademark.

4.1 H2PAK-2 mechanical data

Figure 19: H²PAK-2 leads drawing





Table 8: H²PAK-2 leads mechanical data

Dim.	mm		
	Min.	Typ.	Max.
A	4.30	-	4.80
A1	0.03		0.20
C	1.17		1.37
e	4.98		5.18
E	0.50		0.90
F	0.78		0.85
H	10.00		10.40
H1	7.40		7.80
L	15.30		15.80
L1	1.27		1.40
L2	4.93		5.23
L3	6.85		7.25
L4	1.5		1.7
M	2.6		2.9
R	0.20		0.60
V	0°		8°

Figure 20: H²PAK-2 recommended footprint



5 Packaging mechanical data

Figure 21: Tape




Figure 22: Reel




Table 9: Tape and reel mechanical data

Tape			Reel		
Dim.	mm		Dim.	mm	
	Min.	Max.		Min.	Max.
A0	10.5	10.7	A		330
B0	15.7	15.9	B	1.5	
D	1.5	1.6	C	12.8	13.2
D1	1.59	1.61	D	20.2	
E	1.65	1.85	G	24.4	26.4
F	11.4	11.6	N	100	
K0	4.8	5.0	T		30.4
P0	3.9	4.1			
P1	11.9	12.1	Base qty		1000
P2	1.9	2.1	Bulk qty		1000
R	50				
T	0.25	0.35			
W	23.7	24.3			

6 Revision history

Table 10: Document revision history

Date	Revision	Changes
25-Aug-2014	1	First release. Part numbers STF140N8F7 and STP140N8F7 previously included in the datasheet DocID023888.
10-Oct-2014	2	Updated *Figure 3: "Thermal impedance"*

IMPORTANT NOTICE – PLEASE READ CAREFULLY

STMicroelectronics NV and its subsidiaries (“ST”) reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST’s terms and conditions of sale in place at the time of order acknowledgement.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of Purchasers’ products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2014 STMicroelectronics – All rights reserved